A PINNS APPROACH FOR THE COMPUTATION OF EIGENVALUES IN ELLIPTIC PROBLEMS

JULIÁN FERNÁNDEZ BONDER AND ARIEL SALORT

Abstract. In this paper, we propose a method for computing eigenvalues of elliptic problems using Deep Learning techniques. A key feature of our approach is that it is independent of the space dimension and can compute arbitrary eigenvalues without requiring the prior computation of lower ones. Moreover, the method can be easily adapted to handle nonlinear eigenvalue problems.

1. Introduction

The impact of artificial intelligence (AI) on everyday life has become undeniable in recent years. From smartphones to image recognition, from medical diagnostics to self-driving cars, machine learning, and deep learning in particular, has transformed the way we interact with technology.

This influence has also extended into mathematics and physics, where machine learning techniques are being applied to analyze complex phenomena that were traditionally approached using classical analytical methods. Among these, problems governed by partial differential equations (PDEs) are especially prominent, due to their central role in modeling physical systems across many disciplines. Reflecting this trend, a growing number of software libraries and frameworks have been developed as educational and research tools for solving PDE-based problems in computational science and engineering; see, for instance, [11, 15, 14] and references therein.

In parallel, neural network-based approaches for approximating solutions to PDEs have gained increasing attention. These include successful applications to problems such as the Burgers, Eikonal, and heat equations [2], linear diffusion equations in complex two-dimensional geometries [1], and nonlinear problems such as three-dimensional PDEs, Emden–Fowler systems, and fractional-order predator–prey models [3, 9, 12].

A natural extension of this idea is the use of neural networks (NNs) as general-purpose function approximators for solving differential equations. A prototypical example arises in quantum mechanics, where one seeks to solve the eigenvalue problem

$$-\Delta u + V(x)u = Eu, \quad \text{in } \mathbb{R}^n, \tag{1}$$

with a given potential function $V\colon \mathbb{R}^n \to \mathbb{R}$ and eigenvalue parameter $E \in \mathbb{R}$. The idea of employing NNs to approximate solutions of such equations dates back to the 1990s [10], but the field gained significant momentum with the introduction of *Physics-Informed Neural Networks* (PINNs) in [16], which triggered a wave of research and applications (see also [8]).

Most early PINN-based work focused on source problems, where the term Eu in (1) is replaced by a known forcing function f. The eigenvalue problem itself has been more recently addressed: first in one dimension [6, 7, 18], and later in two dimensions [4]. Related approaches have also been proposed in [17], which include extensions to nonlinear eigenvalue problems.

Several methodologies have been proposed to address eigenvalue problems using neural networks. The approach in [18] constructs a trial wavefunction that automatically satisfies the boundary conditions,

2020 *Mathematics Subject Classification.* 35P05, 35P30, 35J92, 65N25, 68T07.

Key words and phrases. Physics-informed neural networks; eigenvalue problems; elliptic PDEs; p-Laplacian; deep learning.

represents the unknown component with a neural network, and trains the network by minimizing an appropriately defined loss function. In [6, 7], the authors introduce an unsupervised neural network architecture that simultaneously learns both the eigenvalues and the corresponding eigenfunctions through a scanning mechanism. Alternatively, [17] employs a neural network to discretize the eigenfunction and minimize the associated Rayleigh quotient.




FIGURE 1. A fully connected feedforward NN with an n-dimensional input and a 1-dimensional output.

In these works, the solution u is approximated using a fully connected feedforward neural network (see Fig. 1), with variations in the number of hidden layers and activation functions across implementations. To approximate the eigenvalue E, the authors minimize the *Rayleigh quotient*:

$$L(u) = \frac{\int |\nabla u|^2 + V(x)u^2 \, dx}{\int u^2 \, dx}.$$

Minimizing $L(u)$ yields an approximation of the principal eigenvalue E_1 and its associated eigenfunction u_1. Higher-order eigenpairs can be computed by iteratively minimizing the same functional while constraining the search to subspaces orthogonal to previously computed eigenfunctions.

This approach, while effective, presents two main limitations:

(1) It is inherently sequential: to compute eigenvalues within a given range, one must first compute all lower ones, which can be inefficient.
(2) Its extension to nonlinear problems (such as those involving the p-Laplace operator) is limited, since orthogonality conditions between eigenfunctions are no longer available.

2. Our approach

To overcome the drawbacks mentioned above, we propose a different approach to problem (1). We define the following loss function:

$$\Lambda(u, E) = \frac{\int (\Delta u - V(x)u + Eu)^2 \, dx}{\int u^2 \, dx}. \tag{2}$$

Given a fixed $E \in \mathbb{R}$, minimizing with respect to u yields a *loss curve*:

$$\Lambda(E) = \inf_u \Lambda(u, E). \tag{3}$$

A proof of the existence of a minimizer u_E for (3) is provided in Theorem 1 in the appendix.

The minima of the loss curve $\Lambda(E)$ correspond exactly to the eigenvalues of (1). Indeed, $\Lambda \geq 0$, and $\Lambda(E) = 0$ if and only if there is $u \neq 0$ with $\Delta u - Vu + Eu = 0$, i.e. if and only if E is an eigenvalue, the minimizer u_E being an associated eigenfunction. Away from the eigenvalues, expanding $u = \sum_k c_k u_k$ in the eigenfunction basis gives

$$\Lambda(u, E) = \frac{\sum_k c_k^2 (E_k - E)^2}{\sum_k c_k^2} \geq \min_k (E_k - E)^2,$$

with equality for $u = u_k$, E_k the eigenvalue closest to E.

Moreover, if u_k denote the k-th eigenfunction of (1), normalized so that $\int u_k^2 \, dx = 1$, then

$$\Lambda(E) \leq \int (\Delta u_k - V(x)u_k + Eu_k)^2 \, dx = (E_k - E)^2,$$

and hence the following theoretical upper bound holds:

$$\Lambda(E) \leq \min_k (E_k - E)^2. \tag{4}$$

This gives that in the linear case

$$\Lambda(E) = \min_k (E_k - E)^2 \tag{5}$$

Note that the characterization of eigenvalues as the zeros of Λ only uses that $\Lambda(u, E)$ is the squared residual of the equation, and not the spectral decomposition above. Hence the same mechanism applies to nonlinear eigenvalue problems, where no orthogonality between eigenfunctions is available, as shown in the examples in the *Nonlinear Problems* section 5. In the nonlinear case there is no spectral decomposition, so the identity (5) is no longer available. What survives is the mechanism itself: the loss vanishes exactly at the eigenvalues, so they can still be detected as the minima of the loss curve.

Having defined $\Lambda(E)$, the eigenvalues can be found just by scanning E and locating the local minima of Λ, with no need to know the lower ones. This is the powerfulness of the proposed method.

In Fig. 2, the upper bound of $\Lambda(E)$ for problem (1) is plotted in the two-dimensional case with a confining potential given by $V(x) = 0$ for $|x| \leq 1$ and $V(x) = \infty$ for $|x| > 1$. In this case the eigenvalues are known explicitly. The first four are:

$$E_1 = 5.7832, \; E_2 = 14.6819, \; E_3 = 26.3746, \; E_4 = 30.4713.$$




FIGURE 2. The loss curve $\Lambda(E)$ in 2−dimensional space with a confined potential in the unit disk.

Our approach proceeds as follows:

We first fix the interval $[E_*, E^*]$ where the eigenvalues are expected to lie. Then, we take a uniform partition of this interval:

$$E_* = E^1 < E^2 < \cdots < E^j = E^*,$$

and for each E^i we train our neural network to minimize $\Lambda(u, E^i)$, obtaining a corresponding minimizer u^i.

Finally, we look for zeros of the loss curve $\Lambda(E^i)$. By construction, these zeroes correspond with eigenvalues E^i of problem (1), and the associated minimizers u^i approximate the corresponding eigenfunctions.

The aim of this article is to give an approach to compute eigenvalues based on neural networks whose implementation is simple and no need of previous eigenvalues is required. Our goal is not to obtain the best estimates for linear problems (for that aim there is efficient and well-studied methods based on finite differences/elements). However, our method is highly flexible and has several adventages over other method of the literature as explained as follows.

Advantages of our method:

(1) Unlike the aforementioned methods, our approach allows the computation of higher eigenvalues without requiring the prior computation of lower ones.
(2) While other methods often face challenges when computing eigenvalues in higher dimensions, our approach has been shown to be effective regardless of the dimensionality.
(3) The computation of eigenvalues is robust and works effectively independent of the structure of the potential function V or the geometry of the domain under consideration.
(4) The neural network architecture employed in our implementation is simple and extends naturally to nonlinear cases. This enables the computation of higher eigenvalues, producing novel results in several contexts shown ir our examples. While we do not claim more accuracy compared to existing methods, our approach provides the computation of higher eigenvalues even in higher-dimensional settings.
(5) Finally, our approach can be readily adapted to more general operators beyond the p-Laplacian.

3. Implementation details

We consider a fully connected neural network, implemented as a feed-forward multilayer perceptron with three hidden layers. Each hidden layer contains 128 neurons with tanh activation functions. The network maps a spatial coordinate $x \in \mathbb{R}^d$ to a scalar output and is defined as $x \mapsto \mathrm{NN}(x) \in \mathbb{R}$. All linear layers are initialized using Xavier uniform initialization with the appropriate gain for the tanh activation, and all biases are set to zero.

To enforce the homogeneous Dirichlet boundary condition on the domain Ω, the raw network output $\tilde{u}(x)$ is multiplied by a boundary distance function $B(x)$, chosen so that

$$B(x) = 0 \text{ for all } x \in \partial\Omega, \qquad B(x) > 0 \text{ for all } x \in \Omega.$$

This construction ensures that the final approximation automatically vanishes on the boundary. Thus, the network returns

$$u(x) = B(x)\tilde{u}(x),$$

where $\tilde{u}(x)$ is the output of the multilayer perceptron.

We begin by studying the simpler case, where confining potentials, as described in the previous section, are considered. So, we let

$$V(x) = \begin{cases} 0 & \text{if } x \in \Omega \\ \infty & \text{if } x \notin \Omega, \end{cases} \tag{6}$$

which is equivalent to solving the Helmholtz problem with homogeneous Dirichlet boundary condition:

$$\begin{cases} -\Delta u = Eu & \text{in } \Omega \\ u = 0 & \text{on } \partial\Omega. \end{cases} \tag{7}$$

In this case, to impose the boundary condition, we multiply the output of the NN by a boundary factor $B(x) = 1-|x|^2$ that is a smooth approximation to the distance to the boundary. To ensure normalization, we include a penalization term in the loss function to enforce $\|u\|_2 = 1$. The resulting loss is:

$$\bar{\Lambda}(u, E) = \int_\Omega (\Delta u + Eu)^2 \, dx + \mu \left(\int_\Omega u^2 \, dx - 1 \right)^2 \tag{8}$$

with $\mu = 100$. All integrals are approximated using a Monte Carlo scheme, typically using 5000 sampling points.

As described in the previous section, we train the NN to minimize $\bar{\Lambda}(u, E)$ for each value in a discrete partition $E_* = E^1 < \cdots < E^j = E^*$. To improve efficiency, for each E^i, the network is initialized with the weights and biases obtained from training at E^{i-1}.

The model parameters are optimized using the Adam optimizer over a maximum of 3,000 epochs. During each epoch, 5,000 spatial points are dynamically sampled to compute the loss, residual, and norm. An early stopping mechanism terminates training if the loss fails to improve by at least $\varepsilon = 10^{-5}$ across 300 consecutive epochs. Upon completion of training, we obtain the discrete loss curve.

$$\bar{\Lambda}(E^i) = \bar{\Lambda}(u^i, E^i)$$

and each local minimum below a given threshold $\epsilon > 0$ is taken as an approximate eigenvalue for (7).




FIGURE 3. The loss curve $\bar{\Lambda}(E)$ in two-dimensional space with a confined potential in the unit disk compared with the theoretical upper bound.

Fig. 3 shows the loss curve $\bar{\Lambda}(E^i)$ in the case where Ω is the unit disk in $\mathbb{R}^2$. The computed eigenvalues are accurate up to the resolution of the discretized E^i-grid. Naturally, once an approximate eigenvalue E^{i_0} is detected, the method can be refined locally by using a finer grid in the interval $[E^{i_0-1}, E^{i_0+1}]$ to improve precision.

The associated computed eigenfunctions are displayed in Fig. 4

Eigenvalue accuracy versus PDE residual. We stress that the eigenvalue error and the PDE residual measure different things. Let $L = -\Delta + V$ and, for the computed u, set

$$r(u, E) = \frac{\|(L - E)u\|_2}{\|u\|_2} = \Lambda(u, E)^{1/2}.$$

Since L is self-adjoint, the classical Weinstein (Krylov–Bogoliubov) bound [19, 13] gives

$$\operatorname{dist}\big(E, \sigma(L)\big) \le r(u, E),$$

where $\sigma(L)$ denotes the spectrum of L. This follows from the identity $\|(L-E)^{-1}\| = \operatorname{dist}(E, \sigma(L))^{-1}$ for self-adjoint operators. In particular, the residual controls the accuracy of the eigenvalue: every interval $[E - r(u, E),\ E + r(u, E)]$ contains at least one eigenvalue of L. This control is, however, only one-sided: a small eigenvalue error does not force a small residual, and in practice the actual error is well below $r(u, E)$. Moreover, in our method the eigenvalue is not read off from u but from the location of the minimum of $\bar{\Lambda}(E) \approx (E - E_k)^2 + \eta(E)$, where η accounts for optimization, sampling and approximation errors. A nearly constant floor η does not shift the minimizer, so the eigenvalue can be accurate up to the resolution of the E-grid while the residual at the minimum remains comparatively large. The residual therefore measures the accuracy of the eigenfunction and the satisfaction of the PDE, whereas the relative error measures the accuracy of the eigenvalue.

For the nonlinear problems the Weinstein bound is no longer available, since it relies on the spectral theory of self-adjoint operators. Nevertheless, Tables 5 and 6 show the same behavior as in the linear case: accurate eigenvalues together with comparatively large residuals.




FIGURE 4. The first four computed eigenfunctions of (7) in the 2−dimensional unit disk.

4. FURTHER EXAMPLES

In this section, we illustrate the flexibility and robustness of our method by applying it to a variety of settings beyond the two-dimensional unit disk with a confining potential. These examples include the computation of higher-order eigenvalues, problems in higher spatial dimensions, domains with different geometries, and more general potential functions.

All computations and plots presented in this article were generated using the code provided in the 'Code Availability' section.

4.1. **Higher eigenvalues.** Our method enables the computation of higher-order eigenvalues without relying on sequential orthogonalization procedures. By choosing an appropriate interval $[E_*, E^*]$ and refining the discretization grid, we can directly recover eigenvalues that are far from the principal one.

One technical point that must be considered when computing higher eigenvalues is the appropriate choice of the hyperparameter μ in the loss function (8). For a randomly initialized NN output u, the first term in the loss is typically of the order

$$\int_\Omega (\Delta u + Eu)^2 \, dx \sim c_1 E^2 + c_2,$$

while the normalization penalty term is of the order

$$\mu \left(\int_\Omega u^2 \, dx - 1 \right)^2 \sim c_3 \mu.$$

Hence, if $E^2 \gg \mu$, the loss is dominated by the first term, and the network tends to minimize it by driving $u \approx 0$, which is undesirable. To maintain a proper balance between the two terms and ensure meaningful training, it is necessary to scale $\mu \propto E^2$.

To assess the accuracy of our method, we computed the eigenvalues of problem (7) in the two-dimensional unit square $[0,1] \times [0,1]$ that lie within the interval $[44, 55]$. In this case we have taken $\mu = 3000$ and an early stopping mechanism terminates training if the loss fails to improve by at least $\varepsilon = 10^{-5}$ across 300 consecutive epochs. In this range, problem (7) has one eigenvalue, denoted $E_{(1)}$, with value $E_{(1)} = 49.348$. See Fig. 5 for the computed loss curve in this interval, together with the theoretical upper bound.

For illustrative purposes, we compute the eigenvalues of (7) in the two-dimensional unit square. In Table 1 we compare the exact eigenvalues with those obtained by our method, together with the relative error and residuals. In Figures 7 and 8 we display the loss curve $\bar{\Lambda}(E)$ alongside the theoretical upper bound, as well as the first two eigenfunctions.

These computations can be readily carried out for different potentials; however, in such cases, exact eigenvalues are not available for comparison.




FIGURE 5. The loss curve $\bar{\Lambda}(E)$ in two-dimensional space in the unit square computed in the interval [44,55].

m	n	$E_{(m,n)} = \pi^2(m^2+n^2)$	Our method	Relative error	Residual
1	1	$2\pi^2 \approx 19.739$	19.739033	8.9×10^{-6}	6.72×10^{-3}
1	2	$5\pi^2 \approx 49.348$	49.385078	7.5×10^{-4}	1.16×10^{-1}
2	2	$8\pi^2 \approx 78.956$	78.962188	6.78×10^{-5}	1.26×10^{-1}
1	3	$10\pi^2 \approx 98.696$	98.594123	1.03×10^{-3}	1.40×10^{-3}

TABLE 1. Eigenvalues of problem (7) in the two-dimensional unit square $[0,1] \times [0,1]$ compared with the exact values.

4.2. **Higher dimensions.** The proposed framework extends naturally to higher spatial dimensions, with minimal changes required in the implementation. As an example, we consider the unit ball in $\mathbb{R}^d$, with $d = 3, 4$ where the eigenvalue problem becomes:

$$\begin{cases} -\Delta u = Eu & \text{in } B^d \\ u = 0 & \text{on } \partial B^d. \end{cases}$$

Despite the increased computational cost, the method remains effective, as shown in Fig. 6. In this example we considered $\mu = 200$ and an early stopping mechanism terminates training if the loss fails to improve by at least $\varepsilon = 10^{-5}$ across 300 consecutive epochs.

In dimension $d = 3$, exact formulas for the eigenvalues are known, for $m, n \in \mathbb{N}$, the eigenvalues are computed as $E_{(m,n)} = j_{m,n}^2$, where $j_{m,n}$ denotes the $n-$th positive zero of the Bessel function $J_{m+\frac{1}{2}}$. Similarly, when $d = 4$, the eigenvalues are given by $E_{(m,n)} = y_{m,n}^2$, where $y_{m,n}$ denotes the $n-$th positive zero of the Bessel function J_{m+1}.

In Tables 2 and 3, we compare the exact eigenvalues with those obtained by our method.

m	n	$E_{(m,n)} = j_{m,n}^2$	Our method	Relative error	Residual
0	1	$j_{0,1}^2 \approx 9.8696$	9.885022	1.56×10^{-3}	8.61×10^{-2}
1	1	$j_{1,1}^2 \approx 20.1907$	20.182569	4.04×10^{-4}	4.59×10^{-2}
2	1	$j_{2,1}^2 \approx 33.2175$	33.243410	7.81×10^{-4}	1.00×10^{-1}
0	2	$j_{0,2}^2 \approx 39.4784$	39.494155	3.99×10^{-4}	1.81×10^{-1}
3	1	$j_{3,1}^2 \approx 48.8312$	48.826976	8.64×10^{-5}	2.24×10^{-1}
1	2	$j_{1,2}^2 \approx 59.6795$	59.734069	9.14×10^{-4}	2.04×10^{-1}
4	1	$j_{4,1}^2 \approx 66.9543$	66.991853	5.61×10^{-4}	4.82×10^{-1}

TABLE 2. Eigenvalues of problem (7) in the unit ball in $\mathbb{R}^3$ compared with the exact values.

m	n	$E_{(m,n)} = y_{m,n}^2$	Our method	Relative error	Residual
0	1	$y_{0,1}^2 \approx 14.6819$	14.641796	2.73×10^{-3}	3.84×10^{-3}
1	1	$y_{1,1}^2 \approx 26.3746$	26.257056	4.47×10^{-3}	2.13×10^{-1}
2	1	$y_{2,1}^2 \approx 40.7064$	40.794700	2.16×10^{-3}	1.98×10^{-1}
0	2	$y_{0,2}^2 \approx 49.2184$	49.175395	8.74×10^{-4}	6.04×10^{-1}

TABLE 3. Eigenvalues of problem (7) in the unit ball in $\mathbb{R}^4$ compared wih the exact values.




FIGURE 6. The loss curve $\bar{\Lambda}(E)$ in three-dimensional space (above) and in the four-dimensional space (below) in the unit ball compared with the theoretical upper bound.

4.3. **Different geometries.** We also explore domains with more complex geometries, such as squares, annuli, or triangles. The boundary factor $B(x)$ can be adapted to these shapes, ensuring that the Dirichlet condition is enforced. In Fig. 8, we show eigenfunctions obtained in a square, in Fig. 9 the annular region is considered and in Fig. 10 and 11 the results in a triangle are shown. In that example we considered $\mu = 15000$ and an early stopping mechanism terminates training if the loss fails to improve by at least $\varepsilon = 10^{-5}$ across 300 consecutive epochs.

In Table 4, the exact eigenvalues of (7) in a triangle are compared with those obtained by our method.

m	n	$E_{m,n} = \pi^2(m^2+n^2)$	Our method	Relative error	residual
1	2	$5\pi^2 \approx 49.348$	49.369942	4.44×10^{-4}	2.42×10^{-1}
2	1	$5\pi^2 \approx 49.348$	49.369942	4.44×10^{-4}	2.42×10^{-1}
1	3	$10\pi^2 \approx 98.696$	98.892161	1.99×10^{-3}	1.26×10^{0}
3	1	$10\pi^2 \approx 98.696$	98.892161	1.99×10^{-3}	1.26×10^{0}
2	3	$13\pi^2 \approx 128.3049$	128.048509	2.00×10^{-3}	1.98×10^{0}
3	2	$13\pi^2 \approx 128.3049$	128.048509	2.00×10^{-3}	1.98×10^{0}
1	4	$17\pi^2 \approx 167.7833$	167.687185	5.73×10^{-4}	2.16×10^{0}
4	1	$17\pi^2 \approx 167.7833$	167.687185	5.73×10^{-4}	2.16×10^{0}

TABLE 4. Eigenvalues of problem (7) in the two-dimensional triangle with vertices $(0,0)$, $(0,1)$, $(1,0)$ compared with the exact values.




FIGURE 7. The loss curve $\bar{\Lambda}(E)$ in two-dimensional space in the unit square compared with the theoretical upper bound.




FIGURE 8. The first two computed eigenfunctions in the unit square.




FIGURE 9. The loss curve $\bar{\Lambda}(E)$ in two-dimensional space in the unit annulus of radii 0.5 and 1 compared with the theoretical upper bound. Below it is displayed the first eigenfunction.




FIGURE 10. The loss curve $\bar{\Lambda}(E)$ in two-dimensional space in the triangle of vertices $(0,0)$, $(0,1)$, $(1,0)$ compared with the theoretical upper bound.




FIGURE 11. Third and fourth computed eigenfunctions in the triangle of vertices $(0,0)$, $(0,1)$, $(1,0)$.

4.4. **Different potentials.** Beyond hard-wall confinement, our approach accommodates general potential functions $V(x)$, including smooth wells, multi-well potentials, step-like profiles, compactly supported wells, among others.

As an example, we consider a harmonic potential $V(x) = \frac{\omega^2}{2}|x|^2$ for different values of ω, illustrating the method's applicability to physically relevant models. Fig. 13 displays loss curve and the first eigenfunction for $\omega = 1$ and Fig. 12 for $\omega = 10$. In Fig. 17, we display the three-dimensional double-well Gaussian potential $V(x) = -e^{-2|x-x_0|^2} - e^{-2|x+x_0|^2}$, $x_0 = (1,0,0)$, together with the loss curve.

Finally, in Fig. 18 we consider a three-dimensional four-well compactly supported potential and we plot the corresponding loss curve. More precisely, given $w = (x,y,z) \in \mathbb{R}^3$, and define the centers of the four wells as $c_1 = (a,a,0)$, $c_2 = (-a,a,0)$, $c_3 = (a,-a,0)$, $c_4 = (-a,-a,0)$, where $a = 0.22$. Also, let $r_i = \|w - c_i\|$, $\tilde{r}_i = \frac{r_i}{\sigma}$ with $\sigma = 0.2$. We define the compactly supported bump function

$$\phi(\tilde{r}) = \begin{cases} \exp(-(1-\tilde{r}^2)^{-1}), & \tilde{r} < 1, \\ 0, & \tilde{r} \geq 1. \end{cases}$$

Then, the potential $V(w)$ is defined as $V(x) = -\sum_{i=1}^{4} \phi\Big(\frac{\|x-c_i\|}{\sigma}\Big)$, $\quad V_0 = 1$.

In four three examples we have chosen $\mu = 400$, $\mu = 400$ and $\mu = 1000$, respectively, and an early stopping mechanism terminates training if the loss fails to improve by at least $\varepsilon = 10^{-5}$ across 300 consecutive epochs.




FIGURE 12. The loss curve $\bar{\Lambda}(E)$ in two-dimensional disk with harmonic potential $V = \frac{\omega^2}{2}|x|^2$ and $\omega = 10$ with the first computed eigenfunction.




FIGURE 13. The loss curve $\bar{\Lambda}(E)$ in two-dimensional disk with harmonic potential $V = \frac{\omega^2}{2}|x|^2$ and $\omega = 1$ with the first computed eigenfunction.

5. NONLINEAR PROBLEMS

Our method can also be extended to nonlinear eigenvalue problems. As an illustrative example, we consider the eigenvalue problem for the $p-$Laplacian in the two-dimensional unit disk:

$$\begin{cases} -\nabla \cdot (|\nabla u|^{p-2}\nabla u) = E|u|^{p-2}u & \text{in } D, \\ u = 0 & \text{on } \partial D, \end{cases} \tag{9}$$

where $D \subset \mathbb{R}^2$ is the unit disk and $p > 1$.

To approximate the solution using our framework, we modify the loss function accordingly. For a fixed E, we define the following loss:

$$\Lambda_p(u, E) = \int \left(\Delta_p u + E|u|^{p-2}u\right)^2 dx + \mu \left(\int |u|^p \, dx - 1\right)^2,$$

where $\Delta_p u = \nabla \cdot (|\nabla u|^{p-2}\nabla u)$.

As in the linear case, define the loss curve $\Lambda_p(E) = \inf_u \Lambda_p(u, E)$. If u_k is an eigenfunction of (9) with eigenvalue E_k and $\|u_k\|_p = 1$, then $\Delta_p u_k = -E_k|u_k|^{p-2}u_k$, the penalty term vanishes and

$$\Lambda_p(u_k, E) = \int \left(\Delta_p u_k + E|u_k|^{p-2}u_k\right)^2 dx = (E - E_k)^2 \int |u_k|^{2(p-1)}\, dx.$$

Hence

$$\Lambda_p(E) \le \min_k c_k\,(E - E_k)^2, \qquad c_k := \int |u_k|^{2(p-1)}\, dx,$$

which reduces to (4) when $p = 2$, since then $c_k = \|u_k\|_2^2 = 1$. In particular $\Lambda_p(E_k) = 0$ for every eigenvalue, while $\Lambda_p(u, E) = 0$ with $\|u\|_p = 1$ holds only if u is an eigenfunction with eigenvalue E. Unlike the linear case, we only have this upper bound: there is no spectral decomposition giving a matching lower bound, so the shape of Λ_p between consecutive eigenvalues is not determined, and the constants c_k depend on the eigenfunctions and on p.

Here, the normalization condition is adapted to the natural scaling of the $p-$Laplacian: $\|u_k\|_p = 1$. As in the linear case, the output of the neural network is multiplied by a boundary factor to enforce homogeneous Dirichlet boundary conditions.

Since the nonlinear problem lacks an orthogonality structure among eigenfunctions, traditional sequential methods based on orthogonal projections are not directly applicable. Our approach, however, remains valid and does not rely on any such structure, which makes it suitable for problems like (9). As a result, we are still able to detect the first two eigenvalues as the values of E at which the loss attains a sufficiently small minimum.

In Table 5, for $p = 2.2$, we compare our computations with the numerical values of (9) reported in [5], where a variant of the Constrained Steepest Descent Method was used to compute the first eigenpair and the Constrained Mountain Pass Algorithm to compute the second eigenpair. Figures 14 and 15 show the loss curve and the corresponding eigenfunctions.

For the experiments in the $p-$Laplacian equation we have taken $\mu = 4000$ and an early stopping mechanism terminates training if the loss fails to improve by at least $\varepsilon = 10^{-5}$ across 300 consecutive epochs.

We emphasize that our method extends naturally to the computation of eigenvalues of the $p-$Laplacian in higher dimensions. To the best of our knowledge, no previous numerical results are available for this setting. Figure 16 shows the loss curve obtained for the $p-$Laplacian on the unit ball in dimension $d = 3$.

Table 6 exhibits the same comparison when the domain D is the square $[0, 2] \times [0, 2]$.

k	Numerical E_k from [5]	Our result	Relative error	Residual
1	6.5320	6.679258	2.25×10^{-2}	1.81×10^{0}
2	18.395	19.441806	5.69×10^{-2}	9.65×10^{-1}
-	-	37.621714		1.82×10^{0}

TABLE 5. Eigenvalues of the $p-$Laplacian with $p = 2.2$ in the planar unit ball compared with numerical values obtained in [5].

k	Numerical E_k from [5, Table 2]	Our result	Relative error	Residual
1	5.4952	5.861383	6.66×10^{-2}	6.22×10^{-2}
2	15.144	15.144490	3.24×10^{-5}	1.64×10^{0}

TABLE 6. Eigenvalues of the $p-$Laplacian with $p = 2.2$ in the planar square of lenght 2 compared with numerical values obtained in [5].




FIGURE 14. The loss curve $\bar{\Lambda}(E)$ in two-dimensional space for the p-Laplacian with $p = 2.2$ in the unit disk.




FIGURE 15. The first two computed eigenfunctions in two-dimensional space for the p-Laplacian with $p = 2.2$ in the unit disk




FIGURE 16. The loss curve $\bar{\Lambda}(E)$ in three-dimensional space for the p-Laplacian with p=2.5 in the unit disk. This gives $E_1 = 17.4513$ and $E_2 = 45.8908$.




FIGURE 17. The loss curve $\bar{\Lambda}(E)$ in three-dimensional space for the Laplacian with a double-well Gaussian potential in the unit disk.




FIGURE 18. The loss curve $\bar{\Lambda}(E)$ in three-dimensional space for the Laplacian with a Compactly supported four-well potential in the unit disk.

CODE AVAILABILITY

The Python code used in this work is openly accessible at the following URL:

https://github.com/amsalort/PINN-eigenvalues

6. CONCLUSIONS

The method proposed in this work provides a flexible and effective framework for computing eigenvalues and eigenfunctions of differential operators using neural networks. Unlike classical approaches, it does not rely on the Rayleigh quotient or require orthogonality conditions between eigenfunctions. As a result, it is particularly well-suited for computing higher eigenvalues and for addressing nonlinear problems where such structures are no longer available.

Moreover, the approach naturally extends to irregular domains and high-dimensional settings, where traditional mesh-based methods become increasingly difficult to apply. Its non-sequential nature allows for the identification of multiple eigenvalues without the need to compute the entire spectrum in order. These features make it a robust and broadly applicable alternative for spectral problems in both linear and nonlinear contexts.

Funding

This work was partially supported by ANPCyT under grant PICT 2019-3837 and by CONICET under grant PIP 11220150100032CO.

Acknowledgements

JFB thanks Pablo Groisman for encouraging him to teach a course on the Mathematical Foundations of Deep Learning in the fall semester of 2025, which inspired the author to pursue this problem.

Appendix A. The minimization problem

In this appendix, we show that the minimization problem leading to the loss curve $\Lambda(E)$ defined in (3) admits a solution. In order to keep things simple, we consider the case in which $V(x)$ is a confining potential of the form (6) with $\Omega \subset \mathbb{R}^n$ bounded.

To this end, we must specify the function space over which the infimum is taken. The natural choice is the Sobolev space $H^2(\Omega) \cap H_0^1(\Omega)$. The main result of this section reads as follows:

Theorem 1. *Let $V(x)$ be as in (6) with $\Omega \subset \mathbb{R}^n$ bounded. Given $E \geq 0$, there exists $u_E \in H^2(\Omega) \cap H_0^1(\Omega)$ such that*

$$\Lambda(E) = \Lambda(u_E, E) = \inf_{u \in H^2(\Omega) \cap H_0^1(\Omega)} \Lambda(u, E),$$

where $\Lambda(u, E)$ is given in (2).

Proof. The result follows from the *direct method in the Calculus of Variations*. Fix $E \geq 0$, and consider a minimizing sequence $\{u_j\}_{j \in \mathbb{N}} \subset H^2(\Omega) \cap H_0^1(\Omega)$ such that $\|u_j\|_2 = 1$ and

$$\Lambda(E) = \lim_{j \to \infty} \Lambda(u_j, E).$$

In particular, the sequence $\Lambda(u_j, E)$ is bounded and nonnegative:

$$0 \leq \Lambda(u_j, E) \leq C, \tag{10}$$

for some constant $C > 0$. Now observe that

$$\Lambda(u_j, E) = \int_\Omega (\Delta u_j + E u_j)^2 \, dx = \int_\Omega (\Delta u_j)^2 \, dx + 2E \int_\Omega u_j \Delta u_j \, dx + E^2.$$

Using the inequality $ab \leq \epsilon a^2 + \frac{b^2}{4\epsilon}$ for any $a, b > 0$ and $\epsilon > 0$ we estimate:

$$\int_\Omega |u_j||\Delta u_j| \, dx \leq \epsilon \int_\Omega (\Delta u_j)^2 \, dx + \frac{1}{4\epsilon} \int_\Omega u_j^2 \, dx.$$

Taking $\epsilon = 1/4E$, we obtain

$$\Lambda(u_j, E) \geq \frac{1}{2} \int_\Omega (\Delta u_j)^2 \, dx + E^2 - E. \tag{11}$$

Combining (10), (11) and the normalization $\|u_j\|_2 = 1$ we conclude that the sequence $\{u_j\}_{j \in \mathbb{N}}$ is bounded in $H^2(\Omega) \cap H_0^1(\Omega)$.

Therefore, up to a subsequence, we have $u_j \rightharpoonup u_E$ weakly in $H^2(\Omega) \cap H_0^1(\Omega)$ for some u_E in that space.

Since the functional

$$u \mapsto \int_\Omega (\Delta u + E u)^2 \, dx$$

is convex in u, it is weakly lower semicontinuous. Thus,

$$\int_\Omega (\Delta u_E + E u_E)^2 \, dx \leq \liminf_{j \to \infty} \int_\Omega (\Delta u_j + E u_j)^2 \, dx.$$

Moreover, the immersion $H^2(\Omega) \cap H_0^1(\Omega) \hookrightarrow L^2(\Omega)$ is compact, so

$$\int_\Omega u_E^2 \, dx = \lim_{j\to\infty} \int_\Omega u_j^2 \, dx = 1.$$

Hence, u_E is admissible and attains the minimum. □

References

[1] J. Berg and K. Nyström, A unified deep artificial neural network approach to partial differential equations in complex geometries, Neurocomputing **317**, 28 (2018).

[2] J. Blechschmidt and O. G. Ernst, Three ways to solve partial differential equations with neural networks—a review, GAMM-Mitt. **44**, e202100006 (2021).

[3] F. Ghazi and L. Tawfiq, Design optimal neural network based on new LM training algorithm for solving 3D-PDEs, An International Journal of Optimization and Control: Theories & Applications **14**, 249 (2024).

[4] E. G. Holliday, J. F. Lindner, and W. L. Ditto, Solving quantum billiard eigenvalue problems with physics-informed machine learning, *AIP Advances* **13**, 085013 (2023).

[5] J. Horák, Numerical investigation of the smallest eigenvalues of the p-Laplace operator on planar domains, Electron. J. Differential Equations, No. 132, 30 pp. (2011).

[6] H. Jin, M. Mattheakis, and P. Protopapas, Unsupervised neural networks for quantum eigenvalue problems, in *Proceedings of the 2020 NeurIPS Workshop on Machine Learning and the Physical Sciences* (Vancouver, Canada, 2020).

[7] H. Jin, M. Mattheakis, and P. Protopapas, Physics-informed neural networks for quantum eigenvalue problems, in *Proceedings of the 2022 International Joint Conference on Neural Networks (IJCNN)* (IEEE, 2022).

[8] G. E. Karniadakis, I. G. Kevrekidis, L. Lu, P. Perdikaris, S. Wang, and L. Yang, Physics-informed machine learning, Nat. Rev. Phys. **3**, 422 (2021).

[9] A. Kumar, M. Kumar, and P. Goswami, Numerical solution of coupled system of Emden-Fowler equations using artificial neural network technique, An International Journal of Optimization and Control: Theories & Applications **14** (2024).

[10] I. E. Lagaris, A. Likas, and D. I. Fotiadis, Artificial neural networks for solving ordinary and partial differential equations, IEEE Trans. Neural Netw. **9**, 987 (1998).

[11] L. Lu, X. Meng, Z. Mao, and G. E. Karniadakis, DeepXDE: a deep learning library for solving differential equations, SIAM Rev. **63**, 208 (2021).

[12] N. Madani, Z. Hammouch, and N. Ozdemir, Hybrid GA-IPA and neural network-based solution for fractional-order nonlinear predator-prey dynamical systems, Nonlinear Dyn. **113**, 32979 (2025).

[13] B. N. Parlett, *The Symmetric Eigenvalue Problem*, Classics in Applied Mathematics, Vol. 20 (SIAM, Philadelphia, 1998).

[14] C. Rackauckas, M. Innes, Y. Ma, J. Bettencourt, L. White, and V. Dixit, DiffEqFlux.jl – a Julia library for neural differential equations (2019), arXiv:1902.02376 [cs.LG].

[15] C. Rackauckas, Y. Ma, J. Martensen, C. Warner, K. Zubov, R. Supekar, D. Skinner, A. Ramadhan, and A. Edelman, Universal differential equations for scientific machine learning (2021), arXiv:2001.04385 [cs.LG].

[16] M. Raissi, P. Perdikaris, and G. E. Karniadakis, Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations, J. Comput. Phys. **378**, 686 (2019)

[17] C. Rowan, J. Evans, K. Maute, and A. Doostan, Solving engineering eigenvalue problems with neural networks using the Rayleigh quotient, International Journal for Numerical Methods in Engineering, 126(24), e70209.

[18] S. Sarkar, Physics-informed neural networks for one-dimensional quantum well problems, arXiv preprint (2025).

[19] D. H. Weinstein, Modified Ritz method, Proc. Natl. Acad. Sci. USA **20**, 529 (1934).

Departamento de Matemática, Facultad de Ciencias Exactas y Naturales, Universidad de Buenos Aires, Buenos Aires, Argentina, and Instituto de Cálculo UBA-CONICET, Buenos Aires, Argentina

Email address: jfbonder@dm.uba.ar

Departamento de Matemáticas Aplicadas y Ciencia de Datos, Universidad San Pablo-CEU, CEU Universities, Julián Romea 2, 28003 Madrid, Spain

Email address: ariel.salort@ceu.es