

Package ‘TOC’

April 9, 2015

Type Package

Title Total Operating Characteristic (TOC) Curve and ROC Curve

Version 0.0-2

Date 2015-03-28

Author Robert G. Pontius <rpontius@clarku.edu>, Ali Santacruz, Amin Tayyebi, Benoit Parmentier, Kangping Si

Maintainer Ali Santacruz <amsantac@unal.edu.co>

Depends R (>= 2.14.0), raster, bit, rgdal, methods

Description Construction of the Total Operating Characteristic (TOC) Curve and the Receiver (aka Relative) Operating Characteristic (ROC) Curve for spatial and non-spatial data.

License GPL (>= 2)

Encoding UTF-8

R topics documented:

TOC-package	1
plot	2
ROC	3
roctable	5
scaling	6
TOC	7
Toc-class	8
Toc-methods	9
uncertainty	9

Index	11
--------------	-----------

TOC-package	<i>Total Operating Characteristic (TOC) Curve and ROC Curve</i>
-------------	---

Description

Construction of the Total Operating Characteristic (TOC) Curve and the Receiver (aka Relative) Operating Characteristic (ROC) Curve for spatial and non-spatial data.

Details

Package: TOC
 Type: Package
 Version: 0.0-2
 Date: 2015-03-28
 License: GPL (≥ 2)
 LazyLoad: yes

Author(s)

Robert G. Pontius <rpontius@clarku.edu>, Ali Santacruz, Amin Tayyebi, Benoit Parmentier, Kang-ping Si

Maintainer: Ali Santacruz <amsantac@unal.edu.co>

See Also

[TOC](#), [plot](#)

plot

Plot an object of class Toc or Roc

Description

Plot a Total Operating Characteristic (TOC) curve or a Relative Operating Characteristic (ROC) curve

Usage

```
## S4 method for signature 'Toc'
plot(x, labelThres=FALSE, modelLeg="Model", digits=3, nticks=5, ...)
```

```
## S4 method for signature 'Roc'
plot(x, labelThres=FALSE, modelLeg="Model", digits=3, ...)
```

Arguments

x	An object of class Toc or Roc
labelThres	logical, default to FALSE. If TRUE, thresholds are labeled in the TOC plot
modelLeg	a character string for labeling the model in the legend
digits	integer indicating the number of decimal places (round) or significant digits (signif) to be used for labeling the thresholds and the numeric axes. Negative values are allowed. See Details in the round function
nticks	number of tickmarks to be drawn along the axes
...	additional parameters to be passed to plot or axis

Value

a plot showing the TOC or the ROC curves

See Also

[TOC](#), [ROC](#)

Examples

```
## Not run:
index <- raster("p_built01_suitability_1.rst")
boolean <- raster("BuiltGain1985_1999.rst")
mask <- raster("1985NonBuilt01.rst")
tocd <- TOC(index, boolean, mask)
plot(tocd, main="TOC curve")
rocd <- ROC(index, boolean, mask)
plot(rocd, main="ROC curve")

## End(Not run)

## Not run:
index <- raster("Prob_Map2.rst")
boolean <- raster("Change_Map2b.rst")
mask <- raster("MASK3.rst")
tocd <- TOC(index, boolean, mask, nthres=100)
plot(tocd, main="TOC curve")
rocd <- ROC(index, boolean, mask, nthres=100)
plot(rocd, main="ROC curve")

## End(Not run)
```

ROC

Construct the table for the ROC curve

Description

Construct the table for the Relative Operating Characteristic (ROC) curve for spatial or non-spatial data

Usage

```
## S4 method for signature 'numeric,numeric'
ROC(index, boolean, mask=NULL, nthres=NULL, thres=NULL, NAval=0, progress=FALSE)

## S4 method for signature 'RasterLayer,RasterLayer'
ROC(index, boolean, mask=NULL, nthres=NULL, thres=NULL, NAval=0, progress=FALSE)
```

Arguments

index	index object of class numeric or RasterLayer
boolean	boolean object of class numeric or RasterLayer
mask	mask object of class numeric or RasterLayer

<code>nthres</code>	an optional integer indicating the number of equal-interval thresholds to be evaluated for the ROC curve. See Details below
<code>thres</code>	an optional numeric vector of thresholds to be evaluated for the ROC curve. See Details below
<code>NAval</code>	value for nodata (NA values) in the mask object
<code>progress</code>	logical; if TRUE, a progress bar is shown

Details

thresholds are calculated as the unique values of the index object after masking out NA values (default option), if neither `nthres` nor `thres` is provided. The default option can be time-consuming if the amount of unique values in the index object (after masking out NA values) is large (e.g., > 1000). In the latter case, the user may prefer to enter specified thresholds (with the `thres` argument), or to indicate the number of equal-interval thresholds to be evaluated for the ROC curve (with the `nthres` argument)

Value

an object of class `Roc` containing the ROC table, the area under the curve (AUC), maximum AUC and minimum AUC

See Also

[plot](#)

Examples

```
## Not run:
index <- raster("p_built01_suitability_1.rst")
boolean <- raster("BuiltGain1985_1999.rst")
mask <- raster("1985NonBuilt01.rst")

# all unique values of the index map after applying the mask are used as thresholds (default
# option)
rocd <- ROC(index, boolean, mask)
rocd

# thresholds can also be defined by indicating the number of equal-interval thresholds
rocd <- ROC(index, boolean, mask, nthres=10)
rocd

# A vector of thresholds can be used to define the thresholds
rocd <- ROC(index, boolean, mask, thres=seq(0, 100, by=10))
rocd

## End(Not run)
## Not run:
index <- raster("Prob_Map2.rst")
boolean <- raster("Change_Map2b.rst")
mask <- raster("MASK3.rst")

# thresholds can also be defined by indicating the number of equal-interval thresholds
rocd <- ROC(index, boolean, mask, nthres=100)
rocd
```

```
# A vector of thresholds can be used to define the thresholds
rocd <- ROC(index, boolean, mask, thres=seq(0, 100, by=10))
rocd

## End(Not run)
```

roctable	<i>Construct a basic ROC table</i>
----------	------------------------------------

Description

TOC internal function. Construct a basic ROC table

Usage

```
roctable(indval, boolval, maskval=NULL, nthres=NULL, thres=NULL, NAval=0,
         progress=FALSE, ones.bool=NULL, zeros.bool=NULL)
```

Arguments

indval	numeric index vector
boolval	numeric boolean vector
maskval	numeric mask vector
nthres	an optional integer indicating the number of equal-interval thresholds to be evaluated for the TOC curve. See Details below
thres	an optional numeric vector of thresholds to be evaluated for the TOC curve. See Details below
NAval	value for nodata (NA values) in the mask map
progress	logical; if TRUE, a progress bar is shown
ones.bool	numeric value indicating total number of 1's in the boolean vector
zeros.bool	numeric value indicating total number of 0's in the boolean vector

Value

a data.frame with a basic ROC table and a numeric value for minimum value in the index vector

Note

This function is not meant to be called by users directly

scaling

scale the output TOC values and change units

Description

scale the 'Hits' and 'Hits+FalseAlarms' values in the TOC output table, as well as the prevalence and population, using a scaling factor. Labels for the modified units in the TOC object are changed to newUnits

Usage

```
## S4 method for signature 'Toc'
scaling(x, scalingFactor, newUnits)
```

Arguments

x	an object of class Toc
scalingFactor	numeric value to scale 'Hits' and 'Hits+FalseAlarms' values in the TOC output table, as well as the prevalence and population
newUnits	charater string for the new data units in the TOC object

Value

an object of class TOC

See Also

[TOC](#), [ROC](#)

Examples

```
## Not run:
index <- raster("p_built01_suitability_1.rst")
boolean <- raster("BuiltGain1985_1999.rst")
mask <- raster("1985NonBuilt01.rst")
tocd <- TOC(index, boolean, mask)
plot(tocd)

# scale units from square m to square km
tocd_sqkm <- scaling(tocd, scalingFactor=1000000, newUnits="square km")
plot(tocd_sqkm)

## End(Not run)
## Not run:
index <- raster("Prob_Map2.rst")
boolean <- raster("Change_Map2b.rst")
mask <- raster("MASK3.rst")
tocd <- TOC(index, boolean, mask, nthres=100)
plot(tocd)

# scale units from square m to square km
tocd_sqkm <- scaling(tocd, scalingFactor=1000000, newUnits="square km")
```

```
plot(tocd_sqkm)

## End(Not run)
```

TOC

Construct the table for the TOC curve

Description

Construct the table for the Total Operating Characteristic (TOC) curve for spatial or non-spatial data

Usage

```
## S4 method for signature 'numeric,numeric'
TOC(index, boolean, mask=NULL, nthres=NULL, thres=NULL, NAval=0, P=NA, Q=NA,
progress=FALSE, units=NULL)
## S4 method for signature 'RasterLayer,RasterLayer'
TOC(index, boolean, mask=NULL, nthres=NULL, thres=NULL, NAval=0, P=NA, Q=NA,
progress=FALSE, units=NULL)
```

Arguments

index	index object of class numeric or RasterLayer
boolean	boolean object of class numeric or RasterLayer
mask	mask object of class numeric or RasterLayer
nthres	an optional integer indicating the number of equal-interval thresholds to be evaluated for the TOC curve. See Details below
thres	an optional numeric vector of thresholds to be evaluated for the TOC curve. See Details below
NAval	value for nodata (NA values) in the mask object
P	count of reference presence observations in the population
Q	count of reference absence observations in the population
progress	logical; if TRUE, a progress bar is shown
units	character string indicating data units

Details

thresholds are calculated as the unique values of the index object after masking out NA values (default option), if neither `nthres` nor `thres` is provided. The default option can be time-consuming if the amount of unique values in the index object (after masking out NA values) is large (e.g., > 1000). In the latter case, the user may prefer to enter specified thresholds (with the `thres` argument), or to indicate the number of equal-interval thresholds to be evaluated for the TOC curve (with the `nthres` argument)

Value

an object of class `Toc` containing the TOC table, the area under the curve (AUC), maximum AUC and minimum AUC, the prevalence, the population and the data units (for data in the TOC table slot, and the prevalence and population slots)

See Also

[plot](#)

Examples

```
## Not run:
index <- raster("p_built01_suitability_1.rst")
boolean <- raster("BuiltGain1985_1999.rst")
mask <- raster("1985NonBuilt01.rst")

# all unique values of the index map after applying the mask are used as thresholds (default
# option)
tocd <- TOC(index, boolean, mask)
tocd

# thresholds can also be defined by indicating the number of equal-interval thresholds
tocd <- TOC(index, boolean, mask, nthres=10)
tocd

# A vector of thresholds can be used to define the thresholds
tocd <- TOC(index, boolean, mask, thres=seq(0, 100, by=10))
tocd

## End(Not run)
## Not run:
index <- raster("Prob_Map2.rst")
boolean <- raster("Change_Map2b.rst")
mask <- raster("MASK3.rst")

# thresholds can also be defined by indicating the number of equal-interval thresholds
tocd <- TOC(index, boolean, mask, nthres=100)
tocd

# A vector of thresholds can be used to define the thresholds
tocd <- TOC(index, boolean, mask, thres=seq(0, 100, by=10))
tocd

## End(Not run)
```

Toc-class	<i>Toc and Roc classes</i>
-----------	----------------------------

Description

Toc and Roc classes

Objects from the Class

Objects can be created by calls of the form `new("Toc", ...)`, or with the helper functions such as `Toc`.

Slots

Slots for Roc and Toc objects

table: data.frame

AUC: numeric; Area Under the Curve

maxAUC: numeric; maximum AUC

minAUC: numeric; minimum AUC

prevalence: numeric; prevalence

population: numeric; population

units: character; units for data in the TOC table, prevalence and population

Examples

showClass("Toc")

Toc-methods	<i>Methods for the Roc and Toc classes</i>
-------------	--

Description

Methods for the Roc and Toc classes

Details

Methods for the Roc and Toc classes

Value

an object of class Toc or Roc

See Also

[TOC](#), [ROC](#)

uncertainty	<i>Uncertainty in AUC calculation</i>
-------------	---------------------------------------

Description

TOC internal function. It calculates uncertainty in AUC calculation

Usage

uncertainty(index, tocd)

Arguments

index	index vector
tocd	data.frame output from roctable

Value

a numeric value representing uncertainty in AUC calculation

Note

This function is not meant to be called by users directly

Index

- *Topic **classes**
 - Toc-class, [8](#)
- *Topic **methods**
 - plot, [2](#)
 - ROC, [3](#)
 - scaling, [6](#)
 - TOC, [7](#)
 - Toc-methods, [9](#)
- *Topic **package**
 - TOC-package, [1](#)
- *Topic **spatial**
 - plot, [2](#)
 - ROC, [3](#)
 - roctable, [5](#)
 - scaling, [6](#)
 - TOC, [7](#)
 - Toc-class, [8](#)
 - Toc-methods, [9](#)
 - TOC-package, [1](#)
 - uncertainty, [9](#)
- plot, [2, 2, 4, 8](#)
- plot, Roc-method (plot), [2](#)
- plot, Toc-method (plot), [2](#)
- ROC, [3, 3, 6, 9](#)
- ROC, numeric, numeric-method (ROC), [3](#)
- ROC, RasterLayer, RasterLayer-method (ROC), [3](#)
- Roc-class (Toc-class), [8](#)
- Roc-method (Toc-methods), [9](#)
- roctable, [5](#)
- scaling, [6](#)
- scaling, Toc-method (scaling), [6](#)
- setAUC (Toc-methods), [9](#)
- setAUC, Roc (Toc-methods), [9](#)
- setAUC, Roc-method (Toc-methods), [9](#)
- setAUC, Toc (Toc-methods), [9](#)
- setAUC, Toc-method (Toc-methods), [9](#)
- setMaxAUC (Toc-methods), [9](#)
- setMaxAUC, Roc (Toc-methods), [9](#)
- setMaxAUC, Roc-method (Toc-methods), [9](#)
- setMaxAUC, Toc (Toc-methods), [9](#)
- setMaxAUC, Toc-method (Toc-methods), [9](#)
- setMinAUC (Toc-methods), [9](#)
- setMinAUC, Roc (Toc-methods), [9](#)
- setMinAUC, Roc-method (Toc-methods), [9](#)
- setMinAUC, Toc (Toc-methods), [9](#)
- setMinAUC, Toc-method (Toc-methods), [9](#)
- setPopulation (Toc-methods), [9](#)
- setPopulation, Toc (Toc-methods), [9](#)
- setPopulation, Toc-method (Toc-methods), [9](#)
- setPrevalence (Toc-methods), [9](#)
- setPrevalence, Toc (Toc-methods), [9](#)
- setPrevalence, Toc-method (Toc-methods), [9](#)
- setTable (Toc-methods), [9](#)
- setTable, Roc (Toc-methods), [9](#)
- setTable, Roc-method (Toc-methods), [9](#)
- setTable, Toc (Toc-methods), [9](#)
- setTable, Toc-method (Toc-methods), [9](#)
- setUnits (Toc-methods), [9](#)
- setUnits, Toc (Toc-methods), [9](#)
- setUnits, Toc-method (Toc-methods), [9](#)
- TOC, [2, 3, 6, 7, 9](#)
- TOC, numeric, numeric-method (TOC), [7](#)
- TOC, RasterLayer, RasterLayer-method (TOC), [7](#)
- Toc-class, [8](#)
- Toc-method (Toc-methods), [9](#)
- Toc-methods, [9](#)
- TOC-package, [1](#)
- uncertainty, [9](#)