





U ovom slučaju smo imali 10 mogućih putanja koje pokrivaju DietPlan Controller. Ti putevi su:

1 -> 2 -> 13

1 -> 3 -> 4 -> 13

1 -> 3 -> 5 -> 6 -> 10 -> 11 -> 13

1 -> 3 -> 5 -> 6 -> 10 -> 12 -> 13

1 -> 3 -> 5 -> 7 -> 10 -> 11 -> 13

1 -> 3 -> 5 -> 7 -> 10 -> 12 -> 13

1 -> 3 -> 5 -> 8 -> 10 -> 11 -> 13

1 -> 3 -> 5 -> 8 -> 10 -> 12 -> 13

1 -> 3 -> 5 -> 9 -> 10 -> 11 -> 13

1 -> 3 -> 5 -> 9 -> 10 -> 12 -> 13

Kako bih postigla pokrivenost sa najkraćim putem napisala sam sljedeće testne slučajeve:

Prvenstveno sam testirala slučaj kada se pokuša kreirati novi DietPlan, ali zbog Recipe koji je null, dolazi do vraćanja NotFound. Ime tog testa je CreateAction_RecipeIsNull_ReturnsNotFound()

```
291 [TestMethod]
292 // 0 references | Please sign-in to New Relic CodeStream to see Code Level Metrics
293 public async Task CreateAction_RecipeIsNull_ReturnsNotFound()
294 {
295     var nutritionist = new Nutritionist { Id = "1" };
296
297     var premiumUserList = new List<PremiumUser>
298     {
299         new PremiumUser
300         {
301             Id = "userId",
302             AccountNumber = "000",
303             City = "London",
304             Age = 25,
305             Weight = 70.0,
306             Height = 180.0,
307             Points = 0
308         }
309     }; var recipel = new Recipe { };
310     recipel = null;
311     var recipelist = new List<Recipe> {
312         new Recipe{
313             RID=1,
314             NameOfRecipe="Test",
315             TotalCalories=46,
316             Nutritionist=nutritionist,
317             RecipeLink="LINK",
318         },
319     };
320     recipel };
321     DietPlan dp = new DietPlan { DPID = 3, Recipes = recipelist };
322     var dietPlanVm = new EditDietPlanVM
323     {
324         DietPlan = dp,
325         _mockUserManager.Setup(um => um.GetUserId(_mockHttpContextAccessor.Object.HttpContext.User)).Returns("1");
326         _mockDbContext.Setup(db => db.Nutritionist).ReturnsDbSet((IEnumerable<Nutritionist>)new List<Nutritionist> { new Nutritionist { Id = "1", AspUserId = "1" } });
327         _mockDbContext.Setup(db => db.DietPlan).ReturnsDbSet((IEnumerable<DietPlan>)new List<DietPlan> { dp });
328         _mockDbContext.Setup(db => db.Recipe).ReturnsDbSet(recipel);
329         _mockDbContext.Setup(db => db.PremiumUser).ReturnsDbSet(new List<PremiumUser> { new PremiumUser { Id = premiumUserList[0].Id } });
330
331         // Act
332         var result = await _controller.Create(premiumUserList[0].Id, dietPlanVm);
333
334         // Assert
335         Assert.IsInstanceOfType(result, typeof(NotFoundResult));
336     }
337 }
```

Sljedeći testni slučaj koji sam pokrila jeste kada Nutritionist nije pronađen, čime sam pokrila uslov kada je Nutritionist null. Test se zove Create_WhenNutritionistNotLoggedIn_ReturnsNotFound()

```
383 [TestMethod]
384 // 0 references | Please sign-in to New Relic CodeStream to see Code Level Metrics
385 public async Task Create_WhenNutritionistNotLoggedIn_ReturnsNotFound()
386 {
387     _mockUserManager.Setup(x => x.GetUserAsync(It.IsAny<ClaimsPrincipal>())).ReturnsAsync((ApplicationUser)null);
388     _mockDbContext.Setup(x => x.Nutritionist).ReturnsDbSet(new List<Nutritionist>());
389
390     // Arrange
391     var dietPlanVm = new EditDietPlanVM { DietPlan = new DietPlan() };
392
393     // Act
394     var result = await _controller.Create("userId", dietPlanVm);
395
396     // Assert
397     Assert.IsInstanceOfType(result, typeof(NotFoundResult));
398 }
```

Sljedeći uslov koji je trebalo ispitati sve slučajeve, te tako postići pokrivenost koda je u slučaju brisanja DietPlan-ova. To sam pokrila sljedećim slučajevima. Testovi koji to pokrivaju su:
CreateAction_WhenDeletePlansIsNotNullButHasNoPlans_DoesNotRemoveAnyDietPlan()
CreateAction_WhenDeletePlansIsNullButHasPlans_DoesNotRemoveAnyDietPlan()
CreateAction_WithExistingDietPlans_DeletesOldDietPlans()

```
402 [TestMethod]
403 // 0 references | Please sign-in to New Relic CodeStream to see Code Level Metrics
404 public async Task CreateAction_WithExistingDietPlans_DeletesOldDietPlans()
405 {
406     // Arrange
407     var nutritionist = new ApplicationUser { Id = "1" };
408     DietPlan dp = new DietPlan { DPID = 3, Recipes = new List<Recipe> { new Recipe { RID = 1 } } };
409     var dietPlanVm = new EditDietPlanVM
410     {
411         DietPlan = dp,
412     };
413     var premiumUserList = new List<PremiumUser>
414     {
415         new PremiumUser
416         {
417             Id = "userId",
418             AccountNumber = "999",
419             City = "London",
420             Age = 25,
421             Weight = 70.0,
422             Height = 180.0,
423             Points = 0
424         },
425     };
426     _mockUserManager.Setup(um => um.GetUserId(_mockHttpContextAccessor.Object.HttpContext.User)).Returns("1");
427     _mockDbContext.Setup(db => db.Nutritionist).ReturnsDbSet((IEnumerable<Nutritionist>)new List<Nutritionist> { new Nutritionist { Id = "1", AspNetUserId = "1" } });
428     _mockDbContext.Setup(db => db.DietPlan).ReturnsDbSet((IEnumerable<DietPlan>)new List<DietPlan> { new DietPlan { PremiumUser = premiumUserList[0] } });
429     _mockDbContext.Setup(db => db.Recipe).ReturnsDbSet((IEnumerable<Recipe>)new List<Recipe> { new Recipe { RID = 1 }, new Recipe { RID = 2 } });
430     _mockDbContext.Setup(db => db.PremiumUser).ReturnsDbSet(new List<PremiumUser> { new PremiumUser { Id = premiumUserList[0].Id } });
431 }
432
```

```
433 var result = await _controller.Create(premiumUserList[0].Id, dietPlanVm);
434
435 // Assert
436 Assert.IsInstanceOfType(result, typeof(RedirectToActionResult));
437 var redirectResult = (RedirectToActionResult)result;
438 Assert.AreEqual("Index", redirectResult.ActionName);
439 Assert.AreEqual("Nutritionist", redirectResult.ControllerName);
440
441 // Provjera da li su stari planovi ishrane obrisani
442 var deletedDietPlans = _context.DietPlan.ToList();
443 Assert.AreEqual(0, deletedDietPlans.Count, "Old diet plans should be deleted.");
444 }
```

```
451 [TestMethod]
452 // 0 references | Please sign-in to New Relic CodeStream to see Code Level Metrics
453 public async Task CreateAction_WhenDeletePlansIsNullButHasPlans_DoesNotRemoveAnyDietPlan()
454 {
455     // Arrange
456     var nutritionist = new ApplicationUser { Id = "1" };
457     var dietPlanVm = new EditDietPlanVM { DietPlan = new DietPlan() };
458     _mockUserManager.Setup(um => um.GetUserId(_mockHttpContextAccessor.Object.HttpContext.User)).Returns("1");
459     _mockDbContext.Setup(db => db.Nutritionist).ReturnsDbSet(new List<Nutritionist> { new Nutritionist { Id = "1", AspNetUserId = "1" } });
460     _mockDbContext.Setup(db => db.DietPlan).ReturnsDbSet(new List<DietPlan>());
461     _mockDbContext.Setup(db => db.Recipe).ReturnsDbSet(new List<Recipe>());
462     _mockDbContext.Setup(db => db.PremiumUser).ReturnsDbSet(new List<PremiumUser>());
463
464     // Act
465     var result = await _controller.Create("userId", dietPlanVm);
466
467     // Assert
468     Assert.IsInstanceOfType(result, typeof(RedirectToActionResult));
469     var redirectResult = (RedirectToActionResult)result;
470     Assert.AreEqual("Index", redirectResult.ActionName);
471     Assert.AreEqual("Nutritionist", redirectResult.ControllerName);
472
473     // Provjera da li se nisu brisali stari planovi ishrane
474     var deletedDietPlans = _context.DietPlan.ToList();
475     Assert.AreEqual(0, deletedDietPlans.Count, "No diet plans should be deleted.");
476 }
477
```

```

[TestMethod]
0 | 0 references | Please sign-in to New Relic CodeStream to see Code Level Metrics
public async Task CreateAction_WhenDeletePlansIsNotNullButHasNoPlans_DoesNotRemoveAnyDietPlan()
{
    // Arrange
    var nutritionist = new ApplicationUser { Id = "1" };
    var dietPlanVm = new EditDietPlanVM { DietPlan = new DietPlan() };

    _mockUserManager.Setup(u => u.GetUserId(_mockHttpContextAccessor.Object.HttpContext.User)).Returns("1");
    _mockDbContext.Setup(db => db.Nutritionist).ReturnsDbSet(new List<Nutritionist> { new Nutritionist { Id = "1", AspUserId = "1" } });
    _mockDbContext.Setup(db => db.DietPlan).ReturnsDbSet(new List<DietPlan>());
    _mockDbContext.Setup(db => db.Recipe).ReturnsDbSet(new List<Recipe>());
    _mockDbContext.Setup(db => db.PremiumUser).ReturnsDbSet(new List<PremiumUser>());

    // Create deletePlans with count = 0
    var deletePlans = new List<DietPlan>();

    // Act
    var result = await _controller.Create("userId", dietPlanVm);

    // Assert
    Assert.IsInstanceOfType(result, typeof(RedirectActionResult));
    var redirectResult = (RedirectActionResult)result;
    Assert.AreEqual("Index", redirectResult.ActionName);
    Assert.AreEqual("Nutritionist", redirectResult.ControllerName);

    // Provjera da li se nisu brisali stari planovi ishrane
    var deletedDietPlans = _context.DietPlan.ToList();
    Assert.AreEqual(0, deletedDietPlans.Count, "No diet plans should be deleted.");
}

```

Pored POST metode za Create, testirala sam i samu Create metodu. Za ovu metodu sam pokrila neke moguće slučajeve, ali s obzirom na to da nije previše kompleksna metoda nije napisano ni previše testova.

```

[TestMethod]
0 | 0 references | Please sign-in to New Relic CodeStream to see Code Level Metrics
public void CreateAction_WithRecipes_ReturnsCorrectViewModel()
{
    // Aranžman (Arrange)

    // Kreiramo mock context.Recipe sa popunjenom listom recepata
    var mockRecipes = new List<Recipe>
    {
        new Recipe { RID = 1, NameOfRecipe = "Recipe 1" },
        new Recipe { RID = 2, NameOfRecipe = "Recipe 2" },
    };
    // Dodajte dodatne recepte prema potrebi
    _mockQueryable();

    _mockDbContext.Setup(c => c.Recipe).Returns((DbSet<Recipe>)MockDbSet(mockRecipes));

    // Akcija (Act)
    var result = _controller.Create("TestUser") as ViewResult;

    // Assert

    // Provjeravamo da li akcija vraća ViewResult
    Assert.IsNotNull(result);
    Assert.IsInstanceOfType(result, typeof(ViewResult));

    // Provjeravamo da li akcija koristi ispravan View
    Assert.AreEqual("dietPlan", result?.ViewName);

    // Provjeravamo da li ViewModel ima pravilno postavljene vrednosti
    var model = result.Model as EditDietPlanVM;
    Assert.IsNotNull(model);
    Assert.IsNotNull(model.DietPlan);
    Assert.IsNotNull(model.Recipes);
    Assert.AreEqual("TestUser", model.DietPlan.PremiumUser.Id);
    CollectionAssert.AreEqual(mockRecipes.ToList(), model.Recipes.ToList());
}

```

0 references | Please sign-in to New Relic CodeStream to see Code Level Metrics

```
public void CreateAction_AuthorizedNutritionist_ReturnsCorrectViewModel()
{
    // Aranžman (Arrange)

    // Kreiramo mock context.Recipe
    var mockRecipes = new List<Recipe>
    {
        new Recipe { RID = 1, NameOfRecipe = "Recipe 1" },
        new Recipe { RID = 2, NameOfRecipe = "Recipe 2" },
        // Dodajte dodatne recepte prema potrebi
    }.AsQueryable();

    _mockDbContext.Setup(c => c.Recipe).Returns((DbSet<Recipe>)MockDbSet(mockRecipes));

    // Akcija (Act)
    var result = _controller.Create("TestUser") as ViewResult;

    // Assert

    // Proveravamo da li akcija vraća ViewResult
    Assert.IsNotNull(result);
    Assert.IsInstanceOfType(result, typeof(ViewResult));

    // Proveravamo da li akcija koristi ispravan View
    Assert.AreEqual("dietPlan", result?.ViewName);

    // Proveravamo da li ViewModel ima pravilno postavljene vrijednosti
    var model = result.Model as EditDietPlanVM;
    Assert.IsNotNull(model);
    Assert.IsNotNull(model.DietPlan);
    Assert.IsNotNull(model.Recipes);
    Assert.AreEqual("TestUser", model.DietPlan.PremiumUser.Id);
    CollectionAssert.AreEqual(mockRecipes.ToList(), model.Recipes.ToList());
}
```