BusTime GTFS-realtime feed fields

The following tables describe what fields are being supplied as part of the GTFS-realtime feed by BusTime

GTFS-RT field	header->gtfs_realtime_version
Notes	Version number of GTFS-RT specification. 2.0 is used in GTFS-RT v1.0.0.85 and above. Previous GTFS-RT versions use 1.0.

GTFS-RT field	header->incrementality
Notes	“FULL_DATASET” will be returned

GTFS-RT field	header->timestamp
Notes	Timestamp identifying the moment the content of the feed is created, server-side. Value is stored as uint64 representation of the POSIX time (seconds from Jan 1st 1970 00:00:00 UTC).

1 Trip Update Mappings

GTFS-RT field	entity->id
Notes	Feed-unique identifier for an entity.

GTFS-RT field	entity->is_deleted
Notes	Boolean value indicating whether an entity is to be deleted (has expired or been invalidated). Relevant only for incremental fetches. Not being supplied

GTFS-RT field	entity->trip_update->trip->trip_id
Notes	This trip_id matches the trip_id in the GTFS static feed. This comes from the BusTools/CleverWorks export

GTFS-RT field	entity->trip_update->trip->route_id
Notes	Unique identifier for a route. The route_id matches what is in the GTFS static feed. This comes from the BusTools/CleverWorks export.

GTFS-RT field	entity->trip_update->trip->start_time

Notes	Supplied starting with GTFS-realtime 1.0.0.93 when the GTFS-realtime property gtfsrt.trip.allow.start.time.and.date is set to true.

GTFS-RT field	entity->trip_update->trip->start_date
Notes	Supplied starting with GTFS-realtime 1.0.0.93 when the GTFS-realtime property gtfsrt.trip.allow.start.time.and.date is set to true.

GTFS-RT field	entity->trip_update->trip->schedule_relationship
Notes	This will be SCHEDULED for scheduled work, ADDED for manual trips, CANCELED for canceled trips

GTFS-RT field	entity->trip_update->vehicle->id
Notes	Unique identifier for a vehicle.

GTFS-RT field	entity->trip_update->vehicle->label
Notes	Supplied starting with GTFS-realtime 1.0.0.83 when the GTFS-realtime property gtfsrt.vehicle.label.field is configured.

GTFS-RT field	entity->trip_update->vehicle->license
Notes	Not being supplied

GTFS-RT field	entity->trip_update->stop_time_update->stop_sequence
Notes	Ordered sequence identifier to stops on route/trip. Must be the same as in stop_times.txt in the corresponding GTFS feed. Being provided

GTFS-RT field	entity->trip_update->stop_time_update->stop_id
Notes	Matches stop_id in GTFS static feed

GTFS-RT field	entity->trip_update->stop_time_update->[arrival/departure]->delay
Notes	Not being supplied

GTFS-RT field	entity->trip_update->stop_time_update->[arrival/departure]->time
Notes	Timestamp of arrival/departure event. This field is not displayed when the stop_time_update->schedule_relationship field has a value of NO_DATA.

GTFS-RT field	entity->trip_update->stop_time_update->[arrival/departure]->uncertainty
Notes	Not being supplied

GTFS-RT field	entity->trip_update->stop_time_update->schedule_relationship
Notes	SCHEDULED for scheduled stops, CANCELED for canceled or expressed stops, NO_DATA for delayed stops and unknown delayed trips

GTFS-RT field	entity->trip_update->timestamp
Notes	Moment in which the vehicle's realtime progress was measured.

2 Vehicle Update Mappings

GTFS-RT field	entity->vehicle->trip->trip_id
Notes	If the vehicle is running work, this will be supplied. The entire trip entity will not be present if the vehicle is not running work.

GTFS-RT field	entity->vehicle ->trip->route_id
Notes	Unique identifier for a route.

GTFS-RT field	entity->vehicle ->trip->start_time
Notes	Supplied starting with GTFS-realtime 1.0.0.93 when the GTFS-realtime property gtfsrt.trip.allow.start.time.and.date is set to true.

GTFS-RT field	entity->vehicle ->trip->start_date
Notes	Supplied starting with GTFS-realtime 1.0.0.93 when the GTFS-realtime property gtfsrt.trip.allow.start.time.and.date is set to true.

GTFS-RT field	entity->vehicle ->trip->schedule_relationship
Notes	This will be SCHEDULED for scheduled work, ADDED for manual trips, CANCELED for canceled trips

GTFS-RT field	entity->vehicle ->vehicle->id
Notes	Unique identifier for a vehicle.

GTFS-RT field	entity->vehicle ->vehicle->label

Notes	Supplied starting with GTFS-realtime 1.0.0.83 when the GTFS-realtime property gtfsrt.vehicle.label.field is configured.

GTFS-RT field	entity->vehicle ->vehicle->license
Notes	Not being supplied

GTFS-RT field	entity->vehicle ->position->latitude
Notes	The vehicle's latitude value.

GTFS-RT field	entity->vehicle ->position->longitude
Notes	The vehicle's longitude value.

GTFS-RT field	entity->vehicle ->position->bearing
Notes	The vehicle's direction of travel; its bearing or heading.

GTFS-RT field	entity->vehicle ->position->odometer
Notes	Not being supplied

GTFS-RT field	entity->vehicle ->position->speed
Notes	Speed in meters per second. Needs to be enabled within BusTime

GTFS-RT field	entity->vehicle ->current_stop_sequence
Notes	Being supplied as of BusTime 6.3, GTFS-RT 1.0.0.43. Needs to be enabled within BusTime

GTFS-RT field	entity->vehicle ->stop_id
Notes	Being supplied as of BusTime 6.3, GTFS-RT 1.0.0.43. Needs to be enabled within BusTime

GTFS-RT field	entity->vehicle ->current_status
Notes	Being supplied as of BusTime 6.3, GTFS-RT 1.0.0.43. Needs to be enabled within BusTime

GTFS-RT field	entity->vehicle->timestamp
Notes	Moment in which the vehicle's realtime progress was measured.

GTFS-RT field	entity->vehicle->congestion_level

Notes	Not being supplied

GTFS-RT field	entity->vehicle->occupancy_status
Notes	Supplied starting with GTFS-realtime 1.0.0.101 when the GTFS-realtime property gtfsrt.vehicle.allow.occupancystatus is set to true. The occupancy status of the vehicle.

3 Service Alert Mappings

GTFS-RT field	entity->alert->active_period->[start/end]
Notes	Not being supplied

GTFS-RT field	entity->alert->informed_entity->agency_id
Notes	Agency to identify this entity. Matches the GTFS static feed Agency_id

GTFS-RT field	entity->alert->informed_entity->route_id
Notes	Route associated to this alert. Not supplied if the service alert is a system level alert

GTFS-RT field	entity->alert->informed_entity->route_type
Notes	Not being supplied

GTFS-RT field	entity->alert->informed_entity->stop_id
Notes	Service bulletins for a given stop id. Not supplied if the service alert is configured at the route or system level

GTFS-RT field	entity->alert->cause
Notes	Supplied starting with BusTime 5.5 and GTFS-realtime 1.0.0.33 and higher

GTFS-RT field	entity->alert->effect
Notes	Supplied starting with BusTime 5.5 and GTFS-realtime 1.0.0.33 and higher

GTFS-RT field	entity->alert->[header_text/description_text]->translation->text
Notes	The contents and context of an alert.

GTFS-RT field	entity->alert->[header_text/description_text]->translation->language

Notes	Language code. Languages configured within BusTime will be returned

GTFS-RT field	entity->alert->url
Notes	Supplied starting with BusTime 6.3 and GTFS-realtime 1.0.0.37 and higher