

# SCIM

GET	/api/v2/scim/schemas	Get a list of SCIM schemas				
GET	/api/v2/scim/schemas/{schemald}	Get a SCIM schema				
GET	/api/v2/scim/v2/resourcetypes/{resourceType}	Get a resource type				
GET	/api/v2/scim/v2/resourcetypes	Get a list of resource types				
GET	/api/v2/scim/groups/{groupId}	Get a group				
PUT	/api/v2/scim/groups/{groupId}	Replace a group				
PATCH	/api/v2/scim/groups/{groupId}	Modify a group				
GET	/api/v2/scim/groups	Get a list of groups				
GET	/api/v2/scim/resourcetypes/{resourceType}	Get a resource type				
GET	/api/v2/scim/resourcetypes	Get a list of resource types				
GET	/api/v2/scim/v2/users/{userId}	Get a user				
PUT	/api/v2/scim/v2/users/{userId}	Replace a user				
DELETE	/api/v2/scim/v2/users/{userId}	Delete a user				
PATCH	/api/v2/scim/v2/users/{userId}	Modify a user				
GET	/api/v2/scim/v2/users	Get a list of users				
<p>To return all active users, do not use the filter parameter. To return inactive users, set the filter parameter to "active eq false". By default, returns SCIM attributes "externalId", "enterprise-user:manager", and "roles". To exclude these attributes, set the attributes parameter to "id,active" or the excludeAttributes parameter to "externalId,roles,urn:ietf:params:scim:schemas:extension:enterprise:2.0:User:division".</p>						
Required Permissions		Required Scopes				
No permissions required		Apps making this call must have one of these scopes: <ul style="list-style-type: none"><li>scim</li><li>scim:readonly</li></ul>				
Parameters						
	NAME	DEFAULT DESCRIPTION PARAMETER TYPE DATA TYPE REQUIRED				
	startIndex	1	The 1-based index of the first query result.	query	string	
	count	25	The requested number of items per page. A value of 0 returns "totalResults". A page size over 25 may exceed internal resource limits and return a 429 error. For a page size over 25, use the "excludedAttributes" or "attributes" query parameters to exclude or only include secondary lookup values such as "externalId", "enterprise-user:manager", and "roles".	query	string	

"urn:ietf:params:scim:schemas:extension:genesys:purecloud:2.0:User:routingSkills".				
attributes	<p>Indicates which attributes to include. Returns these attributes and the "id", "userName", "active", and "meta" attributes. Use "attributes" to avoid expensive secondary calls for the default attributes.</p> <p><i>Valid values:</i> id, userName, displayName, title, active, externalId, phoneNumbers, emails, groups, roles, meta, meta.version, meta.lastModified,</p> <p>urn:ietf:params:scim:schemas:core:2.0:User:id, , urn:ietf:params:scim:schemas:core:2.0:User:userName, urn:ietf:params:scim:schemas:core:2.0:User:displayName, urn:ietf:params:scim:schemas:core:2.0:User:title, urn:ietf:params:scim:schemas:core:2.0:User:active, urn:ietf:params:scim:schemas:core:2.0:User:externalId, urn:ietf:params:scim:schemas:core:2.0:User:phoneNumbers, urn:ietf:params:scim:schemas:core:2.0:User:emails, urn:ietf:params:scim:schemas:core:2.0:User:groups, urn:ietf:params:scim:schemas:core:2.0:User:roles, urn:ietf:params:scim:schemas:core:2.0:User:meta, urn:ietf:params:scim:schemas:core:2.0:User:meta.version, urn:ietf:params:scim:schemas:core:2.0:User:meta.lastModified, urn:ietf:params:scim:schemas:extension:enterprise:2.0:User, urn:ietf:params:scim:schemas:extension:enterprise:2.0:User:division, urn:ietf:params:scim:schemas:extension:enterprise:2.0:User:department, urn:ietf:params:scim:schemas:extension:enterprise:2.0:User:manager, urn:ietf:params:scim:schemas:extension:enterprise:2.0:User:manager.value, urn:ietf:params:scim:schemas:extension:enterprise:2.0:User:employeeNumber, urn:ietf:params:scim:schemas:extension:genesys:purecloud:2.0:User, urn:ietf:params:scim:schemas:extension:genesys:purecloud:2.0:User:routingSkills, urn:ietf:params:scim:schemas:extension:genesys:purecloud:2.0:User:routingLanguages, urn:ietf:params:scim:schemas:extension:genesys:purecloud:2.0:User:externalIds</p>	query	string	
excludedAttributes	<p>Indicates which attributes to exclude. Returns the default attributes minus "excludedAttributes". Always returns the "id", "userName", "active", and "meta" attributes. Use "excludedAttributes" to avoid expensive secondary calls for the default attributes.</p> <p><i>Valid values:</i> id, userName, displayName, title, active, externalId, phoneNumbers, emails, groups, roles, meta, meta.version, meta.lastModified,</p>	query	string	

urn:ietf:params:scim:schemas:core:2.0:User:u  
serName,  
urn:ietf:params:scim:schemas:core:2.0:User:di  
splayName,  
urn:ietf:params:scim:schemas:core:2.0:User:tit  
le,  
urn:ietf:params:scim:schemas:core:2.0:User:a  
ctive,  
urn:ietf:params:scim:schemas:core:2.0:User:e  
xternalId,  
urn:ietf:params:scim:schemas:core:2.0:User:p  
honeNumbers,  
urn:ietf:params:scim:schemas:core:2.0:User:e  
mails,  
urn:ietf:params:scim:schemas:core:2.0:User:gr  
oups,  
urn:ietf:params:scim:schemas:core:2.0:User:ro  
les,  
urn:ietf:params:scim:schemas:core:2.0:User:m  
eta,  
urn:ietf:params:scim:schemas:core:2.0:User:m  
eta.version,  
urn:ietf:params:scim:schemas:core:2.0:User:m  
eta.lastModified,  
urn:ietf:params:scim:schemas:extension:enter  
prise:2.0:User,  
urn:ietf:params:scim:schemas:extension:enter  
prise:2.0:User:division,  
urn:ietf:params:scim:schemas:extension:enter  
prise:2.0:User:department,  
urn:ietf:params:scim:schemas:extension:enter  
prise:2.0:User:manager,  
urn:ietf:params:scim:schemas:extension:enter  
prise:2.0:User:manager.value,  
urn:ietf:params:scim:schemas:extension:enter  
prise:2.0:User:employeeNumber,  
urn:ietf:params:scim:schemas:extension:gene  
sys:purecloud:2.0:User,  
urn:ietf:params:scim:schemas:extension:gene  
sys:purecloud:2.0:User:routingSkills,  
urn:ietf:params:scim:schemas:extension:gene  
sys:purecloud:2.0:User:routingLanguages,  
urn:ietf:params:scim:schemas:extension:gene  
sys:purecloud:2.0:User:externalIds

filter

Filters results. If nothing is specified, returns  
all active users. Examples of valid values: "id  
eq 857449b0-d9e7-4cd0-acbf-a6adfb9ef1e9",  
"userName eq search@sample.org", "manager  
eq 16e10e2f-1136-43fe-bb84-eac073168a49",  
"email eq search@sample.org", "division eq  
divisionName", "externalId eq 167844", "active  
eq false", "employeeNumber eq 9876543210".

query

string

Request

[HTTP](#) [cURL](#)

```
GET /api/v2/scim/v2/users HTTP/1.1
Host: api.mypurecloud.com
Authorization: Bearer {access_token}
Content-Type: application/json
```

Responses

▼ 200 - successful operation

totalResults	(integer) The total number of results.
startIndex	(integer) The 1-based index of the first result returned by this request. Add this to "itemsPerPage" when requesting the next page of results.
itemsPerPage	(integer) The number of resources returned per page.
Resources	(ScimV2User[]) The list of requested resources. If "count" is 0, then the list will be empty.
ScimV2User	
id	(string) The ID of the SCIM resource. Set by the service provider. "caseExact" is set to "true". "mutability" is set to "readOnly". "returned" is set to "always".
schemas	(string[]) The list of supported schemas.
active	(boolean) Indicates whether the user's administrative status is active.
userName	(string) The user's Genesys Cloud email address. Must be unique.
displayName	(string) The display name of the user.
password	(string) The new password for the Genesys Cloud user. Does not return an existing password. When creating a user, if a password is not supplied, then a password will be randomly generated that is 40 characters in length and contains five characters from each of the password policy groups.
title	(string) The user's title.
phoneNumbers	(ScimPhoneNumber[]) The list of the user's phone numbers.
ScimPhoneNumber	
value	(string) The phone number in E.164 or tel URI format, for example, tel:+nnnnnnnnn; ext=xxxxx.
type	(string) The type of phone number. <i>Valid values:</i> work, work2, work3, work4, home, mobile, other, microsoftteams, zoomphone, ringcentral.
primary	(boolean) Indicates whether the phone number is the primary phone number.
emails	(ScimEmail[]) The list of the user's email addresses.
ScimEmail	
value	(string) The email address. Is immutable if "type" is set to "other".
type	(string) The type of email address. "value" is immutable if "type" is set to "other". <i>Valid values:</i> work, other.
primary	(boolean) Indicates whether the email address is the primary email address.
externalId	(string) The external ID of the user. Set by the provisioning client. "caseExact" is set to "true". "mutability" is set to "readWrite".
groups	(ScimV2GroupReference[]) The list of groups that the user is a member of.
ScimV2GroupReference	
type	(string) The type of SCIM resource. <i>Valid values:</i> User, Group, ServiceProviderConfig, ResourceType, Schema.
value	(string) The ID of the group member. Can be "userId" or "groupId".
\$ref	(string) The reference URI of the SCIM resource.
roles	(ScimUserRole[]) The list of roles assigned to the user.
ScimUserRole	
value	(string) The role of the Genesys Cloud user.
urn:ietf:params:scim:sche...	(ScimV2EnterpriseUser) The URI of the schema for the enterprise user.
ScimV2EnterpriseUser	
division	(string) The division that the user belongs to.
department	(string) The department that the user belongs to.
manager	(Manager) The user's manager.
Manager	
value	(string) The ID of the manager.
\$ref	(string) The reference URI of the manager's user record.
employeeNumber	(string) The user's employee number.
urn:ietf:params:scim:sche...	(ScimUserExtensions) The URI of the schema for the Genesys Cloud user.
ScimUserExtensions	
routingSkills	(ScimUserRoutingSkill[]) The list of routing skills assigned to a user. Maximum 50 skills.
ScimUserRoutingSkill	
name	(string <i>required</i> ) The case-sensitive name of a routing skill configured in Genesys Cloud.
proficiency	(number) A rating from 0.0 to 5.0 that indicates how adept an agent is at a particular skill. When "Best available skills" is enabled for a queue in Genesys Cloud, ACD interactions in that queue are routed to agents with higher proficiency ratings.
routingLanguages	(ScimUserRoutingLanguage[]) The list of routing languages assigned to a user. Maximum 50 languages.
ScimUserRoutingLanguage	
name	(string <i>required</i> ) The case-sensitive name of a routing language configured in Genesys Cloud.
proficiency	(number) A rating from 0.0 to 5.0 that indicates how fluent an agent is in a particular language. ACD

		<b>externalIds</b>	(ScimGenesysUserExternalId[]) The list of external identifiers assigned to user. Always includes an immutable SCIM authority prefixed with "x-pc:scimv2:v1".
		<b>ScimGenesysUserExternalId</b>	
		<b>authority</b>	(string) Authority, or scope, of "externalId". Allows multiple external identifiers to be defined. Represents the source of the external identifier.
		<b>value</b>	(string) Identifier of the user in an external system.
		<b>meta</b>	(ScimMetadata) The metadata of the SCIM resource.
		<b>ScimMetadata</b>	
		<b>resourceType</b>	(string) The type of SCIM resource. <i>Valid values:</i> User, Group, ServiceProviderConfig, ResourceType, Schema.
		<b>lastModified</b>	(string) The last time that the resource was modified. Date time is represented as an "ISO-8601 string", for example, yyyy-MM-ddTHH:mm:ss.SSSZ. Not included with "Schema" and "ResourceType" resources.
		<b>location</b>	(string) The URI of the resource.
		<b>version</b>	(string) The version of the resource. Matches the ETag HTTP response header. Not included with "Schema" and "ResourceType" resources.
		<b>schemas</b>	(string[]) The list of supported schemas.
➤ 400 - The request could not be understood by the server due to malformed syntax.			
➤ 401 - No authentication bearer token specified in authorization header.			
➤ 403 - You are not authorized to perform the requested action.			
➤ 404 - The requested resource was not found.			
➤ 413 - The request is over the size limit. Content-Length: %s			
➤ 415 - Unsupported Media Type - Unsupported or incorrect media type, such as an incorrect Content-Type value in the header.			
➤ 429 - Rate limit exceeded the maximum. Retry the request in [%s] seconds			
➤ 500 - The server encountered an unexpected condition which prevented it from fulfilling the request.			
➤ 503 - Service Unavailable - The server is currently unavailable (because it is overloaded or down for maintenance).			
➤ 504 - The request timed out.			
POST	<b>/api/v2/scim/v2/users</b> Create a user		
GET	<b>/api/v2/scim/v2/schemas</b> Get a list of SCIM schemas		
GET	<b>/api/v2/scim/v2/schemas/{schemald}</b> Get a SCIM schema		
GET	<b>/api/v2/scim/serviceproviderconfig</b> Get a service provider's configuration		
GET	<b>/api/v2/scim/v2/groups/{groupId}</b> Get a group		
PUT	<b>/api/v2/scim/v2/groups/{groupId}</b> Replace a group		
PATCH	<b>/api/v2/scim/v2/groups/{groupId}</b> Modify a group		
GET	<b>/api/v2/scim/v2/groups</b> Get a list of groups		
GET	<b>/api/v2/scim/users/{userId}</b> Get a user		
PUT	<b>/api/v2/scim/users/{userId}</b> Replace a user		

Welcome to the new Genesys Cloud Developer Center!

Take a look around and use the thumbs up/down at the bottom of the page to leave feedback and report any issues with the site.

PATCH	/api/v2/scim/users/{userId}	Modify a user
GET	/api/v2/scim/users	Get a list of users
POST	/api/v2/scim/users	Create a user
GET	/api/v2/scim/v2/serviceproviderconfig	Get a service provider's configuration

Was this page helpful?  