

482. License Key Formatting

Add to List ▾

Question

Editorial Solution

My Submissions (/problems/license-key-formatting/submissions/)

Total Accepted: **4342** Total Submissions: **10094** Difficulty: **Medium** Contributors: **aizj_Forever** (/aizj_forever/)

Now you are given a string S, which represents a software license key which we would like to format. The string S is composed of alphanumerical characters and dashes. The dashes split the alphanumerical characters within the string into groups. (i.e. if there are M dashes, the string is split into M+1 groups). The dashes in the given string are possibly misplaced.

We want each group of characters to be of length K (except for possibly the first group, which could be shorter, but still must contain at least one character). To satisfy this requirement, we will reinsert dashes. Additionally, all the lower case letters in the string must be converted to upper case.

So, you are given a non-empty string S, representing a license key to format, and an integer K. And you need to return the license key formatted according to the description above.

Example 1:

Input: S = "2-4A0r7-4k", K = 4

Output: "24A0-R74K"

Explanation: The string S has been split into two parts, each part has 4 characters.

Example 2:

Input: S = "2-4A0r7-4k", K = 3

Output: "24-A0R-74K"

Explanation: The string S has been split into three parts, each part has 3 characters except the first part as it could be shorter as said above.

Note:

1. The length of string S will not exceed 12,000, and K is a positive integer.
2. String S consists only of alphanumerical characters (a-z and/or A-Z and/or 0-9) and dashes(-).
3. String S is non-empty.

Hide Company Tags

Google (/company/google/)

Have you met this question in a real interview? ☐ Yes ☐ No

Discuss (<https://discuss.leetcode.com/category/619>)

Top Solutions

Pick One (/problems/random-one-question/)

C++



```
1 class Solution {
2 public:
3
4     int countAlphaNum(string& s) {
5         int cnt = 0;
6         for(auto c : s) {
7             cnt += c != '-' ? 1 : 0;
8         }
9         return cnt;
10    }
11
12    string licenseKeyFormatting(string S, int K) {
13        if(K <= 0) return "";
14        int cnt = countAlphaNum(S);
15        if(cnt == 0) return "";
16        stringstream ss;
17        int firstGroup = cnt % K;
18        int j = (K - firstGroup) % K;
19        for (int i = 0; i < S.length(); i++) {
20            if (j == K) {
21                ss << '-';
22                j = 0;
23            }
24            ss << S[i];
25            j++;
26        }
27        return ss.str();
28    }
29 }
```

✉ Send Feedback (mailto:admin@leetcode.com?subject=Feedback)

Notes

```

23         }
24         if (S[i] == '-') continue;
25         else if (S[i] >= 'a' && S[i] <= 'z') {
26             ss << char(S[i] - ('a' - 'A'));
27         } else {
28             ss << S[i];
29         }
30         j++;
31     }
32     string res = ss.str();
33     while (res.back() == '-') res.pop_back();
34     return res;
35 }
36

```

Custom Testcase ☒

Contribute Testcase 

```
"2-4A0r7-4k"
4
```

One line for one parameter. Hint

Shortcut: Command + enter

Run Code

Submit Solution

Submission Result: Accepted (/submissions/detail/90107544/) 

More Details
 > (/submissions/detail/90107544/)

Next challenges:
 (M) Find Permutation (/problems/find-permutation)
 (M) Increasing Subsequences (/problems/increasing-subsequences)
 (M) Target Sum (/problems/target-sum)

Share your acceptance!

Frequently Asked Questions (/faq/)
 | Terms of Service (/tos/)

[Privacy](#)

Copyright © 2017 LeetCode