Ethical Hacking and Countermeasures
Gobuster Cheat Sheet

Gobuster
Source: https://github.com

Gobuster is a Go programming based directory scanner that allows attackers to perform fast-paced enumeration of hidden files and directories of an application. It is a convenient command-oriented tool used to brute-force URIs in web sites, DNS subdomains, names of the virtual hosts on the target server, etc.
The following table lists the various Gobuster commands and their respective operations:

Syntax

```
1.<dns> Mode Options
2. <dir> Mode Options
3. <vhost> Mode Options
4. <dns> Mode Commands
5. <dir> Mode Commands
6. <vhost> Mode Commands
```

1.<dns> Mode Options

Syntax

```
gobuster dns [flags]
```

Flags

`-d, --domain string`	If the service is on a different default port, define it here
`-d, --domain string`	Log in with a single username, or load several logins from FILE of username list
`-r, --resolver string`	Try single password, or load several passwords from FILE of the password list
`-c, --showcname`	Password brute force generation, type "-x -h" to get help
`--showips`	Display IP addresses
`-i, --timeout duration`	DNS resolver timeout
`--wildcard`	Force continued operation when wildcard found

Global Flags

`-z, --noprogress`	Do not display progress
`-o, --output string`	Output file to write results defaults to stdout
`-q, --quiet`	Do not print banner and other noise
`--threads int`	Number of concurrent threads, default is 10
`-t, --delay duration`	Time each thread waits between requests (e.g. 1500ms)
`-v, --verbose`	Enables verbose output
`-w, --wordlist string`	Path to wordlist

2. <dir> Mode Options

Syntax

```
gobuster dir [flags]
```

Flags

`-f, --addslash`	Adds to each request
`-c, --cookies string`	Cookies to use for the requests
`-e, --expanded`	Expanded mode, print full URLs
`-x, --extensions string`	File extension(s) to search for
`-r, --followredirect`	Follow redirects
`-H, --headers stringArray`	Specify HTTP headers, -H 'Header1: val1' -H 'Header2: val2'
`-h, --help`	Help for dir
`-l, --includelength`	Include the length of the body in the output
`-k, --insecuressl`	Skip SSL certificate verification
`-n, --nostatus`	Do not print status codes
`-P, --password string`	Password for basic authentication
`-p, --proxy string`	Proxy to use for requests [http(s)://host:port
`-s, --statuscodes string`	Positive status codes
`-b, --statuscodesblacklist string`	Negative status codes
`-p, --proxy string`	HTTP Timeout
`-u, --url string`	Target URL
`-a, --useragent string`	Set the User-Agent string
`--username string`	Username for Basic Auth
`-U, --wildcard`	Force continued operation when wildcard found

Global Flags

`-z, --noprogress`	Don't display progress
`-o, --output string`	Output file to write results to (defaults to stdout)
`-q, --quiet`	Do not print the banner and other noise
`--threads int`	Number of concurrent threads, default is 10
`-t, --delay duration`	Time each thread waits between requests
`-v, --verbose`	Verbose output
`-w, --wordlist string`	Path to the wordlist

3. <vhost> Mode Options

Syntax

```
gobuster vhost [flags]
```

Flags

`-c, --cookies string`	Cookies used for requests
`-r, --followredirect`	Follow redirects
`-H, --headers stringArray`	Specify HTTP headers, -H 'Header1: val1' -H 'Header2: val2'
`-h, --help`	Help for vhost
`-k, --insecuressl`	Skip SSL certificate verification
`-P, --password string`	Password for basic authentication
`--timeout duration`	HTTP Timeout (default 10s)
`-u, --url string`	Target URL
`-a, --useragent string`	Set the User-Agent string
`-U, --username string`	Username for basic authentication

Global Flags

`-z, --noprogress`	Do not display progress
`-o, --output string`	Output file to write results
`-q, --quiet`	Do not print the banner and other noise
`-o, --output string`	Number of concurrent threads
`-t, -q, --quiet`	Time each thread waits between requests
`-v, --verbose`	-v, --verbose
`-w, --wordlist string`	Path to the wordlist

Over 50% Of Professionals Received Promotions after C|EH

4. <dns> Mode Commands

Commands	Description
`gobuster dns -d <Target Website> -t 50 -w common-names.txt`	Set number of threads to brute-force directories or subdomain names
`gobuster dns -d <Target website> -w ~/wordlists/subdomains.txt`	Display all the sub-domains
`gobuster dns -d <Target website> -w ~/wordlists/subdomains.txt -i`	Display IP addresses of the obtained subdomains
`gobuster dns -d <Target URL/Domain> -w ~/wordlists/subdomains.txt -i`	Display base domain validation warning when it fails to resolve
`gobuster dns -d <Target URL/Domain> -w ~/wordlists/subdomains.txt`	Detects wildcard DNS
`gobuster dns -d <Target URL/Domain> -w ~/wordlists/subdomains.txt --wildcard`	Forces processing of a domain consisting of wildcard entries

5. <dir> Mode Commands

Commands	Description
`gobuster dir -u <Target URL> -c 'session=123456' -t 50 -w common-files.txt -x .php,.html`	Lists out files with specific extensions
`gobuster dir -u <Target URL/Domain> -w ~/wordlists/shortlist.txt`	Obtains files or directories
`gobuster dir -u <Target URL/Domain> -w ~/wordlists/shortlist.txt -n`	Default options with disabled status code
`gobuster dir -u <Target URL/Domain> -w ~/wordlists/shortlist.txt -v`	Display verbose output
`gobuster dir -u <Target URL/Domain> -w ~/wordlists/shortlist.txt -l`	Display content length

6. <vhost> Mode Commands

Commands	Description
`gobuster vhost -u <Target website> -w common-vhosts.txt`	Display subdomains/virtual hosts obtained from the custom wordlist