# Ethical Hacking and Countermeasures
## arpspoof Cheat Sheet

**arpspoof** | arpspoof is a program to perform an ARP spoofing attack against any local unencrypted network. It redirects packets from a target host on the LAN that is meant for another host on the LAN by forging ARP replies

### Syntax

./arpspoof [Option [Arg]]... Victim_IP
Example: arpspoof -i eth0 -t Target_IP Gateway_IP

### Arguments

| | |
|---|---|
| `-i, --interface` | Specify the network interface |
| `-c, own\|host\|both` | Resends packet continuously with a delay given in seconds by the argument |
| `-t, target` | Specify a host to ARP poison |
| `-r, --repeat` | Resends the packet continuously with delay given in seconds by the argument. A delay of zero means only one packet is sent |
| `host` | Specify the host to intercept packets |
| `-a, --attacker-ip` | Choose another machine as the one to be disguised |
| `-g, --gateway-ip` | Spoof to an IP other than the default gateway |
| `-v, --verbose` | Prints extra information regarding the machines involved |

### Installation of ARP Spoof

```
sudo apt-get install arpspoof
```

### Synopsis

```
arpspoof [-i interface] [-c own|host|both] [-t target] [-r] host
```

### arpspoof Commands

| Command | Description |
|---|---|
| `arpspoof -i wlan0 -t <Target IP range>` | Monitor the packet flow from the Victim to the Router |
| `arpspoof -i [Network Interface Name] -t [Victim IP] [Router IP]` | Spoof connection between victim and router |
| `arpspoof -t <Target IP 1> <Target IP 2>` | ARP spoofing |
| `arpspoof -i [Network Interface Name] -t [Router IP] [Victim IP]` | Intercept packets from the router with arpspoof |
| `arpspoof -i eth0 <Target IP> <Target Client>` | Connect to the target network to allow the packets by tricking the access point and client |
| `arp -a` | Shows ARP cache table |
| `arp.spoof on` | Start ARP spoofer |
| `arp.ban on` | Start ARP spoofer in ban mode, meaning the target(s) connectivity will not work |
| `arp.spoof/ban off` | Stop ARP spoofer |
| `arp -d <Target IP>` | Remove ARP cache entry |
| `arpspoof -t victim gateway` | Tells victim host that MAC address belongs to IP of the gateway |
| `arpspoof -t gateway victim` | Tricks gateway that it is the victim |
| `arpspoof -i <network device> -t <Sheep IP>` | Spoof the Sheep |
| `arpspoof -i <network device> -t <Gateway IP> <Sheep IP>` | Spoof the Gateway |



92% Reported That the C|EH Boosted Their Confidence