

Side Channel Attacks in the Browser

Case for Support

Background

Side-Channel Attacks (SCA) are an important class of cryptanalytic techniques which target unintentional information leakage in order to disclose private data. In general, Side-Channel Attacks monitor a device performing an interesting operation and try to find a correlation between the side-channel information and the internal state of the processing device, which is related to the secret parameters involved in the computation. Side-channel information can be obtained by monitoring variations in the execution time (*Timing Attacks*), the power consumption (*Power Analysis*), the electro-magnetic emission (*Electro-magnetic Analysis - EMA*), or the state of the cache memory (*Cache Attacks*) [1]. The goal of an attacker in side-channel attacks is to either recover the secret parameters involved in the computation by targeting faults in the implementation of some cryptographic algorithm, or disclose private information about a user, such as their location or browsing history. Side-channel attacks exploit vulnerabilities in a specific implementation rather than targeting an abstract algorithm, making them less generic but more powerful [1].

The expansion of the Internet determined browser vendors to add more and more features to their software in order to offer richer, dynamic and more interactive web pages. The evolution of browser software not only improved the overall user experience but also opened the way for a new category of side-channel attacks known as browser attacks. These types of attacks target vulnerabilities in the browser software. Browser attack fall into two categories: traditional timing attacks, which measure the time it takes the server to respond, and cache timing attacks, which use the time it takes to retrieve a resource in order to determine its origin, either local storage like the browser's cache memory, or a remote server.

Browser attacks are a very powerful category of side-channel attacks, which require minimal set up and affect a wide range of users. A basic browser attack requires a user to navigate to an untrusted website, which contains attacker-controlled content. The web page has a background script which collects information about the victim that can be used by the attacker to infer a user's location, browsing history, or even current browsing activity. The victims are usually unaware that the website is collecting private data about them. One might think that such attacks can be avoided by simply not visiting untrusted websites; however, researchers discovered that even high-profile websites are using similar techniques to collect information about their visitors[2]. For example, a health insurance provider might want to know if the user has any health problems. If the user visited any health related web pages, they must be stored in the browser's cache memory, therefore an attacker who can investigate the state of the cache memory can find out what health issues the victim might have.

Compared to classic Side-Channel attacks, browser attacks appear and disappear at a faster rate. The majority of vulnerabilities found in the browser software get patched in less than a year. This gives attackers a limited time frame in which they can exploit potential vulnerabilities in web browsers. Sometimes the proposed countermeasure for certain browser attacks can severely impact the browser's performance and browser vendors choose not to include the fixes until a better solution is found. There is no guarantee that a countermeasure, which does not impact the performance of the browser software, will ever be found.

There are browser attack discovered over fifteen years ago that have been improved over the years and are still in use today.

One of the first browser attack was discovered by Felten and Schneider[3] in 2000. Their attack measures the time it takes to retrieve a static web page and determines if it has been fetched from the browser's cache memory or from a remote server. An adversary can use this attack to disclose a user's browsing history. A few years later, Bortz et al.[4] identified a vulnerability in HTML, which allowed them to estimate the size of a remote file. Their work was extended by Van Goethem et al.[5], who use newer web development technologies in order to determine the size of a cross-origin resource.

Browser attacks are not only used to determine how much information a user has access to, in 2015 Jia et al.[6] demonstrated that it is possible to determine a user's location. Additionally, Oren et al.[7] showed that it is possible to disclose a user's current browsing activity by analysing the state of their browser's cache memory.

Motivation

The aforementioned papers present various techniques for disclosing private information about users, by either measuring the amount of data the users have access to, or simply determining what pages they previously accessed by checking the state of their browser's cache memory. Additionally, most of the papers present real world scenarios where the attacks can be used to de-anonymize a user; however, the attacks are presented from the perspective of a malicious user who is trying to gain access to private data. Our research is going to explore how browser attacks can be used by governmental organisations to obtain crucial information about a specific user. More specifically, we are going to target social network website users and determine their friend graph.

In an attempt to offer more interactive, dynamic and richer web pages, browser vendors have been adding support for more and more features. This not only improved the overall user experience, but also led the way to a series of exploits affecting browser software. In general, these vulnerabilities appear and disappear within weeks. Therefore, adversaries have a limited time frame in which they can exploit potential browser vulnerabilities. Sometimes, adding a fix for a browser attack can severely impact the performance of the browser, hence, browser vendors avoid incorporating the countermeasure into their software. Therefore, some browser attacks can be exploited for years until a better solution is found. This is the case of the attacks discovered by Felten et al.[3] and Bortz et al.[4].

This motivated us to investigate new applications for this particular kind of browser attacks. Our research will target social network platforms and explore how side-channel information can be used to obtain a user's list of connections on social networking websites. In their paper, Van Goethem et al.[5], briefly mention a real world application of the browser attack in which they can determine if two people are friends on Facebook, or connected on LinkedIn. We are going to use their idea and efficiently determine a user's full list of contacts on any social network platform.

Project Objectives

The aim of this research is to provide theory, tools and techniques for disclosing a user's list of connections on social media platforms. More specifically, we will focus on the following objectives:

1. To analyse known browser attacks which can be used to obtain hidden information from social media websites.
2. To build a web application which disclosed information about social network users.
3. To find new vulnerabilities in the browser software, which provide more efficient ways of estimating the size of a remote file.

4. To build a basic model which determines a user's connections on a small size internal social network website.
5. To use data provided by the Defence Science and Technology Laboratory (DSTL) in order to refine the algorithm.
6. To build a web application which discloses the full list of friends of a real world social network website user.
7. To run workshops in order to increase awareness about browser attacks and present the latest discoveries in the field.

Programme and Methodology

Throughout this section we will refer to the list of a user's friends or connections on social media platforms as the **friend graph**.

Personnel listed in the program of work are as follows:

Principal Investigator (PI): Ana Dumitras from the University of Bristol with experience in Applied Security and Browser Attacks. **Co-Investigator (CI):** Brian May from the University of Bristol with experience in web based applications.

Co-Investigator: Roger Taylor from the University of Bristol Department of Law, who will assist on any data protection related issues.

Workpackage 1 (WP1) : A preliminary analysis of published attack vectors

Research leader: Ana Dumitras

Principle research objective:

To review the existing literature on side-channel attacks in the browser and determine the efficiency of the attack vectors. Then we will implement a set of chosen browser attack which will later be used to determine the friend graph. Additionally, we will discover new vulnerabilities in the browser software, which will provide more efficient results for estimating the size of a remote file.

Principle deliverables:

1. Review existing literature on the most important side-channel attacks in the browser.
2. Provide implementations for the selected browser attacks, optimised to work on the most recent versions of browser software.
3. Provide new attack vectors for estimating the size of a cross-origin resource.

The goal of this package is to review existing attack vectors and analyse their efficiency in state-of-the-art browser software. Initially, this work package will focus on selecting a series of side-channel attacks in the web browser to be analysed. We will use Semantics Scholar [8] and Google Scholar[9] to identify the set of papers to be reviewed. In order to determine the friend graph in WP3 and WP4 we need to select a specific set of side-channel attacks in web browsers. The criteria for selecting the papers is that they can be applied to real world scenarios where we are trying to determine the size of a remote file. Such attacks have been around for years and there are lots of resources available.

The second task in this work package is to implement some of the selected browser attacks. Before implementing the attacks, we are going to theoretically determine if the attacks are still feasible. Even if

the attacks are still possible, changes in the browser software will require additional work in order to run them on current versions of the browser software. The outcome of this task is a series of browser attacks which work in the most popular browsers, such as Chrome, Firefox, Safari and IE.

The third task, which is to be completed after WP1.1 implies finding new vulnerabilities in the browser software. We are going to use the information gained from reviewing past browser attacks and find similar patterns in new web development technologies.

This work package is to be completed by a PhD student together with a PDRA, under the supervision of the PI. The researchers are going to be supported by the CI, who has experience in web development. The attack vectors which will be reviewed are to be determined by the researchers.

Workpackage 2 (WP2) : Build a model for answering yes-no questions about the user.

Research leader: Brian May

Principle research objective:

To build a web applications which is able to answer yes or no questions about the victim's profile on social network websites.

Principle deliverables:

1. Provide a web application which can be used to determine information about the victim.
2. A collection of tests for analysing the performance of the web application.

This work package builds on the work from WP1, where we determine a set of suitable methods for estimating the size of a remote file. The goal of this work package is to build a web application which is able to infer certain information about a social network website user, such as group membership or if they have access to specific resources on the social network platform. More specifically, given a link to a resource on the social network website, our web application should be able to tell if the user has access to that resource or not by using techniques from WP1. This is similar to asking the application a series of questions whose answer's can only be yes or no.

The work is to be carried by the PhD student together with the PDRA, under the supervision of the CI, who has experience in web applications and social media platforms. The criteria for success will be how our web application guesses is certain facts about the user are true or false. Additionally, the application should be able to check if two users are connected, this would later be used in WP3.

For ethical reasons we are not going to use data from actual users, but we are going to set up several accounts on the most popular social networks, like Facebook, Twitter or LinkedIn, and test our application on those accounts.

Workpackage 3 (WP3) : Build model for determining the friend graph

Research leader: Ana Dumitras

Principle research objective:

To extend the web application developed in WP2 such that it works on a small size social network website provided by the Defence Science and Technology Laboratory (DSTL).

Principle deliverables:

1. Provide a web application which discloses the friend graph on an internal small size social network.
2. A series of workshops about browser attacks targeting social media websites.

This work package focuses on disclosing the friend graph in a small size social network platform. As mentioned in WP2, for ethical reasons we are should not test out web application on real world social network platforms, like Facebook or LinkedIn, so the Defence Science and Technology Laboratory (DSTL) has agreed to provide us access to a internal social network platform where we are going to test our web application.

In general, DSTL prefers work to be conducted by external suppliers. They are interested in being able to disclose the friend graph of social network users and have agreed to support our research by providing us with the needed data for developing the web application. DSTL is interested in learning more about vulnerabilities in social network platform and how to defend against them.

The main goal of this work package is to have a web application which automatically displays the friend graph when given a link to a user's profile on DSTL's social network platform. The work is to be completed by a PhD student together with the PDRA, supervised by the PI. Additionally, DSTL is going to offer support by providing us with access to the internal social network platform. The success of this work package is measured in how accurately we can determine the friend graph on the given social network.

As part of this work package we are going to run a series of workshops to increase awareness about browser attacks. The PDRA will be in charge of the workshops, additional support will be provided by the PI and CI.

Workpackage 4 (WP4) : Test the model on real world social networks

Research leader: Brian May

Principle research objective:

To build a web application which discloses the friend graph of a user on a real world social network website.

Principle deliverables:

1. Provide a web application for obtaining the friend graph of a user on a real world social network website.

After the successful completion of WP3, we are going to focus on extending the web application to work on any social network platform. DSTL are interested in using our web application. The aim of this work package is to disclose the friend graph of a user of any social network website. This is going to be part of an ongoing project by DSTL which focuses on de-anonymising social network users who might pose a threat to national security.

The work will be completed by the PDRA, supervised by the CI. Since DSTL will be the main user of this application, they will provide additional support such as offering testing data and they will provide feedback during the implementation stage. Due to ethical reasons we are not allowed to test the application on random users. Dr. Roger Taylor from the Department of Law at the University of Bristol, who is specialized in Data Protection, is going to support our work during the development of this work package and provide any information needed for working with user data. The success of this work package is measured in how efficiently our web application works in "the wild". Basically, given a link to a new social network website, our application is going to adapt to the new conditions and provide the friend graph.

National Importance

Our work is going to help the Defence Science and Technology Laboratory (DSTL), which are interested in discovering new applications for side-channel attacks in web browsers. Through our work with DSTL, we are contributing to the defence and security of the UK. Additionally, we will run several workshops aimed at increasing awareness about browser attacks, which should significantly decrease the number of users falling victims to browser attacks and make browser vendors more aware of potential exploits in their software.

Academic Impact

Our research will extend existing browser attacks to work in current version of the mainstream browsers. Additionally, we are going to find new vulnerabilities in web development technologies, which will lead to more efficient methods for estimating the size of a cross-origin resource.

We plan to open source the software resulted from WP1 and WP2 in order to encourage researchers to build on top of our work and find new applications for browser attacks.

References

- [1] François-Xavier Standaert. Introduction to side-channel attacks. In *Secure Integrated Circuits and Systems*, pages 27–42. Springer, 2010.
- [2] Dongseok Jang, Ranjit Jhala, Sorin Lerner, and Hovav Shacham. An empirical study of privacy-violating information flows in javascript web applications. In *Proceedings of the 17th ACM conference on Computer and communications security*, pages 270–283. ACM, 2010.
- [3] Edward W Felten and Michael A Schneider. Timing attacks on web privacy. In *Proceedings of the 7th ACM conference on Computer and communications security*, pages 25–32. ACM, 2000.
- [4] Andrew Bortz and Dan Boneh. Exposing private information by timing web applications. In *Proceedings of the 16th international conference on World Wide Web*, pages 621–628. ACM, 2007.
- [5] Tom Van Goethem, Wouter Joosen, and Nick Nikiforakis. The clock is still ticking: Timing attacks in the modern web. In *Proceedings of the 22nd ACM SIGSAC Conference on Computer and Communications Security*, pages 1382–1393. ACM, 2015.
- [6] Yaoqi Jia, Xinshu Dong, Zhenkai Liang, and Prateek Saxena. I know where you’ve been: Geo-inference attacks via the browser cache. *Internet Computing, IEEE*, 19(1):44–53, 2015.
- [7] Yossef Oren, Vasileios P Kemerlis, Simha Sethumadhavan, and Angelos D Keromytis. The spy in the sandbox—practical cache attacks in javascript. *arXiv preprint arXiv:1502.07373*, 2015.
- [8] Semantics scholar. <https://www.semanticscholar.org/>. [Accessed: 2016-05-18].
- [9] Google scholar. <https://scholar.google.co.uk/>. [Accessed: 2016-05-18].

Budget

Item	Cost for 3.5 years (£)
PI	140,000
CI1	70,000
CI2	70,000
PDRA	350,000
PhD student	100,000
Equipment	10,240
International travel costs	52,742
National travel costs	15,366
Workshops	5,346
Total cost	813,694

Justification For Resources

Directly incurred costs: staff

There are five members from the University of Bristol involved in this research project. The Principal-Investigator will spend 20% of their time working on this project. Additionally, we will need two Co-Investigators, each will contribute 10% of their time. The first CI will have a background in web development, while the second CI has experience in Data Protection and is going to provide support during the development of WP2, WP3 and WP4. The main research cost is the time of the PDRA and the PhD student, who are going to work full-time on this project.

Directly incurred costs: consumables

£4,000 is requested for PCs for the PDRA and the PhD student.

£3,740 will be used to acquire additional equipment needed for implementing and testing platform specific attacks, such as mobile phones and tablets.

£1,000 will go towards Cloud Computing costs, we are going to our web applications on Google App Engine (GAE).

£1,500 is going to be used to acquire any software licenses needed.

Directly incurred costs: travel and subsistence

Budget has been allocated for each member to travel to several relevant conferences, such as COSADE: Constructive Side-Channel Analysis and Secure Design. Since our research project combines several field: side-channel attacks, web development and data protection, we are encouraging the researchers to attend conferences and workshops from different domains relevant to our project.

Additionally, £15,366 are going to be used for travelling in order to collaborate with other academics or members from the industry.

Directly incurred costs: workshops

We will run 5 workshops over the next 3.5 years. £5,346 is allocated to cover catering costs and any additional equipment needed for the workshops.

Impact Statement

Our project can be split into two parts: the first one targeting academic development, and the second part which focuses on working with industrial partners and providing them with tools for de-anonymizing social network users. The first part consists of WP1 and WP2, while the second part is going to be completed in WP3 and WP4.

As stated in the Academic Impact section, we are going to improve existing methods and introduce more efficient techniques. We are going to publish our research in both journals specific to the domains we are working on (side-channel attacks, browser security), and interdisciplinary journals such that we will reach a wider audience. Additionally, we will run a series of five workshops aimed at increasing awareness about browser attacks and how they can be used to obtain information about social network platform users.

The primary beneficiaries of the research are security companies, particularly the Defence Science and Technology Laboratory (DSTL), which are going to use the tools we build in order to obtain the friend graph of certain social network website users, who pose a threat to national security. The DSTL are going to provide us with the data needed to build the web application during WP3.

The research outputs from WP1 and WP2 are going to be published in specialised journals and are highly technical. Also, we are going to open-source the implementations such that other researchers can use our work to develop new applications supporting further work in the field.

Our research is mainly focused on providing new applications for browser attacks, more specifically providing tools for disclosing the friend graph of a social network web site user. A successful research will result in two completely different outcomes. On one side, we improve existing browser attacks technique and discover new attack vectors which will allow governmental organisations to obtain vital information. On the other side, through publishing out results from WP1 and WP2, and open-sourcing our software from the aforementioned work packages, we are going to determine browser vendors to pay more attention when introducing new features to their software such that similar attacks can be avoided.

Workplan

TASK	Q3 2016	Q4 2016	Q1 2017	Q2 2017	Q3 2017	Q4 2017	Q1 2018	Q2 2018	Q3 2018	Q4 2018	Q1 2019	Q2 2019	Q3 2019	Q4 2019
WP1.1														
WP1.2														
WP1.3														
WP2.1														
WP2.2														
WP3.1														
WP3.2														
WP4														

Notes to the diagram

Our research is split into four packages, all focusing on different areas. During the first two packages we are going to build the tools needed, while in the last two packages we are going to explore new applications of browser attacks, which can be used by the defence industry.

We are going to start work with WP1.1, which aims at gathering the necessary data. After 3 months we are going to start working on WP1.2, which is closely related to WP1.1 and involves implementing some of the papers. Once we finish, reviewing the literature on browser attacks, we are going to start working on WP1.3, which involves finding new vulnerabilities in browser software. During this time we are going to run two workshops, one in after 6 months focusing on general browser attacks and another one in the second quarter of 2017, which is going to present our findings. After WP1 has been completed, we can start working on WP2, which involves building a web application. At the same time we are going to run another workshop, focusing on attack vectors in social network websites. At the end of 2018, we are going to start working on WP3 together with DSTIL, who are going to provide us with the needed data. During WP3 and WP4 we are going to run two more workshops focusing on de-anonymising social network website users. The last 9 months are going to be spent working on WP4.

We plan to release several papers during WP1 and WP2. Additionally, we expect to publish a technical report after finishing work on each of the last two work packages, WP3 and WP4.