Pushing the Quadratic Boundary when Computing a Closest Pair

Author

November 4, 2026

Contents

1 Introduction **2**
- 1.1 Duplicate Points . . . 2
- 1.2 Points on a Line ($d = 1$) . . . 2

2 Methodology **3**
- 2.1 Language Choice . . . 3
- 2.2 Point Generation . . . 3
- 2.3 Correctness Checks . . . 4
- 2.4 Benchmarking . . . 4

3 Low Dimensions **5**
- 3.1 Two-dimensional Points ($d = 2$) . . . 5
  - 3.1.1 Divide-and-conquer . . . 5
  - 3.1.2 Sweepline . . . 6
  - 3.1.3 Grid Decomposition . . . 6
- 3.2 Beyond Two Dimensions . . . 7
  - 3.2.1 An Attempt to Generalise Sweepline . . . 7
  - 3.2.2 Grid Decomposition (Revisited) . . . 7
  - 3.2.3 k-dimensional Tree . . . 8

4 Heuristics **10**
- 4.1 Random Pairs . . . 10
- 4.2 Neighbours in a Sorted Order . . . 11
  - 4.2.1 Along Each Axis . . . 11
  - 4.2.2 Along Random Directions . . . 11
  - 4.2.3 Along the Z-order Curve . . . 11
- 4.3 Best-first Search on the k-dimensional Tree . . . 13
- 4.4 High Dimensions . . . 14

Chapter 1

Introduction

Computing the distance between two points is a common geometrical task. A natural extension to that would be to find the *closest pair* of points, i.e., the pair that yields the smallest distance. Assuming a point in d-dimensional space, computing the distance between two points takes $\mathcal{O}(d)$ time. There are $\binom{n}{2}$ pairs to check, forcing a total time complexity of $\mathcal{O}(d \cdot n^2)$.

In general, for large d, it's not possible to beat quadratic time in the *worst case*, assuming the **Strong Exponential Time Hypothesis (SETH)**. Luckily for us, there are tricks to salvage the situation at low dimensions, and for practical applications like vector databases, people have ditched the intractable task of obtaining an exact solution, opting for approximate algorithms instead.

1.1 Duplicate Points

Depending on the circumstances in which these points were generated, it's quite possible that we end up with duplicate points. For example, consider the Birthday Paradox. While it seems strange that only 23 people are required to produce a coin flip chance of having a shared birthday (the equivalent of two overlapping points), that's just how the probability checks out.

One way to solve this problem would be to first sort the points and check adjacent items to see if they're equal. Another approach is to inject them into a *hash set* one by one, and prior to the insertion, if the set already contains the point, we know a duplicate exists. The extra logarithmic factor in the former might seem burdensome, but it might actually beat the latter in terms of real runtime, considering hash sets in many languages are often plagued by high constant factors. Not to mention sorting also happens to be the first step in many of the subsequent algorithms, so the duplicate check arrives almost free in a sense.

1.2 Points on a Line ($d = 1$)

At $d = 1$, the points are just an array a of scalar values, so one may simply sort a and compare adjacent elements, consuming $\mathcal{O}(n \log n)$ time. If the range of values ($k = \max(a) - \min(a)$) is small enough, *counting sort* may be exploited to solve the problem in $\mathcal{O}(n + k)$.

At this juncture, it's natural to question if it's possible to achieve $\mathcal{O}(n)$ irrespective of k, and as it turns out, there are randomised algorithms with linear expected time. These algorithms are rooted in the idea of *decomposition*, and they generalise to higher dimensions as well. We'll elaborate more on the details when we get there.

Chapter 2

Methodology

2.1 Language Choice

The algorithms are implemented and tested in C++ for several reasons.

- A low-level compiled language gives you realistic estimates on how fast these algorithms actually are when they aren't held back by overheads like an interpreter.
- You get precise control over memory layouts and whether things go on the stack or the heap. For the most part, data structures like `std::array` are preferred because they reduce pointer chasing and are more cache-friendly.
- Multithreading is easy to perform in C++, thanks to tools like `std::jthread`. Although theoretical time complexities are important, whether or not an algorithm is practical and useful in real life also depends on how well it may be *parallelised*.

Brute force might be an *embarrassingly parallel* algorithm, but it's still easy to write a suboptimal implementation. With n points and t threads, one might think to split the points into contiguous chunks of n/t points each. The issue is that for the points p_i at the start, we have to match them with p_j, where $i < j$, and at say $i = 0$, we check a huge number of points, whereas for a late i, there's nothing much to check. Thus, the thread in charge of the first block bears a lot more work, and takes longer to finish.

To improve the distribution of work, let's implement a rule where point i is handled by thread $i \bmod t$. Each thread has its own local best, and at the end, we update the global pair based on these local pairs. One advantage to this technique is that we avoid having to use synchronisation primitives like atomics or mutexes (which add extra overhead) to protect the global answer from race conditions.

You may get the thread count using `std::thread::hardware_concurrency()`. On my machine that's twelve threads. Unfortunately, this doesn't imply that we'll get a twelvefold speedup, since the processor consists of both performance cores and efficiency cores, with the latter running at only a fraction of the speed.

2.2 Point Generation

A meaningful dataset should try and avoid degenerate cases like duplicate points. This necessarily forces a large-enough range to circumvent the Birthday Paradox. In addition, it should be easy to compute the distance between any two points, and compare distances accurately. In

other words, let's avoid floating point operations. Not only is it easy to mess up comparisons, when adding floats together the ideal strategy is to sort them by size and add the smallest numbers first before merging with the large ones. And this adds extra overhead that detracts from the core task at hand.

So `int` it is, and because we're working with *Euclidean* distances, a trick to preserve precision and reduce operations is to avoid the square root altogether, and compare squared distances instead. To spawn a set of points, we used the *Mersenne Twister* pseudorandom number generator (`std::mt19937_64`) to achieve a uniform random distribution of points. Fixed seeds are also used to ensure fair benchmarking.

2.3 Correctness Checks

As we implement various (increasingly complicated) algorithms, it's essential to validate their correctness. The simplest way to do so is to use the brute-force algorithm as a baseline, and check if the squared distance (conveniently, an integer) between the closest pair is the same across a range of different test cases. From my personal experience, here are some common mistakes and pitfalls.

- You get a best distance of *zero*, even though brute force produced a nonzero value. This is likely because in the inner loop, you wrote `int j = i`, instead of `int j = i + 1`, so you mistakenly used the same point twice.
- You did not achieve the best distance. This might be because you failed to enumerate neighbours correctly (e.g., during grid decomposition), or you messed up the base case in recursive algorithms such as divide-and-conquer.
- Strange and inconsistent behaviour across different runs. This might be a symptom of *undefined behaviour*, and the cause is usually out-of-bounds access, a data race (during multithreading), or signed overflow.

2.4 Benchmarking

To figure out which algorithms are "better" than others, the most practical approach is to measure their runtimes. There are some ground rules we set to provide the fairest comparison. First, point generation should never be considered as part of runtime; we'll always generate them before starting the clock. Next, points are fed to the solver by *value*, not reference. Algorithms are free to mess with the dataset however they like, with the original dataset remaining unaffected. Third, you pay for the cost of building data structures, assuming you need one (e.g., grid decomposition). As long as meaningful work is being done to contribute to the solution, we feel that it should add to the measured runtime. Finally, fixed seeds are used to generate the datasets, ensuring replicable results.

> Well, I haven't quite decided on a good sample size at the moment...
>
> We'll revisit this section another time.

Chapter 3

Low Dimensions

3.1 Two-dimensional Points ($d = 2$)

Numerous works have explored the two-dimensional case, and there exist well-known $\mathcal{O}(n \log n)$ solutions. Perhaps the most famous one is through divide-and-conquer, so let's begin with that.

3.1.1 Divide-and-conquer

Let's divide the set of points into two (approximately equal) halves. If n is odd, the first set will just be of size $\lceil n/2 \rceil$ and the second set will be of size $\lfloor n/2 \rfloor$. Intuitively, we want those with smaller x in one set and those with larger x in the other. For convenience, we can sort the points beforehand, with the sorting key being the point vector itself, i.e., perform element-wise comparison (check who has the smaller x, else if they have equal x, compare by y instead).

In the base case of $n = 1$ we simply return infinity (there's no pair!), else let's assume we have solutions to both halves. Let's take the minimum answer from each half (we'll denote this distance δ). Our goal is to potentially connect points from the two sets to achieve a new minimum. Consider the vertical divider ($x = x_{\text{mid}}$) used to partition the halves. Our candidate points are going to lie in the interval $(x_{\text{mid}} - \delta, x_{\text{mid}} + \delta)$. For some point (x_0, y_0) in this set, we may check just those in the interval $y \in (y_0 - \delta, y_0 + \delta)$. In fact we may just check those points with $y \leq y_0$, avoiding duplicate work.

This "box" of width $2 \cdot \delta$ and height δ contains $\mathcal{O}(1)$ points. Consider the left and right squares composing this box. If we partitioned each square into a grid of four smaller sub-squares of width $\delta/2$, you may fit at most one point into each sub-square. Even if we had placed points as far apart as possible, the distance is still $\delta/\sqrt{2}$. If two points fitted in a sub-square, that'll imply we should have gotten a smaller answer from one of the sub-problems, producing a contradiction.

To check points in this box easily, we'd like the points to be sorted by the y coordinate instead. This can be done exactly like how you'd perform *Merge Sort*. Surprisingly, the nature of our divide-and-conquer approach is no different from that of Merge Sort, and our time complexity is hence $\mathcal{O}(n \log n)$.

> Parallelising this algorithm is nontrivial, which is why we opted out of it. While it seems plausible to assign a new thread to solve each subtree, we end up with way too many threads (in the order of $\mathcal{O}(n)$), and the overhead costs of creating a thread (e.g., reserving a new stack) slow down the system far more than any potential savings. Of course, a smarter solution would opt for tools like thread pools to keep the thread count manageable, but figuring out the right allocation is pretty tricky as well.

3.1.2 Sweepline

One downside of divide-and-conquer is the runtime overhead of the recursive calls. An alternative that yields the same time complexity (and also happens to be a bit faster empirically) is a sweepline approach. We begin by sorting the points like in divide-and-conquer. Next, we'll iterate through the points, and maintain a set of earlier points. This set organises the points in terms of y values.

Given the current minimum distance δ and the current point (x_0, y_0), we only need to check points in the set with $y \in (y_0 - \delta, y_0 + \delta)$. Using a similar box analogy, one may prove we check a constant number of points, producing an overall complexity of $\mathcal{O}(n \log n)$. Implementation-wise, we use C++'s `std::set` that uses a balanced binary search tree (specifically a red-black tree) under the hood.

> Because of the sequential nature of the sweep, it's not easy to parallelise this algorithm either. We require the rolling set of points sorted by y, and it's not feasible to have some sort of shared set across independent sweeps.

3.1.3 Grid Decomposition

As alluded to at the start, there are algorithms that offer linear expected time. The trick is to visualise the search space as a grid, and group points into squares on a grid. To figure out the nearest pair, there are two cases to handle. First, iterate all pairs within a grid square. Second, considering a point within a square, let's check its distance against all other points in adjacent squares. If we pick a good grid width, we'll only run through a constant number of pair checks per grid square, thus yielding $\mathcal{O}(n)$ time.

Intuitively, the grid width should be neither too big nor too small. A grid that's too fine-grained might make it impossible to find a neighbouring point in the vicinity, and a large grid width just degenerates into the brute force search. In a perfect world, we'd take the distance between the closest pair as the grid width, but that brings us right back to the original problem. Eventually, people discovered that taking the minimum distance of a bunch of random points (i.e., sample n pairs) produces a grid width that works surprisingly well.

The first version of the randomised grid approach was actually proposed by Rabin [8] half a century ago. In this version, he sampled about $\sqrt{n}$ points and took the distances produced by these points. This takes only $\mathcal{O}(n)$ time! He also proved that it runs in linear expected time. Many years later, it was Lipton [5] who discovered sampling random pairs worked too, and it made the analysis much easier (because each sampled distance is independent of the others).

Implementation-wise, we use the **SplitMix64** hash function paired with a hash map. At the moment we settled with the standard library's `std::unordered_map`. Despite the amortised $\mathcal{O}(1)$ lookup, its closed addressing scheme isn't particularly cache-friendly.

> Finally, we have a nontrivial algorithm that's worth multithreading. Unlike brute force, where we made each thread responsible for a set of points, this time let's have each thread take charge of a set of squares instead. As usual, we'll allocate a roughly equal number of squares to each thread. Since viewing points in neighbouring squares is a read-only operation, we don't need to guard it from data races. One implementation detail is to extract all the iterators beforehand, and not to be misled by the sneaky `std::views::stride(t)` (it doesn't allow for a random access jump when iterating over `std::unordered_map`).

3.2 Beyond Two Dimensions

While the two-dimensional algorithms have proven encouraging, both theoretically and empirically, the real challenge is to solve the problem at higher dimensions, and this is where tools like divide-and-conquer and sweepline begin to fall apart as you can't easily generalise them.

3.2.1 An Attempt to Generalise Sweepline

To understand why scaling sweepline is hard, let's consider how one might refactor the current implementation. The core of the issue is to support queries where given some δ (the best distance so far), and the current point $(q_1, \ldots, q_d)$, we need to find all points such that along every axis, we have $|p_i - q_i| < \delta$. In two dimensions, we use a two-pointer approach to ensure the x axis satisfies this condition, and on the y axis, we maintain sorting through a balanced binary search tree. Everything hinges on the two-pointer sweep, because solving one-dimensional range queries is easy.

Let's try to solve range queries for more than two dimensions. For a moment, let's forget about the two pointers; in just two dimensions, how may we support the range queries? An esoteric data structure comes to mind: the *Merge Sort Tree*. It's basically a segment tree on the x values, and each node in the segment tree stores its points sorted by y values. To answer a query, we perform a binary search on each relevant node, and there are $\mathcal{O}(\log n)$ of them. Thus, query resolution only costs $\mathcal{O}(\log^2 n)$. This idea may be generalised to any dimension; we may put a merge sort tree into the node of another merge sort tree (in the literature it's known as a *range tree*), so at dimension d it'll take $\mathcal{O}(\log^d n)$ time.

For convenience, let's not bother with point updates, i.e., we'll build the massive tree once at the start and keep querying it repeatedly. Yes, we're dropping the sweep out of the sweepline, but ultimately the total time complexity is still an optimistic $\mathcal{O}(d \cdot n \log^d n)$. The limiting factor is no longer time but *memory*. And since the size of the tree is $\mathcal{O}(d \cdot n \log^{d-1} n)$, at say $n = 10^4$ and $d = 5$, we have already racked up gigabytes of memory. There's simply no space to store the data structure!

3.2.2 Grid Decomposition (Revisited)

One neat property of grid decomposition is that it extends naturally to arbitrary dimensions. A square morphs into a hypercube, and now we need to check adjacent hypercubes instead. There's one big problem though; at dimension d, there are $(3^d - 1)/2$ neighbours to check, and beyond a certain point, you're better off just brute-forcing.

As pessimistic as it sounds, let's try to exploit the nature of the point distribution to improve the selection of the grid width. Knowing that we have a uniform random distribution, it's possible to work out how far, on average, a point is from its nearest neighbour, and then we could use that as a basis for our grid width. This is an ancient problem that was solved by Hertz in 1909 for points scattered through three-dimensional space [4], and the same analysis extends to any dimension. For n points spread uniformly through a box of volume V, the expected distance from a point to its nearest neighbour is

$$\mathbb{E}[R] = \Gamma\left(1 + \frac{1}{d}\right)\left(\frac{V}{n\,\omega_d}\right)^{1/d},$$

where $\omega_d = \pi^{d/2}/\Gamma(d/2 + 1)$ is the volume of a d-dimensional ball of radius 1, and Γ is Euler's *Gamma function*. In our implementation, `unit_ball_volume` supplies ω_d, `std::tgamma` the Gamma function, and `bounding_box_volume` measures V from the points themselves. The function `expected_nearest_neighbour_distance` then puts the pieces together.

While it's possible to use this result directly as the grid width, we hesitated to do so and went with double this expected value instead. One reason is that we don't want to have hypercubes

that are too tiny; with fewer hypercubes, we waste less time on the hash lookups. Another, admittedly more important, reason is rooted in safety. An expected value is not the same as the actual value; if we use a grid width that's too small, we end up not finding anything at all, which is even worse. At small n the variance is too high, and the formula isn't useful, so below `SMALL_POINT_COUNT` we fall back to random sampling.

> A more insidious bug caused by grid widths that are too small is reporting the wrong answer. Let's say that we have two points a and b on a horizontal line, one at $x = 0.95w$ and the other at $x = 2.05w$. They have a distance of $1.1w$, though they won't end up in adjacent squares. Let's also have a point c at $x = 3.95w$; it'll be paired with point b and give a "best" distance of $1.9w$, even though we know the true minimum is lower. Luckily, with the uniform random distribution such an edge case is statistically very unlikely. For guaranteed correctness in arbitrary distributions, stick to random sampling.

3.2.3 k-dimensional Tree

A closely related problem to finding the closest pair is to handle point queries where given a certain point, we ask for the nearest point to it. Answering the main problem then becomes calling point queries on every point, and if we can perform this point query fast enough, we'll beat the brute force approach.

As fate would have it, decades ago people already invented a data structure called the k-dimensional tree. In short, each node of this *binary tree* contains a point. To construct the tree, let's assume we're at the root. To decide which point gets to be the root, we'll take the *median* point based on the first axis (in two dimensions that'll just be x). Now, all points with x less than the median go to the left subtree and the rest go to the right subtree. Recurse down to the next subtree and this time, we'll partition based on the second axis (i.e., y). Rinse and repeat till the tree is fully constructed. Note that the maximum depth of this tree might *not* be d, it could exceed d and if so we just loop back to the first axis.

To resolve a query, let us conduct a depth-first search from the root. At each node in the tree, let's use it to improve the current score. Next, we need to figure out which subtree is likely to give us a better answer, and the instinct is to use the current axis as a basis of comparison. For example, if x of our query point is greater than that of the current node, let's recurse the right subtree. What's important to realise is that this is just a *heuristic*, it's not guaranteed that the nearest point is going to be in the right subtree!

Denoting the gap along this axis as $g = x_q - x_m$, where x_q is the x coordinate of the query point and x_m is the x coordinate of the node, and without loss of generality assume that $g \geq 0$ (the right subtree case), then if $g \geq c_{\text{best}}$, where c_{best} denotes the current minimum distance, there's no point exploring the left subtree since we'll need to pay the cost of g which already exceeds our best answer.

Empirically, this data structure works great on our points because of the underlying uniform random distribution. During tree construction, we're almost always able to attain two subtrees of approximately equal size. As a result, the binary tree is very balanced, and the build stage consumes $\mathcal{O}(n \log n)$ time. Another phenomenon at low dimensions is that this pruning heuristic cuts off useless subtrees really well, allowing us to enjoy point queries in roughly $\mathcal{O}(\log n)$ time, leading to a total time complexity of $\mathcal{O}(n \log n)$. Of course, things break down at higher dimensions because points become sparse, and the contribution of each dimension towards the overall distance is tinier. Eventually, we end up needing to search both subtrees. Fortunately, it just degrades to the brute force, unlike general grid decomposition that mandates searching all neighbouring hypercubes.

Given how promising the k-dimensional tree is, it'd be sweet if we could somehow parallelise it. Between the build and query phases, the latter seems more straightforward to parallelise. In fact, because retrieving the closest pair is just making n queries, we may simply allocate each thread to a set of queries. Though one might think it's yet another embarrassingly parallel problem, it turns out there's some nuance to it.

Observe that the smaller the current best distance, the more effective the pruning. Decoupling the queries across threads leads to improvements for sure, but the speedup isn't as great as we'd expect since the threads can't use the best answer from other threads to improve their search. Thankfully, an easy way to share state is through an atomic like `std::atomic<int64_t>`. The next question is to decide when to update this global best. As correct as it appears to update it during recursion, putting it in the hot path is likely to hurt more than it helps, even with the most lenient memory order, that is, `std::memory_order_relaxed`. Therefore, we'd rather do a quick update at the end of each point query. Not only do you now enjoy extra pruning through the shared global best distance, it comes without paying the full price of synchronisation overheads.

Chapter 4

Heuristics

In the previous chapter, we explored algorithms that found the exact closest pair. However, at high dimensions, with millions of points, these algorithms become computationally infeasible. The saving grace is that in many practical applications, we do not always require the best answer, and can settle for something that is just *good enough*. As we shall see, even trying out many random pairs finds one that happens to be close to the closest one. And we can also use simple principles to improve the quality of our guesses, i.e., *heuristics*. The downside of such techniques is that we cannot prove how good or bad the final answer is, unlike *approximation algorithms* where we put a limit on the magnitude of the final error.

To judge the quality of a heuristic algorithm, we can measure how far off the discovered pair is from the minimum distance. This needs to be handled carefully, however; the more iterations we run of the random pair guessing algorithm, the more likely it is to get a better answer, so it is not fair to buff a heuristic simply through stacking more guesses. Let us introduce the idea of a *budget*, so that each algorithm has a certain "capacity", which may be thought of as a resource to be spent. The implication is that we can fix the budget, and attribute superior performance to smarter ideas, rather than to more compute.

The most tempting approach would be to have this budget be *runtime*, but empirically, it is not that easy to figure out the set of parameters that yield a precise runtime. The alternative is to go with a more theoretical construct, that is, the number of comparisons. Each comparison is a distance computation between two points, and the budget is the number of comparisons you perform per point, i.e., total comparisons over n. The budget is thus an integral "multiple" that is easy to work with. For simplicity, we define the budget rather loosely: if you examine the same pair twice, it counts twice, and we exclude the cost of precomputations from this budget, so you may perform sorting or build data structures free of charge. Of course, the precomputations cannot be ludicrous; the ones used are all of subquadratic time.

4.1 Random Pairs

The simplest heuristic algorithm is born from a tiny modification to the brute force. At each point, instead of trying every other one of the $n - 1$ points, we will pick a partner uniformly at random and repeat this a times (`attempts_per_point`). The budget is just a.

As seen in Figure 4.1, the **ratio** (i.e., the distance found divided by the true minimum distance) steadily decreases as we increase a. At $a = 60$, we have found a pair whose distance is about 2.3 times the closest distance. There are diminishing returns to increasing a; going from $a = 6$ to 18 improves the mean by about as much as going from 18 all the way to 60. Luck is an important component too; for each a, the ratio spread is pretty wide as we go from trial to trial, and you could go anywhere from one to four at $a = 60$. Regardless, it is comforting to know that examining just a tiny fraction of possible pairs already yields such a low ratio.




Figure 4.1: Random pairs at $d = 6$ and $n = 10{,}000$.

4.2 Neighbours in a Sorted Order

Sorting is the basis of the divide-and-conquer and sweepline algorithms. The reason they do not scale to high dimensions is that the "box" of valid neighbours grows exponentially with d. Nevertheless, there are different heuristics we may use to sort the points, the goal being to place points that are close to each other near one another in the sorted order.

4.2.1 Along Each Axis

The first idea that comes to mind is to sort the points using their coordinate on one axis, and then apply a sliding window, i.e., check w neighbours per point. Intuitively, a closest pair should be close on some axis (though there are counterexamples to refute this), and in total we have a budget of $d \cdot w$.

4.2.2 Along Random Directions

To generalise the earlier idea, we can actually create our own axis (so we unlock an arbitrary number of directions to sort by). First, let us pick some direction u in d-dimensional space. Each component of u is drawn independently from a standard normal distribution, which makes the direction uniformly random over all directions [7]. Next, every point p gets a sort key equal to the *projection* $p \cdot u$. The total budget is $m \cdot w$ (where m is captured by `direction_count`).

As Figure 4.2 shows, sorting is truly a powerful tool. Even at a budget of four, we have already surpassed the best ratio random pairs had to offer at a budget of sixty. In fact, given a maximum budget of sixty, trying random directions nets us a best ratio of 1.16.

Between m and w, w appears to have a slightly larger contribution, but that is not to say m is useless, because trying more directions reduces the risk of unlucky projections. Another noteworthy observation is that at a budget of around three hundred, we are even able to find the global minimum.

4.2.3 Along the Z-order Curve

An unorthodox way to sort would be through the Z-order curve (or Morton order [6]). This is a path that goes through every cell of a grid, and it forms a Z shape, giving it its name. A point's position on the curve comes from *interleaving* the bits of its coordinates: starting from




Figure 4.2: Mean ratio of random directions at $d = 6$ and $n = 10{,}000$; the yellow-bordered zone represents cells where $m \cdot w \leq 60$. Cells marked 1 found the distance of the closest pair in *every* trial.

the topmost bit, you take one bit from each axis in turn. For example, $x = 101_2$ and $y = 011_2$ interleave to 100111_2.




Figure 4.3: The Z-order curve on a 4×4 grid. The two highlighted points are close on the grid, but far apart on the curve.

> The most direct method to compare two points is to literally build the interleaved value. Since coordinates take up to 30 bits, the resulting value would have $30 \cdot d$ bits, which does not fit in native types for many d. However, we only really care about the highest bit where the two points differ; a trick to check whether x has a lower top bit than y (`has_lower_most_significant_bit`) is to test $x < y$ and $x < x \oplus y$, where $\oplus$ is bitwise exclusive-or [2].

As is evident from Figure 4.3, points $\binom{0}{1}$ and $\binom{0}{2}$ are close in terms of Euclidean distance, but when inspected in Morton order, they end up far apart. One remedy is to apply a random shift to every point, creating a new order in the process. Implementation-wise, we refrain from adding a shift to the very first order; only later orders get a fresh shift, applied independently

to each axis. With s orders, we have a total budget of $s \cdot w$.




Figure 4.4: Mean ratio of the Z-order curve at $d = 6$ and $n = 10{,}000$; the yellow-bordered zone represents cells where $s \cdot w \leq 60$.

The Z-order curve is staggeringly impressive. Figure 4.4 reveals that across almost the entire budget spectrum, the closest pair was found *thirty out of thirty* times. Only with the fewest orders does the Z-order curve sometimes trip up and find a slightly suboptimal pair.

4.3 Best-first Search on the k-dimensional Tree

In light of the success of the k-dimensional tree in the previous chapter, it seems plausible that we could exploit the structure of the tree to reach nearby points early in the traversal. Let us test out this hypothesis by limiting the number of nodes traversed per query to just b. To pick the nodes for expansion, we can use a Dijkstra-like approach (i.e., a best-first search) with a min-heap. The budget is just b.




Figure 4.5: Best-first search at $d = 6$ and $n = 10{,}000$; yellow rings mark the bounds where *every* trial found the distance of the closest pair.

It is apparent from Figure 4.5 that the results are on par with the Z-order curve. At $b = 6$, the ratio is not particularly great, but that is because traversal always begins from the root,

regardless of the query, and there will always be a few "wasted nodes" that cannot be avoided as part of the expansion process. Nevertheless, from $b = 24$ onwards, it consistently discovers the closest pair.

4.4 High Dimensions

As helpful as the ratio has been in our earlier benchmarking process, this metric begins to lose its effectiveness at higher dimensions. At low dimensions, our best heuristic algorithms are getting perfect scores, and at high dimensions, we are *also* getting near-perfect scores, which should raise some suspicions. The reason is that the distribution of pair distances begins to contract as we increase the number of dimensions, and even random pairs yield tiny ratios at high dimensions (Figure 4.6).




Figure 4.6: Mean ratio of random pairs at $n = 10{,}000$ as d grows, at $a = 6$ and $a = 60$.

Because the ratio only compares our pair with the closest pair, it fails to carry any information about the underlying distribution. As d grows, almost all pairs are about equally far apart, a phenomenon known as *distance concentration* [1]. He et al. measure this with *relative contrast*: the mean distance from a query to the data, divided by the distance to its nearest neighbour [3]. Building on this idea, let δ be the distance of the closest pair, t be the mean distance over all pairs, and x be the distance of a candidate pair. We define the normalised score as:

$$S = \frac{t - x}{t - \delta}$$

Visualise it as a ruler; your average pair lies at 0 and the closest pair at 1. This metric does have a weakness, however, in that at low dimensions, because the "ruler" is incredibly long, almost any pair scores pretty well.

As anticipated, Figure 4.7 reveals that even the strongest heuristic algorithms have their limits. Performance-wise, the Z-order curve and best-first search are clearly the (tied) winners. Random directions holds its own at $d \leq 8$, but its normalised score plummets after that. There are three trends worth noticing. First, the normalised score tends to decrease across the board as d increases; as we enter sparse territory it becomes harder to leverage data structures or representations that put close points beside each other. Second, the *variance* of the normalised score also rises with d before levelling off at around $d = 64$, i.e., it becomes harder to hit the mean score consistently. Finally, all four techniques appear to converge to the same performance

eventually. At super high dimensions, "cleverness" does not help much and you are no better off than just trying random pairs. As pessimistic as it sounds, heuristics still have real value in commonly encountered dimensions. After all, it is not often one needs to work with 2048 dimensions, and even at convergence, getting 90% of the way there by examining about 2.6% of the pairs is still worth the compute.




Figure 4.7: Mean normalised score at a budget of 128 and $n = 10{,}000$, using $s = 8$, $w = 16$ for the Z-order curve, $b = 128$ for best-first search, $m = 8$, $w = 16$ for random directions, and $a = 128$ for random pairs. Shaded bands show the 95% confidence interval of each mean.

Bibliography

[1] Kevin Beyer, Jonathan Goldstein, Raghu Ramakrishnan, and Uri Shaft. When is "nearest neighbor" meaningful? In *Proceedings of the 7th International Conference on Database Theory*, pages 217–235, 1999.

[2] Timothy M. Chan. Closest-point problems simplified on the RAM. In *Proceedings of the 13th Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 472–473, 2002.

[3] Junfeng He, Sanjiv Kumar, and Shih-Fu Chang. On the difficulty of nearest neighbor search. In *Proceedings of the 29th International Conference on Machine Learning*, 2012.

[4] Paul Hertz. Über den gegenseitigen durchschnittlichen Abstand von Punkten, die mit bekannter mittlerer Dichte im Raume angeordnet sind. *Mathematische Annalen*, 67:387–398, 1909.

[5] Richard J. Lipton. Rabin flips a coin. In *The P=NP Question and Gödel's Lost Letter*. Springer, 2010.

[6] Guy M. Morton. A computer oriented geodetic data base and a new technique in file sequencing. Technical report, IBM Ltd., Ottawa, Canada, 1966.

[7] Mervin E. Muller. A note on a method for generating points uniformly on n-dimensional spheres. *Communications of the ACM*, 2(4):19–20, 1959.

[8] Michael O. Rabin. Probabilistic algorithms. In Joseph F. Traub, editor, *Algorithms and Complexity: New Directions and Recent Results*, pages 21–39. Academic Press, New York, 1976.