

1. SPACING (Margin & Padding)

Format

`{property}{sides}-{size}`
`{property}{sides}-{breakpoint}-{size}`

Properties:

`m` = Margin | `p` = Padding

Sides:

`t` top | `b` bottom | `s` left | `e` right
`x` left&right | `y` top&bottom | blank = all sides

Breakpoints (Responsive):

`sm` ≥576px | `md` ≥768px | `lg` ≥992px
`xl` ≥1200px | `xxl` ≥1400px

Examples:

`mt-3` | `px-md-4` | `py-lg-5`
`mx-auto` | `mb-0`

Size	Value	Margin	Padding	Example
0	0rem	<code>m-0</code>	<code>p-0</code>	Remove space
1	0.25rem (4px)	<code>m-1</code>	<code>p-1</code>	<code>mt-1</code>
2	0.5rem (8px)	<code>m-2</code>	<code>p-2</code>	<code>px-2</code>
3	1rem (16px)	<code>m-3</code>	<code>p-3</code>	<code>py-3</code>
4	1.5rem (24px)	<code>m-4</code>	<code>p-4</code>	<code>mb-4</code>
5	3rem (48px)	<code>m-5</code>	<code>p-5</code>	<code>p-5</code>
auto	auto	<code>m-auto</code>	<code>p-auto</code>	<code>mx-auto</code>

Gap Utilities (for Grid/Flex):

`gap-0` `gap-1` `gap-2` `gap-3` `gap-4` `gap-5`
`row-gap-3` `column-gap-3`

2. DISPLAY PROPERTY

Class	CSS	Responsive Example
<code>d-none</code>	<code>display: none</code>	<code>d-md-none</code>
<code>d-inline</code>	<code>display: inline</code>	<code>d-lg-inline</code>
<code>d-inline-block</code>	<code>display: inline-block</code>	<code>d-xl-inline-block</code>
<code>d-block</code>	<code>display: block</code>	<code>d-sm-block</code>
<code>d-grid</code>	<code>display: grid</code>	<code>d-md-grid</code>
<code>d-flex</code>	<code>display: flex</code>	<code>d-lg-flex</code>
<code>d-inline-flex</code>	<code>display: inline-flex</code>	<code>d-xl-inline-flex</code>
<code>d-table</code>	<code>display: table</code>	<code>d-md-table</code>
<code>d-table-row</code>	<code>display: table-row</code>	-
<code>d-table-cell</code>	<code>display: table-cell</code>	-

Common Display Patterns:

- Hide mobile, show desktop: `d-none d-md-block`
- Show mobile, hide desktop: `d-block d-md-none`
- Show only on large: `d-none d-lg-block`
- Hide print: `d-print-none`

3. FLEXBOX

Flex Direction:

```
flex-row
flex-row-reverse
flex-column
flex-column-reverse
```

Justify Content (Horizontal):

```
justify-content-start
justify-content-end
justify-content-center
justify-content-between
justify-content-around
justify-content-evenly
```

Align Items (Vertical):

```
align-items-start
align-items-end
align-items-center
align-items-baseline
align-items-stretch
```

Align Self:

`align-self-start`
`align-self-end`
`align-self-center`
`align-self-baseline`
`align-self-stretch`

Flex Wrap:

`flex-wrap`
`flex-nowrap`
`flex-wrap-reverse`

Flex Fill:

`flex-fill`
`flex-grow-0`
`flex-grow-1`
`flex-shrink-0`
`flex-shrink-1`

Order:

`order-0` `order-1` `order-2` `order-3` `order-4` `order-5` `order-first` `order-last`

Align Content:

`align-content-start` `align-content-end` `align-content-center` `align-content-between`
`align-content-around` `align-content-stretch`

4. WIDTH & HEIGHT

Width Class	Value	Height Class	Value
w-25	25%	h-25	25%
w-50	50%	h-50	50%
w-75	75%	h-75	75%
w-100	100%	h-100	100%
w-auto	auto	h-auto	auto
vw-100	100vw	vh-100	100vh
min-vw-100	min 100vw	min-vh-100	min 100vh
mw-100	max-width 100%	mh-100	max-height 100%

5. TYPOGRAPHY

Font Size (fs):

Class	Size	Equivalent
fs-1	2.5rem	40px
fs-2	2rem	32px
fs-3	1.75rem	28px
fs-4	1.5rem	24px
fs-5	1.25rem	20px
fs-6	1rem	16px (base)

Font Weight (fw):

Class	Weight	Class	Weight
fw-bold	700	fw-normal	400
fw-bolder	bolder	fw-light	300
fw-semibold	600	fw-lighter	lighter
fw-medium	500		

Font Style:

fst-italic | fst-normal

Line Height (lh):

Class	Value	Class	Value
lh-1	1	lh-base	1.5
lh-sm	1.25	lh-lg	2

Text Alignment:

Class	Alignment
<code>text-start</code>	Left (LTR) / Right (RTL)
<code>text-center</code>	Center
<code>text-end</code>	Right (LTR) / Left (RTL)

Text Transform:

`text-lowercase` | `text-uppercase` | `text-capitalize`

Text Decoration:

`text-decoration-none` | `text-decoration-underline` | `text-decoration-line-through`

Other Text Utilities:

- `text-wrap` - Wrap text
- `text-nowrap` - No wrap
- `text-break` - Break long words
- `text-truncate` - Ellipsis overflow
- `text-reset` - Reset color to inherit
- `font-monospace` - Monospace font
- `user-select-all` - Select all on click
- `user-select-auto` - Default selection
- `user-select-none` - Prevent selection

6. COLORS & BACKGROUNDS

Text Colors:

Class	Preview	Class	Preview
<code>text-primary</code>	Primary	<code>text-warning</code>	Warning
<code>text-secondary</code>	Secondary	<code>text-info</code>	Info
<code>text-success</code>	Success	<code>text-light</code>	Light
<code>text-danger</code>	Danger	<code>text-dark</code>	Dark
<code>text-white</code>	White	<code>text-muted</code>	Muted
<code>text-body</code>	Body	<code>text-black-50</code>	Black 50%
<code>text-white-50</code>	White 50%	<code>text-reset</code>	Inherit

Background Colors:

Class	Class	Class
<code>bg-primary</code>	<code>bg-success</code>	<code>bg-dark</code>
<code>bg-secondary</code>	<code>bg-danger</code>	<code>bg-light</code>
<code>bg-warning</code>	<code>bg-info</code>	<code>bg-white</code>
<code>bg-transparent</code>	<code>bg-body</code>	

Background Gradient:

`bg-primary bg-gradient` (adds gradient effect to any bg-color)

7. BORDERS

Add Borders:

`border`
`border-top`
`border-bottom`
`border-start`
`border-end`

Remove Borders:

`border-0`
`border-top-0`
`border-bottom-0`
`border-start-0`
`border-end-0`

Border Width:

`border-1`
`border-2`
`border-3`

border-4
border-5

Border Colors:

border-primary
border-success
border-danger
border-warning
border-info
border-dark
border-white

Border Radius:

Class	Description
rounded	Default border radius (0.375rem)
rounded-0	No border radius
rounded-1	Small radius (0.25rem)
rounded-2	Default radius (0.375rem)
rounded-3	Large radius (0.5rem)
rounded-4	X-Large radius (1rem)
rounded-5	XX-Large radius (2rem)
rounded-circle	Perfect circle (50%)
rounded-pill	Pill shape (50rem)
rounded-top	Top corners only
rounded-bottom	Bottom corners only
rounded-start	Left corners only
rounded-end	Right corners only

8. POSITION

Position Types:

position-static
position-relative
position-absolute
position-fixed
position-sticky

Position Values:

top-0 top-50 top-100
bottom-0 bottom-50 bottom-100
start-0 start-50 start-100
end-0 end-50 end-100

Translate (Centering):

translate-middle | translate-middle-x | translate-middle-y

9. SHADOWS

Class	Description
shadow-none	No shadow
shadow-sm	Small shadow
shadow	Regular shadow
shadow-lg	Large shadow

10. OPACITY

Class	Value
opacity-0	0% (invisible)
opacity-25	25%
opacity-50	50%
opacity-75	75%
opacity-100	100% (fully visible)

11. OVERFLOW

Class	Description
overflow-auto	Scrollbar when needed
overflow-hidden	Hide overflow

Class	Description
<code>overflow-visible</code>	Show overflow
<code>overflow-scroll</code>	Always show scrollbar

12. VISIBILITY

Class	Description
<code>visible</code>	visibility: visible
<code>invisible</code>	visibility: hidden (still takes space)

13. Z-INDEX

Class	Value
<code>z-0</code>	0
<code>z-1</code>	1
<code>z-2</code>	2
<code>z-3</code>	3
<code>z-n1</code>	-1

14. VERTICAL ALIGN

Class	Alignment
<code>align-baseline</code>	Baseline
<code>align-top</code>	Top
<code>align-middle</code>	Middle
<code>align-bottom</code>	Bottom
<code>align-text-top</code>	Text top
<code>align-text-bottom</code>	Text bottom

15. OBJECT FIT

Class	Description
<code>object-fit-contain</code>	Contain within container
<code>object-fit-cover</code>	Cover container
<code>object-fit-fill</code>	Fill container
<code>object-fit-scale</code>	Scale down
<code>object-fit-none</code>	No scaling

16. INTERACTIONS

Class	Description
<code>pe-none</code>	pointer-events: none (no click)
<code>pe-auto</code>	pointer-events: auto (clickable)
<code>user-select-all</code>	Select all text on click
<code>user-select-auto</code>	Default text selection
<code>user-select-none</code>	Prevent text selection

17. CURSOR

Class	Cursor Type
<code>cursor-auto</code>	Default browser cursor
<code>cursor-pointer</code>	Pointer (hand)
<code>cursor-wait</code>	Wait/loading
<code>cursor-text</code>	Text I-beam
<code>cursor-move</code>	Move
<code>cursor-help</code>	Help
<code>cursor-not-allowed</code>	Not allowed
<code>cursor-none</code>	No cursor
<code>cursor-context-menu</code>	Context menu
<code>cursor-progress</code>	Progress
<code>cursor-cell</code>	Cell
<code>cursor-crosshair</code>	Crosshair
<code>cursor-vertical-text</code>	Vertical text
<code>cursor-alias</code>	Alias
<code>cursor-copy</code>	Copy
<code>cursor-no-drop</code>	No drop
<code>cursor-grab</code>	Grab
<code>cursor-grabbing</code>	Grabbing

Bootstrap 5.3 Complete CSS Utilities

All basic CSS style classes in one reference

Responsive breakpoints: sm(≥576px) | md(≥768px) | lg(≥992px) | xl(≥1200px) | xxl(≥1400px)