

DEVIEW
2016

딥러닝과 강화 학습으로 나보다 잘하는 쿠키런 AI 구현하기

김태훈
DEVSISTERS



저는




UNIST 졸업

DEVSISTERS 병특

EMNLP, DataCom, IJBDI 논문 게재

<http://carpedm20.github.io>

딥러닝 + 강화 학습



Playing Atari with Deep Reinforcement Learning (2013)




Mastering the game of Go with deep neural networks and tree search (2016)



ViZDOOM (2016)

딥러닝 + 강화 학습

딥러닝 + 강화 학습






“뉴럴뉴럴”한 뉴럴 네트워크

딥러닝 + 강화 학습?

Reinforcement Learning



Machine Learning





지도 학습

비지도 학습

지도 학습

비지도 학습

강화 학습

지도 학습

비지도 학습

강화 학습

지도 학습



동전



음식



동전음식



음식

지도 학습



동전



음식



?



?

지도 학습

DEV'S STARS

DEV



동전



음식



?



?

분류


Classification

지도 학습

비지도 학습

강화 학습

비지도 학습



비지도 학습



비지도 학습

DEVSI STARS

2024




군집화

Clustering

지도 학습

비지도 학습

강화 학습




분류도 아니고 군집화도 아닌것?



로봇을 걷게 하려면?



처음에는 학습할 데이터가 없다



조금씩 관절을 움직여 보면서

(처음에는 아무것도 모르니 랜덤으로)



시행 착오로부터 배운다

(정답이 없기 때문에 학습 결과는 다양함)




강화 학습
(Reinforcement Learning)

목표


목표




목표



부부








Agent



Environment

























즉, 강화 학습은

- Agent가 action을 결정하는 방법을 학습시키는 것
- 각 action은 그 다음 state에 영향을 끼친다
- 성공한 정도는 reward로 측정
- 목표 : 미래의 reward가 최대가 되도록 action을 취하는 것

Reinforcement Learning



그래서,

DL+RL 로 무엇을 했나?



AlphaRun



+



쿠키가 스스로 달릴 수 있으면?

게임 밸런싱을

자동으로 할 수 있지 않을까?



쿠키 30개 (평균 8레벨)



펫 30개



보물 9개 (2개씩 장착)



맵 7개



평균 플레이 4분

$$30 \times 8 \times 30 \times_9 C_2 \times 7 \times 4 =$$

5,040일



평균 플레이 4초

$$\frac{30 \times 8 \times 30 \times 9 C_2 \times 7 \times 4}{6} =$$



1대 × 6개 프로세스

14일



AlphaRun

쿠키런 A.I.를 지탱하는 기술들

쿠키런 AI를 지탱하는 8가지 기술

1. Deep Q-Network (2013)
2. Double Q-Learning (2015)
3. Dueling Network (2015)
4. Prioritized Experience Replay (2015)
5. Model-free Episodic Control (2016)
6. Asynchronous Advantage Actor-Critic method (2016)
7. Human Checkpoint Replay (2016)
8. Gradient Descent with Restart (2016)



쿠키런 AI를 지탱하는 8가지 기술


1. Deep Q-Network (2013)
2. Double Q-Learning (2015)
3. Dueling Network (2015)
4. Prioritized Experience Replay (2015)
5. Model-free Episodic Control (2016)
6. Asynchronous Advantage Actor-Critic method (2016)
7. Human Checkpoint Replay (2016)
8. Gradient Descent with Restart (2016)




1. Deep Q-Network

State s_t

0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	1	1	3	3	0	—	—
0	1	1	3	3	—	—	—
0	1	1	0	0	—	—	—
—	—	—	—	—	—	—	—
1	1	1	1	1	1	1	1



Action $a_t = ?$



Action a_t

? ? ?

0


None 슬라이드 점프

DEVS STUDERS

Action $a_t = ?$

0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	1	1	3	3	0	-	-
0	1	1	3	3	-	-	-
0	1	1	0	0	-	-	-
-	-	-	-	-	-	-	-
1	1	1	1	1	1	1	1

s_t




가장 좋은 행동

DEVS STUDERS

Action $a_t = ?$

0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	1	1	3	3	0	-	-
0	1	1	3	3	-	-	-
0	1	1	0	0	-	-	-
-	-	-	-	-	-	-	-
1	1	1	1	1	1	1	1

s_t




$Q(s, a)$

State s 에서

Action a 를 했을 때

기대되는 미래 가치 Q

S



$Q(s, \text{점프})$




$Q(s, \text{슬라이드})$



$Q(s, \text{가만히})$

S




$$Q(s, \text{점프}) = 1$$




$$Q(s, \text{슬라이드}) = 5$$



$$Q(s, \text{가만히}) = 0$$



S




$$Q(s, \text{점프}) = 1$$



$$Q(s, \text{슬라이드}) = 5$$



$$Q(s, \text{가만히}) = 0$$



Q : 기대되는 미래 가치



's 가치 =





's 가 치 = 점 수


Q



미래에 얻을 점수들의 합







$$loss = \left(\textcolor{red}{Q}(s, a) - r + \gamma \max_{a'} \textcolor{red}{\hat{Q}}(s, a') \right)^2$$

결과 는 ?

BONUSTIME

0

48,884



2

내 최고 점수

369,815



Jump



보름

Slide



하지만 #1...

- 왜 하나씩 놓치고, 이상한 행동을 하는 걸까



2. Double Q-Learning

핵심은,

미래의 가치를 나타내는 Q 가

낙관적 예측 or 발산하는 것을 막음

$$loss = \left(Q(s, a) - r + \gamma \max_{a'} \hat{Q}(s, a') \right)^2$$

$$loss = (\text{예측} - \text{정답})^2$$



$$loss = \left(Q(s, a) - r + \gamma \max_{a'} \hat{Q}(s, a') \right)^2$$

예측 - 정답

$$loss = \left(Q(s, a) - r + \gamma \max_{a'} \hat{Q}(s, a') \right)^2$$



0 —————
예측 - 정답

$$loss = \left(Q(s, a) - r + \gamma \max_{a'} \hat{Q}(s, a') \right)^2$$





예측 - 정답

$$loss = \left(\underbrace{Q(s, a)}_{\text{predicted}} - r + \gamma \max_{a'} \underbrace{\hat{Q}(s, a')}_{\text{target}} \right)^2$$




예측 - 정답

$$loss = \left(Q(s, a) - r + \gamma \max_{a'} \hat{Q}(s, a') \right)^2$$



예측 - 정답

Q



$$loss = \left(Q(s, a) - r + \gamma \max_{a'} \hat{Q}(s, a') \right)^2$$


DQN

$$\begin{aligned} loss &= \left(Q(s, a) - r + \gamma \max_{a'} \hat{Q}(s, a') \right)^2 \\ &= \left(Q(s, a) - r + \gamma \hat{Q} \left(s, \arg \max_{a'} \hat{Q}(s, a') \right) \right)^2 \end{aligned}$$

Double
DQN

$$loss = \left(Q(s, a) - r + \gamma \hat{Q} \left(s, \arg \max_{a'} Q(s, a') \right) \right)^2$$


Double Q가 Q 값은 작지만



— : Deep Q-learning — : Double Q-learning


Double Q가 Q 값은 작지만

gb-alfarun/average.q



점수는 훨씬 높다!

gb-alfarun/validation/real_score



— : Deep Q-learning — : Double Q-learning

결과 는 ?


BONUSTIME

341

77,414



10/10 ✓



내 최고 점수

1,141,767

Jump

Slide

verts: 1262

calls: 33

0.8 / 0.016



“아, 다했다.”

하지만 #2...

- 단조로운 land 1이 아닌 land 3를 가보니...



하지만 #2...

- 그리고 충격과 공포의 **보너스 타임**...



3. Dueling Network

0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	1	1	3	3	0	0	0
0	1	1	3	3	0	0	0
0	1	1	0	0	0	0	0
-	-	-	-	-	-	-	-
1	1	1	1	1	1	1	1

기대되는 미래 가치

$Q(s, a)$ 의 값은?

+1+1+1...

앞에 젤리가 많은지,



0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	1	1	3	3	0	0	0
0	1	1	3	3	0	0	0
0	1	1	0	0	0	0	0
-	-	-	-	-	-	-	-
1	1	1	1	1	1	1	1

0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
3	3	3	3	0	0
3	3	3	3	0	0
0	0	0	0	0	0
-1	-1	-1	-1	-1	-1

+1+1+1...

+0-1-1+...

앞에 젤리가 많은지, 장애물이 많은지 전혀 알 수 없음



0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	1	1	3	3	0	0	0
0	1	1	3	3	0	0	0
0	1	1	0	0	0	0	0
-	-	-	-	-	-	-	-
1	1	1	1	1	1	1	1

0	0	0	0	0	0
0	0	0	-1	-1	0
0	0	0	-1	-1	0
-1	-1	0	-1	-1	0
-1	-1	0	-1	-1	0
-1	-1	0	-1	-1	0
-1	-1	-1	-1	-1	-1

정확한 Q 예측이 어렵다



0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	1	1	3	3	0	0	0
0	1	1	3	3	0	0	0
0	1	1	0	0	0	0	0
-	-	-	-	-	-	-	-
1	1	1	1	1	1	1	1

?

점프 : 10? 8?

슬라이드 : -2? 1?

가만히 : 5? 12?

0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	1	1	3	3	0	0	0
0	1	1	3	3	0	0	0
0	1	1	0	0	0	0	0
-	-	-	-	-	-	-	-
1	1	1	1	1	1	1	1

하지만!

0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	1	1	3	3	0	0	0
0	1	1	3	3	0	0	0
0	1	1	0	0	0	0	0
-	-	-	-	-	-	-	-
1	1	1	1	1	1	1	1

Q 를 정확하게 예측할 필요가 있을까?

0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0
0	1	1	3	3	0	0	0
0	1	1	3	3	0	0	0
0	1	1	0	0	0	0	0
-	-	-	-	-	-	-	-
1	1	1	1	1	1	1	1

슬라이드 : x (기준)

점프 : $x+1?$ $x+3?$

가만히 : $x+1?$ $x+2?$

10? 20?

0? 1?

14? 32?

Q

0 (기준)

+1? +3?

-1? -2?

어느 것이 예측하기 더 쉬울까?

Q

0 (기준)

+1? +3?

-1? -2?

당연히 차이를 배우는 것이 쉽다

$Q(s,a)$


Value

$$Q(s,a) = V(s)$$


기준점 x

$$Q(s,a) = \overset{\text{Value}}{V(s)} + \overset{\text{Advantage}}{A(s,a)}$$


기준점 x 상대적인 Q값의 차이




Deep Q-Network



Dueling Network



Dueling Network



$$\text{Sum : } Q(s, a; \theta, \alpha, \beta) = \textcolor{blue}{V}(s; \theta, \beta) + \textcolor{red}{A}(s, a; \theta, \alpha)$$


$$\text{Max : } Q(s, a; \theta, \alpha, \beta) = \textcolor{blue}{V}(s; \theta, \beta) + \left(\textcolor{red}{A}(s, a; \theta, \alpha) - \max_{a' \in \mathcal{A}} \textcolor{red}{A}(s, a'; \theta, \alpha) \right)$$

$$\text{Average: } Q(s, a; \theta, \alpha, \beta) = \textcolor{blue}{V}(s; \theta, \beta) + \left(\textcolor{red}{A}(s, a; \theta, \alpha) - \frac{1}{|\mathcal{A}|} \sum_{a'} \textcolor{red}{A}(s, a'; \theta, \alpha) \right)$$

3. Dueling network



60만점 차이

gb-alfarun/validation/real_score



— : DQN — : Sum — : Max

3. Dueling network



— : DQN — : Sum — : Max

쿠키런 AI를 지탱하는 8가지 기술

1. Deep Q-Network (2013)
2. Double Q-Learning (2015)
3. Dueling Network (2015)
4. Prioritized Experience Replay (2015)
5. Model-free Episodic Control (2016)
6. Asynchronous Advantage Actor-Critic method (2016)
7. Human Checkpoint Replay (2016)
8. Gradient Descent with Restart (2016)

쿠키런 AI를 지탱하는 8가지 기술

1. Deep Q-Network (2013)
2. Double Q-Learning (2015)
3. Dueling Network (2015)
4. Prioritized Experience Replay (2015)
5. Model-free Episodic Control (2016)
6. Asynchronous Advantage Actor-Critic method (2016)
7. Human Checkpoint Replay (2016)
8. Gradient Descent with Restart (2016)

강화에 계속해서 실패한다면?

논문 8개나 갈아 넣었는데 안된다고..?

엔지니어링 ~~이라고 쓰고 노가다라고 부른다~~

1. Hyperparameter tuning
2. Debugging
3. Pretrained model
4. Ensemble method

1. Hyperparameter tuning

네트워크 바꾸기
Optimizer 바꾸기
reward 식 바꾸기
...

총 70+개

Network

Environment

Experience memory

Training method

1. **activation_fn** : activation function (relu, tanh, elu, leaky)
2. **initializer** : weight initializer (xavier)
3. **regularizer** : weight regularizer (None, l1, l2)
4. **apply_reg** : layers where regularizer is applied
5. **regularizer_scale** : scale of regularizer
6. **hidden_dims** : dimension of network
7. **kernel_size** : kernel size of CNN network
8. **stride_size** : stride size of CNN network
9. **dueling** : whether to use dueling network
10. **double_q** : whether to use double Q-learning
11. **use_batch_norm** : whether to use batch normalization

1. **history_length** : the length of history
2. **memory_size** : size of experience memory
3. **priority** : whether to use prioritized experience memory
4. **preload_memory** : whether to preload a saved memory
5. **preload_batch_size** : batch size of preloaded memory
6. **preload_prob** : probability of sampling from pre-mem
7. **alpha** : alpha of prioritized experience memory
8. **beta_start** : beta of prioritized experience memory
9. **beta_end_t** : beta of prioritized experience memory

1. **screen_height** : # of rows for a grid state
2. **screen_height_to_use** : actual # of rows for a state
3. **screen_width** : # of columns for a grid state
4. **screen_width_to_us** : actual # of columns for a state
5. **screen_expr** : actual # of row for a state
 - c : cookie
 - p : platform
 - s : score of cells
 - p : plain jelly
 - i : plain item
 - h : heal
 - m : magic
 - hi : height
 - sp : speed
 - rj : remained jump

ex) (c+2*p)-s,i+h+m,[rj,sp], ((c+2*p)-s)/2.,i+h+m,[rj,sp,hi]
6. **action_repeat** : # of reapt of an action (frame skip)

1. **optimizer** : type of optimizer (adam, adagrad, **rmsprop**)
2. **batch_norm** : whether to use batch normalization
3. **max_step** : maximum step to train
4. **target_q_update_step** : # of step to update target network
5. **learn_start_step** : # of step to begin a training
6. **learning_rate_start** : the maximum value of learning rate
7. **learning_rate_end** : the minimum value of learning rate
8. **clip_grad** : value for a max gradient
9. **clip_delta** : value for a max delta
10. **clip_reward** : value for a max reward
11. **learning_rate_restart** : whether to use learning rate restart

過猶不及

과유불급



성능은 올릴 수는 있지만,

그만큼 끊임없는 실험을 해야한

다

고정시킴 변수들을 정해서
한동안 건드리지 않는다!


```
for land in range(3, 7):
```

```
    for cookie in cookies:
```

```
        options = []
```

```
        option = {
```

```
            'hidden_dims': ["[800, 400, 200]", "[1000, 800, 200]"],
```

```
            'double_q': [True, False],
```

```
            'start_land': land,
```

```
            'cookie': cookie,
```

```
        }
```

```
        options.append(option.copy())
```

```
        array_run(options, 'double_q_test')
```

☒ Write a regex to create a tag group ✕

☐ Split on underscores

☐ Data download links

Tooltip sorting method: default ▾

Smoothing
0.642

Horizontal Axis
STEP **RELATIVE** WALL

Runs


Write a regex to filter runs

- 2016-10-10_15-52-22
- 2016-10-10_16-13-18
- 2016-10-10_16-43-22
- 2016-10-10_17-01-10
- 2016-10-10_17-01-53
- 2016-10-10_17-07-31
- 2016-10-10_17-28-27_devview_test_0
- 2016-10-10_17-28-28_devview_test_1
- 2016-10-10_17-28-29_devview_test_2
- 2016-10-10_17-28-31_devview_test_3
- 2016-10-10_17-28-32_devview_test_4
- 2016-10-10_17-28-33_devview_test_5
- 2016-10-10_17-30-44_devview_test_0
- 2016-10-10_17-30-45_devview_test_1
- 2016-10-10_17-30-46_devview_test_2
- 2016-10-10_17-30-47_devview_test_3
- 2016-10-10_17-30-49_devview_test_4
- 2016-10-10_17-30-50_devview_test_5
- 2016-10-10_17-32-51_devview_test_0
- 2016-10-10_17-32-52_devview_test_1
- 2016-10-10_17-32-53_devview_test_2
- 2016-10-10_17-32-55_devview_test_3
- 2016-10-10_17-32-56_devview_test_4
- 2016-10-10_17-32-57_devview_test_5
- 2016-10-10_17-33-46_devview_test_0

TOGGLE ALL RUNS


gb-alpharun

gb-alpharun/average.loss



🔍 ☰

gb-alpharun/episode.avg reward



🔍 ☰

gb-alpharun/training.epsilon




🔍 ☰

gb-dev

gb-timerchest

gb-alpharun/average.q




🔍 ☰

gb-alpharun/episode.max reward




🔍 ☰

gb-alpharun/training.learning_rate




🔍 ☰

gb-alpharun/episode.avg crash




🔍 ☰

gb-alpharun/episode.min reward




🔍 ☰

gb-alpharun/validation/real_score




🔍 ☰

gb-alpharun/episode.avg fall




🔍 ☰

gb-alpharun/episode.num of game



🔍 ☰

gb-alpharun/validation/reward



🔍 ☰

실험, 실험, 실험, 실험, 실험,
실험, 실험, 실험, 실험, 실험,
실험, 실험, 실험, 실험, 실험,
실험, 실험, 실험, 실험, 실험,
실험, 실험, 실험, 실험, 실험,
실험, 실험, 실험, 실험, 실험,
실험, 실험, 실험,

2. Debugging

“쿠키가 이상하게 행동하는데
이유라도 알려줬으면...”

Previous REWARD: 0.08

```

# # # #
# # # #
* # *** # *** # *** #
* @@@ # *** @ # *** # *** #
* @@@ # *** @ # *** # *** #
* @@@ # *** @ # *** # *** #
* @@@@@ # *** @@@@@ # *** @@@@@ # $$*** @@@@ #
* $$@@@@@@ # *$$ @@@@@@@@ # $$* @@@@@@@@ # $$*** @@@@@ #
  $$@  @@ # $$@@@  @@ # $$@@@  @ # $$@@@@@ #
*$$***** # *$$***** # *$$***** # ***** #
```

ACT:	NOOP	SLIDE	JUMP
Q:	7.3161182	7.2896504	6.9471564
DIFF:	0.0264678	0.0000000	-0.3424940
V:	5.7694306		
ADV:	1.5466874	1.5202198	1.1777259

History

Previous REWARD: 0.08									
	#			#			#		#
	#			#			#		#
*	#	***		#	***		#	***	#
*	@@@	#	***	@	#	***	#	***	#
*	@@@	#	***	@	#	***	#	***	#
*	@@@	#	***	@	#	***	#	***	#
*	@@@@@@	#	***	@@@@@@	#	***	@@@@@@	#	\$\$\$*** @@@@
*	\$\$\$@@@@@@	#	\$\$\$ @@@@@@@	#	\$\$\$* @@@@@@@	#	\$\$\$*** @@@@@	#	
	\$\$\$@ @@	#	\$\$\$@@@ @@	#	\$\$\$@@@ @	#	\$\$\$@@@@@	#	
*	\$\$\$*****	#	\$\$\$*****	#	\$\$\$*****	#	*****	#	
ACT:	NOOP			SLIDE			JUMP		
Q:	7.3161182			7.2896504			6.9471564		
DIFF:	0.0264678			0.0000000			-0.3424940		
V:	5.7694306								
ADV:	1.5466874			1.5202198			1.1777259		



```
@
@
@@
@@

$$@@      @@
*$$@@@    @@@
*$$  @@@@@
*****
```



```

Previous REWARD: 0.08

# # # #
# # # #
* # *** # *** # *** #
* @@@ # *** @ # *** # *** #
* @@@ # *** @ # *** # *** #
* @@@ # *** @ # *** # *** #
* @@@@@ # *** @@@@@ # *** @@@@@ # $$*** @@@@ #
* $$@@@@@@ # *$$ @@@@@@@ # $$* @@@@@@@ # $$*** @@@@@ #
  $$@  @@ # $$@@@  @@ # $$@@@  @ # $$@@@@@ #
*$$***** # *$$***** # *$$***** # ***** #
ACT:          NOOP          SLIDE          JUMP
Q:          7.3161182        7.2896504        6.9471564
DIFF:        0.0264678        0.0000000       -0.3424940
V:          5.7694306
ADV:        1.5466874        1.5202198        1.1777259

```

Q-value




Dueling
Network

ACT:	NOOP	SLIDE	JUMP
Q:	7.3161182	7.2896504	6.9471564
DIFF:	0.0264678	0.0000000	-0.3424940
V:	5.7694306		
ADV:	1.5466874	1.5202198	1.1777259

$V(s)$


$A(s,a)$

도움이 된 순간



도움이 된 순간

- 모든 action에 대해서 Q 값이 0
- State 값을 조금 바꿔서 출력해도 여전히 0
- Tensorflow의 `fully_connected` 함수에 activation function의 default값이 `nn.relu`로 설정되어 있음
- Activation function을 `None`으로 지정하니 해결!



```

146 -         scope='value_hid')
147 -     value = fully_connected(value_hid, 1,
148 -                             weights_initializer=initializer,
149 -                             weights_regularizer=weights_regularizer,
150 -                             scope='value')
151 -
152 -     advantage_hid = fully_connected(layer, hidden_dim,
153 -                                     activation_fn=activation_fn,

```

```

146 +         scope='value_hid')
147 +     self.value = fully_connected(self.value_hid, 1,
148 +                                 activation_fn=None,
149 +                                 weights_initializer=initializer,
150 +                                 weights_regularizer=weights_regularizer,
151 +                                 scope='value')
152 +
153 +     self. advantage hid = fully connected(layer, hidden dim,

```

tensorflow/contrib/layers/python/layers/layers.py

```

727 @add_arg_scope
728 def fully_connected(inputs,
729                     num_outputs,
730                     activation_fn=nn.relu,
731                     normalizer_fn=None,
732                     normalizer_params=None,

```

Args:

```

756 inputs: A tensor of with at least rank 2 and value fo
757 i.e. `[batch_size, depth]`, `[None, None, None, cha
758 num_outputs: Integer, the number of output units in t
759 activation_fn: activation function.
760 normalizer fn: normalization function to use instead

```

시도해 봤다면 좋았을 디버깅


- State를 실시간으로 수정하면서 Q 변화 보기
 - ex) 젤리를 쿠키 앞에 그려보면서 변화 확인
- Exploration을 어떻게 하고 있는지
 - reward는 제대로 학습 될 수 있도록 정해져 있었는지?



3. Pretrained model

하나의 모델을 처음부터 학습하기 위해선

gb-alpharun/validation/real_score



“반복된 실험의 학습 시간
을
단축시켜야 한다.”

모든 네트워크의 weight를 저장하

고,

새로운 실험을 할 때


비슷한 실험의 weight를 처음부터

사용

더 높은 점수를 얻을 확률이 높다


Max: 3,199,324

gb-alpharun/validation/real_score



Max: 3,586,503

gb-dev/validation/real_score



4. Ensemble methods

Experiment #1

Experiment #2

Experiment #3

Experiment #4

S


점프

점프

가만
히

점프

점프



“하나의 실험에서 만들어
진

여러 weight들을
동시에 로드 하려면?”

Ex) 가장 잘했던 weight는
보너스 타임은 잘하는데,
두번째로 잘하는 weight는
젤리를 잘 먹는다



Session




Session

Graph

The diagram consists of two nested rounded rectangles. The outer rectangle has a solid orange border and is labeled 'Session' at the top center. Inside it is a smaller rectangle with a dashed blue border, labeled 'Graph' at its top center. The 'Graph' rectangle is positioned such that it is centered within the 'Session' rectangle.



Session

Graph




Session

Graph





Session

Graph



같은 이름의 node는
하나의 그래프에
두개 이상 존재할 수 없
다

Session





한 세션에는
하나의 그래프만 존재

Session

Session

Graph

Graph



핵심은,

평소처럼 이렇게 선언하지 마시고

```
with tf.session() as sess:  
    network = Network()  
    sess.run(network.output)
```

이렇게 Session을 살려서 선언하시면 됩니다

```
sessions = []  
g = tf.Graph()  
with g.as_default():  
    network = Network()  
    sess = tf.Session(graph=g)  
    sessions.append(sess)  
  
sessions[0].run(network.output)
```

같은 방식으로
보너스 타임도 학습!




BONUSTIME

1,188,172

651

221/400

1



Giant!

Giant!




Jump

Slide


GL verts: 2436
GL calls: 26
59.9 / 0.017

쿠키런 A.I.로 밸런싱 자동화 하 기

밸런스를 360배 빠르게 해 봅시다



학습된 A.I.로 모든 쿠키의 평균적인 점수를 계산하거나



썬을 바꿔 보면서 성능 차이를 확인하거나

네,

“알파런 잘 씹니다.”

감사합니다