

v0.1.2 OAS 3.1.0

utoipa-actix-web

✉ Juha Kukkonen MIT OR Apache-2.0

Download OpenAPI Document

Utoipa's actix-web bindings for seamless integration of the two

Server

http://10.140.0.11:8080

Client Libraries

>_ Shell

Ruby

Node.js

PHP

Python

... More

Shell Curl

/v1/alertas

Responses

- > 200
- > 500 Unexpected error

GET /v1/alertas

Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/alertas

▶ Test Request

200 500

Show Schema ☐

```
{
  "data": [
    {
      "mensagem": null,
      "nivel": "baixo",
      "origem": null,
      "resolvido_em": null,
      "tour_id": null
    }
  ],
  "message": "string"
}
```

/v1/alertas

Body **required**

application/json

nivel string · enum **required**

baixo

medio

alto

mensagem string | null

origem string | null

resolvido_em string | null · date-time

tour_id integer | null · int32

Responses

> 200 Alert created

> 500 Unexpected error

POST /v1/alertas

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/alertas \
2   --request POST \
3   --header 'Content-Type: application/json' \
4   --data '{
```

```
5  "mensagem": null,  
6  "nivel": "baixo",  
7  "origem": null,  
8  "resolvido_em": null,  
9  "tour_id": null  
10 }'
```

[▶ Test Request](#)

200 500

Show Schema ☐

```
{  
  "data": {  
    "mensagem": null,  
    "nivel": "baixo",  
    "origem": null,  
    "resolvido_em": null,  
    "tour_id": null  
  },  
  "message": "string"  
}
```

Alert created

/v1/alertas/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

› 200 Alert found

› 404 Alert not found

› 500 Unexpected error

[GET /v1/alertas/{id}](#)

Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/alertas/1

▶ Test Request

200 404 500 Show Schema ☐

```
{
  "data": {
    "mensagem": null,
    "nivel": "baixo",
    "origem": null,
    "resolvido_em": null,
    "tour_id": null
  },
  "message": "string"
}
```

Alert found

/v1/alertas/{id}

Path Parameters

id integer · int32 required
Signed 32-bit integers (commonly used integer type).

Body required application/json

nivel string · enum required
baixo
medio
alto

mensagem string | null

origem string | null

resolvido_em string | null · date-time

tour_id integer | null · int32

Responses

- > 200 Alert updated
- > 404 Alert not found
- > 500 Unexpected error

PUT /v1/alertas/{id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/alertas/1 \  
2   --request PUT \  
3   --header 'Content-Type: application/json' \  
4   --data '{  
5     "mensagem": null,  
6     "nivel": "baixo",  
7     "origem": null,  
8     "resolvido_em": null,  
9     "tour_id": null  
10  }'
```

▶ Test Request

200 404 500

Show Schema ☐

```
{  
  "data": {  
    "mensagem": null,  
    "nivel": "baixo",  
    "origem": null,  
    "resolvido_em": null,  
    "tour_id": null  
  },  
  "message": "string"  
}
```

Alert updated

/v1/alertas/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

- > 200 Alert deleted
- > 404 Alert not found
- > 500 Unexpected error

DELETE /v1/alertas/{id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/alertas/1 \  
2 --request DELETE
```

▶ Test Request

200 404 500

Show Schema ☐

```
{  
  "message": "string"  
}
```

Alert deleted

/v1/checkpoint

Responses

- > 200
- > 500 Unexpected error

GET /v1/checkpoint

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/checkpoint
```

▶ Test Request

200 500

Show Schema ☐

```
{
  "data": [
    {
      "fim_real": null,
      "inicio_previsto": null,
      "inicio_real": null,
      "ordem": 1,
      "status": "pending",
      "tipo": "recepcao",
      "tour_id": 1
    }
  ],
  "message": "string"
}
```

/v1/checkpoint

Body required

application/json

ordem integer · int32 required

Signed 32-bit integers (commonly used integer type).

status string · enum required

pending

running

finished

tipo string · enum required

recepcao

auditorio

atelie

casinhas

dog_house

tour_id integer · int32 required

Signed 32-bit integers (commonly used integer type).

fim_real string | null · date-time

inicio_previsto string | null · date-time

inicio_real string | null · date-time

Responses

> 200 Checkpoint created

> 500 Unexpected error

POST /v1/checkpoint

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/checkpoint \  
2   --request POST \  
3   --header 'Content-Type: application/json' \  
4   --data '{  
5     "fim_real": null,  
6     "inicio_previsto": null,  
7     "inicio_real": null,  
8     "ordem": 1,  
9     "status": "pending",  
10    "tipo": "recepcao",  
11    "tour_id": 1  
12  }'
```

▶ Test Request

200 500

Show Schema ☐

```
{  
  "data": {  
    "fim_real": null,  
    "inicio_previsto": null,  
    "inicio_real": null,  
    "ordem": 1,  
    "status": "pending",  
    "tipo": "recepcao",  
    "tour_id": 1  
  },  
  "message": "string"  
}
```

Checkpoint created

/v1/checkpoint/tour/{tour_id}

Path Parameters

tour_id integer · int32 **required**
Signed 32-bit integers (commonly used integer type).

Responses

- > 200 Checkpoints found
- > 500 Unexpected error

GET /v1/checkpoint/tour/{tour_id} Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/checkpoint/tour/1

▶ Test Request

200 500 Show Schema ☐

```
{
  "data": [
    {
      "fim_real": null,
      "inicio_previsto": null,
      "inicio_real": null,
      "ordem": 1,
      "status": "pending",
      "tipo": "recepcao",
      "tour_id": 1
    }
  ],
  "message": "string"
}
```

Checkpoints found

/v1/checkpoint/{id}

Path Parameters

id integer · int32 **required**
Signed 32-bit integers (commonly used integer type).

Responses

- > 200 Checkpoint found
- > 404 Checkpoint not found
- > 500 Unexpected error

GET /v1/checkpoint/{id} Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/checkpoint/1

▶ Test Request

200 404 500 Show Schema ☐

```
{
  "data": {
    "fim_real": null,
    "inicio_previsto": null,
    "inicio_real": null,
    "ordem": 1,
    "status": "pending",
    "tipo": "recepcao",
    "tour_id": 1
  },
  "message": "string"
}
```

Checkpoint found

/v1/checkpoint/{id}

Path Parameters

`id` integer · int32 **required**
Signed 32-bit integers (commonly used integer type).

Body **required** application/json

`ordem` integer · int32 **required**
Signed 32-bit integers (commonly used integer type).

`status` string · enum **required**
 pending
 running
 finished

`tipo` string · enum **required**
 recepcao
 auditorio
 atelie
 casinhas
 dog_house

`tour_id` integer · int32 **required**
Signed 32-bit integers (commonly used integer type).

`fim_real` string | null · date-time

`inicio_previsto` string | null · date-time

`inicio_real` string | null · date-time

Responses

- > 200 Checkpoint updated
- > 404 Checkpoint not found
- > 500 Unexpected error

`PUT /v1/checkpoint/{id}`

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/checkpoint/1 \  
2 --request PUT \  
3 --header 'Content-Type: application/json' \  
4 --data '{  
5   "fim_real": null,  
6   "inicio_previsto": null,  
7   "inicio_real": null,  
8   "ordem": 1,  
9   "status": "pending",  
10  "tipo": "recepcao",  
11  "tour_id": 1
```

[▶ Test Request](#)

200 404 500

[Show Schema](#) ☐

```
{  
  "data": {  
    "fim_real": null,  
    "inicio_previsto": null,  
    "inicio_real": null,  
    "ordem": 1,  
    "status": "pending",  
    "tipo": "recepcao",  
    "tour_id": 1  
  },  
  "message": "string"  
}
```

Checkpoint updated

/v1/checkpoint/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

› 200 Checkpoint deleted

› 404 Checkpoint not found

> 500 Unexpected error

DELETE /v1/checkpoint/{id} Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/checkpoint/1 \  
2 --request DELETE
```

▶ Test Request

200 404 500 Show Schema ☐

```
{  
  "message": "string"  
}
```

Checkpoint deleted

/v1/notificacoes

Responses

> 200

> 500 Unexpected error

GET /v1/notificacoes Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/notificacoes
```

▶ Test Request

200 500 Show Schema ☐

```
{  
  "data": [  
    {  
      "corpo": null,  
      "lido": true,  
      "payload_json": null,  
    }  
  ]  
}
```

```
    "titulo": null,  
    "usuario_id": null  
  },  
],  
"message": "string"  
}
```

/v1/notificacoes

Body **required**

application/json

lido boolean **required**

corpo string | null

payload_json

titulo string | null

usuario_id integer | null · int32

Responses

› 200 Notifications created

› 500 Unexpected error

POST /v1/notificacoes

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/notificacoes \  
2   --request POST \  
3   --header 'Content-Type: application/json' \  
4   --data '{  
5     "corpo": null,  
6     "lido": true,  
7     "payload_json": null,  
8     "titulo": null,  
9     "usuario_id": null  
10  }'
```

▶ Test Request

200 500 Show Schema ☐

```
{
  "data": {
    "corpo": null,
    "lido": true,
    "payload_json": null,
    "titulo": null,
    "usuario_id": null
  },
  "message": "string"
}
```

Notifications created

/v1/notificacoes/{id}

Path Parameters

id integer · int32 required
Signed 32-bit integers (commonly used integer type).

Responses

- > 200 Notifications found
- > 404 Notifications not found
- > 500 Unexpected error

GET /v1/notificacoes/{id} Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/notificacoes/1

▶ Test Request

200 404 500 Show Schema ☐

```
{
  "data": {
```

```
    "corpo": null,
    "lido": true,
    "payload_json": null,
    "titulo": null,
    "usuario_id": null
  },
  "message": "string"
}
```



Notifications found

/v1/notificacoes/{id}

Path Parameters

id integer · int32 **required**
Signed 32-bit integers (commonly used integer type).

Body **required** application/json

lido boolean **required**

corpo string | null

payload_json

titulo string | null

usuario_id integer | null · int32

Responses

- > 200 Notifications updated
- > 404 Notifications not found
- > 500 Unexpected error

PUT /v1/notificacoes/{id} Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/notificacoes/1 \  
2 --request PUT \
```



```
3 --header 'Content-Type: application/json' \  
4 --data '{  
5   "corpo": null,  
6   "lido": true,  
7   "payload_json": null,  
8   "titulo": null,  
9   "usuario_id": null  
10 }'
```

[▶ Test Request](#)

200 404 500

[Show Schema](#) ☐

```
{  
  "data": {  
    "corpo": null,  
    "lido": true,  
    "payload_json": null,  
    "titulo": null,  
    "usuario_id": null  
  },  
  "message": "string"  
}
```

Notifications updated

/v1/notificacoes/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

› 200 Notifications deleted

› 404 Notifications not found

› 500 Unexpected error

DELETE /v1/notificacoes/{id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/notificacoes/1 \  
2 --request DELETE
```

▶ Test Request

200 404 500

Show Schema ☐

```
{  
  "message": "string"  
}
```

Notifications deleted

/v1/perguntas

Responses

> 200

> 500 Unexpected error

GET /v1/perguntas

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/perguntas
```

▶ Test Request

200 500

Show Schema ☐

```
{  
  "data": [  
    {  
      "checkpoint_id": 1,  
      "estado": "queued",  
      "liberado_em": null,  
      "question_topic": null,  
      "respondido_em": null,  
      "texto": "string",  
      "tour_id": null
```

```
    }
  ],
  "message": "string"
}
```

/v1/perguntas

Body required

application/json

checkpoint_id integer · int32 required
Signed 32-bit integers (commonly used integer type).

estado string · enum required

- queued
- answerable
- answered
- discarded

texto string required

liberado_em string | null · date-time

question_topic string | null

respondido_em string | null · date-time

tour_id integer | null · int32

Responses

- > 200 Question created
- > 500 Unexpected error

POST /v1/perguntas

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/perguntas \
2   --request POST \
3   --header 'Content-Type: application/json' \
4   --data '{
5     "checkpoint_id": 1,
```

```
6  "estado": "queued",
7  "liberado_em": null,
8  "question_topic": null,
9  "respondido_em": null,
10 "texto": "",
11 "tour_id": null
12 }'
```

[▶ Test Request](#)

200 500

[Show Schema](#) ☐

```
{
  "data": {
    "checkpoint_id": 1,
    "estado": "queued",
    "liberado_em": null,
    "question_topic": null,
    "respondido_em": null,
    "texto": "string",
    "tour_id": null
  },
  "message": "string"
}
```

Question created

/v1/perguntas/tour/{tour_id}

Path Parameters

`tour_id` integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

> 200

> 500 Unexpected error

[GET /v1/perguntas/tour/{tour_id}](#)[Shell Curl](#) ☐

```
1 curl http://10.140.0.11:8080/v1/perguntas/tour/1
```

[▶ Test Request](#)

200 500

[Show Schema](#) ☐

```
{
  "data": [
    {
      "checkpoint_id": 1,
      "estado": "queued",
      "liberado_em": null,
      "question_topic": null,
      "respondido_em": null,
      "texto": "string",
      "tour_id": null
    }
  ],
  "message": "string"
}
```

/v1/perguntas/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

> 200 Question found

> 404 Question not found

> 500 Unexpected error

```
GET /v1/perguntas/{id}
```

[Shell](#) [Curl](#) [▼](#)

```
1 curl http://10.140.0.11:8080/v1/perguntas/1
```

▶ Test Request

200 404 500

Show Schema ☐

```
{
  "data": {
    "checkpoint_id": 1,
    "estado": "queued",
    "liberado_em": null,
    "question_topic": null,
    "respondido_em": null,
    "texto": "string",
    "tour_id": null
  },
  "message": "string"
}
```

Question found

/v1/perguntas/{id}

Path Parameters

id integer · int32 required
Signed 32-bit integers (commonly used integer type).

Body required application/json

checkpoint_id integer · int32 required
Signed 32-bit integers (commonly used integer type).

estado string · enum required
 queued
 answerable
 answered
 discarded

texto string required

liberado_em string | null · date-time

question_topic string | null

respondido_em string | null · date-time

tour_id integer | null · int32

Responses

- > 200 Question updated
- > 404 Question not found
- > 500 Unexpected error

PUT /v1/perguntas/{id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/perguntas/1 \  
2   --request PUT \  
3   --header 'Content-Type: application/json' \  
4   --data '{  
5     "checkpoint_id": 1,  
6     "estado": "queued",  
7     "liberado_em": null,  
8     "question_topic": null,  
9     "respondido_em": null,  
10    "texto": "",  
11    "tour_id": null  
12  }'
```

▶ Test Request

200 404 500

Show Schema ☐

```
{  
  "data": {  
    "checkpoint_id": 1,  
    "estado": "queued",  
    "liberado_em": null,  
    "question_topic": null,  
    "respondido_em": null,  
    "texto": "string",  
    "tour_id": null  
  },  
  "message": "string"  
}
```

Question updated

/v1/perguntas/{id}

Path Parameters

id integer · int32 **required**
Signed 32-bit integers (commonly used integer type).

Responses

- > 200 Question deleted
- > 404 Question not found
- > 500 Unexpected error

DELETE /v1/perguntas/{id} Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/perguntas/1 \  
2 --request DELETE
```

▶ Test Request

200 404 500 Show Schema ☐

```
{  
  "message": "string"  
}
```

Question deleted

/v1/rastreio-robo

Responses

- > 200
- > 500 Unexpected error

GET /v1/rastreio-robo

Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/rastreio-robo

▶ Test Request

200 500

Show Schema ☐

```
{
  "data": [
    {
      "checkpoint_id": null,
      "progresso_pct": null,
      "tour_id": null,
      "waypoint": null
    }
  ],
  "message": "string"
}
```

/v1/rastreio-robo

Body required

application/json

checkpoint_id integer | null · int32

progresso_pct number | null · double

tour_id integer | null · int32

waypoint string | null

Responses

- > 200 Rastreio created
- > 500 Unexpected error

POST /v1/rastreio-robo

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/rastreio-robo \  
2   --request POST \  
3   --header 'Content-Type: application/json' \  
4   --data '{  
5     "checkpoint_id": null,  
6     "progresso_pct": null,  
7     "tour_id": null,  
8     "waypoint": null  
9   }'
```

▶ Test Request

200 500

Show Schema ☐

```
{  
  "data": {  
    "checkpoint_id": null,  
    "progresso_pct": null,  
    "tour_id": null,  
    "waypoint": null  
  },  
  "message": "string"  
}
```

Rastreio created

/v1/rastreio-robo/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

> 200 Rastreio found

> 404 Rastreio not found

> 500 Unexpected error

`GET /v1/rastreio-robo/{id}`

Shell Curl ▾

1 `curl http://10.140.0.11:8080/v1/rastreio-robo/1`

▶ Test Request

200 404 500

Show Schema ☐

```
{
  "data": {
    "checkpoint_id": null,
    "progresso_pct": null,
    "tour_id": null,
    "waypoint": null
  },
  "message": "string"
}
```

Rastreio found

/v1/rastreio-robo/{id}

Path Parameters

`id` integer · int32 **required**
Signed 32-bit integers (commonly used integer type).

Body required	application/json
<code>checkpoint_id</code>	integer null · int32
<code>progresso_pct</code>	number null · double
<code>tour_id</code>	integer null · int32
<code>waypoint</code>	string null

Responses

- > 200 Rastreio updated
- > 404 Rastreio not found
- > 500 Unexpected error

PUT /v1/rastreio-robo/{id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/rastreio-robo/1 \  
2 --request PUT \  
3 --header 'Content-Type: application/json' \  
4 --data '{  
5   "checkpoint_id": null,  
6   "progresso_pct": null,  
7   "tour_id": null,  
8   "waypoint": null  
9 }'
```

▶ Test Request

200 404 500

Show Schema ☐

```
{  
  "data": {  
    "checkpoint_id": null,  
    "progresso_pct": null,  
    "tour_id": null,  
    "waypoint": null  
  },  
  "message": "string"  
}
```

Rastreio updated

/v1/rastreio-robo/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

- > 200 Rastreio deleted
- > 404 Rastreio not found
- > 500 Unexpected error

DELETE /v1/rastreio-robo/{id} Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/rastreio-robo/1 \
2 --request DELETE

▶ Test Request

200 404 500 Show Schema ☐

{
 "message": "string"
}

Rastreio deleted

/v1/respostas

Responses

- > 200
- > 500 Unexpected error

GET /v1/respostas Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/respostas

▶ Test Request

200 500 Show Schema ☐

```
{
  "data": [
    {
      "pergunta_id": 1,
      "respondido_por_tipo": "string",
      "respondido_por_usuario": null,
      "texto": "string"
    }
  ],
  "message": "string"
}
```

/v1/respostas

Body **required**

application/json

pergunta_id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

respondido_por_tipo string **required**

texto string **required**

respondido_por_usuario integer | null · int32

Responses

> 200 Answer created

> 500 Unexpected error

POST /v1/respostas

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/respostas \
2   --request POST \
3   --header 'Content-Type: application/json' \
4   --data '{
5     "pergunta_id": 1,
6     "respondido_por_tipo": "",
7     "respondido_por_usuario": null,
8     "texto": ""
9   }'
```

[▶ Test Request](#)

200 500

Show Schema ☐

```
{
  "data": {
    "pergunta_id": 1,
    "respondido_por_tipo": "string",
    "respondido_por_usuario": null,
    "texto": "string"
  },
  "message": "string"
}
```

Answer created

/v1/respostas/pergunta/{pergunta_id}

Path Parameters

pergunta_id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

> 200

> 500 Unexpected error

GET /v1/respostas/pergunta/{pergunta_id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/respostas/pergunta/1
```

[▶ Test Request](#)

200 500

Show Schema ☐

```
{
  "data": [
    {
```

```
{
  "pergunta_id": 1,
  "respondido_por_tipo": "string",
  "respondido_por_usuario": null,
  "texto": "string"
},
{
  "message": "string"
}
```

/v1/respostas/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

- > 200 Answer found
- > 404 Answer not found
- > 500 Unexpected error

GET /v1/respostas/{id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/respostas/1
```

▶ Test Request

200 404 500

Show Schema ☐

```
{
  "data": {
    "pergunta_id": 1,
    "respondido_por_tipo": "string",
    "respondido_por_usuario": null,
    "texto": "string"
  },
}
```



```
"message": "string"
}
```

Answer found

/v1/respostas/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Body **required**

application/json

pergunta_id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

respondido_por_tipo string **required**

texto string **required**

respondido_por_usuario integer | null · int32

Responses

> 200 Answer updated

> 404 Answer not found

> 500 Unexpected error

PUT /v1/respostas/{id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/respostas/1 \  
2   --request PUT \  
3   --header 'Content-Type: application/json' \  
4   --data '{  
5     "pergunta_id": 1,  
6     "respondido_por_tipo": "",  
7     "respondido_por_usuario": null,  
8     "texto": ""
```

9 `}`[▶ Test Request](#)

200 404 500

Show Schema ☐

```
{
  "data": {
    "pergunta_id": 1,
    "respondido_por_tipo": "string",
    "respondido_por_usuario": null,
    "texto": "string"
  },
  "message": "string"
}
```

Answer updated

/v1/respostas/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

- > 200 Answer deleted
- > 404 Answer not found
- > 500 Unexpected error

DELETE /v1/respostas/{id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/respostas/1 \
2 --request DELETE
```

[▶ Test Request](#)

200 404 500

Show Schema ☐

```
{
  "message": "string"
}
```

Answer deleted

/v1/robo

Responses

> 200

> 500 Unexpected error

GET /v1/robo

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/robo
```

▶ Test Request

200 500

Show Schema ☐

```
{
  "data": [
    {
      "ativo": null,
      "modelo": null,
      "nome": null,
      "numero_serie": null
    }
  ],
  "message": "string"
}
```

/v1/robo

Body required

application/json

ativo boolean | null

modelo string | null

nome string | null

numero_serie string | null

Responses

- > 200 Robo created
- > 500 Unexpected error

POST /v1/robo

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/robo \  
2   --request POST \  
3   --header 'Content-Type: application/json' \  
4   --data '{  
5     "ativo": null,  
6     "modelo": null,  
7     "nome": null,  
8     "numero_serie": null  
9   }'
```

▶ Test Request

200 500

Show Schema ☐

```
{  
  "data": {  
    "ativo": null,  
    "modelo": null,  
    "nome": null,  
    "numero_serie": null  
  },  
  "message": "string"  
}
```

Robo created

/v1/robo/{id}

Path Parameters

id integer · int32 **required**
Signed 32-bit integers (commonly used integer type).

Responses

- > 200 Robo found
- > 404 Robo not found
- > 500 Unexpected error

GET /v1/robo/{id} Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/robo/1

▶ Test Request

200 404 500 Show Schema ☐

```
{
  "data": {
    "ativo": null,
    "modelo": null,
    "nome": null,
    "numero_serie": null
  },
  "message": "string"
}
```

Robo found

/v1/robo/{id}

Path Parameters

id integer · int32 **required**
Signed 32-bit integers (commonly used integer type).

Body **required** application/json

ativo boolean | null

modelo string | null

nome string | null

numero_serie string | null

Responses

- > 200 Robo updated
- > 404 Robo not found
- > 500 Unexpected error

PUT /v1/robo/{id} Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/robo/1 \  
2   --request PUT \  
3   --header 'Content-Type: application/json' \  
4   --data '{  
5     "ativo": null,  
6     "modelo": null,  
7     "nome": null,  
8     "numero_serie": null  
9   }'
```

▶ Test Request

200 404 500 Show Schema ☐

```
{  
  "data": {  
    "ativo": null,  
    "modelo": null,  
    "nome": null,  
    "numero_serie": null  
  }  
}
```

```
    "nome": null,  
    "numero_serie": null  
  },  
  "message": "string"  
}
```

Robo updated

/v1/robo/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

- > 200 Robo deleted
- > 404 Robo not found
- > 500 Unexpected error

DELETE /v1/robo/{id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/robo/1 \  
2 --request DELETE
```

▶ Test Request

200 404 500

Show Schema ☐

```
{  
  "message": "string"  
}
```

Robo deleted

/v1/tour

Responses

- > 200
- > 500 Unexpected error

GET /v1/tour

Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/tour

▶ Test Request

200 500

Show Schema ☐

```
{
  "data": [
    {
      "codigo": "string",
      "data_local": "2025-12-04",
      "fim_real": null,
      "hora_fim_prevista": null,
      "hora_inicio_prevista": null,
      "inicio_real": null,
      "responsavel_id": null,
      "robo_id": 1,
      "status": "scheduled",
      "titulo": null
    }
  ],
  "message": "string"
}
```

/v1/tour

Body required

application/json

`codigo` string **required**

`data_local` string · date **required**

full-date notation as defined by RFC 3339, section 5.6, for example, 2017-07-21

`robo_id` integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

`status` string · enum **required**

`scheduled`

`inprogress`

`completed`

`cancelled`

`fim_real` string | null · date-time

`hora_fim_prevista` string | null

`hora_inicio_prevista` string | null

`inicio_real` string | null · date-time

`responsavel_id` integer | null · int32

`titulo` string | null

Responses

› 200 Tour created

› 500 Unexpected error

POST /v1/tour

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/tour \  
2   --request POST \  
3   --header 'Content-Type: application/json' \  
4   --data '{  
5     "codigo": "",  
6     "data_local": "",  
7     "fim_real": null,  
8     "hora_fim_prevista": null,  
9     "hora_inicio_prevista": null,  
10    "inicio_real": null,  
11    "responsavel_id": null,  
12    "robo_id": 1,  
13    "status": "scheduled",  
14    "titulo": null
```

15 `}`

▶ Test Request

200 500Show Schema ☐

```
{
  "data": {
    "codigo": "string",
    "data_local": "2025-12-04",
    "fim_real": null,
    "hora_fim_prevista": null,
    "hora_inicio_prevista": null,
    "inicio_real": null,
    "responsavel_id": null,
    "robo_id": 1,
    "status": "scheduled",
    "titulo": null
  },
  "message": "string"
}
```

Tour created

/v1/tour-status-log

Responses

- > 200
- > 500 Unexpected error

GET /v1/tour-status-logShell Curl ▾

1 `curl http://10.140.0.11:8080/v1/tour-status-log`

▶ Test Request

200 500Show Schema ☐

```
{
  "data": [
```

```
{
  "atualizado_em": null,
  "observacoes": null,
  "status": "string",
  "tour_id": 1
},
"message": "string"
}
```

/v1/tour-status-log

Body **required**

application/json

status string **required**

tour_id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

atualizado_em string | null · date-time

observacoes string | null

Responses

➤ 200 Tour status log created

➤ 500 Unexpected error

POST /v1/tour-status-log

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/tour-status-log \
2   --request POST \
3   --header 'Content-Type: application/json' \
4   --data '{
5     "atualizado_em": null,
6     "observacoes": null,
7     "status": "",
8     "tour_id": 1
9   }'
```

▶ Test Request

200 500

Show Schema ☐

```
{
  "data": {
    "atualizado_em": null,
    "observacoes": null,
    "status": "string",
    "tour_id": 1
  },
  "message": "string"
}
```

Tour status log created

/v1/tour-status-log/tour/{tour_id}

Path Parameters

tour_id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

> 200 Tour status logs found

> 500 Unexpected error

GET /v1/tour-status-log/tour/{tour_id}

Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/tour-status-log/tour/1

[▶ Test Request](#)

200 500

Show Schema ☐

```
{
  "data": [
    {
      "atualizado_em": null,
      "observacoes": null,

```

```
    "status": "string",
    "tour_id": 1
  }
],
"message": "string"
}
```

Tour status logs found

/v1/tour-status-log/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

- 200 Tour status log found
- 404 Tour status log not found
- 500 Unexpected error

GET /v1/tour-status-log/{id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/tour-status-log/1
```

▶ Test Request

200 404 500

Show Schema ☐

```
{
  "data": {
    "atualizado_em": null,
    "observacoes": null,
    "status": "string",
    "tour_id": 1
  },
}
```

```
"message": "string"
}
```

Tour status log found

/v1/tour-status-log/{id}

Path Parameters

id integer · int32 required
Signed 32-bit integers (commonly used integer type).

Body required application/json

status string required

tour_id integer · int32 required
Signed 32-bit integers (commonly used integer type).

atualizado_em string | null · date-time

observacoes string | null

Responses

- > 200 Tour status log updated
- > 404 Tour status log not found
- > 500 Unexpected error

PUT /v1/tour-status-log/{id} Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/tour-status-log/1 \  
2   --request PUT \  
3   --header 'Content-Type: application/json' \  
4   --data '{  
5     "atualizado_em": null,  
6     "observacoes": null,  
7     "status": "",  
8     "tour_id": 1
```

9 `}`[▶ Test Request](#)

200 404 500

Show Schema ☐

```
{
  "data": {
    "atualizado_em": null,
    "observacoes": null,
    "status": "string",
    "tour_id": 1
  },
  "message": "string"
}
```

Tour status log updated

/v1/tour-status-log/{id}

Path Parameters

`id` integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

- > 200 Tour status log deleted
- > 404 Tour status log not found
- > 500 Unexpected error

DELETE /v1/tour-status-log/{id}Shell Curl ▼

```
1 curl http://10.140.0.11:8080/v1/tour-status-log/1 \
2 --request DELETE
```

[▶ Test Request](#)

200 404 500

Show Schema ☐

```
{
  "message": "string"
}
```

Tour status log deleted

/v1/tour-visitante

Responses

> 200

> 500 Unexpected error

GET /v1/tour-visitante

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/tour-visitante
```

▶ Test Request

200 500

Show Schema ☐

```
{
  "data": [
    {
      "tour_id": 1,
      "visitante_id": 1
    }
  ],
  "message": "string"
}
```

/v1/tour-visitante

Body required

application/json

tour_id integer · int32 required

Signed 32-bit integers (commonly used integer type).

visitante_id integer · int32 required

Signed 32-bit integers (commonly used integer type).

Responses

> 201 TourVisitante created

> 500 Unexpected error

POST /v1/tour-visitante

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/tour-visitante \  
2   --request POST \  
3   --header 'Content-Type: application/json' \  
4   --data '{  
5     "tour_id": 1,  
6     "visitante_id": 1  
7   }'
```

▶ Test Request

201 500

Show Schema ☐

```
{  
  "data": {  
    "tour_id": 1,  
    "visitante_id": 1  
  },  
  "message": "string"  
}
```

TourVisitante created

/v1/tour-visitante/tour/{tour_id}

Path Parameters

`tour_id` integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

› 200 Visitantes of tour found

› 500 Unexpected error

GET /v1/tour-visitante/tour/{tour_id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/tour-visitante/tour/1
```

▶ Test Request

200 500

Show Schema ☐

```
{
  "data": [
    {
      "tour_id": 1,
      "visitante_id": 1
    }
  ],
  "message": "string"
}
```

Visitantes of tour found

/v1/tour-visitante/visitante/{visitante_id}

Path Parameters

`visitante_id` integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

- > 200 Tours of visitante found
- > 500 Unexpected error

GET /v1/tour-visitante/visitante/{visitante_id}

Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/tour-visitante/visitante/1

▶ Test Request

200 500

Show Schema ☐

```
{
  "data": [
    {
      "tour_id": 1,
      "visitante_id": 1
    }
  ],
  "message": "string"
}
```

Tours of visitante found

/v1/tour-visitante/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

- > 200 TourVisitante found
- > 404 TourVisitante not found
- > 500 Unexpected error

GET /v1/tour-visitante/{id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/tour-visitante/1
```

▶ Test Request

200 404 500

Show Schema ☐

```
{
  "data": {
    "tour_id": 1,
    "visitante_id": 1
  },
  "message": "string"
}
```

TourVisitante found

/v1/tour-visitante/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

- > 200 TourVisitante deleted
- > 404 TourVisitante not found
- > 500 Unexpected error

DELETE /v1/tour-visitante/{id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/tour-visitante/1 \
2   --request DELETE
```

► Test Request

200 404 500

Show Schema ☐

```
{
  "message": "string"
}
```

TourVisitante deleted

/v1/tour/{id}

Path Parameters

id integer · int32 required
Signed 32-bit integers (commonly used integer type).

Responses

- > 200 Tour found
- > 404 Tour not found
- > 500 Unexpected error

GET /v1/tour/{id}

Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/tour/1

► Test Request

200 404 500

Show Schema ☐

```
{
  "data": {
    "codigo": "string",
    "data_local": "2025-12-04",
    "fim_real": null,
    "hora_fim_prevista": null,
  }
}
```

```
"hora_inicio_prevista": null,
"inicio_real": null,
"responsavel_id": null,
"robo_id": 1,
"status": "scheduled",
"titulo": null
},
"message": "string"
}
```

Tour found

/v1/tour/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Body **required**

application/json

codigo string **required**

data_local string · date **required**

full-date notation as defined by RFC 3339, section 5.6, for example, 2017-07-21

robo_id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

status string · enum **required**

scheduled

inprogress

completed

cancelled

fim_real string | null · date-time

hora_fim_prevista string | null

hora_inicio_prevista string | null

inicio_real string | null · date-time

responsavel_id integer | null · int32

titulo string | null

Responses

- > 200 Tour updated
- > 404 Tour not found
- > 500 Unexpected error

PUT /v1/tour/{id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/tour/1 \  
2   --request PUT \  
3   --header 'Content-Type: application/json' \  
4   --data '{  
5     "codigo": "",  
6     "data_local": "",  
7     "fim_real": null,  
8     "hora_fim_prevista": null,  
9     "hora_inicio_prevista": null,  
10    "inicio_real": null,  
11    "responsavel_id": null,  
12    "robo_id": 1,  
13    "status": "scheduled",  
14    "titulo": null  
15  }'
```

▶ Test Request

200 404 500

Show Schema ☐

```
{  
  "data": {  
    "codigo": "string",  
    "data_local": "2025-12-04",  
    "fim_real": null,  
    "hora_fim_prevista": null,  
    "hora_inicio_prevista": null,  
    "inicio_real": null,  
    "responsavel_id": null,  
    "robo_id": 1,  
    "status": "scheduled",  
    "titulo": null  
  },  
}
```

<pre>"message": "string" }</pre>
Tour updated

/v1/tour/{id}

Path Parameters

id integer · int32 required
Signed 32-bit integers (commonly used integer type).

Responses

- > 200 Tour deleted
- > 404 Tour not found
- > 500 Unexpected error

DELETE /v1/tour/{id} Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/tour/1 \  
2 --request DELETE
```

▶ Test Request

200 404 500 Show Schema ☐

```
{  
  "message": "string"  
}
```

Tour deleted

/v1/visitante

Responses

- > 200
- > 500 Unexpected error

GET /v1/visitante

Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/visitante

▶ Test Request

200 500

Show Schema ☐

```
{
  "data": [
    {
      "email": null,
      "nome": null,
      "telefone": null
    }
  ],
  "message": "string"
}
```

/v1/visitante

Body required

application/json

email string | null

nome string | null

telefone string | null

Responses

> 201 Visitante created

> 500 Unexpected error

POST /v1/visitante

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/visitante \  
2   --request POST \  
3   --header 'Content-Type: application/json' \  
4   --data '{  
5     "email": null,  
6     "nome": null,  
7     "telefone": null  
8   }'
```

▶ Test Request

201 500

Show Schema ☐

```
{  
  "data": {  
    "email": null,  
    "nome": null,  
    "telefone": null  
  },  
  "message": "string"  
}
```

Visitante created

/v1/visitante/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

> 200 Visitante found

> 404 Visitante not found

> 500 Unexpected error

GET /v1/visitante/{id}

Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/visitante/1

▶ Test Request

200 404 500

Show Schema ☐

```
{
  "data": {
    "email": null,
    "nome": null,
    "telefone": null
  },
  "message": "string"
}
```

Visitante found

/v1/visitante/{id}

Path Parameters

id integer · int32 required

Signed 32-bit integers (commonly used integer type).

Body required

application/json

email string | null

nome string | null

telefone string | null

Responses

- > 200 Visitante updated
- > 404 Visitante not found
- > 500 Unexpected error

PUT /v1/visitante/{id}

Shell Curl ▾

```
1 curl http://10.140.0.11:8080/v1/visitante/1 \  
2   --request PUT \  
3   --header 'Content-Type: application/json' \  
4   --data '{  
5     "email": null,  
6     "nome": null,  
7     "telefone": null  
8   }'
```

▶ Test Request

200 404 500

Show Schema ☐

```
{  
  "data": {  
    "email": null,  
    "nome": null,  
    "telefone": null  
  },  
  "message": "string"  
}
```

Visitante updated

/v1/visitante/{id}

Path Parameters

id integer · int32 **required**

Signed 32-bit integers (commonly used integer type).

Responses

> 200 Visitante deleted

> 404 Visitante not found

> 500 Unexpected error

DELETE /v1/visitante/{id}

Shell Curl ▾

1 curl http://10.140.0.11:8080/v1/visitante/1 \

2 --request DELETE

▶ Test Request

200 404 500

Show Schema ☐

{
 "message": "string"
}

Visitante deleted

Models

Show More ▾