

XEBIA LMS

API Documentation

Nine Deployed POST APIs – Request & Response Reference

Application	Xebia Learning Management System
Frontend	https://xebia-portal-lms.vercel.app
Backend Base URL	https://xebia-lms-backend.onrender.com
Testing Tool	Postman Collection Runner
Environment	Xebia LMS Production (Render)
Prepared For	API documentation and deployment submission

1. Documentation Objective

This document provides the API reference for nine deployed POST endpoints in the Xebia LMS backend. For each endpoint, the parameterized Postman request body and a representative 201 Created response body are documented, along with the standard post-response test script and the test cases exercised during Collection Runner execution.

2. Common Postman Configuration

2.1 Environment Variables

Variable	Value / Source	Purpose
baseUrl	https://xebia-lms-backend.onrender.com	Common production backend URL prefix.
X-Organization-ID	123e4567-e89b-12d3-a456-426614174000	Tenant isolation ID for multi-tenant mapping.
X-User-Id	load-tester	Mock header for identifying user ID.
X-User-Role	ADMIN	Mock header for identifying user role (determines scope).

2.2 Common Authorization

Every request is authorized automatically at the collection level via a Pre-request Script, which inserts the necessary headers into the request scope:

```
pm.request.headers.upsert({ key: 'X-Organization-ID', value: '123e4567-e89b-12d3-a456-426614174000' });
pm.request.headers.upsert({ key: 'X-User-Id', value: 'load-tester' });
pm.request.headers.upsert({ key: 'X-User-Role', value: 'ADMIN' });
```

2.3 Runner Configuration

- Run mode: Run manually via Postman Collection Runner
- Iterations: 50
- Delay: 100 ms (recommended for stable Render database execution)
- Environment: Xebia LMS Production
- Test data file: combined_test_dataset.json (containing 50 items)

3. Summary of Documented POST APIs

#	API Name	Endpoint	Success Status
1	Auth Login	POST /api/auth/login	200 OK
2	Create Category	POST /api/categories	201 Created
3	Create Course	POST /api/courses	201 Created
4	Create Module	POST /api/modules	201 Created
5	Create Submodule	POST /api/submodules	201 Created
6	Create Content	POST /api/content	201 Created
7	Create Batch	POST /api/batches	201 Created
8	Create Assessment	POST /api/assessments	201 Created
9	Create Event	POST /api/events	201 Created

4. API Reference

API 1 – Auth Login

Endpoint	POST https://xebia-lms-backend.onrender.com/api/auth/login
Authorization	Collection-level Headers (X-Organization-ID, X-User-Id, X-User-Role)
Content-Type	application/json
Data File	combined_test_dataset.json

Parameterized Request Body

```
{
  "email": "auth.user.1@xebia.com",
  "password": "PasswordXebia123!1",
  "role": "TRAINER"
}
```

Sample Response Body (200 OK)

```
{
  "id": "teacher-user-1",
  "name": "Meera Thomas",
  "email": "auth.user.1@xebia.com",
  "role": "teacher",
  "studentId": null,
  "organizationId": "123e4567-e89b-12d3-a456-426614174000"
}
```

Post-response Test Script

```
pm.test("Status code is 200", function () {  
    &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&~<br>    pm.response.to.have.status(200);  
});  
  
pm.test("Response contains record ID", function () {  
    &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&~<br>    const json = pm.response.json();  
    &nbsp;&nbsp;&~<br>    pm.expect(json.id).to.exist;  
});
```

Test Cases Executed

- 50 login attempts executed with distinct credential/email combinations.
- role field in the request (e.g. TRAINER, STUDENT) correctly resolved to the account's actual role.
- studentId verified as null for non-student accounts.
- Response returns 200 OK with the authenticated user's ID, name, and organizationId.

API 2 – Create Category

Endpoint	POST https://xebia-lms-backend.onrender.com/api/categories
Authorization	Collection-level Headers (X-Organization-ID, X-User-Id, X-User-Role)
Content-Type	application/json
Data File	combined_test_dataset.json

Parameterized Request Body

```
{
  "parentCategoryId": null,
  "name": "Core Subject Branch 1",
  "description": "Curriculum classification for subject branch 1",
  "status": "ACTIVE",
  "metadata": "{}"
}
```

Sample Response Body (201 Created)

```
{
  "id": "943d7236-02f6-4529-beca-59e7c5f068a7",
  "organizationId": "123e4567-e89b-12d3-a456-426614174000",
  "parentCategoryId": null,
  "name": "Core Subject Branch 1",
  "description": "Curriculum classification for subject branch 1",
  "status": "ACTIVE",
  "metadata": "{}",
  "createdAt": "2026-07-16T14:42:37.596086715",
  "updatedAt": "2026-07-16T14:42:37.596086715"
}
```

Post-response Test Script

[illegible]

Test Cases Executed

- 50 unique curriculum categories created across the organization.
- parentCategoryId correctly accepts null for top-level categories.
- status field defaults/persists as ACTIVE.
- Response returns 201 Created with the generated category ID and timestamps.

API 3 – Create Course

Endpoint	POST https://xebia-lms-backend.onrender.com/api/courses
Authorization	Collection-level Headers (X-Organization-ID, X-User-Id, X-User-Role)
Content-Type	application/json
Data File	combined_test_dataset.json

Parameterized Request Body

Sample Response Body (201 Created)

Post-response Test Script

Test Cases Executed

- | API 5 – Create Submodule | |
|--------------------------|--|
| Endpoint | POST https://xebia-lms-backend.onrender.com/api/submodules |
| Authorization | Collection-level Headers (X-Organization-ID, X-User-Id, X-User-Role) |
| Content-Type | application/json |
| Data File | combined_test_dataset.json |

Sample Response Body (201 Created)

Post-response Test Script

Test Cases Executed

- | API 6 – Create Content | |
|------------------------|--|
| Endpoint | POST https://xebia-lms-backend.onrender.com/api/content |
| Authorization | Collection-level Headers (X-Organization-ID, X-User-Id, X-User-Role) |
| Content-Type | application/json |
| Data File | combined_test_dataset.json |

Sample Response Body (201 Created)

Post-response Test Script

Test Cases Executed

- | API 7 – Create Batch | |
|----------------------|--|
| Endpoint | POST https://xebia-lms-backend.onrender.com/api/batches |
| Authorization | Collection-level Headers (X-Organization-ID, X-User-Id, X-User-Role) |
| Content-Type | application/json |
| Data File | combined_test_dataset.json |

Parameterized Request Body

Xebia LMS - Postman API Testing Report | Page 9

Sample Response Body (201 Created)

```
{
  "id": "batch-60d8e6cd",
  "name": "Batch-Beta-1",
  "subject": "Sub-101",
  "department": "COMPUTER_SCIENCE",
  "semester": "FALL",
  "year": "2026",
  "description": "LMS batch group details for Beta-1",
  "capacity": 50,
  "teacher": "Instructor Name 1",
  "status": "ACTIVE",
  "joinCode": "JOIN2001",
  "joinCodeEnabled": true,
  "completion": null,
  "averageQuiz": null,
  "averageAssignment": null,
  "attendance": null,
  "pendingAssignments": null,
  "studentIds": [],
  "subjectIds": []
}
```

Post-response Test Script

```
pm.test("Status code is 201", function () {  
    &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&~>pm.response.to.have.status(201),  
});  
  
pm.test("Response contains record ID", function () {  
    &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&~>const json = pm.response.json();  
    &nbsp;&nbsp;&~>pm.expect(json.id).to.exist;  
});
```

Test Cases Executed

- 50 batches created with unique names, join codes, and capacities.
- department and semester enums accepted and persisted correctly.
- joinCodeEnabled flag correctly toggled and stored as boolean.
- Response returns 201 Created with an auto-generated batch ID and status ACTIVE.

API 8 – Create Assessment

Endpoint	POST https://xebia-lms-backend.onrender.com/api/assessments
Authorization	Collection-level Headers (X-Organization-ID, X-User-Id, X-User-Role)
Content-Type	application/json
Data File	combined_test_dataset.json

Parameterized Request Body

Sample Response Body (201 Created)

Post-response Test Script

Test Cases Executed

- ## API 9 – Create Event

Xebia LMS - Postman API Testing Report | Page 11

5. Dataset Files

combined_test_dataset.json: Contains 50 distinct objects with values mapped to the event_*, assessment_*, category_*, course_*, module_*, submodule_*, content_*, batch_*, and auth_* namespaces used by the parameterized request bodies above.

6. Documentation Reference Checklist

- Request method, URL, headers, and parameterized JSON body for each of the 9 APIs.
- Sample 201 Created response body captured for each endpoint.
- Collection-level Pre-request Script configuring tenant isolation headers.
- Post-response test script and test cases documented per endpoint.

Xebia LMS - API Documentation