RECONSTRUCT
BRICK VENEER TO
MATCH EXISTING

STRIP IN BRICK TIE WITH
WALL WATERPROOFING

ADJUSTABLE BRICK
ANCHORS AT 11" O.C.
MAX. VERTICALLY AND 16"
O.C. MAX. HORIZONTALLY

WALL WATERPROOFING

METAL THROUGH—WALL
FLASHING — EXTEND
BEYOND OPENING
ONE BRICK LENGTH

PLYWOOD SHEATHING,
¾" THICK, TYP.

STANDING SEAM METAL
PANELS, TYP.

CONTINUOUS HOOK STRIP

SLOPED MORTAR BED

5x5x⅜" GALV. STEEL LOOSE LINTEL, 8" MIN. BEARING

LINE OPENING WITH SHEET
METAL, FULLY—SOLDERED
WATERTIGHT, WITH FLANGES AT
THE HEAD AND JAMBS FASTENED
AT 8" O.C.

CONTINUOUS HOOK STRIP

METAL FLASHING DRIP EDGE —
FASTEN AT 8" O.C.

RECONSTRUCT
BRICK VENEER TO
MATCH EXISTING

STEEL ANGLE — FASTEN
TO STRUCTURE AT 12" O.C.

STRIP IN BRICK TIE WITH
WALL WATERPROOFING

HIGH TEMPERATURE WALL
WATERPROOFING —
EXTEND INTO OPENING
AT BOTTOM AND SIDES

SLIP SHEET

WALL WATERPROOFING,
EXTEND INTO OPENING
AT BOTTOM AND SIDES

OPENING IN PARAPET
N.T.S.

COMMENTS:
1. ??
2. ??
3. ??
4. ??
5. ??

ENGINEER: xxxxx

LAST UPDATE: change to todays date

DRAFTER: xxxxxx

DRAWING SCALE: AS NOTED

FILENAME: TDBK020.DWG