

JAWAHARLAL NEHRU TECHNOLOGICAL UNIVERSITY VIZIANAGARAM

VIZIANAGARAM – 535003

ANDHRA PRADESH

ELECTRICITY USAGE TRACKER

By

A.MAHESWARULU

(Regd. No. 24VV1A1204)

Under the supervision of

MRS. MADHUMITA CHANDA

Department of Information Technology

JNTU-GV, Vizianagaram

Academic Year: 2026–2027

CONTENTS

1. Introduction....1
2. Project Overview and Requirements....2
3. Project Architecture and Structure....4
4. Flutter Development Environment Setup....7
5. Dart Programming Fundamentals Used in the Project....10
6. Creating and Configuring the Flutter Project....13
7. Electricity Usage Tracker – Case Study....14
8. User Authentication and Profile Management....16
9. Meter Reading Management....18
10. Consumption and Bill Estimation....20
11. Usage Analytics and History....22
12. Alerts and Energy-Saving Guidance....24
13. Exploring Flutter Widgets in the Project....26
14. Responsive UI Design....28
15. Navigation Between Screens....30
16. Stateful and Stateless Widgets....32
17. State Management....33
18. Custom Widgets and Styling....35
19. Forms and Validation....38
20. Local Data Storage with SQLite....40
21. Database and Data Models....42
22. Animations and User Experience....44
23. Testing and Debugging....45
24. Application Workflow....47
25. Security and Data Validation....52
26. Conclusion....53

1. Introduction

Flutter is an opensource UI framework developed by Google for building crossplatform applications from a single codebase. Flutter uses the Dart programming language and provides a widgetbased approach for creating interactive mobile interfaces.

The Electricity Usage Tracker is a Flutter application that helps a user record meter readings, calculate units consumed and estimated bills, review usage history, and understand consumption patterns. The application stores its data locally and presents the information through a responsive interface.

Advantages of Flutter

- Crossplatform development from a common

codebase. • Hot reload for faster interface development.

- A large collection of customizable Material widgets.

Dart Language

Dart is object-oriented, strongly typed, and supports asynchronous programming through Future, async, and await. These features are used while reading and writing SQLite data and while updating screens after user actions.

Key Flutter Features Used in This Project

- Widget-based screens for dashboards, forms, cards, charts, and lists.
- Stateful widgets for readings, theme selection, and changing usage data.
- Navigation between authentication, dashboard, history, analytics, and profile screens.

2. Project Overview and Requirements

The Electricity Usage Tracker is a mobile application for maintaining electricity meter records. A user can register, sign in, add readings, estimate a bill, review past consumption, inspect monthly charts, and configure a tariff value used in calculations.

Problem Statement

Electricity consumption is often recorded manually, which makes it difficult to compare monthly usage or estimate a bill before it arrives. Users need a simple way to preserve meter readings, calculate units and charges consistently, and identify high-consumption periods.

Main Objectives

- Provide account registration, login, and profile management. • Allow users to add, view, and delete meter readings.
- Calculate consumed units from consecutive readings. • Estimate electricity bills using a configurable tariff.
- Present usage history and monthly analytics.
- Provide in-app high-usage alerts and energy-saving guidance. • Persist user data and readings locally using SQLite.
- Support light and dark themes with a responsive interface.

Application Scope

The application is a single-device tracker. It does not connect to an electricity provider, read a smart meter, synchronise data to a cloud service, or send scheduled notifications outside the application.

Functional Requirements

Module	Requirement
Authentication	Registration, login, logout, duplicate-email checks, and form validation.
Profile	View and update the user name, email address, and electricity tariff.
Readings	Add, list, and delete meter readings for the signed-in user.
Calculation	Compute units from consecutive readings and calculate the bill from the tariff.
Bill Estimate	Estimate a bill from a user-entered number of units without saving a reading.
Analytics	Display monthly usage and bill charts, averages, and a highest-usage insight.
Alerts	Show high-usage warnings, monthly reminders, and energy-saving tips.
Storage	Persist users, readings, and settings locally with SQLite.

Non-Functional Requirements

- Usability: clear forms, readable cards, and straightforward navigation.
- Performance: database work is asynchronous and does not block the interface. • Maintainability: screens, models, services, and theme code are separated.
- Scalability: additional modules can be added without rebuilding every screen. • Portability: the interface adapts to different mobile screen sizes.

3. Project Architecture and Structure

The application follows a modular Flutter structure. Interface code is separated from models, database access, and shared theme configuration so that each part can be maintained independently.

Project Directory

```
electricity_usage_t
racker/ ├── lib/
│   ├──
main.dart │
├──
database/
 │   │   └──
 database_helper.dart │
 ├── models/
 │   │   └──
 electricity_reading.dart │
 ├── services/
 │   │   └──
 database_service.dart │
 ├── screens/
 │   │   ├──
 splash_screen.dart  │
 │   ├──
 landing_screen.dart │
 │   ├──
 login_screen.dart
 │   │   ├──
 register_screen.dart  │
 │   ├──
 dashboard_screen.dart
 │   │   ├── add_reading_screen.dart
 │   │   ├──
 bill_estimate_screen.dart │
 │   ├──
 usage_history_screen.dart │
 │   ├──
 analytics_screen.dart
 │   │   ├──
 alerts_screen.dart  │
 │   ├──
 profile_screen.dart
 │   │   └──
 personal_information_screen.dart │
 └── theme/
 │       ├── app_theme.dart
 │       └──
 theme_controller.dart ├──
 android/
 ├──
 assets/
 ├──
```

```
test/
└── pubspec.yaml
```

Description of Project Modules

Directory	Purpose
lib/	Contains the Dart source code for the application.
database/	Defines the local SQLite connection and table creation logic.
models/	Represents an electricity reading and converts database rows into objects.
services/	Provides asynchronous CRUD operations and tariff settings.
screens/	Contains complete page-level interfaces and user interactions.
theme/	Defines the light and dark visual styles and persisted theme selection.
assets/	Stores static application resources declared in pubspec.yaml.
test/	Contains automated tests; the current file is the default Flutter template test.
pubspec.yaml	Declares Flutter dependencies, assets, and project configuration.


Architecture Flow

```
Flutter Widgets and
       Screens ↓
Local UI State and
       ThemeController ↓
DatabaseHelper /
       DatabaseService ↓
sqflite SQLite
       Database ↓
users, readings and settings tables
```

4. Flutter Development Environment Setup

Flutter SDK Installation

1. Download the stable Flutter SDK from the official Flutter website. 2. Extract the SDK to a location such as C:\src\flutter.
3. Add C:\src\flutter\bin to the Windows PATH. 4. Open a new terminal and run flutter --version.
5. Run flutter doctor to identify missing components.



Flutter SDK installation and toolchain verification


Android Toolchain Without Android Studio

The project can be developed with Visual Studio Code and the Android command-line tools. Android Studio is not required as the code editor.

1. Install the Android SDK command-line tools.
2. Configure the Android SDK path and platform tools.
3. Accept the licences with flutter doctor --android-licenses.
4. Run flutter doctor and confirm the Android toolchain checks.
5. Use a connected device or emulator when running the application.

Visual Studio Code


1. Install Visual Studio Code.
2. Open the Extensions panel with Ctrl + Shift + X.
3. Install the Flutter extension; Dart is installed as a dependency. 4. Open the project folder in VS Code.
5. Use the integrated terminal for Flutter commands and debugging.



Dart and Flutter extensions installed in Visual Studio Code

Verify the Environment

```
flutter --
version dart
--version
flutter
doctor
flutter
devices
```



Flutter doctor output confirming the available toolchain

Environment Checks

- Confirm that the Flutter SDK and Dart versions are available. • Resolve any missing Android SDK or platform-tool warnings.
- Check that a device or emulator is listed before running the app.
- Use a clean terminal after changing PATH environment variables.

Useful Commands

```
flutter
doctor -v
flutter
clean
flutter pub
get flutter
analyze
flutter run
```

The verification screenshots on this and the preceding pages document the development environment. They do not represent screens inside the Electricity Usage Tracker application.

5. Dart Programming Fundamentals Used in the Project

Dart provides the programming foundation for the Flutter application. The project uses variables, classes, lists, maps, functions, conditional statements, loops, asynchronous programming, and null safety.

Variables and Data Types

```
String deviceName = "Home
Meter"; int userId = 101;
double tariff
= 7.0; bool
isDark = true;
List<double> readings = [120.5,
145.0]; Map<String, dynamic> user =
{"name": "Dileep"};
```

Conditional Statements

```
if (current < previous) {
  showMessage("Invalid
  reading");
} else {
  units = current -
previous; }
```

Lists

Lists hold collections such as readings, chart entries, and dashboard cards.

```
final readings = <double>[120.5, 145.0];

for (final units in
  readings) {
  print("Units:
  $units");
}
```

Classes and Models

```
class
  ElectricityReadin
  g { final int? id;
  final int userId;
  final double
  previousReading; final
  double currentReading;
  final double units;
  final double
  billAmount; final
  String date;

  ElectricityRea
    ding({
    this.id,
    required this.userId,
    required
    this.previousReading,
    required
    this.currentReading,
    required this.units,
    required
    this.billAmount,
    required
    this.date,
  });

  Map<String, dynamic>
       toMap() => { "id":
       id,
       "user_id": userId,
       "previous_reading":
       previousReading,
       "current_reading":
       currentReading, "units":
       units,
       "bill_amount":
       billAmount, "date":
       date,
      }
; }
```

Asynchronous Programming

Database operations are asynchronous so that the interface remains responsive while SQLite reads or writes data.

```
Future<List<ElectricityReading>> loadReadings(int
  userId) async { final db = await
  DatabaseService.instance.database;
  final rows = await
    db.query(
    "readings",
```

```
    where: "user_id
    = ?",
    whereArgs:
    [userId],
    orderBy: "id
    DESC",
  );
  return
rows.map(ElectricityReading.fromMap).toList
(); }
```

6. Creating and Configuring the Flutter Project

Creating the Application

```
flutter create
electricity_usage_tracker cd
electricity_usage_tracker
code .
flutter
run
```

pubspec.yaml

The pubspec declares the Flutter SDK and the packages used by the application. The current project depends on sqflite, path, fl_chart, shared_preferences, and cupertino_icons.

```
dependen
  cies:
  flutter
  :
    sdk: flutter
  cupertino_icons:
  ^1.0.8 sqflite:
  ^2.4.3
  path:
  ^1.9.1
  fl_chart:
  ^1.2.0
  shared_preferences: ^2.5.6
```

Main Application Entry Point

```
void main() {
  WidgetsFlutterBinding.ensureInit
  ialized(); runApp(const
  ElectricityUsageTracker());
}

class ElectricityUsageTracker extends
  StatefulWidget { const
  ElectricityUsageTracker({super.key});

  @override
  State<ElectricityUsageTracker>
      createState() =>
      _ElectricityUsageTrackerState();
}
```

7. Electricity Usage Tracker – Case Study

The Electricity Usage Tracker is the central case study for this Flutter documentation. It is designed for a user who wants to record meter readings, monitor consumption, understand monthly trends, and estimate electricity costs without relying on a cloud account.

Core Features

- User registration, login, and local account storage.
- Profile viewing, personal-information editing, and tariff configuration. • Meter-reading entry with previous and current values.
- Automatic calculation of consumed units and estimated bill. • Usage history with single-item deletion and clear-all support.
- Monthly usage and bill charts with averages and an insight message. • In-app high-usage alerts, reminders, and energy-saving guidance.
- Light and dark themes with a persisted user preference. • Responsive layouts for different mobile screen sizes.
- Local SQLite persistence for users, readings, and settings.

User Journey

1. The user opens the splash screen and continues from the landing page. 2. A new user registers with a name, email, and password.
3. The user signs in and reaches the dashboard.
4. The dashboard displays the latest usage, bill, and previous usage. 5. The user adds a meter reading with previous and current values. 6. The app calculates units and the estimated bill immediately.
7. The reading is stored locally and appears in usage history. 8. The user reviews monthly charts and the energy insight. 9. The user checks alerts or updates the tariff in the profile. 10. Logout clears the navigation stack and returns to login.

Technologies Used

Technology	Role in the Project
Flutter	Cross-platform UI, navigation, and widget composition.
Dart	Application language and model classes.
sqflite	Asynchronous SQLite access on mobile devices.
SQLite	Local storage for users, readings, and tariff settings.
fl_chart	Bar and line charts in the analytics screen.
shared_preferences	Persisted light or dark theme selection.
Material 3	Cards, forms, dialogs, and responsive layout.
Visual Studio Code	Development and debugging environment.

System Overview

```
Presentation
  MaterialApp, Splash, Landing,
  Login/Register Dashboard and
  feature screens
        ↓
 UI
state
  setState, AnimationController,
       ThemeController ↓
Data access
  DatabaseHelper (users) / DatabaseService
       (readings) ↓
Storage
  electricity_tracker.db + electricity_usage.db
```

Technology and data-flow overview of the application

8. User Authentication and Profile Management

Registration creates a local account, while login verifies the entered email and password against the users table. Authentication is handled by DatabaseHelper rather than a remote service.

Registration

- All fields are required.
- The email must match a simple email pattern.
- The password must contain at least six characters. • The password and confirmation must match.
- Duplicate email addresses are rejected before insertion.

Login


The login screen validates empty input, queries the local users table, and opens the dashboard only when matching credentials are found.

```
final user = await
  DatabaseHelper.instance.loginUser(
  email: email,
  password:
password, );

if (!mounted) return;

if (user == null) {
  showMessage("Invalid email or
  password."); return;
}

Navigator.pushRepla
  cement( context,
  MaterialPageRoute
  (
    builder: (_) =>
      DashboardScreen( userId:
      user["id"] as int,
      userName: user["name"] as
      String, userEmail:
      user["email"] as String,
    )
  ,
  )
  ,
);
```



LOGIN

SCREEN Profile Management

The profile screen displays the signed-in user's name and email, provides access to personal-information editing, and manages the electricity tariff and appearance settings.

- View the current account name and email address. • Edit the name and email through a separate screen.
- Prevent an update to an email address that already exists. • Configure the tariff used for new reading calculations.
- Choose between the dark and light themes.

Updated profile values are returned to the dashboard so that the welcome section reflects the new name without requiring the user to sign in again.

9. Meter Reading Management

A meter reading records the previous meter value, the current meter value, the calculated units, the tariff used, the estimated bill, the owning user, and the date. Readings are the main data source for the dashboard, history, analytics, and alerts.


Reading Management Operations

- Add a reading for the signed-in user.
- Reject non-numeric, negative, or decreasing meter values. • Calculate units and the estimated bill before saving.
- View readings in reverse chronological order.
- Delete one reading or clear all readings after confirmation.

Reading Card

```
Card(
  child: ListTile(
    leading: const
    Icon(Icons.bolt_rounded),
    title: Text(
      "${item.units.toStringAsFixed(
    1)} kWh", ),
    subtitle: Text(
      "${item.previousReadin
      g} → "
      "${item.currentReading
      } kWh",
    ),
    trailing: IconButton(
      icon: const
      Icon(Icons.delete_outline),
      onPressed: onDelete,
    )
  ,
  )
  ,
)
```

The history screen also presents the previous and current readings and the calculated bill beneath each card. Delete operations use a confirmation dialog to avoid accidental data loss.



Reading Ownership

Each saved reading contains a user_id value. DatabaseService filters every query by the current user, so the history, analytics, and alert screens receive only that user's readings.

- One user can own many readings.
- Each reading belongs to exactly one user.
- Readings store their own date and calculated values.
- Deletion affects only the selected reading unless clear-all is confirmed.

This is a one-to-many relationship. Unlike a many-to-many skill model, the application does not require a separate reading-membership table.

10. Consumption and Bill Estimation

Consumption is calculated from the difference between the current and previous meter values. The estimated bill is the consumed units multiplied by the tariff. Both values are stored with the reading so that historical bills remain consistent if the tariff changes later.

Calculation Operations

- Read the previous value, current value, and tariff.
- Reject empty, non-numeric, or negative input.
- Reject a current reading below the previous reading.
- Calculate units as current minus previous.
- Calculate the estimated bill as units multiplied by tariff.


Calculation Code

```
void calculateUsage() {
  final values =
  readInputs(); if
  (values == null)
  return;

  setState(() {
    units = values.current -
    values.previous; estimatedBill =
    units * values.rate;
  }
);
}
```

Worked Example

Value	Example	Result
Previous reading	1200	Starting value
Current reading	1285	85 units consumed
Tariff	₹8.00	₹680.00 estimated bill



BILL ESTIMATE

Meter Reading vs Bill Estimate

Feature	Behaviour
Purpose	A reading records actual consumption; the estimate is a quick what-if calculation.
Storage	Readings are saved; estimates are temporary and are not inserted.
Input	Reading uses previous, current, and tariff; estimate accepts the same values independently.
Result	Both display units and a bill, but only a saved reading affects history and analytics.

11. Usage Analytics and History

The analytics screen reads the user's saved readings, sorts them by date, and presents summary metrics, a bar chart for monthly consumption, a line chart for bill amounts, and a short insight based on the latest two readings.

Summary Metrics

- Average units across all saved readings.
- Average estimated bill across all saved readings. • Highest-usage reading and its date.
- Latest-versus-previous usage insight.

Analytics Flow

1. Load the current user's readings from DatabaseService. 2. Sort the records by date in ascending order.
3. Calculate average usage and average bill. 4. Identify the highest-usage reading.
5. Build the usage bar chart and bill line chart.
6. Compare the latest two readings for the insight.

Average Calculation

```
double get averageUsage {
  if (readings.isEmpty) return 0;

  return
       readings.fold<dou
       ble>( 0,
        (total, reading) => total +
      reading.units, ) /
      readings.le
ngth; }
```

History is separate from analytics: the history screen focuses on individual records and deletion, while analytics aggregates the same data into trends and comparisons.


History and Chart Interpretation

The usage history screen lists every saved reading with its date, meter values, consumed units, and bill. The analytics screen uses the same records to compare consumption over time.

Chart Interpretation

- A rising bar indicates higher consumption in a later reading.
- A falling line indicates a lower estimated bill.
- The average cards provide a quick baseline for comparison.
- The highest-usage card identifies the peak record and date.

Charts are generated locally with fl_chart. No chart data is uploaded to an external analytics service.



Analytics screen with summary cards, charts, and insight

12. Alerts and Energy-Saving Guidance

Alerts are presented inside the application. The screen loads the latest readings and compares the newest consumed units with the previous reading. It does not schedule operating-system notifications or send messages to another device.

High-Usage Check

```
bool get hasHighUsage {
  final latest =
  latestReading; final
  previous =
  previousReading;

  if (latest == null || previous == null) return false;

  return latest.units >
previous.units; }
```

Alert Types

- High-usage warning when the latest units exceed the previous units. • Monthly reminder to add a new meter reading.
- Bill update showing the latest estimated amount.
- Energy-saving tip for reducing high-power appliance use.

If fewer than two readings exist, the comparison is unavailable and the screen shows a helpful empty or caught-up state instead of a false warning.


Alert Presentation

The alerts screen uses theme-aware cards and a compact empty state. A refresh action reloads readings after new data has been added.

Alert

States	Meaning
State	The latest reading has more units than the previous reading.
High usage	The user is encouraged to keep meter records current.
Reminder	The latest estimated bill is displayed.
Bill update	No warning is required, or there are too few readings to compare.
Caught up	

These messages are informational guidance, not electricity-provider notices. The estimated bill may differ from the actual bill because taxes, fixed charges, and slab rates are not modelled.



S

Alerts and energy-saving guidance

13. Exploring Flutter Widgets in the Project

Flutter widgets are the building blocks of every screen. The project combines standard Material widgets with private builder methods and custom painters to create a consistent energy-themed
interface.

Important Widgets

Widget	Use in the Project
MaterialApp	Root configuration, themes, and initial route.
Scaffold	Base structure for each screen.
AppBar	Titles, back actions, alerts, and clear-history action.
Text	Names, readings, units, bills, and messages.
TextField	Email, password, meter values, and tariff input.
Card / Container	Reading cards, stat cards, and action tiles.
ListView	Dashboard sections, history, and alerts.
Column / Row	Vertical sections and paired summary cards.
Expanded	Balanced stat cards without horizontal overflow.
SingleChildScrollView	Scrollable forms and profile content.
CustomPaint	Animated energy backgrounds on major screens.
AnimatedBuilder	Rebuilds animated backgrounds efficiently.
CircularProgressIndicator	Loading and splash feedback.

The screens avoid fixed screen coordinates where possible and use padding, spacing, and flexible containers to remain readable at different widths.

Example Widget Tree

```
ElectricityUsageT
 racker └──
 MaterialApp
      └── SplashScreen
          └──
              LandingScr
              een └──
              LoginScree
              n
                   └── DashboardScreen
                       ├──
                       AddReadingScreen
                       ├──
                       UsageHistoryScre
                       en ├──
                       AnalyticsScreen
                       ├──
                       BillEstimateScre
                       en ├──
                       AlertsScreen
                       └── ProfileScreen
```

```
DashboardS
 creen └──
 Scaffold
      ├── AppBar (alerts,
      profile) └── Body
           └── Stack
               ├── CustomPaint
               background └──
               RefreshIndicator
                    └── ListView
                        ├── Welcome
                        header ├──
                        Main usage
                        card ├── Stat
                        cards
                        ├── Quick
                        actions ├──
                        Comparison
                        card └──
                        Latest
                        readings
```

Dashboard widget composition in the Electricity Usage Tracker

The tree mirrors the source structure: the dashboard owns its animated background, refresh behaviour, and scrollable content, while feature screens are opened as separate routes.

14. Responsive UI Design

Responsive design keeps content usable across different Android screen sizes. The application relies on flexible layout widgets, scrollable content, and theme-aware spacing rather than fixed screen coordinates.

Responsive Techniques

- SafeArea keeps content away from system bars and cutouts.
- Expanded and Flexible share horizontal space without overflow. • ListView handles long dashboard, history, and alert content.
- SingleChildScrollView protects forms on shorter screens.
- MediaQuery.sizeOf is used for height-sensitive alert content. • Consistent padding and spacing maintain readability.

Dashboard Layout Pattern


The dashboard uses a refreshable ListView and pairs summary cards inside a Row with Expanded children. This lets both cards share the available width safely.

```
RefreshIndicator(
  onRefresh:
  loadDashboard,
  child: ListView(
    padding: const EdgeInsets.fromLTRB(18,
    12, 18, 28), children: [
      _buildWelcomeSect
      ion(),
      _buildMainUsageCa
      rd(), Row(
        children: [
          Expanded(child:
          _statCard(...)), const
          SizedBox(width: 12),
          Expanded(child:
          _statCard(...)),
        ]
      ,
      )
      ,
    ]
  ,
  )
  ,
)
```

Project Application

The dashboard, history list, analytics charts, alerts, and forms must remain accessible when device width or height changes. The interface therefore avoids depending on fixed positions for core content.

- Long content is scrollable rather than clipped.
- Card rows use Expanded children for balanced widths.
- MediaQuery is used only where a proportional height is useful.
- Forms remain usable when the keyboard reduces available space.



Responsive dashboard layout

The placeholder above should be replaced with a screenshot of the Electricity Usage Tracker dashboard. The surrounding description already reflects the implemented responsive structure.

15. Navigation Between Screens

Navigation connects the authentication flow, dashboard, and feature modules. The application uses MaterialPageRoute for feature screens and replaces the login route after successful authentication.

Main Navigation Flow

```
SplashS
  creen
  ↓
LandingS
  creen ↓
LoginScreen ↔
  RegisterScreen ↓
DashboardScreen
  ├──
  AddReadingScreen
  ├──
  UsageHistoryScre
  en ├──
  AnalyticsScreen
  ├──
  BillEstimateScre
  en ├──
  AlertsScreen
  └── ProfileScreen
      └── PersonalInformationScreen
```

Logout

Logout clears the authenticated navigation stack so that the user cannot return to the dashboard with the back button.

```
Navigator.pushAndRemov
  eUntil( context,
  MaterialPageRoute(
    builder: (_) => const
  LoginScreen(), ),
  (route) =>
false, );
```

The dashboard also reloads its readings and profile values after returning from feature screens, keeping the visible summary current.

Logout → Login

Navigation stack cleared

16. Stateful and Stateless Widgets

A StatelessWidget is used when a widget does not maintain mutable state. A StatefulWidget is used when the interface must change after a database read, form submission, theme update, or animation tick.

Stateless Widgets

The landing screen and small reusable presentation pieces are stateless where no mutable data is required. They receive values and callbacks through their constructors.

Stateful Widgets

- Login and registration screens maintain form and loading state.
- The dashboard maintains readings, the current name, and loading state. • Add Reading and Bill Estimate maintain entered values and results.
- Analytics, history, alerts, and profile load and refresh local data.

setState Example

```
Future<void> loadDashboard()
  async { try {
    final data = await
      DatabaseService.instance.getReadings(
      widget.userId,
    );
    if (!mounted)
    return;
    setState(() {
      readings =
      data;
      isLoading =
      false;
    });
  } catch (_) {
    if (!mounted) return;
    setState(() => isLoading =
  false); }
}
```

The mounted checks prevent state updates after a screen has been removed from the widget tree.

17. State Management

The project uses local screen state for readings and forms, and a singleton ChangeNotifier for application-wide theme state. It does not use Provider or a remote authentication session.

Why State Management Is Required

- The selected theme affects every screen in the MaterialApp.
- The dashboard must refresh after readings are added or deleted. • Profile changes must flow back to the dashboard name.
- Loading and error states must be reflected in the interface.

Current Approach

ThemeController extends ChangeNotifier and is observed by AnimatedBuilder in main.dart. Screens observe it directly when they expose theme choices. User and reading data are reloaded from SQLite rather than stored in a global provider.

```
class ThemeController extends
  ChangeNotifier {
  ThemeController._();
  static final ThemeController instance = ThemeController._();

 ThemeMode _themeMode =
 ThemeMode.dark; ThemeMode get
 themeMode => _themeMode;

  Future<void> loadTheme() async {
    final preferences = await
    SharedPreferences.getInstance(); final
    savedTheme =
    preferences.getString("app_theme_mode");
    _themeMode = savedTheme == "light"
       ?
       ThemeMode.li
       ght :
       ThemeMode.da
       rk;
    notifyListen
  ers(); }

  Future<void> setTheme(ThemeMode mode) async {
    final preferences = await
    SharedPreferences.getInstance(); await
    preferences.setString(
      "app_theme_mode",
      mode == ThemeMode.light ? "light"
    : "dark", );
   _themeMode =
   mode;
   notifyListen
```

```
        ers();
       }

    }
```

This approach is sufficient for a mostly local application, but a larger version would benefit from a shared session or repository layer.

18. Custom Widgets and Styling

Reusable UI patterns reduce duplication and keep the visual language consistent. The project uses private builder methods for repeated cards and sections, custom painters for energy backgrounds, and shared ThemeData for colours and input styles.

Reusable UI Patterns

- Stat cards for estimated bill and previous usage.
- Action cards for adding readings, viewing history, and analytics. • Section headers for dashboard and profile groups.
- Reading cards for history entries.
- Profile option tiles for account and appearance settings. • Custom painters for animated backgrounds.

Styling Principles

- Use the dark cyber and premium light palettes consistently. • Use rounded cards, dialogs, and input borders.
- Keep primary actions visually distinct from destructive actions. • Maintain readable contrast in both themes.

Theme Configuration

```
static final ThemeData darkTheme =
  ThemeData( useMaterial3: true,
  brightness: Brightness.dark,
  scaffoldBackgroundColor:
  background, colorScheme:
  const ColorScheme.dark(
    primary:
    electricBlue,
    secondary:
    cyberPurple,
    surface: surface,
  ),
  elevatedButtonTheme:
    ElevatedButtonThemeData( style:
    ElevatedButton.styleFrom(
     backgroundColor:
     electricBlue, shape:
     RoundedRectangleBorder
     (
       borderRadius:
      BorderRadius.circular(16), ),
    )
  ,
  )
  ,
```

```
);
```

Dark Cyber Theme



#070B14 #101827 #00B7FF #8B5CF6 #FFD60A

Premium Light Theme



#F4F6FC #FFFFFF #1769D2 #6741C8 #FFC928

APPLICATION ICON



Electricit
y Usage
Tracker

19. Forms and Validation

Forms are used for registration, login, meter readings, bill estimation, profile editing, and tariff changes. Validation prevents invalid values from reaching SQLite and gives the user a clear message
when input cannot be accepted.

Validation Requirements

Validation

Required fields, email pattern, minimum password length, matching confirmation.

Form	
Registration	Both email and password must be entered; credentials must match. Name and email are required; email must contain @ and remain unique.
Login	Numeric, non-negative values; current cannot be below previous.
Personal Information	Numeric, non-negative values and a positive tariff.
Add Reading	A finite amount greater than zero.
Bill Estimate	
Tariff Dialog	

Registration Validation

```
final name =
nameController.text.trim(); final
email =
emailController.text.trim();
final password =
passwordController.text;

if (name.isEmpty || email.isEmpty ||
  password.isEmpty) { _showMessage("Please
  fill all fields");
  ret
urn;
}
```


```
if
    (!RegExp(r"^[^@\s]+@[^@\s]+\.
    [^@\s]+$") .hasMatch(email))
    {
  _showMessage("Please enter a valid email
  address"); return;
}
```

Submission

```
if (name.isEmpty || email.isEmpty) {
  _showMessage("Please fill in all
  fields."); return;
}

await
  DatabaseHelper.instance.insert
  User( name: name,
  email: email,
  password:
  password,
);
```

Client-side validation improves usability, but it is not a security boundary. This project performs validation locally and stores credentials locally as well. A production version should add password hashing and avoid storing raw passwords.



Registration form with validation feedback

The form placeholder should be replaced with a screenshot showing the actual registration fields and validation message. The current project does not use a remote backend for submission.

20. Local Data Storage with SQLite

The application persists data on the device with sqflite. There is no REST API, Java backend, or cloud database. Account information and readings are stored in two SQLite database files.

Local Persistence

- DatabaseHelper manages the electricity_tracker.db user and reading tables. • DatabaseService manages electricity_usage.db readings and settings.
- Database access is asynchronous and uses parameterised queries. • Records are filtered by user_id where appropriate.
- The tariff is stored in a settings row with id 1.

Database Files

File	Contents
electricity_tracker.db	users and a legacy readings table used by DatabaseHelper.
electricity_usage.db	readings and settings used by the dashboard and feature screens.

Database Initialisation

```
Future<Database> _initDatabase() async {
  final databasePath = await
  getDatabasesPath(); final path =
  join(
    databasePath,
    "electricity_usag
    e.db",
  );
  return
    openDatabase(
    path,
    version: 3,
    onCreate:
    _createDatabase,
    onUpgrade:
    _upgradeDatabase,
  )
;
}
```

Data Access Layering

```
Widget or screen
       action ↓
setState /
       ThemeControll
       er ↓
DatabaseHelper or
       DatabaseService ↓
sqflite query, insert, update,
       or delete ↓
SQLite file on the
       device ↓
Dart
       m
       o
       d
       e
       l

       ↓
Updated interface
```

Error Handling

- Show a loading indicator while asynchronous work is running.
- Catch database failures and avoid leaving the screen stuck in loading state. • Display a short, meaningful message instead of a raw exception.
- Refresh the visible data only after a successful operation. • Use confirmation dialogs before destructive actions.

DatabaseHelper and DatabaseService are both singletons that cache the opened database. Screens await their operations and update local state after the future completes.

Data Integrity Notes

- Readings are inserted with calculated units and bill values.
- Deletion is scoped to a selected id unless clear-all is confirmed. • The tariff update replaces the single settings row.
- The two database files create a maintenance risk that should be consolidated in a later version.

21. Database and Data Models

The project uses SQLite tables for users, readings, and settings. The schema is intentionally small, but two separate data layers currently define overlapping reading information.

Database Tables

Table / File	Important Columns
users / tracker	id, name, email (unique), password
readings / tracker	user_id, previous_reading, current_reading, units, tariff, estimated_bill, date
readings / usage	user_id, previous_reading, current_reading, units, bill_amount, date
settings / usage	id, tariff

Conceptual Relationships

```
users 1 ──────< readings

users 1 ──────< readings

settings 1 ─── tariff
```

```
(DatabaseHelper)

(DatabaseService)

(global default: 7.0)
```

There is no many-to-many relationship or connection-request model in this application. A reading belongs to one user, and the settings table stores a single global tariff.

Model Responsibilities

- ElectricityReading carries reading values between the UI and database. • toMap converts the model into a SQLite-compatible map.
- fromMap converts a database row back into a typed model.
- The model does not perform calculation; screens and services provide values.

Dart Model

```
class
  ElectricityReadin
  g { final int? id;
  final int userId;
  final double
  previousReading; final
  double currentReading;
  final double units;
  final double
  billAmount; final
  String date;

  ElectricityRea
    ding({
    this.id,
    required this.userId,
    required
    this.previousReading,
    required
    this.currentReading,
    required this.units,
    required
    this.billAmount,
    required
    this.date,
  });

  Map<String, dynamic>
       toMap() => { "id":
       id,
       "user_id": userId,
       "previous_reading":
       previousReading,
       "current_reading":
       currentReading, "units":
       units,
       "bill_amount":
       billAmount, "date":
       date,
      }
; }
```

The fromMap factory casts numeric SQLite values through num and calls toDouble, which handles integer values returned by SQLite for whole-number REAL columns.

Schema Improvement

- Consolidate the duplicate reading tables into one source of truth. • Associate the tariff with a user if per-user rates are required.
- Add indexes on user_id and date for larger histories.
- Store password hashes instead of plain-text passwords.

22. Animations and User Experience

Animations are used to reinforce the energy theme and provide feedback. They are deliberately lightweight: no quiz-result effects, leaderboards, or complex page transitions are required.

Suitable Animations

- Slow custom-painted energy backgrounds on major screens.
- Circular progress indicators during loading and authentication. • AnimatedContainer feedback for theme selection.
- Button and card ripple feedback for user actions.
- Smooth refresh behaviour after readings are added or deleted.

Animation Controller

```
late final AnimationController _animationController;

@override
void
  initState() {
  super.initSt
  ate();
  _animationController =
    AnimationController( vsync:
    this,
    duration: const
  Duration(seconds: 11),
  )..repeat();
}
```

AnimatedBuilder rebuilds only the custom-painted background while the controller runs. The controller is disposed when the screen is removed to avoid unnecessary work.

23. Testing and Debugging

Testing should verify calculations, validation, persistence, navigation, and the visual states of each screen. The current repository does not yet contain a complete test suite for the implemented
application.

Current Test Status

Area	Current Status
Widget test	Only the default counter test remains; it does not test this app.
Unit tests	No dedicated tests for calculation or validation.
Integration tests	No automated integration suite.
Manual testing	Requires an Android device or emulator for sqflite.

Recommended Tests

- Unit-test unit and bill calculations, including invalid readings.
- Test registration email validation and duplicate-email rejection. • Test ElectricityReading toMap and fromMap conversions.
- Widget-test login fields, reading forms, and validation messages. • Integration-test add reading → history → analytics → alerts.
- Replace the default widget_test.dart with application-specific tests.

Debugging Tools

- Flutter DevTools for widget inspection and performance checks. • The Visual Studio Code debugger for breakpoints and stepping. • debugPrint and console output for development diagnostics.
- flutter analyze for static analysis and lint feedback.
- Device or emulator logs for runtime and SQLite failures.

Error Handling Example

```
Future<void> loadAnalytics()
  async { try {
    final data = await
      DatabaseService.instance.getReadings(
      widget.userId,
    );
    data.sort((a, b) =>
    a.date.compareTo(b.date)); if
    (!mounted) return;
    setState(() {
      readings =
      data;
      isLoading =
      false;
    });
  } catch (_) {
    if (!mounted) return;
    setState(() => isLoading =
    false); _showMessage("Unable to
    load analytics.");
  }

}
```

The catch block stops the loading state and shows a short message. It does not expose the internal exception to the user.

24. Application Workflow

The complete workflow moves from splash and landing screens through authentication to the dashboard, where the user can add readings, view history, analyse trends, estimate bills, check alerts, and manage the profile.

Complete Screen Workflow

```
SplashS
  creen
  ↓
LandingS
  creen ↓
LoginScreen ↔
  RegisterScreen ↓
DashboardScreen
  ├──
  AddReadingScreen
  ├──
  UsageHistoryScre
  en ├──
  AnalyticsScreen
  ├──
  BillEstimateScre
  en ├──
  AlertsScreen
  └── ProfileScreen
      ├──
      PersonalInformationScr
      een ├── Tariff dialog
      └── Logout → LoginScreen
```

Dashboard Responsibilities

- Provide the central starting point after authentication.
- Show the latest units, estimated bill, and previous usage.
- Open reading, history, analytics, bill, alert, and profile screens. • Reload data after returning from a feature screen.
- Keep loading and empty states clear without duplicating feature logic.


Data Flow

```
User
    Act
    ion
    ↓
Flutter
    Widget
    ↓
setState /
    ThemeController
    ↓
DatabaseHelper /
    DatabaseService ↓
SQLite query or
    mutation ↓
Dart
    Mo
    del
    ↓
Updated UI
```


Application Screens








Splash, landing, and login screens




S

REGISTER_SCREEN




R

DASHBOARD_SCREEN



R


ADD METER READING_SCREEN




S

R


BILL ESTIMATE_SCREEN



HISTORY_SCREEN




ANALYTICS_SCREEN



ALERTS_SCREEN




PROFILE_SCREEN



SC

PERSONAL INFORMATION_SCREEN



R

LOGOUT_SCREEN

25. Security and Data Validation

The application stores account information and user-generated readings on the device. Security must therefore be considered at the interface, database, and device levels. The current implementation is suitable for a local academic project but is not production hardened.

Application-Side Practices

- Validate required fields, email format, and password length.
- Reject negative meter values and decreasing readings.
- Confirm destructive actions before deleting data.
- Avoid showing raw database exceptions to the user.
- Use parameterised whereArgs queries rather than string concatenation.
- Clear the navigation stack on logout.

Current Limitations

- Passwords are stored as plain text in the local users table.
- There is no password hashing, encryption, or secure session token.
- There is no account recovery or server-side authentication.
- A local database can be accessed on a rooted or compromised device.
- The app does not protect against a modified client because there is no backend authority.
- The app has no cloud backup or remote access control.

Recommended Improvements

- Hash passwords with a slow, salted password-hashing algorithm.
- Encrypt sensitive local data with platform keystore support.
- Add a shared repository layer instead of duplicate database helpers.
- Add automated validation and security regression tests.
- Remove debug prints that expose internal data before release.

26. Conclusion

The Electricity Usage Tracker demonstrates how Flutter and Dart can be used to build a practical local mobile application. The project combines authentication, profile management, meter readings, bill calculation, usage history, monthly charts, alerts, theme selection, and SQLite persistence.

The architecture separates screens, models, database services, and theme code. This structure makes the application easier to understand and extend, while also revealing maintenance issues such as duplicate reading tables and plain-text password storage.

The project also demonstrates input validation, asynchronous programming, error handling, responsive layouts, reusable UI patterns, and custom-painted animation. These concepts provide a foundation for developing a more complete energy-management application.

Final Project Summary

Area	Implementation
Frontend	Flutter and Dart with Material 3 widgets.
Authentication	Local registration, login, and logout.
Profile	Name and email editing plus tariff configuration.
Readings	Add, list, delete, and clear meter readings.
Calculation	Units difference and tariff-based bill estimation.
Analytics	Average usage, average bill, highest usage, bar and line charts.

Final Project Summary (continued)

Area	Implementation
Alerts	In-app high-usage warning, reminder, bill update, and energy tip.
Storage	sqflite databases for users, readings, and the tariff setting.
State	Local setState plus ThemeController for appearance.
Testing	Limited automated coverage; default widget test needs replacement.
Security	Local validation only; passwords are currently stored in plain text.

This documentation focuses exclusively on the Electricity Usage Tracker implementation. The original SkillX material has been replaced with this project's actual authentication, reading, calculation, analytics, alert, profile, SQLite, testing, and security behaviour.

The report also identifies clear next steps: consolidate the duplicated data layer, replace the default widget test, remove plain-text passwords, add real application screenshots, and consider a per-user tariff if the application is extended beyond a single-device academic prototype.