Not For Publication

Sun Java System Application Server Platform Edition 9 Application Deployment Guide

Beta



Sun Microsystems, Inc. 4150 Network Circle Santa Clara, CA 95054 U.S.A.

Part No: 819-3660

Review Copy Composed April 28, 2006

Copyright 2006 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. All rights reserved.

Sun Microsystems, Inc. has intellectual property rights relating to technology embodied in the product that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more U.S. patents or pending patent applications in the U.S. and in other countries.

U.S. Government Rights – Commercial software. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements.

This distribution may include materials developed by third parties.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, the Solaris logo, the Java Coffee Cup logo, docs.sun.com, Java, and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK and Sun" Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

Products covered by and information contained in this publication are controlled by U.S. Export Control laws and may be subject to the export or import laws in other countries. Nuclear, missile, chemical or biological weapons or nuclear maritime end uses or end users, whether direct or indirect, are strictly prohibited. Export or reexport to countries subject to U.S. embargo or to entities identified on U.S. export exclusion lists, including, but not limited to, the denied persons and specially designated nationals lists is strictly prohibited.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 2006 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. Tous droits réservés.

Sun Microsystems, Inc. détient les droits de propriété intellectuelle relatifs à la technologie incorporée dans le produit qui est décrit dans ce document. En particulier, et ce sans limitation, ces droits de propriété intellectuelle peuvent inclure un ou plusieurs brevets américains ou des applications de brevet en attente aux Etats-Unis et dans d'autres pays.

Cette distribution peut comprendre des composants développés par des tierces personnes.

Certaines composants de ce produit peuvent être dérivées du logiciel Berkeley BSD, licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays; elle est licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, le logo Solaris, le logo Java Coffee Cup, docs.sun.com, Java et Solaris sont des marques de fabrique ou des marques déposées de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

L'interface d'utilisation graphique OPEN LOOK et Sun a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui, en outre, se conforment aux licences écrites de Sun.

Les produits qui font l'objet de cette publication et les informations qu'il contient sont régis par la legislation américaine en matière de contrôle des exportations et peuvent être soumis au droit d'autres pays dans le domaine des exportations et importations. Les utilisations finales, ou utilisateurs finaux, pour des armes nucléaires, des missiles, des armes chimiques ou biologiques ou pour le nucléaire maritime, directement ou indirectement, sont strictement interdites. Les exportations ou réexportations vers des pays sous embargo des Etats-Unis, ou vers des entités figurant sur les listes d'exclusion d'exportation américaines, y compris, mais de manière non exclusive, la liste de personnes qui font objet d'un ordre de ne pas participer, d'une façon directe ou indirecte, aux exportations des produits ou des services qui sont régis par la legislation américaine en matière de contrôle des exportations et la liste de ressortissants spécifiquement designés, sont rigoureusement interdites.

LA DOCUMENTATION EST FOURNIE "EN L'ETAT" ET TOUTES AUTRES CONDITIONS, DECLARATIONS ET GARANTIES EXPRESSES OU TACITES SONT FORMELLEMENT EXCLUES, DANS LA MESURE AUTORISEE PAR LA LOI APPLICABLE, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE A LA QUALITE MARCHANDE, A L'APTITUDE A UNE UTILISATION PARTICULIERE OU A L'ABSENCE DE CONTREFACON.

Contents

	Preface	11
1	Assembling and Deploying Applications	
	Overview of Assembly and Deployment	
	About Modules	
	About Applications	19
	Java EE Standard Annotation	
	Java EE Standard Descriptors	
	Application Server Descriptors	22
	Naming Standards	22
	Directory Structure	23
	Assembling Modules and Applications	24
	The asant Utility	24
	The NetBeans IDE	24
	The verifier Utility	24
	Deploying Modules and Applications	
	Deployment Errors	29
	The Deployment Life Cycle	29
	Deployment for Development	30
	Tools for Deployment	34
	Deployment by Module or Application	35
	Deploying a Web Service	36
	Deploying a WAR Module	36
	Deploying an EJB JAR Module	37
	Deploying a Lifecycle Module	37
	Deploying an Application Client	37
	▼ To Deploy an Application Client	38
	▼ To Prepare Another Machine for Executing an Application Client	39
	Deploying a J2EE CA Connector Module	40

	Access to Shared Frameworks	40
A	Deployment Descriptor Files	41
-	Sun Java System Application Server Descriptors	
	The sun-application.xml File	
	The sun-web.xml File	
	The sun-ejb-jar.xml File	
	The sun-cmp-mappings.xml File	
	The sun-application-client.xml file	
	The sun-acc.xml File	
	Alphabetical Listing of All Elements	
	A	
	activation-config	57
	activation-config-property	58
	activation-config-property-name	58
	activation-config-property-value	
	as-context	59
	auth-method	59
	auth-realm	60
	В	61
	bean-cache	61
	bean-pool	62
	C	62
	cache	62
	cache-helper	64
	cache-helper-ref	65
	cache-idle-timeout-in-seconds	
	cache-mapping	66
	call-property	
	caller-propagation	67
	cert-db	67
	check-all-at-commit	68
	check-modified-at-commit	68
	check-version-of-accessed-instances	
	checkpoint-at-end-of-method	
	checkpointed-methods	69

	class-loader	69
	client-container	70
	client-credential	71
	cmp	72
	cmp-field-mapping	73
	cmp-resource	73
	cmr-field-mapping	74
	cmr-field-name	75
	cmt-timeout-in-seconds	75
	column-name	75
	column-pair	76
	commit-option	76
	confidentiality	76
	consistency	77
	constraint-field	77
	constraint-field-value	78
	context-root	79
	cookie-properties	79
	create-tables-at-deploy	80
D.		81
	database-vendor-name	81
	debugging-enabled	81
	default	81
	default-helper	82
	default-resource-principal	82
	description	
	dispatcher	83
	drop-tables-at-undeploy	84
Ε		84
	ejb	84
	ejb-name	87
	ejb-ref	87
	ejb-ref-name	88
	eligible	88
	endpoint-address-uri	88
	enterprise-beans	89
	entity-mapping	90

establish-trust-in-client	91
establish-trust-in-target	91
F	92
fetched-with	92
field-name	93
finder	93
flush-at-end-of-method	94
G	94
gen-classes	94
group-name	95
Н	95
http-method	95
I	90
idempotent-url-pattern	90
integrity	90
ior-security-config	90
is-cache-overflow-allowed	97
is-one-one-cmp	97
is-read-only-bean	97
J	98
java-method	98
java-web-start-access	98
jms-durable-subscription-name	99
jms-max-messages-load	99
jndi-name	100
jsp-config	100
K	103
key-field	103
L	104
level	104
local-home-impl	104
local-impl	105
locale-charset-info	105
locale-charset-map	106
localpart	
lock-when-loaded	107
lock-when-modified	107

	log-service	108
	login-config	108
M	[109
	manager-properties	109
	mapping-properties	110
	max-cache-size	110
	max-pool-size	111
	max-wait-time-in-millis	111
	mdb-connection-factory	111
	mdb-resource-adapter	112
	message	112
	message-destination	113
	message-destination-name	113
	message-destination-ref	114
	message-destination-ref-name	114
	message-security	114
	message-security-binding	115
	message-security-config	116
	method	117
	method-intf	117
	method-name	117
	method-param	118
	method-params	118
N		119
	name	119
	named-group	119
	namespaceURI	119
	none	120
О		120
	one-one-finders	120
	operation-name	120
Ρ.		121
	parameter-encoding	121
	pass-by-reference	121
	password	122
	pm-descriptors	123
	pool-idle-timeout-in-seconds	123

	port-component-name	123
	port-info	123
	prefetch-disabled	124
	principal	125
	principal-name	125
	property (with attributes)	126
	property (with subelements)	127
	provider-config	127
Q.		129
	query-filter	129
	query-method	129
	query-ordering	129
	query-params	130
	query-variables	130
R		130
	read-only	130
	realm	130
	refresh-field	131
	refresh-period-in-seconds	131
	removal-timeout-in-seconds	132
	remote-home-impl	132
	remote-impl	132
	request-policy	133
	request-protection	133
	required	134
	res-ref-name	134
	resize-quantity	135
	resource-adapter-mid	135
	resource-env-ref	136
	resource-env-ref-name	136
	resource-ref	136
	response-policy	137
	response-protection	138
	role-name	138
S		139
	sas-context	139
	schema	139

T

	schema-generator-properties	140
	secondary-table	141
	security	142
	security-role-mapping	142
	service-endpoint-interface	143
	service-impl-class	143
	service-qname	143
	service-ref	144
	service-ref-name	145
	servlet	145
	servlet-impl-class	145
	servlet-name	146
	session-config	146
	session-manager	146
	session-properties	147
	ssl	148
	steady-pool-size	149
	store-properties	149
	stub-property	150
	sun-application	151
	sun-application-client	151
	sun-cmp-mapping	152
	sun-cmp-mappings	153
	sun-ejb-jar	153
	sun-web-app	154
Τ.		156
	table-name	156
	target-server	157
	tie-class	157
	timeout	158
	transport-config	158
	transport-guarantee	159
U		159
	unique-id	159
	url-pattern	160
	use-thread-pool-id	
V .	-	160

Contents

	value	160
	vendor	
	victim-selection-policy	161
W		162
	web	162
	web-uri	162
	webservice-description	162
	webservice-description-name	
	webservice-endpoint	
	wsdl-override	164
	wsdl-port	165
	wsdl-publish-location	
اء دا	I.v.	1.65

Preface

This Application Deployment Guide describes deployment of applications and application components to the Sun Java™ System Application Server, and includes information about deployment descriptors.

Who Should Use This Book

This Application Deployment Guide is intended for use by administrators and software developers who maintain and use Sun Java System servers and software. Application Server administrators and software developers should already understand the following technologies:

- Java technology
- The Java Platform, Enterprise Edition (Java EE platform), version 5
- Extensible Markup Language (XML)

How This Book Is Organized

This book has the following contents:

- Chapter 1, which describes deployment processes
- Appendix A, which describes deployment descriptors

Application Server Documentation Set

The Application Server documentation set describes deployment planning and system installation. The Uniform Resource Locator (URL) for stand-alone Application Server documentation is http://docs.sun.com/app/docs/coll/1343.3. For an introduction to Application Server, refer to the books in the order in which they are listed in the following table.

TABLE P-1 Books in the Application Server Documentation Set

Book Title	Description
Documentation Center	Application Server documentation topics organized by task and subject.

TABLE P-1 Books in the Application Server Documentation Set (Continued)

Book Title	Description	
Release Notes	Late-breaking information about the software and the documentation. Includes a comprehensive, table-based summary of the supported hardware, operating system, Java Development Kit (JDK^{\bowtie}) , and database drivers.	
Quick Start Guide	How to get started with the Application Server product.	
Installation Guide	Installing the software and its components.	
Application Deployment Guide	Deployment of applications and application components to the Application Server. Includes information about deployment descriptors.	
Developer's Guide	Creating and implementing Java Platform, Enterprise Edition (Java EE platform) applications intended to run on the Application Server that follow the open Java standards model for Java EE components and APIs. Includes information about developer tools, security, debugging, and creating lifecycle modules.	
Java EE 5 Tutorial	Using Java EE 5 platform technologies and APIs to develop Java EE applications.	
Administration Guide	Configuring, managing, and deploying Application Server subsystems and components from the Admin Console.	
Administration Reference	Editing the Application Server configuration file, domain.xml.	
Upgrade and Migration Guide	Migrating your applications to the new Application Server programming model, specifically from Application Server 6.x, and 7.x, and 8.x. This guide also describes differences between adjacent product releases and configuration options that can result in incompatibility with the product specifications.	
Troubleshooting Guide	Solving Application Server problems.	
Error Message Reference	Solving Application Server error messages.	
Reference Manual	Utility commands available with the Application Server; written in man page style. Includes the asadmin command line interface.	

Related Books

For documentation about other stand-alone Sun Java System server products, go to the following:

- Message Queue documentation (http://docs.sun.com/app/docs/coll/1343.3)
- Directory Server documentation (http://docs.sun.com/app/docs/coll/1316.1)
- Web Server documentation (http://docs.sun.com/app/docs/coll/1308.1)

Default Paths and File Names

The following table describes the default paths and file names that are used in this book.

TABLE P-2 Default Paths and File Names

Placeholder	Description	Default Value
install-dir	Represents the base installation directory for Application Server.	Solaris™ and Linux operating system installations, non-root user: user's-home-directory/SUNWappserver Solaris and Linux installations, root user: /opt/SUNWappserver Windows, all installations: SystemDrive:\Sun\AppServer
domain-root-dir	Represents the directory containing all domains.	install-dir/domains/
domain-dir	Represents the directory for a domain. In configuration files, you might see domain-dir represented as follows: \${com.sun.aas.instanceRoot}	domain-root-dir/domain-dir

Typographic Conventions

The following table describes the typographic changes that are used in this book.

TABLE P-3 Typographic Conventions

Typeface	Meaning	Example
AaBbCc123	The names of commands, files, and directories, and onscreen computer output	Edit your .login file. Use ls -a to list all files. machine_name% you have mail.
AaBbCc123	What you type, contrasted with onscreen computer output	machine_name% su Password:
AaBbCc123	A placeholder to be replaced with a real name or value	The command to remove a file is rm filename.

TABLE P-3 Typographic Conventions (Continued)

Typeface	Meaning	Example
AaBbCc123	Book titles, new terms, and terms to be emphasized (note	Read Chapter 6 in the <i>User's Guide</i> .
	that some emphasized items appear bold online)	A <i>cache</i> is a copy that is stored locally.
		Do <i>not</i> save the file.

Symbol Conventions

The following table explains symbols that might be used in this book.

TABLE P-4 Symbol Conventions

Symbol	Description	Example	Meaning
[]	Contains optional arguments and command options.	ls [-l]	The -l option is not required.
{ }	Contains a set of choices for a required command option.	-d {y n}	The -d option requires that you use either the y argument or the n argument.
\${ }	Indicates a variable reference.	\${com.sun.javaRoot}	References the value of the com.sun.javaRoot variable.
-	Joins simultaneous multiple keystrokes.	Control-A	Press the Control key while you press the A key.
+	Joins consecutive multiple keystrokes.	Ctrl+A+N	Press the Control key, release it, and then press the subsequent keys.
\rightarrow	Indicates menu item selection in a graphical user interface.	$File \to New \to Templates$	From the File menu, choose New. From the New submenu, choose Templates.

Accessing Sun Resources Online

The docs.sun.com SM web site enables you to access Sun technical documentation online. You can browse the docs.sun.com archive or search for a specific book title or subject. Books are available as online files in PDF and HTML formats. Both formats are readable by assistive technologies for users with disabilities.

To access the following Sun resources, go to http://www.sun.com:

- Downloads of Sun products
- Services and solutions
- Support (including patches and updates)
- Training
- Research

Communities (for example, Sun Developer Network)

Third-Party Web Site References

Third-party URLs are referenced in this document and provide additional, related information.

Note – Sun is not responsible for the availability of third-party web sites mentioned in this document. Sun does not endorse and is not responsible or liable for any content, advertising, products, or other materials that are available on or through such sites or resources. Sun will not be responsible or liable for any actual or alleged damage or loss caused or alleged to be caused by or in connection with use of or reliance on any such content, goods, or services that are available on or through such sites or resources.

Sun Welcomes Your Comments

Sun is interested in improving its documentation and welcomes your comments and suggestions. To share your comments, go to http://docs.sun.com and click Send Comments. In the online form, provide the full document title and part number. The part number is a 7-digit or 9-digit number that can be found on the book's title page or in the document's URL. For example, the part number of this book is 819-3660.



Assembling and Deploying Applications

This chapter describes Sun Java™ System Application Server modules and how these modules are assembled separately or together in an application. This chapter also describes tools for assembly and deployment.

The Application Server modules and applications include Java Platform, Enterprise Edition (Java EE platform) standard features and Application Server specific features. Only Application Server specific features are described in detail in this chapter.

The following topics are presented in this chapter:

- "Overview of Assembly and Deployment" on page 17
- "Assembling Modules and Applications" on page 24
- "Deploying Modules and Applications" on page 28

Overview of Assembly and Deployment

Application assembly (also known as packaging) is the process of combining discrete components of an application into a single unit that can be deployed to a Java-EE-compliant application server. A package can be classified either as a module or as a full-fledged application. This section covers the following topics:

- "About Modules" on page 18
- "About Applications" on page 19
- "Java EE Standard Annotation" on page 21
- "Java EE Standard Descriptors" on page 21
- "Application Server Descriptors" on page 22
- "Naming Standards" on page 22
- "Directory Structure" on page 23

About Modules

A Java EE module is a collection of one or more Java EE components that execute in the same container type (for example, web or EJB) with annotations or deployment descriptors of that type. One descriptor is Java EE standard, the other is Application Server specific. Annotations can be used instead of Java EE standard descriptors.

Types of Java EE modules are as follows:

- **Web Application Archive (WAR)** A web application is a collection of servlets, HTML pages, classes, and other resources that can be bundled and deployed to several Java EE application servers. A WAR file can consist of the following items: servlets, JavaServer Pages™ (JSP™) files, JSP tag libraries, utility classes, static pages, client-side applets, beans, bean classes, and annotations or deployment descriptors (web.xml and sun-web.xml).
- **EJB JAR File** The EJB JAR file is the standard format for assembling enterprise beans. This file contains the bean classes (home, remote, local, and implementation), all of the utility classes, and annotations or deployment descriptors (ejb-jar.xml and sun-ejb-jar.xml). If the EJB component is a version 2.1 or earlier entity bean with container managed persistence, a .dbschema file and a CMP mapping descriptor, sun-cmp-mapping.xml, must be included as well.
- **Application Client Container JAR File** An ACC client is an Application Server specific type of Java EE client. An ACC client supports the standard Java EE Application Client specifications, and in addition, supports direct access to the Application Server. Its deployment descriptors are application-client.xml and sun-application-client.xml.
- **Resource RAR File** RAR files apply to J2EE CA connectors. A connector extends the EJB container to allow access to external systems much like a device driver provides access to a peripheral device from a process hosted by an operating system. It is a portable way of allowing EJB components to access a foreign enterprise system. Each Application Server connector has annotations or a Java EE XML file, ra.xml.

Package definitions must be used in the source code of all modules so the class loader can properly locate the classes after the modules have been deployed.

Because the information in a deployment descriptor is declarative, it can be changed without requiring modifications to source code. At run time, the Java EE server reads this information and acts accordingly.

The Application Server also supports lifecycle modules. See Chapter 13, "Developing Lifecycle Listeners," in Sun Java System Application Server Platform Edition 9 Developer's Guide for more information.

EJB JAR and Web modules can also be deployed separately, outside of any application, as in the following figure. EJB components are assembled in a JAR file with ejb-jar.xml and sun-ejb-jar.xml deployment descriptors. Web components are assembled in a WAR file with web.xml and sun-web.xml deployment descriptors. Both module types are deployed to the Application Server.




FIGURE 1-1 Module Assembly and Deployment

About Applications

A Java EE application is a logical collection of one or more Java EE modules tied together by application deployment descriptors. Components can be assembled at either the module or the application level. Components can also be deployed at either the module or the application level.

The following diagram illustrates how components are assembled into modules and then assembled into an Application Server application and deployed. EJB components are assembled in a JAR file with ejb-jar.xml and sun-ejb-jar.xml deployment descriptors. Web components are assembled in a WAR file with web.xml and sun-web.xml deployment descriptors. An application client is assembled in a JAR file with application-client.xml and sun-application-client.xml deployment descriptors. A resource adapter is assembled in a RAR file with a ra.xml deployment descriptor. All modules are assembled in an EAR file and deployed to the Application Server.




FIGURE 1-2 Application Assembly and Deployment

Each module has an Application Server deployment descriptor and a Java EE deployment descriptor. The Application Server uses the deployment descriptors to deploy the application components and to register the resources with the Application Server.

An application consists of one or more modules, an optional Application Server deployment descriptor, and a Java EE application deployment descriptor. All items are assembled, using the Java ARchive (.jar) file format, into one file with an extension of .ear.

Java EE Standard Annotation

The Application Server supports applications and modules annotated according to the following specifications:

- JSR 250 Common Annotation Specification (http://www.jcp.org/en/jsr/detail?id=250)
- JSR 181 Annotation for Web Services Specification (http://www.jcp.org/en/jsr/detail?id=181)
- EJB 3.0 Specification (http://www.jcp.org/en/jsr/detail?id=220)

The following annotation and deployment descriptor combinations are supported:

- Java EE applications or modules can be packaged with full Java EE 5.0 compliant standard and
 runtime deployment descriptors. If the standard deployment descriptors have specified the
 attribute full, annotations in the application or module are ignored.
- Java EE applications or modules can be fully annotated with metadata defined by the listed specifications. Annotation eliminates the need for Java EE standard deployment descriptors. In most cases, the Application Server deployment descriptors are also optional.
- Java EE applications or modules can be partially annotated with some deployment information in standard deployment descriptors. In case of conflicts, deployment descriptor values supersede the annotated metadata, but a warning message is logged.

To check the correctness of annotations or deployment descriptors prior to deployment, see "The verifier Utility" on page 24.

Java EE Standard Descriptors

Java EE standard deployment descriptors are described in the Java EE specification, v5. You can find the specification at http://java.sun.com/products/.

The following table shows where to find more information about the most commonly used Java EE standard deployment descriptors.

TABLE 1-1 Java EE Standard Descriptors

Deployment Descriptor	oyment Descriptor Where to Find More Information	
application.xml	Java Platform Enterprise Edition Specification, v5, Chapter 8, "Application Assembly and Deployment" - Java EE: Application XML DTD	

Deployment Descriptor	ent Descriptor Where to Find More Information		
web.xml	Java Servlet Specification, v2.5 Chapter 13, "Deployment Descriptor," and JavaServer Pages Specification v2.1, Chapter 7, "JSP Pages as XML Documents," and Chapter 5, "Tag Extensions"		
ejb-jar.xml	Enterprise JavaBeans Specification, v3.0, Chapter 16, "Deployment Descriptor"		
application- client.xml	Java Platform Enterprise Edition Specification, v5, Chapter 9, "Application Clients - Java EE: Application-client XML DTD"		
ra.xml	Java Enterprise Edition, Connector Architecture Specification, v1.5, Chapter 10, "Packaging and Deployment."		

Application Server Descriptors

The Application Server uses additional deployment descriptors for configuring features specific to the Application Server. The sun-application-client.xml and sun-acc.xml files are required; all the others are optional.

To check the correctness of these deployment descriptors prior to deployment, see "The verifier Utility" on page 24.

For complete descriptions of these files, see Appendix A.

Naming Standards

Names of applications and individually deployed EJB JAR, WAR, and connector RAR modules must be unique within an Application Server domain. Modules of the same type within an application must have unique names. In addition, for entity beans that use CMP, . dbschema file names must be unique within an application.

If you do not explicitly specify a name, the default name is the first portion of the file name (without the .war or . jar extension). Modules of different types can have the same name within an application, because the directories holding the individual modules are named with _jar, _war and _rar suffixes. This is the case when you use the Admin Console or the asadmin command. See "Tools for Deployment" on page 34.

You can specify a name in one of these ways:

- If deploying using the Admin Console, specify the name in the Application Name field.
- If deploying using the asadmin deploy command, the default name of the application or module is the prefix of the JAR file that you are deploying. For example, for the hello.war file, the Web application name is hello. To override the default name, specify the --name option.

Make sure your package and file names do not contain spaces or characters that are illegal for your operating system.

Using a Java package-like naming scheme is recommended for module filenames, EAR filenames, module names as found in the <module-name> portion of the ejb-jar.xml files, and EJB names as found in the <ejb-name> portion of the ejb-jar.xml files. The use of this package-like naming scheme ensures that name collisions do not occur. The benefits of this naming practice apply not only to the Application Server, but to other Java EE application servers as well.

JNDI lookup names for EJB components must also be unique. Establishing a consistent naming convention might help. For example, appending the application name and the module name to the EJB name is one way to guarantee unique names. In this case, mycompany.pkging.pkgingEJB.MyEJB would be the JNDI name for an EJB in the module pkgingEJB.jar, which is packaged in the application pkging.ear.

If you are writing your own JSR 88 client to deploy applications to the Application Server using the following API, the name of the application is taken from the display-name entry in the Java EE standard deployment descriptor, because there is no file name in this case. If the display-name entry is not present, the Application Server creates a temporary file name and uses that name to deploy the application.

javax.enterprise.deploy.spi.DeploymentManager.distribute(Target[], InputStream, InputStream)

Neither the Admin Console nor the asadmin command uses this API.

Note – Use of the following JSR 88 API is preferred. In this case, the name is derived from the file name as previously described.

javax.enterprise.deploy.spi.DeploymentManager.distribute(Target[], File, File)

For more information about JSR 88, see the JSR 88 page at http://jcp.org/en/jsr/detail?id=88.

Directory Structure

When you deploy an application, the application is expanded from the EAR file to an open directory structure. The directories holding the individual modules are named with <code>_jar</code>, <code>_war</code> and <code>_rar</code> suffixes. If you use the <code>asadmin</code> deploydir command to deploy a directory instead of an EAR file, your directory structure must follow this same convention. Module and application directory structures follow the structure outlined in the Java EE specification.

Assembling Modules and Applications

Assembling (or packaging) modules and applications in Application Server conforms to all of the customary Java-EE-defined specifications. The only difference is that when you assemble in Application Server, you include Application Server specific deployment descriptors that enhance the functionality of the Application Server.

For example, when you assemble an EJB JAR module, you annotate or create two deployment descriptor files with these names: ejb-jar.xml and sun-ejb-jar.xml. If the EJB component is an entity bean with container-managed persistence, you can also create a .dbschema file and a sun-cmp-mapping.xml file. For more information about sun-ejb-jar.xml and sun-cmp-mapping.xml, see Appendix A.

Note – According to the Java EE specification, section 8.1.1.2, "Dependencies," you cannot package utility classes within an individually deployed EJB module. Instead, package the EJB module and utility JAR within an application using the JAR Extension Mechanism Architecture. For other alternatives, see Chapter 2, "Class Loaders," in *Sun Java System Application Server Platform Edition 9 Developer's Guide*.

The Application Server provides these tools for assembling and verifying a module or an application:

- "The asant Utility" on page 24
- "The NetBeans IDE" on page 24
- "The verifier Utility" on page 24

The asant Utility

The asant utility can help you assemble and deploy modules and applications. For details, see Chapter 3, "The asant Utility," in *Sun Java System Application Server Platform Edition 9 Developer's Guide.*

The NetBeans IDE

You can use the NetBeans™ Integrated Development Environment (IDE) to assemble Java EE applications and modules. The Platform Edition of the Application Server is bundled with the NetBeans 5.5 IDE. For more information about using the NetBeans IDE, see http://www.netbeans.org.

The verifier Utility

The verifier utility validates Java EE annotations and deployment descriptors and Application Server specific deployment descriptors against their corresponding DTD schema files. It gives errors

and warnings if a module or application is not Java EE and Application Server compliant. You can verify deployment descriptors in EAR, WAR, RAR, and JAR files.

The verifier tool is not simply an XML syntax verifier. Rules and interdependencies between various elements in the deployment descriptors are verified. Where needed, user application classes are introspected to apply validation rules.

The verifier is integrated into Application Server deployment and the asant task "The sun-appserv-deploy Task" in *Sun Java System Application Server Platform Edition 9 Developer's Guide*. You can also run it as a stand-alone utility from the command line. The verifier utility is located in the *install-dir/*bin directory.

You can run the verifier during Application Server deployment using the Admin Console or the asadmin deploy command with the --verify="true" option (see "The asadmin Deployment Commands" on page 34 and "The Admin Console Deployment Pages" on page 35). In these cases, the output of the verifier is written to the *tempdir*/verifier-results/ directory, where *tempdir* is the temporary directory defined in the operating system. Deployment fails if any failures are reported during the verification process. The verifier also logs information about verification progress to the standard output.

For details on all the assertions tested by the verifier, see the assertions documentation provided at http://java.sun.com/j2ee/avk/index.html.

Tip – Using the verifier tool can help you avoid runtime errors that are difficult to debug.

This section covers the following topics:

- "Command-Line Syntax" on page 25
- "Ant Integration" on page 27
- "Sample Results Files" on page 27

Command-Line Syntax

The verifier tool's syntax is as follows:

verifier [options] file

The file can be an EAR, WAR, RAR, or JAR file.

The following table shows the *options* for the verifier tool.

TABLE 1-2 Verifier Options

Short Form	Long Form	Description
- V	verbose	Turns on verbose mode. In verbose mode, the status of each run of each test is displayed on the verifier console.
-d output-dir	destdir output-dir	Writes test results to the <i>output-dir</i> , which must already exist. By default, the results files are created in the current directory.
-D domain-dir	domain domain-dir	Specifies the absolute path to the domain directory. This option is ignored if the -p option is used. The default domain directory is <i>install-dir</i> /domains/domain1.
- rlevel	reportlevel level	Sets the output report level to one of the following values: a or all - Reports all results. worwarnings - Reports only warning and failure results. This is the default. for failures - Reports only failure results.
-t	timestamp	Appends a timestamp to the output file name. The format of the timestamp is yyyyMMddhhmmss.
-?	help	Displays help for the verifier command. If you use this option, you do not need to specify an EAR, WAR, RAR, or JAR file.
-V	version	Displays the verifier tool version. If you use this option, you do not need to specify an EAR, WAR, RAR, or JAR file.
- p	portability	Verifies portable features only. By default, the verifier also checks correct usage of Application Server features in the sun-*.xml deployment descriptor files.
-a	app	Runs only the application tests.
-A	appclient	Runs only the application client tests.
- C	connector	Runs only the connector tests.
-е	ejb	Runs only the EJB tests.
-W	web	Runs only the web module tests.
- S	webservices	Runs only the web service tests.
-1	webservicesclient	Runs only the web service client tests.

For example, the following command runs the verifier on the ejb. jar file with default settings:

verifier ejb.jar

The results files are ejb.jar.txt and ejb.jar.xml.

For a more complex example, the following command runs the verifier on the ejb. jar file in portability mode displaying only failures and with a timestamp:

```
verifier -p -rf -t ejb.jar
```

The results files are ejb.jartimestamp.txt and ejb.jartimestamp.xml. The format of the timestamp is yyyyMMddhhmmss.

If the verifier runs successfully and no verification errors occurred, a result code of 0 is returned. A nonzero error code is returned if errors occurred or the verifier fails to run.

Ant Integration

You can integrate the verifier into an Ant build file as a target and use the Ant call feature to call the target each time an application or module is assembled. You can use any of the arguments described in Table 1–2. Example code for an Ant verify target is as follows:

Sample Results Files

Here is a sample results XML file:

```
<static-verification>
<eib>
     <failed>
        <test>
             <test-name>
tests.ejb.session.TransactionTypeNullForContainerTX
            </test-name>
             <test-assertion>
Session bean with bean managed transaction demarcation test
            </test-assertion>
             <test-description>
For [ TheGreeter ] Error: Session Beans [ TheGreeter ] with
[ Bean ] managed transaction demarcation should not have
container transactions defined.
             </test-description>
         </test>
     </failed>
</eib>
</static-verification>
```

Chapter 1 • Assembling and Deploying Applications

```
Here is a sample results TXT file:
STATIC VERIFICATION RESULTS
-----
NUMBER OF FAILURES/WARNINGS/ERRORS
# of Failures : 1
# of Warnings : 0
# of Errors : 0
RESULTS FOR EJB-RELATED TESTS
-----
-----
FAILED TESTS :
Test Name: tests.ejb.ejb30.BusinessIntfInheritance
Test Assertion: A business interface must not extend javax.ejb.EJBObject
or javax.ejb.EJBLocalObject. Please refer to EJB 3.0 Simplified API Section
#3.2 for further information.
Test Description : For [ sessionApp#session-ejb.jar#HelloEJB ]
[ com.sun.sample.session.Hello ] extends either javax.ejb.EJBObject or
javax.ejb.EJBLocalObject.
END OF STATIC VERIFICATION RESULTS
_____
```

Deploying Modules and Applications

This section describes the different ways to deploy Java EE applications and modules to the Application Server. It covers the following topics:

- "Deployment Errors" on page 29
- "The Deployment Life Cycle" on page 29
- "Deployment for Development" on page 30
- "Tools for Deployment" on page 34
- "Deployment by Module or Application" on page 35
- "Deploying a Web Service" on page 36
- "Deploying a WAR Module" on page 36

- "Deploying an EJB JAR Module" on page 37
- "Deploying a Lifecycle Module" on page 37
- "Deploying an Application Client" on page 37
- "Deploying a J2EE CA Connector Module" on page 40
- "Access to Shared Frameworks" on page 40

Deployment Errors

If an error occurs during deployment, the application or module is not deployed. If a module within an application contains an error, the entire application is not deployed. This prevents a partial deployment that could leave the server in an inconsistent state.

The Deployment Life Cycle

After installing the Application Server and starting a domain, you can deploy (install) Java EE applications and modules. During deployment and as the application is changed, an application or module can go through the following stages:

1. Initial Deployment

Before deploying an application or module, start the domain.

Deploy (install) an application or module. Because applications and modules are packaged in archive files, specify the archive file name during deployment.

Deployment is *dynamic*: you don't need to restart the server instance after deploying application or module for applications to be available. If you do restart, all deployed applications and modules are still deployed and available.

2. Enabling or Disabling

By default, a deployed application or module is enabled, which means that it is runnable and can be accessed by clients. To prevent access, disable the application or module. A disabled application or module is not uninstalled from the domain and can be easily enabled after deployment. For more information, see "Disabling a Deployed Application or Module" on page 30.

3. Redeployment

To replace a deployed application or module, redeploy it. Redeploying automatically undeploys the previously deployed application or module and replaces it with the new one.

4. Undeployment

To uninstall an application or module, undeploy it.

Deployment for Development

This section covers the following topics related to deployment for development:

- "Dynamic Deployment" on page 30
- "Disabling a Deployed Application or Module" on page 30
- "Dynamic Reloading" on page 31
- "Automatic Deployment" on page 31
- "Directory Deployment" on page 32
- "Using a Deployment Plan" on page 33

Note – You can overwrite a previously deployed application by using the --force option of asadmin deploy or by checking the appropriate box in the Admin Console during deployment. However, you must remove a preconfigured resource before you can update it.

Dynamic Deployment

You can deploy, redeploy, and undeploy an application or module without restarting the server. This is called dynamic deployment. Although primarily for developers, dynamic deployment can be used in operational environments to bring new applications and modules online without requiring a server restart.

Whenever a redeployment is done, the sessions at that transit time become invalid. The client must restart the session.

Disabling a Deployed Application or Module

You can disable a deployed application or module without removing it from the server. Disabling an application makes it inaccessible to clients.

To disable an application or module using the asadmin disable command, see the Sun Java System Application Server Platform Edition 9 Reference Manual.

▼ To Disable an Application or Module in the Admin Console

- Open the Applications component.
- 2 Go to the page for the type of application or module.

For example, for a web application, go to the Web Applications page.

- 3 Click on the name of the application or module you wish to disable.
- 4 Uncheck the Status Enabled box.

See Also For details, click the Help button in the Admin Console.

Dynamic Reloading

If dynamic reloading is enabled (it is by default), you do not have to redeploy an application or module when you change its code or deployment descriptors. Simply copy the changed JSP or class files into the deployment directory for the application or module. The server checks for changes periodically and redeploys the application, automatically and dynamically, with the changes.

Dynamic reloading is useful in a development environment, because it allows code changes to be tested quickly. In a production environment, however, dynamic reloading might degrade performance. In addition, whenever a reload is done, the sessions at that transit time become invalid. The client must restart the session.

You can also use the sun-appserv-update task with the asant utility to update an application or module. See Chapter 3, "The asant Utility," in *Sun Java System Application Server Platform Edition 9 Developer's Guide*.

▼ To Enable Dynamic Reloading in the Admin Console

- 1 Select the Application Settings component under the relevant configuration.
- 2 Check the Reload Enabled box to enable dynamic reloading.
- 3 Enter a number of seconds in the Reload Poll Interval field.

This sets the interval at which applications and modules are checked for code changes and dynamically reloaded. The default is 2.

See Also For details, click the Help button in the Admin Console.

▼ To Reload Code or Deployment Descriptor Changes

1 Create an empty file named . reload at the root of the deployed application or module.

For an application:

domain-dir/applications/j2ee-apps/app-name/.reload

For an individually deployed module:

domain-dir/applications/j2ee-modules/module-name/.reload

Explicitly update the . reload file's timestamp (touch . reload in UNIX) each time you make changes.

Automatic Deployment

Automatic deployment, also called *autodeployment*, involves copying an application or module file (JAR, WAR, RAR, or EAR) into a special directory, where it is automatically deployed by the

Application Server. To undeploy an automatically deployed application or module, simply remove its file from the special autodeployment directory. This is useful in a development environment, because it allows new code to be tested quickly.

Autodeployment of a web services JSR 181 annotated file is supported. For more information, see JSR 181 (http://www.jcp.org/en/jsr/detail?id=181) and Chapter 6, "Developing Web Services," in Sun Java System Application Server Platform Edition 9 Developer's Guide.

Autodeployment is enabled by default.

To Enable and Configure or to Disable Autodeployment

- 1 Select the Application Settings component under the relevant configuration.
- 2 Check the Auto Deploy Enabled box to enable autodeployment, or uncheck this box to disable autodeployment.
- 3 Enter a number of seconds in the Auto Deploy Poll Interval field.

This sets the interval at which applications and modules are checked for code changes and dynamically reloaded. The default is 2.

4 You can change the Auto Deploy Directory.

You can enter an absolute or relative path. A relative path is relative to *domain-dir*. The default is *domain-dir*/autodeploy.

- 5 You can check the Verifier Enabled box to verify your deployment descriptor files. This is optional. For details about the verifier, see "The verifier Utility" on page 24.
- 6 Check the Precompile Enabled box to precompile any JSP files.

See Also For details, click the Help button in the Admin Console.

Directory Deployment

A directory containing an unpackaged application or module is sometimes called an exploded directory. To deploy a directory instead of an EAR, WAR, JAR, or RAR file, you can do one of the following:

- Use the Admin Console as described in "The Admin Console Deployment Pages" on page 35
 and enter a path to an exploded directory instead of a path to an archive file.
- Use the asadmin deploydir command. See the Sun Java System Application Server Platform Edition 9 Reference Manual.

The contents of the directory must match the contents of a corresponding Java EE archive file. For example, if you deploy a Web application from a directory, the contents of the directory must be the

same as a corresponding WAR file. In addition, the directories holding the individual modules must be named with _jar, _war and _rar suffixes. For information about the required directory contents, see the appropriate specifications.

You can change the deployment descriptor files directly in the exploded directory. If your environment is configured to use dynamic reloading, you can also dynamically reload applications deployed from the directory. For more information, see "Dynamic Reloading" on page 31.

Note – On Windows, if you are deploying a directory on a mapped drive, you must be running the Application Server as the same user to which the mapped drive is assigned, or the Application Server won't see the directory.

Using a Deployment Plan

This feature is for advanced developers.

A deployment plan is an JAR file that contains only the deployment descriptors that are specific to the Application Server. The deployment plan is part of the implementation of JSR 88. Use a deployment plan to deploy an application or module that does not contain the deployment descriptors that are specific to the Application Server. For more information about JSR 88, see the JSR 88 page at http://jcp.org/en/jsr/detail?id=88.

To deploy using a deployment plan, specify the --deploymentplan option of the asadmin deploy command. The following command, for example, deploys the enterprise application in the myrostapp.ear file according to the plan specified by the mydeployplan.jar file.

```
$ asadmin deploy --user admin --deploymentplan mydeployplan.jar myrostapp.ear
```

In the deployment plan file for an enterprise application (EAR), the sun-application.xml file is located at the root. The deployment descriptor for each module is stored according to this syntax: module-name.sun-dd-name, where the sun-dd-name depends on the module type. If a module contains a CMP mappings file, the file is named module-name.sun-cmp-mappings.xml. A .dbschema file is stored at the root level with each forward slash character (/) replaced by a pound sign (#). The following listing shows the structure of the deployment plan file for an enterprise application (EAR).

```
$ jar -tvf mydeployplan.jar
420 Thu Mar 13 15:37:48 PST 2003 sun-application.xml
370 Thu Mar 13 15:37:48 PST 2003 RosterClient.war.sun-web.xml
418 Thu Mar 13 15:37:48 PST 2003 roster-ac.jar.sun-application-client.xml
1281 Thu Mar 13 15:37:48 PST 2003 roster-ejb.jar.sun-ejb-jar.xml
2317 Thu Mar 13 15:37:48 PST 2003 team-ejb.jar.sun-ejb-jar.xml
3432 Thu Mar 13 15:37:48 PST 2003 team-ejb.jar.sun-cmp-mappings.xml
84805 Thu Mar 13 15:37:48 PST 2003 team-ejb.jar.RosterSchema.dbschema
```

In the deployment plan for a web application or a module file, the deployment descriptor that is specific to the Application Server is at the root level. If a stand-alone EJB module contains a CMP bean, the deployment plan includes the sun-cmp-mappings.xml and .dbschema files at the root level. In the following listing, the deployment plan describes a CMP bean.

```
$ jar r -tvf myotherplan.jar
3603 Thu Mar 13 15:24:20 PST 2003 sun-ejb-jar.xml
3432 Thu Mar 13 15:24:20 PST 2003 sun-cmp-mappings.xml
84805 Thu Mar 13 15:24:20 PST 2003 RosterSchema.dbschema
```

Tools for Deployment

This section discusses the various tools that can be used to deploy modules and applications. The deployment tools include:

- "The asant Utility" on page 34
- "JSR 88" on page 34
- "The asadmin Deployment Commands" on page 34
- "The Admin Console Deployment Pages" on page 35

The asant Utility

The asant utility can help you assemble and deploy modules and applications. For details, see Chapter 3, "The asant Utility," in *Sun Java System Application Server Platform Edition 9 Developer's Guide.*

JSR 88

You can write your own JSR 88 client to deploy applications to the Application Server. For more information, see the JSR 88 page at http://jcp.org/en/jsr/detail?id=88.

The syntax of the URI entry for the getDeploymentManager method is as follows:

```
deployer:Sun:AppServer::admin-host:admin-port
For example:
deployer:Sun:AppServer::localhost:4848
```

See "Naming Standards" on page 22 for application and module naming considerations.

The asadmin Deployment Commands

You can use the asadmin deploy or asadmin deploydir command to deploy or undeploy applications and individually deployed modules on local servers. For details, see "Directory Deployment" on page 32 and the Sun Java System Application Server Platform Edition 9 Reference Manual.

To deploy a lifecycle module, see "Deploying a Lifecycle Module" on page 37.

The Admin Console Deployment Pages

You can use the Admin Console to deploy modules and applications to both local and remote Application Server sites.

To Use the Admin Console for Deployment

- Open the Applications component.
- Go to the page for the type of application or module.

For example, for a web application, go to the Web Applications page.

Type the path to the WAR, JAR, EAR, or RAR file or the exploded directory structure.

For more information on deploying from an exploded directory structure, see "Directory Deployment" on page 32.

Click on the Deploy button.

You can undeploy, enable, or disable an application or module from this page. You can also change deployment settings that vary according to the type of application or module.

See Also For details, click the Help button in the Admin Console.

To deploy a lifecycle module, see "Deploying a Lifecycle Module" on page 37.

Deployment by Module or Application

You can deploy applications or individual modules that are independent of applications; see "About Modules" on page 18 and "About Applications" on page 19. Individual module-based deployment is preferable when components need to be accessed by:

- Other modules
- Java EE applications
- ACC clients (Module-based deployment allows shared access to a bean from an ACC client, a servlet, or an EJB component.)

Modules can be combined into an EAR file and then deployed as a single module. This is similar to deploying the modules of the EAR independently.

Deploying a Web Service

You deploy a web service endpoint to the Application Server just as you would any servlet or stateless session bean (SLSB). You can use the --registryjndiname option of the asadmin deploy command to publish the web service as part of deployment, but this is optional. See "Tools for Deployment" on page 34.

To deploy a JSR 181 annotated file, use the autodeployment feature. You can compile and deploy in one step, as in the following example:

javac -cp javaee.jar -d domain-dir/autodeploy MyWS.java

For more information about JSR 181, see http://jcp.org/en/jsr/detail?id=181. For more information about autodeployment, see "Automatic Deployment" on page 31.

The Sun-specific deployment descriptor files sun-web.xml and sun-ejb-jar.xml provide optional web service enhancements in their "webservice-endpoint" on page 163 and "webservice-description" on page 162 elements.

For more information about web services, see JSR 181 (http://www.jcp.orq/en/jsr/detail?id=181) and Chapter 6, "Developing Web Services," in Sun Java System Application Server Platform Edition 9 Developer's Guide.

Deploying a WAR Module

You deploy a WAR module as described in "Tools for Deployment" on page 34. If you do not specify a context root, the default is the name of the WAR file without the extension.

If a web application accesses a DataSource that is not specified in a resource-ref in sun-web.xml, or there is no sun-web.xml file, the resource-ref-name defined in web.xml is used. A warning message is logged recording the JNDI name used to look up the resource.

You can precompile JSP files during deployment by checking the appropriate box in the Admin Console, or by using the --precompile is poption of the asadmin deploy or asadmin deploydir command. The asant tasks sun-appserv-deploy and sun-appserv-jspc also allow you to precompile JSP files. For more information, see Chapter 3, "The asant Utility," in Sun Java System Application Server Platform Edition 9 Developer's Guide.

You can keep the generated source for JSP files by adding the -keepgenerated flag to the jsp-config element in sun-web.xml. If you include this property when you deploy the WAR module, the generated source is kept in domain-dir/generated/jsp/j2ee-apps/app-name/module-name, if it is in an application, or domain-dir/generated/jsp/j2ee-modules/module-name, if it is in an individually deployed web module.

For more information about JSP precompilation, see "jsp-config" on page 100 and "Options for Compiling JSP Files" in Sun Java System Application Server Platform Edition 9 Developer's Guide.

Deploying an EJB JAR Module

You deploy an EJB JAR module as described in "Tools for Deployment" on page 34.

If no JNDI name for the EJB JAR module is specified in the jndi-name element immediately under the ejb element in sun-ejb-jar.xml, or there is no sun-ejb-jar.xml file, a default, non-clashing JNDI name is derived. A warning message is logged recording the JNDI name used to look up the EJB JAR module.

You can keep the generated source for stubs and ties by adding the -keepgenerated flag to the rmic-options attribute of the java-config element in domain.xml. If you include this flag when you deploy the EJB JAR module, the generated source is kept in

domain-dir/generated/ejb/j2ee-apps/app-name/module-name, if it is in an application, or domain-dir/generated/ejb/j2ee-modules/module-name, if it is in an individually deployed EJB JAR module. For more information about the -keepgenerated flag, see the Sun Java System Application Server Platform Edition 9 Administration Reference.

Generation of stubs and ties is performed asynchronously, so unless you request their generation during deployment (for example, using the --retrieve option of the asadmin deploy command), stubs and ties are not guaranteed to be available immediately after deployment. You can use the asadmin get-client-stubs command to retrieve the stubs and ties whether or not you requested their generation during deployment. For details, see the Sun Java System Application Server Platform Edition 9 Reference Manual.

Deploying a Lifecycle Module

For general information about lifecycle modules, see Chapter 13, "Developing Lifecycle Listeners," in Sun Java System Application Server Platform Edition 9 Developer's Guide.

You can deploy a lifecycle module using the following tools:

- In the Admin Console, open the Applications component and go to the Lifecycle Modules page.
 For details, click the Help button in the Admin Console.
- Use the asadmin create-lifecycle-module command. For details, see the Sun Java System Application Server Platform Edition 9 Reference Manual.

Note – If the is-failure-fatal setting is set to true (the default is false), lifecycle module failure prevents server initialization or startup, but not shutdown or termination.

Deploying an Application Client

Deployment is only necessary for application clients that communicate with EJB components.

Java Web Start is supported for application clients and for applications that contain application clients. It is enabled by default both in application clients and in the Application Server.

If you are using Java Web Start, you should deploy the application or application client as an EAR or JAR file rather than using directory deployment. Java Web Start uses JAR files, which means that the Application Server must JAR application client files during deployment, resulting in slower performance.

This section contains the following topics:

- "To Deploy an Application Client" on page 38
- "To Prepare Another Machine for Executing an Application Client" on page 39
- "Undeployment of Application Clients" on page 40

To Deploy an Application Client

- 1 Assemble the necessary client files.
- 2 Assemble the EJB components to be accessed by the client.
- 3 Package the client and EJB components together in an application.
- 4 Deploy the application as described in "Tools for Deployment" on page 34.
- 5 If Java Web Start is *not* enabled for the application client, retrieve the client JAR file.

The client JAR file contains the ties and necessary classes for the ACC client.

You can use the --retrieve option to get the client JAR file.

You can also use the asadmin get-client-stubs command to retrieve the stubs and ties whether or not you requested their generation during deployment. For details, see the *Sun Java System Application Server Platform Edition 9 Reference Manual*.

6 If Java Web Start is *not* enabled for the application client, copy the client JAR file to the client machine, and set the APPCPATH environment variable on the client to point to this JAR.

Next Steps You can execute the client on the Application Server machine to test it in one of the following ways:

- If Java Web Start is enabled for the application client, use the Launch button on the App Client Modules page to launch the application client using Java Web Start.
- If Java Web Start is not enabled for the application client, use the appclient script in the install-dir/bin directory. The only required option is -client. For example:

```
appclient -client converterClient.jar
```

The -xml parameter specifies the location of the sun-acc.xml file.

See Also For more detailed information about Java Web Start, see Chapter 11, "Developing Java Clients," in *Sun Java System Application Server Platform Edition 9 Developer's Guide.*

For more detailed information about the appclient script, see the Sun Java System Application Server Platform Edition 9 Reference Manual.

▼ To Prepare Another Machine for Executing an Application Client

If Java Web Start is enabled, the default URL for an application is as follows:

http://host:port/context-root

The default URL for a stand-alone application client module is as follows:

http://host:port/module-id

If the *context-root* or *module-id* is not specified during deployment, the name of the EAR or JAR file without the extension is used. For an application, the relative path to the application client JAR file is also included. If the application or module is not in EAR or JAR file format, a *context-root* or *module-id* is generated.

Regardless of how the *context-root* or *module-id* is determined, it is written to the server log. For details about naming, see "Naming Standards" on page 22.

To set a different URL for an application client, use the context-root subelement of the "java-web-start-access" on page 98 element in the sun-application-client.xml file.

If Java Web Start is *not* enabled for the application client, follow these steps.

1 You can use the package-appolient script in the *install-dir/*bin directory to create the ACC package JAR file. This is optional.

This JAR file is created in the *install-dir*/lib/appclient directory.

- 2 Copy the ACC package JAR file to the client machine and unjar it.
- 3 Configure the sun-acc.xml file.

This file is located in the appclient/appserv/lib/appclient directory by default if you used the package-appclient script.

4 Configure the asenv.conf (asenv.bat on Windows) file.

This file is located in appclient/appserv/bin by default if you used the package-appclient script.

5 Copy the client JAR file to the client machine.

You are now ready to execute the client.

See Also For more detailed information about Java Web Start and the package-appclient script, see Chapter 11, "Developing Java Clients," in *Sun Java System Application Server Platform Edition 9 Developer's Guide.*

Undeployment of Application Clients

Once application clients are downloaded, they remain on the client until removed manually. The Java Web Start control panel provides a simple interface you can use to discard downloaded application clients that used Java Web Start. When you undeploy an application client, you can no longer use Java Web Start, or any other mechanism, to download the application client. If you try to launch an application client that was previously downloaded even though the server side of the application client is no longer present, the results depend on whether the application client has been written to tolerate such situations.

You can write your application client to detect failures in contacting server-side components and to continue running anyway. In this case, Java Web Start can run an undeployed application client as it is cached locally. For example, your application client can be written to catch and recover from a java.naming.NamingException in locating a resource or a java.rmi.RemoteException in referring to a previously-located resource that becomes inaccessible.

Deploying a J2EE CA Connector Module

You deploy a J2EE Connector Architecture (CA) connector module as described in "Tools for Deployment" on page 34. After deploying the module, you must configure it as described in Chapter 12, "Developing Connectors," in Sun Java System Application Server Platform Edition 9 Developer's Guide.

Access to Shared Frameworks

When Java EE applications and modules use shared framework classes (such as utility classes and libraries) the classes can be put in the path for the System Classloader, the Common Classloader, or an application-specific class loader rather than in an application or module. If you assemble a large, shared library into every module that uses it, the result is a huge file that takes too long to register with the server. In addition, several versions of the same class could exist in different classloaders, which is a waste of resources. For more information, see Chapter 2, "Class Loaders," in *Sun Java System Application Server Platform Edition 9 Developer's Guide*.

◆ ◆ ◆ A P P E N D I X A

Deployment Descriptor Files

This chapter describes deployment descriptor files specific to the Sun Java System Application Server in the following sections:

- "Application Server Descriptors" on page 22
- "The sun-application.xml File" on page 43
- "The sun-web.xml File" on page 43
- "The sun-ejb-jar.xml File" on page 46
- "The sun-cmp-mappings.xml File" on page 51
- "The sun-application-client.xml file" on page 55
- "The sun-acc.xml File" on page 57
- "Alphabetical Listing of All Elements" on page 57

Sun Java System Application Server Descriptors

Sun Java System Application Server uses deployment descriptors in addition to the Java EE standard descriptors for configuring features specific to the Application Server. The sun-application.xml, sun-web.xml, sun-ejb-jar.xml, and sun-cmp-mappings.xml files are optional; all the others are required.

Note – Settings in the Application Server deployment descriptors override corresponding settings in the Java EE deployment descriptors and in the Application Server's domain.xml file unless otherwise stated. For more information about the domain.xml file, see the *Sun Java System Application Server Platform Edition 9 Administration Reference*.

Each deployment descriptor (or XML) file has a corresponding DTD file, which defines the elements, data, and attributes that the deployment descriptor file can contain. For example, the sun-application_5_0-0.dtd file defines the structure of the sun-application.xml file. The DTD files for the Application Server deployment descriptors are located in the <code>install-dir/lib/dtds</code> directory.

Note – Do not edit the DTD files; their contents change only with new versions of the Application Server.

To check the correctness of these deployment descriptors prior to deployment, see "The verifier Utility" on page 24.

For general information about DTD files and XML, see the XML specification at http://www.w3.org/TR/REC-xml.

The following table lists the Application Server deployment descriptors and their DTD files.

TABLE A-1 Sun Java System Application Server Descriptors

Deployment Descriptor	DTD File	Description
sun-application.xml	sun-application_5_0-0.dtd	Configures an entire Java EE application (EAR file).
sun-web.xml	sun-web-app_2_5-0.dtd	Configures a web application (WAR file).
sun-ejb-jar.xml	sun-ejb-jar_3_0-0.dtd	Configures an enterprise bean (EJB JAR file).
sun-cmp-mappings.xml	sun-cmp-mapping_1_2.dtd	Configures container-managed persistence for an enterprise bean.
sun-application-client.xml	sun-application-client_5_0-0.dtd	Configures an Application Client Container (ACC) client (JAR file).
sun-acc.xml	sun-application-client-container_1_2.dtd	Configures the Application Client Container.

Note – The Application Server deployment descriptors must be readable and writable by the file owners.

In each deployment descriptor file, subelements must be defined in the order in which they are listed under each **Subelements** heading, unless otherwise noted.

The sun-application.xml File

The element hierarchy in the sun-application.xml file is as follows:

```
sun-application
. web
. . web-uri
. . context-root
. pass-by-reference
. unique-id
. security-role-mapping
. role-name
. principal-name
. group-name
. realm
```

Here is a sample sun-application.xml file:

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE sun-application PUBLIC '-//Sun Microsystems, Inc.//DTD
Application Server 9.0 Java EE Application 5.0//EN'
'http://www.sun.com/software/appserver/dtds/sun-application_5_0-0.dtd'>
<sun-application>
    <unique-id>67488732739338240</unique-id>
</sun-application>
```

The sun-web.xml File

The element hierarchy in the sun-web.xml file is as follows:

```
sun-web-app
. context-root
  security-role-mapping
  . role-name
     principal-name
     group-name
  servlet
     servlet-name
     principal-name
     webservice-endpoint
        port-component-name
        endpoint-address-uri
        login-config
     . . auth-method
     . message-security-binding
        . message-security
```

```
message
             . java-method
                . method-name
                   method-params
                   . method-param
             . operation-name
        . . request-protection
        . . response-protection
  . . transport-quarantee
        service-gname
 . . tie-class
  . . servlet-impl-class
. . debugging-enabled
        property (with attributes)
. . . description
. idempotent-url-pattern
. session-config
     session-manager
        manager-properties
     . . property (with attributes)
     . . . description
  . . store-properties
     . . property (with attributes)
  . . . description
     session-properties
        property (with attributes)
     . . description
. . cookie-properties
  . . property (with attributes)
. . . description
  ejb-ref

    ejb-ref-name

     indi-name
  resource-ref
  . res-ref-name
  . jndi-name
 . default-resource-principal
     . name
 . . password
 resource-env-ref
  . resource-env-ref-name
     jndi-name
  service-ref
     service-ref-name
     port-info
  . . service-endpoint-interface
. . . wsdl-port
. . . namespaceURI
```

```
localpart
      stub-property
         name
        value
      call-property
         name
         value
      message-security-binding
         message-security
            message
               java-method
                  method-name
                  method-params
                     method-param
            . operation-name
            request-protection
            response-protection
   call-property
     name
  . value
  wsdl-override
   service-impl-class
   service-qname
     namespaceURI
     localpart
message-destination-ref
   message-destination-ref-name
   indi-name
cache
   cache-helper
     property (with attributes)
      . description
   default-helper
     property (with attributes)
     . description
   property (with attributes)
     description
   cache-mapping
      servlet-name
     url-pattern
      cache-helper-ref
     dispatcher
     timeout
      refresh-field
     http-method
     key-field
      constraint-field
      . constraint-field-value
```

```
. class-loader
  . property (with attributes)
 . . description
 jsp-config
 locale-charset-info
  . locale-charset-map
     parameter-encoding
  property (with attributes)
  . description
 parameter-encoding
  message-destination
  . message-destination-name
 . jndi-name
. webservice-description
 . webservice-description-name
     wsdl-publish-location
Here is a sample sun-web.xml file:
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE sun-web-app PUBLIC '-//Sun Microsystems, Inc.//DTD
Application Server 9.0 Servlet 2.5//EN'
'http://www.sun.com/software/appserver/dtds/sun-web-app 2 5-0.dtd'>
<sun-web-app>
  <session-config>
     <session-manager/>
  </session-config>
  <resource-ref>
     <res-ref-name>mail/Session</res-ref-name>
     <jndi-name>mail/Session</jndi-name>
  </resource-ref>
  <jsp-config/>
</sun-web-app>
```

The sun-ejb-jar.xml File

The element hierarchy in the sun-ejb-jar.xml file is as follows:

```
sun-ejb-jar
. security-role-mapping
. . role-name
. . principal-name
. . group-name
. enterprise-beans
. . name
. . unique-id
. . ejb
```

```
ejb-name
jndi-name
ejb-ref
   ejb-ref-name
   jndi-name
resource-ref
   res-ref-name
   jndi-name
   default-resource-principal
      name
      password
resource-env-ref
   resource-env-ref-name
   jndi-name
service-ref
   service-ref-name
   port-info
      service-endpoint-interface
      wsdl-port
         namespaceURI
         localpart
      stub-property
         name
         value
      call-property
         name
         value
      message-security-binding
         message-security
            message
               java-method
                  method-name
                  method-params
              . . method-param
               operation-name
        . request-protection
         . response-protection
   call-property
      name
      value
   wsdl-override
   service-impl-class
   service-gname
      namespaceURI
   . localpart
message-destination-ref
   message-destination-ref-name
   jndi-name
```

```
pass-by-reference
   cmp
      mapping-properties
     is-one-one-cmp
      one-one-finders
        finder
            method-name
            query-params
            query-filter
            query-variables
            query-ordering
      prefetch-disabled
         query-method
            method-name
            method-params
               method-param
   principal
      name
   mdb-connection-factory
      indi-name
      default-resource-principal
        name
  . . password
   jms-durable-subscription-name
   jms-max-messages-load
   ior-security-config
      transport-config
     . integrity
         confidentiality
        establish-trust-in-target
        establish-trust-in-client
      as-context
        auth-method
     . realm
     . required
  . sas-context
  . . caller-propagation
   is-read-only-bean
   refresh-period-in-seconds
   commit-option
   cmt-timeout-in-seconds
   use-thread-pool-id
   gen-classes
     remote-impl
     local-impl
     remote-home-impl
. . local-home-impl
   bean-pool
```

```
steady-pool-size
   resize-quantity
   max-pool-size
   pool-idle-timeout-in-seconds
   max-wait-time-in-millis
bean-cache
   max-cache-size
   resize-quantity
   is-cache-overflow-allowed
   cache-idle-timeout-in-seconds
   removal-timeout-in-seconds
   victim-selection-policy
mdb-resource-adapter
   resource-adapter-mid
   activation-config
   . description
  . activation-config-property
   . . activation-config-property-name
  . . activation-config-property-value
webservice-endpoint
   port-component-name
   endpoint-address-uri
   login-config
   . auth-method
   message-security-binding
      message-security
         message
            java-method
               method-name
               method-params
                  method-param
            operation-name
         request-protection
         response-protection
   transport-quarantee
. service-qname
. tie-class
   servlet-impl-class
   debugging-enabled
   property (with subelements)
      name
      value
flush-at-end-of-method
   method
   . description
   . eib-name
. . method-name
      method-intf
```

```
. . method-params
        . . method-param
     checkpointed-methods
     checkpoint-at-end-of-method
        method
           description
           ejb-name
           method-name
           method-intf
  . . method-params
        . . method-param
  pm-descriptors
  cmp-resource
     indi-name
     default-resource-principal
     . name
        password
     property (with subelements)
        name
        value
     create-tables-at-deploy
     drop-tables-at-undeploy
     database-vendor-name
     schema-generator-properties
     . property (with subelements)
     . . name
          value
  message-destination
  . message-destination-name
  . jndi-name
. webservice-description
     webservice-description-name
     wsdl-publish-location
```

Note – If any configuration information for an enterprise bean is not specified in the sun-ejb-jar.xml file, it defaults to a corresponding setting in the EJB container if an equivalency exists.

Here is a sample sun-ejb-jar.xml file:

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE sun-ejb-jar PUBLIC '-//Sun Microsystems, Inc.//DTD
Application Server 9.0 EJB 3.0//EN'
'http://www.sun.com/software/appserver/dtds/sun-ejb-jar_3_0-0.dtd'>
<sun-ejb-jar>
<display-name>First Module</display-name>
<enterprise-beans>
```

```
<ejb>
        <ejb-name>CustomerEJB</ejb-name>
        <jndi-name>customer</jndi-name>
        <bean-pool>
            <steady-pool-size>10</steady-pool-size>
            <resize-quantity>10</resize-quantity>
            <max-pool-size>100</max-pool-size>
            <pool-idle-timeout-in-seconds>600</pool-idle-timeout-in-seconds>
        </bean-pool>
        <bean-cache>
            <max-cache-size>100</max-cache-size>
            <resize-quantity>10</resize-quantity>
            <removal-timeout-in-seconds>3600</removal-timeout-in-seconds>
            <victim-selection-policy>LRU</victim-selection-policy>
        </bean-cache>
    </ejb>
    <cmp-resource>
        <jndi-name>jdbc/ default</jndi-name>
        <create-tables-at-deploy>true</create-tables-at-deploy>
        <drop-tables-at-undeploy>true</drop-tables-at-undeploy>
    </cmp-resource>
</enterprise-beans>
</sun-ejb-jar>
```

The sun-cmp-mappings.xml File

The element hierarchy in the sun-cmp-mappings.xml file is as follows:

```
sun-cmp-mappings
   sun-cmp-mapping
      schema
      entity-mapping
        ejb-name
         table-name
         cmp-field-mapping
            field-name
            column-name
            read-only
            fetched-with
               default
               level
               named-group
               none
        cmr-field-mapping
            cmr-field-name
            column-pair
               column-name
```

```
fetched-with
           . default
              level
           . named-group
     . . none
        secondary-table
         . table-name
         . column-pair
     . . . column-name
        consistency
           none
        . check-modified-at-commit
     . . lock-when-loaded
           check-all-at-commit
     . . lock-when-modified
        . check-version-of-accessed-instances
     . . . column-name
Here is a sample database schema definition:
create table TEAMEJB (
  TEAMID varchar2(256) not null,
  NAME varchar2(120) null,
  CITY char(30) not null,
  LEAGUEEJB LEAGUEID varchar2(256) null,
  constraint PK_TEAMEJB primary key (TEAMID)
create table PLAYEREJB (
  POSITION varchar2(15) null,
  PLAYERID varchar2(256) not null,
  NAME char(64) null,
  SALARY number(10, 2) not null,
  constraint PK PLAYEREJB primary key (PLAYERID)
)
create table LEAGUEEJB (
  LEAGUEID varchar2(256) not null,
  NAME varchar2(256) null,
  SPORT varchar2(256) null,
  constraint PK LEAGUEEJB primary key (LEAGUEID)
)
create table PLAYEREJBTEAMEJB (
  PLAYEREJB PLAYERID varchar2(256) null,
  TEAMEJB TEAMID varchar2(256) null
alter table TEAMEJB
  add constraint FK LEAGUE foreign key (LEAGUEEJB LEAGUEID)
  references LEAGUEEJB (LEAGUEID)
```

```
alter table PLAYEREJBTEAMEJB
  add constraint FK TEAMS foreign key (PLAYEREJB PLAYERID)
  references PLAYEREJB (PLAYERID)
alter table PLAYEREJBTEAMEJB
  add constraint FK PLAYERS foreign key (TEAMEJB TEAMID)
  references TEAMEJB (TEAMID)
Here is a corresponding sample sun-cmp-mappings.xml file:
<?xml version="1.0" encoding="UTF-8"?>
<sun-cmp-mappings>
<sun-cmp-mapping>
    <schema>Roster</schema>
    <entity-mapping>
        <ejb-name>TeamEJB</ejb-name>
        <table-name>TEAMEJB</table-name>
        <cmp-field-mapping>
            <field-name>teamId</field-name>
            <column-name>TEAMEJB.TEAMID</column-name>
        </cmp-field-mapping>
        <cmp-field-mapping>
            <field-name>name</field-name>
            <column-name>TEAMEJB.NAME</column-name>
        </cmp-field-mapping>
        <cmp-field-mapping>
            <field-name>city</field-name>
            <column-name>TEAMEJB.CITY</column-name>
        </cmp-field-mapping>
        <cmr-field-mapping>
            <cmr-field-name>league</cmr-field-name>
            <column-pair>
                <column-name>TEAMEJB.LEAGUEEJB LEAGUEID</column-name>
                <column-name>LEAGUEEJB.LEAGUEID</column-name>
            </column-pair>
            <fetched-with>
                <none/>
            </fetched-with>
        </cmr-field-mapping>
        <cmr-field-mapping>
            <cmr-field-name>players
            <column-pair>
                <column-name>TEAMEJB.TEAMID</column-name>
                <column-name>PLAYEREJBTEAMEJB.TEAMEJB TEAMID</column-name>
            </column-pair>
            <column-pair>
               <column-name>PLAYEREJBTEAMEJB.PLAYEREJB PLAYERID</column-name>
                <column-name>PLAYEREJB.PLAYERID</column-name>
```

```
</column-pair>
        <fetched-with>
            <none/>
        </fetched-with>
    </cmr-field-mapping>
</entity-mapping>
<entity-mapping>
    <ejb-name>PlayerEJB</ejb-name>
    <table-name>PLAYEREJB</table-name>
    <cmp-field-mapping>
        <field-name>position</field-name>
        <column-name>PLAYEREJB.POSITION</column-name>
    </cmp-field-mapping>
    <cmp-field-mapping>
        <field-name>playerId</field-name>
        <column-name>PLAYEREJB.PLAYERID</column-name>
    </cmp-field-mapping>
    <cmp-field-mapping>
        <field-name>name</field-name>
        <column-name>PLAYEREJB.NAME</column-name>
    </cmp-field-mapping>
    <cmp-field-mapping>
        <field-name>salary</field-name>
        <column-name>PLAYEREJB.SALARY</column-name>
    </cmp-field-mapping>
    <cmr-field-mapping>
        <cmr-field-name>teams/cmr-field-name>
        <column-pair>
            <column-name>PLAYEREJB.PLAYERID</column-name>
            <column-name>PLAYEREJBTEAMEJB.PLAYEREJB PLAYERID</column-name>
        </column-pair>
        <column-pair>
            <column-name>PLAYEREJBTEAMEJB.TEAMEJB TEAMID</column-name>
            <column-name>TEAMEJB.TEAMID</column-name>
        </column-pair>
        <fetched-with>
            <none/>
        </fetched-with>
    </cmr-field-mapping>
</entity-mapping>
<entity-mapping>
    <ejb-name>LeagueEJB</ejb-name>
    <table-name>LEAGUEEJB</table-name>
    <cmp-field-mapping>
        <field-name>leagueId</field-name>
        <column-name>LEAGUEEJB.LEAGUEID</column-name>
    </cmp-field-mapping>
    <cmp-field-mapping>
```

```
<field-name>name</field-name>
            <column-name>LEAGUEEJB.NAME</column-name>
        </cmp-field-mapping>
        <cmp-field-mapping>
            <field-name>sport</field-name>
            <column-name>LEAGUEEJB.SPORT</column-name>
        </cmp-field-mapping>
        <cmr-field-mapping>
            <cmr-field-name>teams/cmr-field-name>
            <column-pair>
                <column-name>LEAGUEEJB.LEAGUEID</column-name>
                <column-name>TEAMEJB.LEAGUEEJB LEAGUEID</column-name>
            </column-pair>
            <fetched-with>
                <none/>
            </fetched-with>
        </cmr-field-mapping>
    </entity-mapping>
</sun-cmp-mapping>
</sun-cmp-mappings>
```

The sun-application-client.xml file

The element hierarchy in the sun-application-client.xml file is as follows:

```
sun-application-client
. ejb-ref
   . ejb-ref-name
      jndi-name
   resource-ref
     res-ref-name
      jndi-name
      default-resource-principal
        name
        password
   resource-env-ref
     resource-env-ref-name
     indi-name
   service-ref
      service-ref-name
      port-info
         service-endpoint-interface
        wsdl-port
           namespaceURI
           localpart
  . . stub-property
```

```
value
        call-property
           name
           value
        message-security-binding
           message-security
              message
                 java-method
                . method-name
                    method-params
           . . . method-param
           . . operation-name
     . . . request-protection
          . response-protection
     call-property
  . . name
     . value
   . wsdl-override
     service-impl-class
     service-qname
  . . namespaceURI
 . . localpart
  message-destination
  . message-destination-name
     jndi-name
  message-destination-ref
     message-destination-ref-name
  . indi-name
  java-web-start-access
     context-root
  . eligible
Here is a sample sun-application-client.xml file:
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE sun-application-client PUBLIC "-//Sun Microsystems, Inc.//DTD
Application Server 9.0 Application Client 5.0//EN"
"http://www.sun.com/software/appserver/dtds/sun-application-client_5_0-0.dtd">
<sun-application-client>
 <message-destination-ref>
   <message-destination-ref-name>ClientQueue</message-destination-ref-name>
   <jndi-name>jms/security mdb OutQueue</jndi-name>
 </message-destination-ref>
</sun-application-client>
```

The sun-acc.xml File

The element hierarchy in the sun-acc.xml file is as follows:

```
client-container
  target-server
  . description
     security
     . ssl
    . cert-db
  auth-realm
     property (with attributes)
  client-credential
     property (with attributes)
  log-service
     property (with attributes)
  message-security-config
     provider-config
         request-policy
     . response-policy
        property (with attributes)
  property (with attributes)
```

Alphabetical Listing of All Elements

```
"A" on page 57 "B" on page 61 "C" on page 62 "D" on page 81 "E" on page 84 "F" on page 92 "G" on page 94 "H" on page 95 "I" on page 96 "J" on page 98 "K" on page 103 "L" on page 104 "M" on page 109 "N" on page 119 "O" on page 120 "P" on page 121 "Q" on page 129 "R" on page 130 "S" on page 139 "T" on page 156 "U" on page 159 "V" on page 160 "W" on page 162
```

A

activation-config

Specifies an activation configuration, which includes the runtime configuration properties of the message-driven bean in its operational environment. For example, this can include information about the name of a physical JMS destination. Matches and overrides the activation-config element in the ejb-jar.xml file.

Superelements

```
"mdb-resource-adapter" on page 112 (sun-ejb-jar.xml)
```

Subelements

The following table describes subelements for the activation-config element.

TABLE A-2 activation - config subelements

Element	Required	Description
"description" on page 83	zero or one	Specifies a text description of the activation configuration.
"activation-config-property" on page 58	one or more	Specifies an activation configuration property.

activation-config-property

Specifies the name and value of an activation configuration property.

Superelements

"activation-config" on page 57 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the activation-config-property element.

TABLE A-3 activation-config-property subelements

Element	Required	Description
"activation-config-property-name" on page 58	only one	Specifies the name of an activation configuration property.
"activation-config-property-value" on page 58	only one	Specifies the value of an activation configuration property.

activation-config-property-name

Specifies the name of an activation configuration property.

Superelements

"activation-config-property" on page 58 (sun-ejb-jar.xml)

Subelements

none - contains data

activation-config-property-value

Specifies the value of an activation configuration property.

Superelements

"activation-config-property" on page 58 (sun-ejb-jar.xml)

Subelements

none - contains data

as-context

Specifies the authentication mechanism used to authenticate the client.

Superelements

"ior-security-config" on page 96 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the as-context element.

TABLE A-4 as - context Subelements

Element	Required	Description
"auth-method" on page 59	only one	Specifies the authentication method. The only supported value is USERNAME_PASSWORD.
"realm" on page 130	only one	Specifies the realm in which the user is authenticated.
"required" on page 134	only one	Specifies whether the authentication method specified must be used for client authentication.

auth-method

Specifies the authentication method.

If the parent element is "as-context" on page 59, the only supported value is USERNAME_PASSWORD.

If the parent element is "login-config" on page 108, specifies the authentication mechanism for the web service endpoint. As a prerequisite to gaining access to any web resources protected by an authorization constraint, a user must be authenticated using the configured mechanism.

Superelements

"login-config" on page 108 (sun-web.xml), "as-context" on page 59 (sun-ejb-jar.xml)

Subelements

none - contains data

auth-realm

JAAS is available on the ACC. Defines the optional configuration for a JAAS authentication realm. Authentication realms require provider-specific properties, which vary depending on what a particular implementation needs. For more information about how to define realms, see "Realm Configuration" in Sun Java System Application Server Platform Edition 9 Developer's Guide.

Superelements

"client-container" on page 70 (sun-acc.xml)

Subelements

The following table describes subelements for the auth-realm element.

TABLE A-5 auth-realm subelement

Element	Required	Description
"property (with attributes)" on page 126	zero or more	Specifies a property, which has a name and a value.

Attributes

The following table describes attributes for the auth-realm element.

TABLE A-6 auth-realmattributes

Attribute	Default	Description	
name	none	Defines the name of this realm.	
classname	none	Defines the Java class which implements this realm.	

Example

Here is an example of the default file realm:

Which properties an auth-realm element uses depends on the value of the auth-realm element's name attribute. The file realm uses file and jaas-context properties. Other realms use different properties. See "Realm Configuration" in Sun Java System Application Server Platform Edition 9 Developer's Guide.

B

bean-cache

Specifies the entity bean cache properties. Used for entity beans and stateful session beans.

Superelements

```
"ejb" on page 84 (sun-ejb-jar.xml)
```

Subelements

The following table describes subelements for the bean-cache element.

TABLE A-7 bean - cache Subelements

Element	Required	Description
"max-cache-size" on page 110	zero or one	Specifies the maximum number of beans allowable in cache.
"is-cache-overflow-allowed" on page 97	zero or one	Deprecated.
"cache-idle-timeout-in-seconds" on page 65	zero or one	Specifies the maximum time that a stateful session bean or entity bean is allowed to be idle in cache before being passivated. Default value is 10 minutes (600 seconds).
"removal-timeout-in-seconds" on page 132	zero or one	Specifies the amount of time a bean remains before being removed. If removal-timeout-in-seconds is less than idle-timeout, the bean is removed without being passivated.
"resize-quantity" on page 135	zero or one	Specifies the number of beans to be created if the pool is empty (subject to the max-pool-size limit). Values are from 0 to MAX_INTEGER.
"victim-selection-policy" on page 161	zero or one	Specifies the algorithm that must be used by the container to pick victims. Applies only to stateful session beans.

Example

```
<bean-cache>
  <max-cache-size>100</max-cache-size>
  <cache-resize-quantity>10</cache-resize-quantity>
  <removal-timeout-in-seconds>3600</removal-timeout-in-seconds>
  <victim-selection-policy>LRU</victim-selection-policy>
        <cache-idle-timeout-in-seconds>600</cache-idle-timeout-in-seconds>
        <removal-timeout-in-seconds>5400</removal-timeout-in-seconds>
  </bean-cache>
```

bean-pool

Specifies the pool properties of stateless session beans, entity beans, and message-driven bean.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the bean-pool element.

TABLE A-8 bean-pool Subelements

Element	Required	Description
"steady-pool-size" on page 149	zero or one	Specifies the initial and minimum number of beans maintained in the pool. Default is 32.
"resize-quantity" on page 135	zero or one	Specifies the number of beans to be created if the pool is empty (subject to the max-pool-size limit). Values are from 0 to MAX_INTEGER.
"max-pool-size" on page 111	zero or one	Specifies the maximum number of beans in the pool. Values are from 0 to MAX_INTEGER. Default is to the EJB container value or 60.
"max-wait-time-in-millis" on page	zero or one	Deprecated.
"pool-idle-timeout-in-seconds" on page 123	zero or one	Specifies the maximum time that a bean is allowed to be idle in the pool. After this time, the bean is removed. This is a hint to the server. Default time is 600 seconds (10 minutes).

Example

```
<bean-pool>
    <steady-pool-size>10</steady-pool-size>
    <resize-quantity>10</resize-quantity>
    <max-pool-size>100</max-pool-size>
    <pool-idle-timeout-in-seconds>600</pool-idle-timeout-in-seconds>
</bean-pool>
```

C

cache

Configures caching for web application components.

Superelements

"sun-web-app" on page 154 (sun-web.xml)

Subelements

The following table describes subelements for the cache element.

TABLE A-9 cache Subelements

Element	Required	Description
"cache-helper" on page 64	zero or more	Specifies a custom class that implements the CacheHelper interface.
"default-helper" on page 82	zero or one	Allows you to change the properties of the default, built-in "cache-helper" on page 64 class.
"property (with attributes)" on page 126	zero or more	Specifies a cache property, which has a name and a value.
"cache-mapping" on page 66	zero or more	Maps a URL pattern or a servlet name to its cacheability constraints.

Attributes

The following table describes attributes for the cache element.

TABLE A-10 cache Attributes

Attribute	Default	Description
max-entries	4096	(optional) Specifies the maximum number of entries the cache can contain. Must be a positive integer.
timeout-in-seconds	30	(optional) Specifies the maximum amount of time in seconds that an entry can remain in the cache after it is created or refreshed. Can be overridden by a "timeout" on page 158 element.
enabled	true	(optional) Determines whether servlet and JSP caching is enabled.

Properties

The following table describes properties for the cache element.

TABLE A-11 cache Properties

Property	Default	Description
cacheClassName	com.sun.appserv.web. cache.LruCache	Specifies the fully qualified name of the class that implements the cache functionality. See "Cache Class Names" on page 64 for possible values.

TABLE A-11 cache Properties	(Continued)		
Property	Default	Description	
MultiLRUSegmentSize	4096	Specifies the number of entries in a segment of the cache table that should have its own LRU (least recently used) list. Applicable only if cacheClassName is set to com.sun.appserv.web.cache. MultiLruCache.	
MaxSize	unlimited; Long . MAX_VALUE	Specifies an upper bound on the cache memory size in bytes (KB or MB units). Example values are 32 KB or 2 MB. Applicable only if cacheClassName is set to com.sun.appserv.web.cache. BoundedMultiLruCache.	

Cache Class Names

The following table lists possible values of the cacheClassName property.

TABLE A-12 cacheClassName Values

Value	Description
com.sun.appserv.web.cache.LruCache	A bounded cache with an LRU (least recently used) cache replacement policy.
com.sun.appserv.web.cache. BaseCache	An unbounded cache suitable if the maximum number of entries is known.
com.sun.appserv.web.cache. MultiLruCache	A cache suitable for a large number of entries (>4096). Uses the MultiLRUSegmentSize property.
com.sun.appserv.web.cache. BoundedMultiLruCache	A cache suitable for limiting the cache size by memory rather than number of entries. Uses the MaxSize property.

cache-helper

Specifies a class that implements the com.sun.appserv.web.cache.CacheHelper interface.

Superelements

"cache" on page 62 (sun-web.xml)

Subelements

The following table describes subelements for the cache-helper element.

TABLE A-13 cache-helper Subelements

Element	Required	Description
"property (with attributes)" on page 126	zero or more	Specifies a property, which has a name and a value.

Attributes

The following table describes attributes for the cache-helper element.

TABLE A-14 cache-helper Attributes

Attribute	Default	Description
name	default	Specifies a unique name for the helper class, which is referenced in the "cache-mapping" on page 66 element.
class-name	none	Specifies the fully qualified class name of the cache helper, which must implement the com.sun.appserv.web.CacheHelper interface.

cache-helper-ref

Specifies the name of the "cache-helper" on page 64 used by the parent "cache-mapping" on page 66 element.

Superelements

"cache-mapping" on page 66 (sun-web.xml)

Subelements

none - contains data

cache-idle-timeout-in-seconds

Specifies the maximum time that a bean can remain idle in the cache. After this amount of time, the container can passivate this bean. A value of 0 specifies that beans never become candidates for passivation. Default is 600.

Applies to stateful session beans and entity beans.

Superelements

"bean-cache" on page 61 (sun-ejb-jar.xml)

Subelements

none - contains data

cache-mapping

Maps a URL pattern or a servlet name to its cacheability constraints.

Superelements

"cache" on page 62 (sun-web.xml)

Subelements

The following table describes subelements for the cache-mapping element.

TABLE A-15 cache-mapping Subelements

Element	Required	Description
"servlet-name" on page 146	requires one servlet-name or url-pattern	Contains the name of a servlet.
"url-pattern" on page 160	requires one servlet-name or url-pattern	Contains a servlet URL pattern for which caching is enabled.
"cache-helper-ref" on page 65	required if dispatcher, timeout, refresh-field, http-method, key-field, and constraint-field are not used	Contains the name of the "cache-helper" on page 64 used by the parent cache-mapping element.
"dispatcher" on page	zero or one if cache-helper-ref is not used	Contains a comma-separated list of RequestDispatcher methods for which caching is enabled.
"timeout" on page 158	zero or one if cache-helper-ref is not used	Contains the "cache-mapping" on page 66 specific maximum amount of time in seconds that an entry can remain in the cache after it is created or refreshed.
"refresh-field" on page 131	zero or one if cache-helper-ref is not used	Specifies a field that gives the application component a programmatic way to refresh a cached entry.
"http-method" on page 95	zero or more if cache-helper-ref is not used	Contains an HTTP method that is eligible for caching.
"key-field" on page 103	zero or more if cache-helper-ref is not used	Specifies a component of the key used to look up and extract cache entries.
"constraint-field" on page 77	zero or more if cache-helper-ref is not used	Specifies a cacheability constraint for the given url-pattern or servlet-name.

call-property

Specifies JAX-RPC property values that can be set on a javax.xml.rpc.Call object before it is returned to the web service client. The property names can be any properties supported by the JAX-RPC Call implementation.

Superelements

"port-info" on page 123, "service-ref" on page 144 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

The following table describes subelements for the call-property element.

TABLE A-16 call-property subelements

Element	Required	Description
"name" on page 119	only one	Specifies the name of the entity.
"value" on page 160	only one	Specifies the value of the entity.

caller-propagation

Specifies whether the target accepts propagated caller identities. The values are NONE, SUPPORTED, or REQUIRED.

Superelements

"sas-context" on page 139 (sun-ejb-jar.xml)

Subelements

none - contains data

cert-db

Not implemented. Included for backward compatibility only. Attribute values are ignored.

Superelements

"security" on page 142 (sun-acc.xml)

Subelements

none

Attributes

The following table describes attributes for the cert-db element.

Appendix A • Deployment Descriptor Files

TABLE A-17 cert-db attributes

Attribute	Default	Description	
path	none	Specifies the absolute path of the certificate database.	
password	none	Specifies the password to access the certificate database.	

check-all-at-commit

This element is not implemented. Do not use.

Superelements

"consistency" on page 77 (sun-cmp-mappings.xml)

check-modified-at-commit

Checks concurrent modification of fields in modified beans at commit time.

Superelements

"consistency" on page 77 (sun-cmp-mappings.xml)

Subelements

none - element is present or absent

check-version-of-accessed-instances

Checks the version column of the modified beans.

Version consistency allows the bean state to be cached between transactions instead of read from a database. The bean state is verified by primary key and version column values. This occurs during a custom query (for dirty instances only) or commit (for both clean and dirty instances).

The version column must be a numeric type, and must be in the primary table. You must provide appropriate update triggers for this column.

Superelements

"consistency" on page 77 (sun-cmp-mappings.xml)

Subelements

The following table describes subelements for the check-version-of-accessed-instances element.

TABLE A-18 check-version-of-accessed-instances Subelements

Element	Required	Description
"column-name" on page 75	only one	Specifies the name of the version column.

checkpoint-at-end-of-method

Enterprise Edition only. Do not use.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

checkpointed-methods

Enterprise Edition only. Do not use.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

class-loader

Configures the class loader for the web module.

Superelements

"sun-web-app" on page 154 (sun-web.xml)

Subelements

The following table describes subelements for the class-loader element.

TABLE A-19 class-loader Subelements

Element	Required	Description
"property (with attributes)" on page 126	zero or more	Specifies a property, which has a name and a value.

Attributes

The following table describes attributes for the class-loader element.

TABLE A-20 class-loader Attributes

Attribute	Default	Description
extra-class-path	null	(optional) Specifies additional classpath settings for this web module.
delegate	true	(optional) If true, the web module follows the standard class loader delegation model and delegates to its parent class loader first before looking in the local class loader. You must set this to true for a web application that accesses EJB components or that acts as a web service client or endpoint.
		If false, the web module follows the delegation model specified in the Servlet specification and looks in its class loader before looking in the parent class loader. It's safe to set this to false only for a web module that does not interact with any other modules.
dynamic-reload- interval		(optional) Not implemented. Included for backward compatibility with previous Sun Java System Web Server versions.

Note – If the delegate element is set to false, the class loader delegation behavior complies with the Servlet 2.4 specification, section 9.7.2. If set to its default value of true, classes and resources residing in container-wide library JAR files are loaded in preference to classes and resources packaged within the WAR file.

Portable programs that use this element should not be packaged with any classes or interfaces that are a part of the Java EE specification. The behavior of a program that includes such classes or interfaces in its WAR file is undefined.

Properties

The following table describes properties for the class-loader element.

TABLE A-21 class - loader Properties

Property	Default	Description
ignoreHiddenJarFiles		If true, specifies that all JAR and ZIP files in the WEB-INF/lib directory that start with a period (.) are ignored by the class loader.

client-container

Defines the Application Server specific configuration for the application client container. This is the root element; there can only be one client-container element in a sun-acc.xml file. See "The sun-acc.xml File" on page 57.

Superelements

none

Subelements

The following table describes subelements for the client-container element.

TABLE A-22 client-container Subelements

Element	Required	Description
"target-server" on page 157	only one	Specifies the IIOP listener for the target server. A listener is in the form <i>host:port</i> , where the <i>host</i> is an IP address or host name, and the <i>port</i> specifies the port number.
"auth-realm" on page 60	zero or one	Specifies the optional configuration for JAAS authentication realm.
"client-credential" on page 71	zero or one	Specifies the default client credential that is sent to the server.
"log-service" on page 108	zero or one	Specifies the default log file and the severity level of the message.
"message-security-config" on page 116	zero or more	Specifies configurations for message security providers.
"property (with attributes)" on page 126	zero or more	Specifies a property, which has a name and a value.

Attributes

The following table describes attributes for the client-container element.

TABLE A-23 client-container Attributes

Attribute	Default	Description
send-password		If true, specifies that client authentication credentials must be sent to the server. Without authentication credentials, all access to protected EJB components results in exceptions.

client-credential

Default client credentials that are sent to the server. If this element is present, the credentials are automatically sent to the server, without prompting the user for the user name and password on the client side.

Superelements

"client-container" on page 70 (sun-acc.xml)

Subelements

The following table describes subelements for the client-credential element.

TABLE A-24 client-credential subelement

Element	Required	Description
"property (with attributes)" on page 126	zero or more	Specifies a property, which has a name and a value.

Attributes

The following table describes attributes for the client-credential element.

TABLE A-25 client-credential attributes

Attribute	Default	Description
user-name	none	The user name used to authenticate the Application client container.
password	none	The password used to authenticate the Application client container.
realm	default realm for the domain	(optional) The realm (specified by name) where credentials are to be resolved.

cmp

Describes runtime information for a CMP entity bean object for EJB 1.1 and EJB 2.1 beans.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the cmp element.

TABLE A-26 cmp Subelements

Element	Required	Description
"mapping-properties" on page 110	zero or one	This element is not implemented.
"is-one-one-cmp" on page 97	zero or one	This element is not implemented.
"one-one-finders" on page 120	zero or one	Describes the finders for CMP 1.1 beans.
"prefetch-disabled" on page 124	zero or one	Disables prefetching of entity bean states for the specified query methods.

cmp-field-mapping

The cmp-field-mapping element associates a field with one or more columns to which it maps. The column can be from a bean's primary table or any defined secondary table. If a field is mapped to multiple columns, the column listed first in this element is used as a source for getting the value from the database. The columns are updated in the order they appear. There is one cmp-field-mapping element for each cmp-field element defined in the ejb-jar.xml file.

Superelements

"entity-mapping" on page 90 (sun-cmp-mappings.xml)

Subelements

The following table describes subelements for the cmp-field-mapping element.

TABLE A-27 cmp-field-mapping Subelements

Element	Required	Description
"field-name" on page 93	only one	Specifies the Java identifier of a field. This identifier must match the value of the field-name subelement of the cmp-field that is being mapped.
"column-name" on page 75	one or more	Specifies the name of a column from the primary table, or the qualified table name (TABLE.COLUMN) of a column from a secondary or related table.
"read-only" on page 130	zero or one	Specifies that a field is read-only.
"fetched-with" on page 92	zero or one	Specifies the fetch group for this CMP field's mapping.

cmp-resource

Specifies the database to be used for storing CMP beans. For more information about this element, see "Configuring the CMP Resource" in *Sun Java System Application Server Platform Edition 9 Developer's Guide*.

Superelements

"enterprise-beans" on page 89 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the cmp-resource element.

Appendix A • Deployment Descriptor Files

TABLE A-28 cmp - resource Subelements

Element	Required	Description
"jndi-name" on page 100	only one	Specifies the absolute jndi-name of a JDBC resource.
"default-resource-principal" on page 82	zero or one	Specifies the default runtime bindings of a resource reference.
"property (with subelements)" on page 127	zero or more	Specifies a property name and value. Used to configure PersistenceManagerFactory properties.
"create-tables-at-deploy" on page 80	zero or one	If true, specifies that database tables are created for beans that are automatically mapped by the EJB container.
"drop-tables-at-undeploy" on page 84	zero or one	If true, specifies that database tables that were automatically created when the bean(s) were last deployed are dropped when the bean(s) are undeployed.
"database-vendor-name" on page 81	zero or one	Specifies the name of the database vendor for which tables can be created.
"schema-generator-properties" on page 140	zero or one	Specifies field-specific type mappings and allows you to set the use-unique-table-names property.

cmr-field-mapping

A container-managed relationship field has a name and one or more column pairs that define the relationship. There is one cmr-field-mapping element for each cmr-field element in the ejb-jar.xml file. A relationship can also participate in a fetch group.

Superelements

"entity-mapping" on page 90 (sun-cmp-mappings.xml)

Subelements

The following table describes subelements for the cmr-field-mapping element.

TABLE A-29 cmr-field-mapping Subelements

Element	Required	Description
"cmr-field-name" on page 75	only one	Specifies the Java identifier of a field. Must match the value of the cmr-field-name subelement of the cmr-field that is being mapped.
"column-pair" on page 76	one or more	Specifies the pair of columns that determine the relationship between two database tables.
"fetched-with" on page 92	zero or one	Specifies the fetch group for this CMR field's relationship.

cmr-field-name

Specifies the Java identifier of a field. Must match the value of the cmr-field-name subelement of the cmr-field element in the ejb-jar.xml file.

Superelements

"cmr-field-mapping" on page 74 (sun-cmp-mappings.xml)

Subelements

none - contains data

cmt-timeout-in-seconds

Overrides the Transaction Timeout setting of the Transaction Service for an individual bean. The default value, 0, specifies that the default Transaction Service timeout is used. If positive, this value is used for all methods in the bean that start a new container-managed transaction. This value is *not* used if the bean joins a client transaction.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Subelements

none - contains data

column-name

Specifies the name of a column from the primary table, or the qualified table name (TABLE.COLUMN) of a column from a secondary or related table.

Superelements

"check-version-of-accessed-instances" on page 68, "cmp-field-mapping" on page 73, "column-pair" on page 76 (sun-cmp-mappings.xml)

Subelements

none - contains data

column-pair

Specifies the pair of columns that determine the relationship between two database tables. Each column-pair must contain exactly two column-name subelements, which specify the column's names. The first column-name element names the table that this bean is mapped to, and the second column-name names the column in the related table.

Superelements

"cmr-field-mapping" on page 74, "secondary-table" on page 141 (sun-cmp-mappings.xml)

Subelements

The following table describes subelements for the column-pair element.

TABLE A-30 column-pair Subelements

Element	Required	Description	
"column-name" on page 75		Specifies the name of a column from the primary table, or the qualified table name (TABLE.COLUMN) of a column from a secondary or related table.	

commit-option

Specifies the commit option used on transaction completion. Valid values for the Application Server are B or C. Default value is B. Applies to entity beans.

Note - Commit option A is not supported for this Application Server release.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Subelements

none - contains data

confidentiality

Specifies if the target supports privacy-protected messages. The values are NONE, SUPPORTED, or REOUIRED.

Superelements

"transport-config" on page 158 (sun-ejb-jar.xml)

Subelements

none - contains data

consistency

Specifies container behavior in guaranteeing transactional consistency of the data in the bean.

Superelements

"entity-mapping" on page 90 (sun-cmp-mappings.xml)

Subelements

The following table describes subelements for the consistency element.

TABLE A-31 consistency Subelements

Element	Required	Description
"none" on page 120	exactly one subelement is required	No consistency checking occurs.
"check-modified-at-commit" on page 68	exactly one subelement is required	Checks concurrent modification of fields in modified beans at commit time.
"lock-when-loaded" on page 107	exactly one subelement is required	Obtains an exclusive lock when the data is loaded.
"check-all-at-commit" on page 68		This element is not implemented. Do not use.
"lock-when-modified" on page 107		This element is not implemented. Do not use.
"check-version-of-accessed-instances" on page 68	exactly one subelement is required	Checks the version column of the modified beans.

constraint-field

Specifies a cacheability constraint for the given "url-pattern" on page 160 or "servlet-name" on page 146.

All constraint-field constraints must pass for a response to be cached. If there are value constraints, at least one of them must pass.

Superelements

"cache-mapping" on page 66 (sun-web.xml)

Subelements

The following table describes subelements for the constraint-field element.

TABLE A-32 constraint-field Subelements

Element	Required	Description
"constraint-field-value" on page 78	zero or more	Contains a value to be matched to the input parameter value.

Attributes

The following table describes attributes for the constraint-field element.

TABLE A-33 constraint-field Attributes

Attribute	Default	Description
name	none	Specifies the input parameter name.
scope	request.parameter	(optional) Specifies the scope from which the input parameter is retrieved. Allowed values are context.attribute, request.header, request.parameter, request.cookie, request.attribute, and session.attribute.
cache-on-match	true	(optional) If true, caches the response if matching succeeds. Overrides the same attribute in a "constraint-field-value" on page 78 subelement.
cache-on-match -failure	false	(optional) If true, caches the response if matching fails. Overrides the same attribute in a "constraint-field-value" on page 78 subelement.

constraint-field-value

Specifies a value to be matched to the input parameter value. The matching is case sensitive. For example:

<value match-expr="in-range">1-60</value>

Superelements

"constraint-field" on page 77 (sun-web.xml)

Subelements

none - contains data

Attributes

The following table describes attributes for the constraint-field-value element.

TABLE A-34 constraint-field-value Attributes

Attribute	Default	Description	
match-expr	equals	(optional) Specifies the type of comparison performed with the value. Allowed values at equals, not-equals, greater, lesser, and in-range.	
		If match-expr is greater or lesser, the value must be a number. If match-expr is in-range, the value must be of the form $n1-n2$, where $n1$ and $n2$ are numbers.	
cache-on-match	true	(optional) If true, caches the response if matching succeeds.	
cache-on-match -failure	false	(optional) If true, caches the response if matching fails.	

context-root

Contains the web context root for the application or web application. Overrides the corresponding element in the application.xml or web.xml file.

If the parent element is java-web-start-access, this element contains the context root for the Java Web Start enabled application client module. If none is specified, a default is generated; see "java-web-start-access" on page 98.

Superelements

```
"web" on page 162 (sun-application.xml), "sun-web-app" on page 154 (sun-web.xml), "java-web-start-access" on page 98 (sun-application-client.xml)
```

Subelements

none - contains data

cookie-properties

Specifies session cookie properties.

Superelements

"session-config" on page 146 (sun-web.xml)

Subelements

The following table describes subelements for the cookie-properties element.

Appendix A • Deployment Descriptor Files

TABLE A-35 cookie-properties Subelements

Element	Required	Description
"property (with attributes)" on page 126	zero or more	Specifies a property, which has a name and a value.

Properties

The following table describes properties for the cookie-properties element.

TABLE A-36 cookie-properties Properties

Property	Default	Description
cookiePath	Context path at which the web module is installed.	Specifies the pathname that is set when the cookie is created. The browser sends the cookie if the pathname for the request contains this pathname. If set to / (slash), the browser sends cookies to all URLs served by the Application Server. You can set the path to a narrower mapping to limit the request URLs to which the browser sends cookies.
cookieMaxAgeSeconds	-1	Specifies the expiration time (in seconds) after which the browser expires the cookie.
cookieDomain	(unset)	Specifies the domain for which the cookie is valid.
cookieComment	Sun Java System Application Server Session Tracking Cookie	Specifies the comment that identifies the session tracking cookie in the cookie file. Applications can provide a more specific comment for the cookie.

create-tables-at-deploy

Specifies whether database tables are created for beans that are automatically mapped by the EJB container. If true, creates tables in the database. If false (the default if this element is not present), does not create tables.

This element can be overridden during deployment. See "Generation Options for CMP" in *Sun Java System Application Server Platform Edition 9 Developer's Guide*.

Superelements

"cmp-resource" on page 73 (sun-ejb-jar.xml)

Subelements

none - contains data

D

database-vendor-name

Specifies the name of the database vendor for which tables can be created. Allowed values are javadb, db2, mssql, oracle, postgresql, pointbase, derby (also for CloudScape), and sybase, case-insensitive.

If no value is specified, a connection is made to the resource specified by the "jndi-name" on page 100 subelement of the "cmp-resource" on page 73 element, and the database vendor name is read. If the connection cannot be established, or if the value is not recognized, SQL-92 compliance is presumed.

This element can be overridden during deployment. See "Generation Options for CMP" in *Sun Java System Application Server Platform Edition 9 Developer's Guide*.

Superelements

"cmp-resource" on page 73 (sun-ejb-jar.xml)

Subelements

none - contains data

debugging-enabled

Specifies whether the debugging servlet is enabled for this web service endpoint. Allowed values are true (the default) and false.

Superelements

"webservice-endpoint" on page 163 (sun-web.xml, sun-ejb-jar.xml)

Subelements

none - contains data

default

Specifies that a field belongs to the default hierarchical fetch group, and enables prefetching for a CMR field. To disable prefetching for specific query methods, use a "prefetch-disabled" on page 124 element in the sun-ejb-jar.xml file.

Superelements

"fetched-with" on page 92 (sun-cmp-mappings.xml)

Appendix A • Deployment Descriptor Files

Subelements

none - element is present or absent

default-helper

Passes property values to the built-in default "cache-helper" on page 64 class.

Superelements

"cache" on page 62 (sun-web.xml)

Subelements

The following table describes subelements for the default-helper element.

TABLE A-37 default-helper Subelements

Element	Required	Description
"property (with attributes)" on page 126	zero or more	Specifies a property, which has a name and a value.

Properties

The following table describes properties for the default-helper element.

TABLE A-38 default-helper Properties

Property	Default	Description
cacheKeyGeneratorAttrName	Uses the built-in default "cache-helper" on page 64 key generation, which concatenates the servlet path with "key-field" on page 103 values, if any.	The caching engine looks in the ServletContext for an attribute with a name equal to the value specified for this property to determine whether a customized CacheKeyGenerator implementation is used. An application can provide a customized key generator rather than using the default helper. See "The CacheKeyGenerator Interface" in Sun Java System Application Server Platform Edition 9 Developer's Guide.

default-resource-principal

Specifies the default principal (user) for the resource.

If this element is used in conjunction with a JMS Connection Factory resource, the name and password subelements must be valid entries in the Sun Java™ System Message Queue broker user repository. See the Security Management chapter in the Sun Java System Message Queue 3 2006Q2 Administration Guide for details.

Superelements

"resource-ref" on page 136 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml); "cmp-resource" on page 73, "mdb-connection-factory" on page 111 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the default-resource-principal element.

TABLE A-39 default-resource-principal Subelements

Element	Required	Description	
"name" on page 119	only one	Specifies the default resource principal name used to sign on to a resource manager.	
"password" on page 122	only one	Specifies password of the default resource principal.	

description

Specifies a text description of the containing element.

Superelements

"property (with attributes)" on page 126 (sun-web.xml); "activation-config" on page 57, "method" on page 117 (sun-ejb-jar.xml); "target-server" on page 157 (sun-acc.xml)

Subelements

none - contains data

dispatcher

Specifies a comma-separated list of RequestDispatcher methods for which caching is enabled on the target resource. Valid values are REQUEST, FORWARD, INCLUDE, and ERROR. If this element is not specified, the default is REQUEST. See SRV.6.2.5 of the Servlet 2.4 specification for more information.

Superelements

"cache-mapping" on page 66 (sun-web.xml)

Subelements

none - contains data

drop-tables-at-undeploy

Specifies whether database tables that were automatically created when the bean(s) were last deployed are dropped when the bean(s) are undeployed. If true, drops tables from the database. If false (the default if this element is not present), does not drop tables.

This element can be overridden during deployment. See "Generation Options for CMP" in *Sun Java System Application Server Platform Edition 9 Developer's Guide*.

Superelements

"cmp-resource" on page 73 (sun-ejb-jar.xml)

Subelements

none - contains data

Ε

ejb

Defines runtime properties for a single enterprise bean within the application. The subelements listed below apply to particular enterprise beans as follows:

- All types of beans: ejb-name, ejb-ref, resource-ref, resource-env-ref, ior-security-config, gen-classes, jndi-name, use-thread-pool-id, message-destination-ref, pass-by-reference, service-ref
- Stateless session beans: bean-pool, webservice-endpoint
- Entity beans: commit-option, bean-cache, bean-pool, cmp, is-read-only-bean, refresh-period-in-seconds, flush-at-end-of-method
- Message-driven beans: mdb-resource-adapter, mdb-connection-factory, jms-durable-subscription-name, jms-max-messages-load, bean-pool

Superelements

"enterprise-beans" on page 89 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the ejb element.

TABLE A-40 ejb Subelements

Element	Required	Description
"ejb-name" on page 87	only one	Matches the ejb-name in the corresponding ejb-jar.xml file.
"jndi-name" on page 100	zero or more	Specifies the absolute jndi-name.
"ejb-ref" on page 87	zero or more	Maps the absolute JNDI name to the ejb-ref element in the corresponding Java EE XML file.
"resource-ref" on page 136	zero or more	Maps the absolute JNDI name to the resource-ref in the corresponding Java EE XML file.
"resource-env-ref" on page 136	zero or more	Maps the absolute JNDI name to the resource-env-ref in the corresponding Java EE XML file.
"service-ref" on page 144	zero or more	Specifies runtime settings for a web service reference.
"message-destination-ref" on page 114	zero or more	Specifies the name of a physical message destination.
"pass-by-reference" on page 121	zero or one	Specifies the passing method used by an enterprise bean calling a remote interface method in another bean that is colocated within the same process.
"cmp" on page 72	zero or one	Specifies runtime information for a container-managed persistence (CMP) entity bean for EJB 1.1 and EJB 2.1 beans.
"principal" on page 125	zero or one	Specifies the principal (user) name in an enterprise bean that has the run-as role specified.
"mdb-connection-factory" on page 111	zero or one	Specifies the connection factory associated with a message-driven bean.
"jms-durable-subscription-name" on page 99	zero or one	Specifies the durable subscription associated with a message-driven bean.
"jms-max-messages-load" on page 99	zero or one	Specifies the maximum number of messages to load into a Java Message Service session at one time for a message-driven bean to serve. The default is 1.
"ior-security-config" on page 96	zero or one	Specifies the security information for the IOR.
"is-read-only-bean" on page 97	zero or one	Specifies that this entity bean is read-only.
"refresh-period-in-seconds" on page 131	zero or one	Specifies the rate at which a read-only-bean must be refreshed from the data source.
"commit-option" on page 76	zero or one	Has valid values of B or C. Default value is B.
"cmt-timeout-in-seconds" on page 75	zero or one	Overrides the Transaction Timeout setting of the Transaction Service for an individual bean.
"use-thread-pool-id" on page 160	zero or one	Specifies the thread pool from which threads are selected for remote invocations of this bean.

TABLE A-40 e i b Subelements	(Continued)
TABLE A-40 e 10 Subelements	(Commuea)

Element	Required	Description
"gen-classes" on page 94	zero or one	Specifies all the generated class names for a bean.
"bean-pool" on page 62	zero or one	Specifies the bean pool properties. Used for stateless session beans, entity beans, and message-driven beans.
"bean-cache" on page 61	zero or one	Specifies the bean cache properties. Used only for stateful session beans and entity beans.
"mdb-resource-adapter" on page 112	zero or one	Specifies runtime configuration information for a message-driven bean.
"webservice-endpoint" on page 163	zero or more	Specifies information about a web service endpoint.
"flush-at-end-of-method" on page 94	zero or one	Specifies the methods that force a database flush after execution. Used for entity beans.
"checkpointed-methods" on page 69	zero or one	Enterprise Edition only. Do not use.
"checkpoint-at-end-of-method" on page 69	zero or one	Enterprise Edition only. Do not use.

Attributes

The following table describes attributes for the ejb element.

TABLE A-41 ejb Attributes

Attribute	Default	Description
availability-enabled	false	(optional)Enterprise Edition only. Do not use.

Example

```
<ejb>
  <ejb-name>CustomerEJB</ejb-name>
  <jndi-name>customer</jndi-name>
  <resource-ref>
     <res-ref-name>jdbc/SimpleBank</res-ref-name>
     <jndi-name>jdbc/ default</jndi-name>
  </resource-ref>
  <is-read-only-bean>false</is-read-only-bean>
  <commit-option>B</commit-option>
  <ben-pool>
     <steady-pool-size>10</steady-pool-size>
     <resize-quantity>10</resize-quantity>
     <max-pool-size>100</max-pool-size>
     <pool-idle-timeout-in-seconds>600</pool-idle-timeout-in-seconds>
  </bean-pool>
  <bean-cache>
     <max-cache-size>100</max-cache-size>
```

```
<resize-quantity>10</resize-quantity>
  <removal-timeout-in-seconds>3600</removal-timeout-in-seconds>
  <victim-selection-policy>LRU</victim-selection-policy>
  </bean-cache>
</ejb>
```

ejb-name

In the sun-ejb-jar.xml file, matches the ejb-name in the corresponding ejb-jar.xml file. The name must be unique among the names of the enterprise beans in the same EJB JAR file.

There is no architected relationship between the ejb-name in the deployment descriptor and the JNDI name that the deployer assigns to the EJB component's home.

In the sun-cmp-mappings.xml file, specifies the ejb-name of the entity bean in the ejb-jar.xml file to which the container-managed persistence (CMP) bean corresponds.

Superelements

```
"ejb" on page 84, "method" on page 117 (sun-ejb-jar.xml); "entity-mapping" on page 90 (sun-cmp-mappings.xml)
```

Subelements

none - contains data

ejb-ref

Maps the ejb-ref-name in the corresponding Java EE deployment descriptor file ejb-ref entry to the absolute jndi-name of a resource.

The ejb-ref element is used for the declaration of a reference to an EJB's home. Applies to session beans or entity beans.

Superelements

```
"sun-web-app" on page 154 (sun-web.xml), "ejb" on page 84 (sun-ejb-jar.xml), "sun-application-client" on page 151 (sun-application-client.xml)
```

Subelements

The following table describes subelements for the ejb-ref element.

TABLE A-42 ejb-ref Subelements

Element	Required	Description
"ejb-ref-name" on page 88	only one	Specifies the ejb-ref-name in the corresponding Java EE deployment descriptor file ejb-ref entry.
"jndi-name" on page 100	only one	Specifies the absolute jndi-name of a resource.

ejb-ref-name

Specifies the ejb-ref-name in the corresponding Java EE deployment descriptor file ejb-ref entry.

Superelements

"ejb-ref" on page 87 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

none - contains data

eligible

Specifies whether the application client module is eligible to be Java Web Start enabled. Allowed values are true (the default) and false.

Superelements

"java-web-start-access" on page 98 (sun-application-client.xml)

Subelements

none - contains data

endpoint-address-uri

Specifies the relative path combined with the web server root to form the fully qualified endpoint address for a web service endpoint. This is a required element for EJB endpoints and an optional element for servlet endpoints.

For servlet endpoints, this value is relative to the web application context root. For EJB endpoints, the URI is relative to root of the web server (the first portion of the URI is a context root). The context root portion must not conflict with the context root of any web application deployed to the same web server.

In all cases, this value must be a fixed pattern (no "*' allowed).

If the web service endpoint is a servlet that implements only a single endpoint and has only one url-pattern, it is not necessary to set this value, because the web container derives it from the web.xml file.

Superelements

"webservice-endpoint" on page 163 (sun-web.xml, sun-ejb-jar.xml)

Subelements

none - contains data

Example

If the web server is listening at http://localhost:8080, the following endpoint-address-uri:

<endpoint-address-uri>StockQuoteService/StockQuotePort</endpoint-address-uri>
results in the following target endpoint address:

http://localhost:8080/StockQuoteService/StockQuotePort

enterprise-beans

Specifies all the runtime properties for an EJB JAR file in the application.

Superelements

"sun-ejb-jar" on page 153 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the enterprise-beans element.

TABLE A-43 enterprise-beans Subelements

Element	Required	Description
"name" on page 119	zero or one	Specifies the name string.
"unique-id" on page 159	zero or one	Specifies a unique system identifier. This data is automatically generated and updated at deployment/redeployment. Do not specify or edit this value.

TABLE A-43 enterprise-beans Subelements (Continued)

Element	Required	Description
"ejb" on page 84	zero or more	Defines runtime properties for a single enterprise bean within the application.
"pm-descriptors" on page 123	zero or one	Deprecated.
"cmp-resource" on page 73	zero or one	Specifies the database to be used for storing container-managed persistence (CMP) beans in an EJB JAR file.
"message-destination" on page 113	zero or more	Specifies the name of a logical message destination.
"webservice-description" on page 162	zero or more	Specifies a name and optional publish location for a web service.

Example

```
<enterprise-beans>
<eib>
     <ejb-name>CustomerEJB</ejb-name>
     <jndi-name>customer</jndi-name>
     <resource-ref>
         <res-ref-name>jdbc/SimpleBank</res-ref-name>
         <jndi-name>jdbc/__default</jndi-name>
     </resource-ref>
     <is-read-only-bean>false</is-read-only-bean>
     <commit-option>B</commit-option>
     <bean-pool>
         <steady-pool-size>10</steady-pool-size>
        <resize-quantity>10</resize-quantity>
         <max-pool-size>100</max-pool-size>
         <pool-idle-timeout-in-seconds>600</pool-idle-timeout-in-seconds>
     </bean-pool>
     <ben-cache>
         <max-cache-size>100</max-cache-size>
         <resize-quantity>10</resize-quantity>
         <removal-timeout-in-seconds>3600</removal-timeout-in-seconds>
         <victim-selection-policy>LRU</victim-selection-policy>
     </bean-cache>
</ejb>
</enterprise-beans>
```

entity-mapping

Specifies the mapping a bean to database columns.

Superelements

"sun-cmp-mapping" on page 152 (sun-cmp-mappings.xml)

Subelements

The following table describes subelements for the entity-mapping element.

TABLE A-44 entity-mapping Subelements

Element	Required	Description
"ejb-name" on page 87	only one	Specifies the name of the entity bean in the ejb-jar.xml file to which the CMP bean corresponds.
"table-name" on page 156	only one	Specifies the name of a database table. The table must be present in the database schema file.
"cmp-field-mapping" on page 73	one or more	Associates a field with one or more columns to which it maps.
"cmr-field-mapping" on page 74	zero or more	A container-managed relationship field has a name and one or more column pairs that define the relationship.
"secondary-table" on page 141	zero or more	Describes the relationship between a bean's primary and secondary table.
"consistency" on page 77	zero or one	Specifies container behavior in guaranteeing transactional consistency of the data in the bean.

establish-trust-in-client

Specifies if the target is capable of authenticating a client. The values are NONE, SUPPORTED, or REOUIRED.

Superelements

"transport-config" on page 158 (sun-ejb-jar.xml)

Subelements

none - contains data

establish-trust-in-target

Specifies if the target is capable of authenticating *to* a client. The values are NONE, SUPPORTED, or REQUIRED.

Superelements

"transport-config" on page 158 (sun-ejb-jar.xml)

Appendix A • Deployment Descriptor Files

Subelements

none - contains data

F

fetched-with

Specifies the fetch group configuration for fields and relationships. The fetched-with element has different allowed and default subelements based on its parent element and the data types of the fields.

If there is no fetched-with subelement of a "cmp-field-mapping" on page 73, and the data type is not BLOB, CLOB, VARBINARY, LONGVARBINARY, or OTHER, fetched-with can have any valid subelement. The default subelement is as follows:

```
<fetched-with><default/></fetched-with>
```

■ If there is no fetched-with subelement of a "cmp-field-mapping" on page 73, and the data type is BLOB, CLOB, VARBINARY, LONGVARBINARY, or OTHER, fetched-with can have any valid subelement *except* <default/>. The default subelement is as follows:

```
<fetched-with><none/></fetched-with>
```

■ If there is no fetched-with subelement of a "cmr-field-mapping" on page 74, fetched-with can have any valid subelement. The default subelement is as follows:

```
<fetched-with><none/></fetched-with>
```

Managed fields are multiple CMP or CMR fields that are mapped to the same column. A managed field can have any fetched-with subelement except <default/>. For additional information, see "Managed Fields" in Sun Java System Application Server Platform Edition 9 Developer's Guide.

Superelements

"cmp-field-mapping" on page 73, "cmr-field-mapping" on page 74 (sun-cmp-mappings.xml)

Subelements

The following table describes subelements for the fetched-with element.

TABLE A-45 fetched-with Subelements

Element	Required	Description
"default" on page 81	exactly one subelement is required	Specifies that a CMP field belongs to the default hierarchical fetch group, which means it is fetched any time the bean is loaded from a database. Enables prefetching of a CMR field.
"level" on page 104	exactly one subelement is required	Specifies the level number of a hierarchical fetch group.
"named-group" on page 119	exactly one subelement is required	Specifies the name of an independent fetch group.
"none" on page 120	exactly one subelement is required	Specifies that this field or relationship is placed into its own individual fetch group, which means it is loaded from a database the first time it is accessed in this transaction.

field-name

Specifies the Java identifier of a field. This identifier must match the value of the field-name subelement of the cmp-field element in the ejb-jar.xml file.

Superelements

"cmp-field-mapping" on page 73 (sun-cmp-mappings.xml)

Subelements

none - contains data

finder

Describes the finders for CMP 1.1 with a method name and query.

Superelements

"one-one-finders" on page 120 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the finder element.

TABLE A-46 finder Subelements

Element	Required	Description
"method-name" on page 117	only one	Specifies the method name for the finder.
"query-params" on page 130	zero or one	Specifies the query parameters for the CMP 1.1 finder.
"query-filter" on page 129	zero or one	Specifies the query filter for the CMP 1.1 finder.
"query-variables" on page 130	zero or one	Specifies variables in query expression for the CMP 1.1 finder.
"query-ordering" on page 129	zero or one	Specifies the query ordering for the CMP 1.1 finder.

flush-at-end-of-method

Specifies the methods that force a database flush after execution. Applicable to entity beans.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the flush-at-end-of-method element.

TABLE A-47 flush-at-end-of-method Subelements

Element	Required	Description
"method" on page 117	one or more	Specifies a bean method.

G

gen-classes

Specifies all the generated class names for a bean.

Note – This value is automatically generated by the server at deployment or redeployment time. Do not specify it or change it after deployment.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the gen-class element.

TABLE A-48 gen-classes Subelements

Element	Required	Description
"remote-impl" on page 132	zero or one	Specifies the fully-qualified class name of the generated EJBObject impl class.
"local-impl" on page 105	zero or one	Specifies the fully-qualified class name of the generated EJBLocalObject impl class.
"remote-home-impl" on page 132	zero or one	Specifies the fully-qualified class name of the generated EJBHome impl class.
"local-home-impl" on page 104	zero or one	Specifies the fully-qualified class name of the generated EJBLocalHome impl class.

group-name

Specifies a group name in the current realm.

Superelements

"security-role-mapping" on page 142 (sun-application.xml, sun-web.xml, sun-ejb-jar.xml)

Subelements

none - contains data

Н

http-method

Specifies an HTTP method that is eligible for caching. The default is GET.

Superelements

"cache-mapping" on page 66 (sun-web.xml)

Subelements

none - contains data

ı

idempotent-url-pattern

Enterprise Edition only. Do not use.

Superelements

"sun-web-app" on page 154 (sun-web.xml)

integrity

Specifies if the target supports integrity-protected messages. The values are NONE, SUPPORTED, or REQUIRED.

Superelements

"transport-config" on page 158 (sun-ejb-jar.xml)

Subelements

none - contains data

ior-security-config

Specifies the security information for the input-output redirection (IOR).

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the ior-security-config element.

TABLE A-49 ior-security-config Subelements

Element	Required	Description
"transport-config" on page 158	zero or one	Specifies the security information for transport.

		inued) Description
"as-context" on page 59	zero or one	Specifies the authentication mechanism used to authenticate the client. If specified, it is USERNAME_PASSWORD.
"sas-context" on page 139	zero or one	Describes the sas-context fields.

is-cache-overflow-allowed

This element is deprecated. Do not use.

Superelements

"bean-cache" on page 61 (sun-ejb-jar.xml)

is-one-one-cmp

This element is not used.

Superelements

"cmp" on page 72 (sun-ejb-jar.xml)

is-read-only-bean

Specifies that this entity bean is a read-only bean if true. If this element is absent, the default value of false is used.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Subelements

none - contains data

ı

ı

java-method

Specifies a method.

Superelements

"message" on page 112 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

The following table describes subelements for the java-method element.

TABLE A-50 java-method Subelements

Element	Required	Description
"method-name" on page 117	only one	Specifies a method name.
"method-params" on page 118	zero or one	Specifies fully qualified Java type names of method parameters.

java-web-start-access

Specifies changes to default Java Web Start parameters for an embedded or stand-alone application client module.

Superelements

"sun-application-client" on page 151 (sun-application-client.xml)

Subelements

The following table describes subelements for the java-web-start-access element.

TABLE A-51 java-web-start-access subelements

Element	Required	Description
"context-root" on page 79	zero or one	Contains the context root for the Java Web Start enabled application client module. If none is specified, a default is generated. The default for an application is as follows:
		The default for an application is as follows: http://host:port/app-name/relative-URI-to-appclient-jar The default for a stand-alone application client module is as follows:
		http://host:port/module-name If the app-name or module-name is not specified during deployment, the name of the EAR or JAR file without the extension is used. If the application or module is not in EAR or JAR file format, a name is generated and written to the server log.
"eligible" on page 88	zero or one	Specifies whether the application client module is eligible to be Java Web Start enabled. Allowed values are true (the default) and false.
"vendor" on page 161	zero or one	Specifies the name of the vendor as it appears in Java Web Start download and launch screens. The default value is Application Client.

jms-durable-subscription-name

Specifies the durable subscription associated with a message-driven bean class. Only applies to the Java Message Service Topic Destination type, and only when the message-driven bean deployment descriptor subscription durability is Durable.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Subelements

none - contains data

jms-max-messages-load

Specifies the maximum number of messages to load into a Java Message Service session at one time for a message-driven bean to serve. The default is 1.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Appendix A • Deployment Descriptor Files

Subelements

none - contains data

jndi-name

Specifies the absolute jndi-name of a URL resource or a resource.

For entity beans and session beans, this value specifies the global JNDI name of the EJBHome object. It is only needed if the entity or session bean exposes a remote view.

For JMS message-driven beans, this is the JNDI name of the JMS resource from which the message-driven bean consumes JMS messages. This information is alternatively specified within the "activation-config" on page 57 subelement of the "mdb-resource-adapter" on page 112 element. For more information about JMS resources, see Chapter 18, "Using the Java Message Service," in *Sun Java System Application Server Platform Edition 9 Developer's Guide*.

Superelements

```
"ejb-ref" on page 87, "message-destination" on page 113, "resource-env-ref" on page 136, "resource-ref" on page 136 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml); "cmp-resource" on page 73, "ejb" on page 84, "mdb-connection-factory" on page 111 (sun-ejb-jar.xml)
```

Subelements

none - contains data

jsp-config

Specifies JSP configuration information.

Superelements

```
"sun-web-app" on page 154 (sun-web.xml)
```

Subelements

The following table describes subelements for the jsp-config element.

TABLE A-52 jsp-config Subelements

Element	Required	Description
"property (with attributes)" on page 126	zero or more	Specifies a property, which has a name and a value.

Properties

The default property values are tuned for development of JSP files at the cost of performance. To maximize performance, set jsp-config properties to these non-default values:

- development false (as an alternative, set to true and give modificationTestInterval a large value)
- mappedfile false
- trimSpaces true
- suppressSmap true
- fork false (on Solaris)
- classdebuginfo-false

The following table describes properties for the jsp-config element.

TABLE A-53 jsp-config Properties

Property	Default	Description
checkInterval	0	If development is set to false and checkInterval is greater than zero, background compilations are enabled. The checkInterval is the time in seconds between checks to see if a JSP file needs to be recompiled.
classdebuginfo	true	Specifies whether the generated Java servlets are compiled with the debug option set (-g for javac).
classpath	created dynamically based on the current web application	Specifies the classpath to use when compiling generated servlets.
compiler	javac	Specifies the compiler Ant uses to compile JSP files. See the Ant documentation for more information: http://antinstaller.sourceforge.net/manual/manual/
compilerSourceVM	Depends on the Application Server's Java runtime	Specifies the JDK release with which source compatibility of the generated servlets is provided. Same as the -source <i>release</i> option of javac.
		For more information, see http://java.sun.com/j2se/1.5.0/docs/tooldocs/solaris/javac.html#options.

TABLE A-53 jsp-config Properties (Continued)

Property	Default	Description
compilerTargetVM	Depends on the Application Server's Java runtime	Specifies the JVM version for which the servlet class files are generated. Same as the -target <i>release</i> option of javac.
		For more information, see http://java.sun.com/j2se/1.5.0/docs/tooldocs/solaris/javac.html#options.
development	true	If set to true, enables development mode, which allows JSP files to be checked for modification. Specify the frequency at which JSPs are checked using the modificationTestInterval property.
dumpSmap	false	If set to true, dumps SMAP information for JSR 45 debugging to a file. Set to false if suppressSmap is true.
enablePooling	true	If set to true, tag handler pooling is enabled.
enableTldValidation	false	If set to true, all Tag Library Descriptor (TLD) files referenced by the web application are validated against their underlying schema or DTD file.
errorOnUseBeanInvalid ClassAttribute	false	If set to true, issues an error when the value of the class attribute in a useBean action is not a valid bean class.
fork	true	Specifies that Ant forks the compiling of JSP files, using a JVM separate from the one in which Tomcat is running.
genStrAsCharArray	false	If set to true, generates text strings as char arrays, which improves performance in some cases.
ieClassId	clsid:8AD9C840- 044E-11D1-B3E9- 00805F499D93	Specifies the Java plug-in COM class ID for Internet Explorer. Used by the <jsp:plugin> tags.</jsp:plugin>
initialCapacity	32	Specifies the initial capacity of the HashMap that maps JSP files to their corresponding servlets.
javaEncoding	UTF8	Specifies the encoding for the generated Java servlet. This encoding is passed to the Java compiler that is used to compile the servlet as well. By default, the web container tries to use UTF8. If that fails, it tries to use the javaEncoding value.
		For encodings, see:
		http://java.sun.com/j2se/1.5.0/docs/guide/intl/encoding.doc.html
keepgenerated	true	If set to true, keeps the generated Java files. If false, deletes the Java files.
mappedfile	true	If set to true, generates static content with one print statement per input line, to ease debugging.

Property	Default	Description
modification TestInterval	0	Specifies the frequency in seconds at which JSPs are checked for modification. A value of 0 causes the JSP to be checked on every access. Used only if development is set to true.
scratchdir	The default work directory for the web application	Specifies the working directory created for storing all the generated code.
suppressSmap	false	If set to true, generation of SMAP information for JSR 45 debugging is suppressed.
trimSpaces	false	If set to true, trims white spaces in template text between actions or directives.
usePrecompiled	false	If set to true, an accessed JSP file is not compiled. Its precompiled servlet class is used instead. It is assumed that JSP files have been precompiled, and their corresponding servlet classes have been bundled in the web application's WEB-INF/lib or WEB-INF/classes directory.
xpoweredBy	true	If set to true, the X-Powered-By response header is added by the generated servlet.

K

key-field

Specifies a component of the key used to look up and extract cache entries. The web container looks for the named parameter, or field, in the specified scope.

If this element is not present, the web container uses the Servlet Path (the path section that corresponds to the servlet mapping that activated the current request). See the Servlet 2.4 specification, section SRV 4.4, for details on the Servlet Path.

Superelements

"cache-mapping" on page 66 (sun-web.xml)

Subelements

none

Attributes

The following table describes attributes for the key-field element.

TABLE A-54 key-field Attributes

Attribute	Default	Description
name	none	Specifies the input parameter name.
scope	request.parameter	(optional) Specifies the scope from which the input parameter is retrieved. Allowed values are context.attribute, request.header, request.parameter, request.cookie, session.id, and session.attribute.

L

level

Specifies the name of a hierarchical fetch group. The name must be an integer. Fields and relationships that belong to a hierarchical fetch group of equal (or lesser) value are fetched at the same time. The value of level must be greater than zero. Only one is allowed.

Superelements

"fetched-with" on page 92 (sun-cmp-mappings.xml)

Subelements

none - contains data

local-home-impl

Specifies the fully-qualified class name of the generated EJBLocalHome impl class.

Note – This value is automatically generated by the server at deployment or redeployment time. Do not specify it or change it after deployment.

Superelements

"gen-classes" on page 94 (sun-ejb-jar.xml)

Subelements

none - contains data

local-impl

Specifies the fully-qualified class name of the generated EJBLocalObject impl class.

Note – This value is automatically generated by the server at deployment or redeployment time. Do not specify it or change it after deployment.

Superelements

"gen-classes" on page 94 (sun-ejb-jar.xml)

Subelements

none - contains data

locale-charset-info

Deprecated. For backward compatibility only. Use the "parameter-encoding" on page 121 subelement of "sun-web-app" on page 154 instead. Specifies information about the application's internationalization settings.

Superelements

"sun-web-app" on page 154 (sun-web.xml)

Subelements

The following table describes subelements for the locale-charset-info element.

TABLE A-55 locale-charset-info Subelements

Element	Required	Description
"locale-charset-map" on page 106	one or more	Maps a locale and an agent to a character encoding. Provided for backward compatibility. Used only for request processing, and only if no parameter-encoding is defined.
"parameter-encoding" on page 121	zero or one	Determines the default request character encoding and how the web container decodes parameters from forms according to a hidden field value.

Attributes

The following table describes attributes for the locale-charset-info element.

1

TABLE A-56 locale-charset-info Attributes

Attribute	Default	Description
default-locale	none	Although a value is required, the value is ignored. Use the default-charset attribute of the "parameter-encoding" on page 121 element.

locale-charset-map

Maps locales and agents to character encodings. Provided for backward compatibility. Used only for request processing. Used only if the character encoding is not specified in the request and cannot be derived from the optional "parameter-encoding" on page 121 element. For encodings, see http://java.sun.com/j2se/1.5.0/docs/guide/intl/encoding.doc.html.

Superelements

"locale-charset-info" on page 105 (sun-web.xml)

Subelements

The following table describes subelements for the locale-charset-map element.

TABLE A-57 locale-charset-map Subelements

Element	Required	Description	
"description" on page 83	zero or one	Specifies an optional text description of a mapping.	

Attributes

The following table describes attributes for the locale-charset-map element.

TABLE A-58 locale-charset-map Attributes

Attribute	Default	Description
locale	none	Specifies the locale name.
agent	none	(optional) Specifies the type of client that interacts with the application server. For a given locale, different agents can have different preferred character encodings. The value of this attribute must exactly match the value of the user-agent HTTP request header sent by the client. See Table A-59 for more information.
charset	none	Specifies the character encoding to which the locale maps.

Example Agents

The following table specifies example agent attribute values.

TABLE A-59 Example agent Attribute Values

Agent	user-agent Header and agent Attribute Value
Internet Explorer 5.00 for Windows 2000	Mozilla/4.0 (compatible; MSIE 5.01; Windows NT 5.0)
Netscape 4.7.7 for Windows 2000	Mozilla/4.77 [en] (Windows NT 5.0; U)
Netscape 4.7 for Solaris	Mozilla/4.7 [en] (X11; u; Sun OS 5.6 sun4u)

localpart

Specifies the local part of a QNAME.

Superelements

"service-qname" on page 143, "wsdl-port" on page 165 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

none - contains data

lock-when-loaded

Places a database update lock on the rows corresponding to the bean whenever the bean is loaded. How the lock is placed is database-dependent. The lock is released when the transaction finishes (commit or rollback). While the lock is in place, other database users have read access to the bean.

Superelements

"consistency" on page 77 (sun-cmp-mappings.xml)

Subelements

none - element is present or absent

lock-when-modified

This element is not implemented. Do not use.

Superelements

"consistency" on page 77 (sun-cmp-mappings.xml)

Appendix A · Deployment Descriptor Files

log-service

Specifies configuration settings for the log file.

Superelements

"client-container" on page 70 (sun-acc.xml)

Subelements

The following table describes subelements for the log-service element.

TABLE A-60 log-service subelement

Element	Required	Description
"property (with attributes)" on page 126	zero or more	Specifies a property, which has a name and a value.

Attributes

The following table describes attributes for the log-service element.

TABLE A-61 log-service attributes

Attribute	Default	Description
log-file	your-ACC-dir/logs/client.log	(optional) Specifies the file where the application client container logging information is stored.
level	SEVERE	(optional) Sets the base level of severity. Messages at or above this setting get logged to the log file.

login-config

Specifies the authentication configuration for an EJB web service endpoint. Not needed for servlet web service endpoints. A servlet's security configuration is contained in the web.xml file.

Superelements

"webservice-endpoint" on page 163 (sun-web.xml, sun-ejb-jar.xml)

Subelements

The following table describes subelements for the login-config element.

TABLE A-62 login-config subelements

Element	Required	Description
"auth-method" on page 59	only one	Specifies the authentication method.

M

manager-properties

Specifies session manager properties.

Superelements

"session-manager" on page 146 (sun-web.xml)

Subelements

The following table describes subelements for the manager-properties element.

TABLE A-63 manager-properties Subelements

Element	Required	Description
"property (with attributes)" on page 126	zero or more	Specifies a property, which has a name and a value.

Properties

The following table describes properties for the manager-properties element.

TABLE A-64 manager-properties Properties

Property	Default	Description
reapIntervalSeconds	60	Specifies the number of seconds between checks for expired sessions. This is also the interval at which sessions are passivated if maxSessions is exceeded.
		To prevent data inconsistency, set this value lower than the frequency at which session data changes. For example, this value should be as low as possible (1 second) for a hit counter servlet on a frequently accessed web site, or the last few hits might be lost each time the server is restarted.
		Applicable only if the persistence-type attribute of the parent "session-manager" on page 146 element is file.
maxSessions	-1	Specifies the maximum number of sessions that are permitted in the cache, or -1 for no limit. After this, an attempt to create a new session causes an IllegalStateException to be thrown.
		The session manager passivates sessions to the persistent store when this maximum is reached.
		Applicable only if the persistence-type attribute of the parent "session-manager" on page 146 element is file.
sessionFilename	One of the following:	Specifies the absolute or relative path to the directory in which the
	domain-dir/generated/jsp/ j2ee-modules/module-name/ context-path_SESSIONS.ser	session state is preserved between application restarts, if preserving the state is possible. A relative path is relative to the temporary directory for this web application. To disable preservation of the session state, set this property's value to an empty string.
	<pre>domain-dir/generated/jsp/ j2ee-apps/app-name/module-name/ context-path_SESSIONS.ser</pre>	Applicable only if the persistence-type attribute of the parent "session-manager" on page 146 element is memory.

mapping-properties

This element is not implemented.

Superelements

"cmp" on page 72 (sun-ejb-jar.xml)

max-cache-size

Specifies the maximum number of beans allowable in cache. A value of zero indicates an unbounded cache. In reality, there is no hard limit. The max-cache-size limit is just a hint to the cache implementation. Default is 512.

Applies to stateful session beans and entity beans.

Superelements

"bean-cache" on page 61 (sun-ejb-jar.xml)

Subelements

none - contains data

max-pool-size

Specifies the maximum number of bean instances in the pool. Values are from 0 (1 for message-driven bean) to MAX_INTEGER. A value of 0 means the pool is unbounded. Default is 64.

Applies to all beans.

Superelements

"bean-pool" on page 62 (sun-ejb-jar.xml)

Subelements

none - contains data

max-wait-time-in-millis

This element is deprecated. Do not use.

Superelements

"bean-pool" on page 62 (sun-ejb-jar.xml)

mdb-connection-factory

Specifies the connection factory associated with a message-driven bean. Queue or Topic type must be consistent with the Java Message Service Destination type associated with the message-driven bean class.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the mdb-connection-factory element.

TABLE A-65 mdb - connection - factory Subelements

Element	Required	Description
"jndi-name" on page 100	only one	Specifies the absolute jndi-name.
"default-resource-principal" on page 82	zero or one	Specifies the default sign-on (name/password) to the resource manager.

mdb-resource-adapter

Specifies runtime configuration information for a message-driven bean.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the mdb-resource-adapter element.

TABLE A-66 mdb - resource - adapter subelements

Element	Required	Description
"resource-adapter-mid" on page 135	zero or one	Specifies a resource adapter module ID.
"activation-config" on page 57	one or more	Specifies an activation configuration.

message

Specifies the methods or operations to which message security requirements apply.

Superelements

"message-security" on page 114 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

The following table describes subelements for the message element.

TABLE A-67 message Subelements

Element	Required	Description
"java-method" on page 98	zero or one	Specifies the methods or operations to which message security requirements apply.
"operation-name" on page 120	zero or one	Specifies the WSDL name of an operation of a web service.

message-destination

Specifies the name of a logical message-destination defined within an application. The message-destination-name matches the corresponding message-destination-name in the corresponding Java EE deployment descriptor file. Use when the message destination reference in the corresponding Java EE deployment descriptor file specifies a message-destination-link to a logical message-destination.

Superelements

```
"sun-web-app" on page 154 (sun-web.xml), "enterprise-beans" on page 89 (sun-ejb-jar.xml), "sun-application-client" on page 151 (sun-application-client.xml)
```

Subelements

The following table describes subelements for the message-destination element.

TABLE A-68 message-destination subelements

Element	Required	Description
"message-destination-name" on page 113	only one	Specifies the name of a logical message destination defined within the corresponding Java EE deployment descriptor file.
"jndi-name" on page 100	only one	Specifies the jndi-name of the associated entity.

message-destination-name

Specifies the name of a logical message destination defined within the corresponding Java EE deployment descriptor file.

Superelements

```
"message-destination" on page 113 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)
```

Subelements

message-destination-ref

Directly binds a message destination reference to the JNDI name of a Queue, Topic, or other physical destination. Use only when the message destination reference in the corresponding Java EE deployment descriptor file does *not* specify a message-destination-link to a logical message-destination.

Superelements

```
"sun-web-app" on page 154 (sun-web.xml), "ejb" on page 84 (sun-ejb-jar.xml), "sun-application-client" on page 151 (sun-application-client.xml)
```

Subelements

The following table describes subelements for the message-destination-ref element.

TABLE A-69 message-destination-ref subelements

Element	Required	Description
"message-destination-ref-name" on page 114	only one	Specifies the name of a physical message destination defined within the corresponding Java EE deployment descriptor file.
"jndi-name" on page 100	only one	Specifies the jndi-name of the associated entity.

message-destination-ref-name

Specifies the name of a physical message destination defined within the corresponding Java EE deployment descriptor file.

Superelements

```
"message-destination-ref" on page 114 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)
```

Subelements

none - contains data

message-security

Specifies message security requirements.

- If the grandparent element is "webservice-endpoint" on page 163, these requirements pertain to request and response messages of the endpoint.
- If the grandparent element is "port-info" on page 123, these requirements pertain to the port of the referenced service.

Superelements

"message-security-binding" on page 115 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

The following table describes subelements for the message-security element.

TABLE A-70 message-security Subelements

Element	Required	Description
"message" on page 112	one or more	Specifies the methods or operations to which message security requirements apply.
"request-protection" on page 133	zero or one	Defines the authentication policy requirements of the application's request processing.
"response-protection" on page 138	zero or one	Defines the authentication policy requirements of the application's response processing.

message-security-binding

Specifies a custom authentication provider binding for a parent "webservice-endpoint" on page 163 or "port-info" on page 123 element in one or both of these ways:

- By binding to a specific provider
- By specifying the message security requirements enforced by the provider

Superelements

"webservice-endpoint" on page 163, "port-info" on page 123 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

The following table describes subelements for the message-security-binding element.

TABLE A-71 message-security-binding Subelements

Element	Required	Description
"message-security" on page 114	zero or more	Specifies message security requirements.

Attributes

The following table describes attributes for the message-security-binding element.

TABLE A-72 message-security-binding Attributes

Attribute	Default	Description
auth-layer	none	Specifies the message layer at which authentication is performed. The value must be SOAP.
provider-id	none	(optional) Specifies the authentication provider used to satisfy application-specific message security requirements.
		If this attribute is not specified, a default provider is used, if it is defined for the message layer.
		if no default provider is defined, authentication requirements defined in the message-security-binding are not enforced.

message-security-config

Specifies configurations for message security providers.

Superelements

"client-container" on page 70 (sun-acc.xml)

Subelements

The following table describes subelements for the message-security-config element.

TABLE A-73 message-security-config Subelements

Element	Required	Description
"provider-config" on page 127	one or more	Specifies a configuration for one message security provider.

Attributes

The following table describes attributes for the message-security-config element.

TABLE A-74 message-security-config Attributes

Attribute	Default	Description
auth-layer	none	Specifies the message layer at which authentication is performed. The value must be SOAP.
default-provider	none	(optional) Specifies the server provider that is invoked for any application not bound to a specific server provider.
default-client-provider	none	(optional) Specifies the client provider that is invoked for any application not bound to a specific client provider.

method

Specifies a bean method.

Superelements

"flush-at-end-of-method" on page 94 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the method element.

TABLE A-75 method Subelements

Element	Required	Description
"description" on page 83	zero or one	Specifies an optional text description.
"ejb-name" on page 87	zero or one	Matches the ejb-name in the corresponding ejb-jar.xml file.
"method-name" on page 117	only one	Specifies a method name.
"method-intf" on page 117	zero or one	Specifies the method interface to distinguish between methods with the same name in different interfaces.
"method-params" on page 118	zero or one	Specifies fully qualified Java type names of method parameters.

method-intf

Specifies the method interface to distinguish between methods with the same name in different interfaces. Allowed values are Home, Remote, Local Home, and Local.

Superelements

"method" on page 117 (sun-ejb-jar.xml)

Subelements

none - contains data

method-name

Specifies a method name or * (an asterisk) for all methods. If a method is overloaded, specifies all methods with the same name.

Superelements

"java-method" on page 98 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml); "finder" on page 93, "query-method" on page 129, "method" on page 117 (sun-ejb-jar.xml)

Subelements

none - contains data

Examples

```
<method-name>findTeammates</method-name>
```

method-param

<method-name>*</method-name>

Specifies the fully qualified Java type name of a method parameter.

Superelements

```
"method-params" on page 118 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)
```

Subelements

none - contains data

method-params

Specifies fully qualified Java type names of method parameters.

Superelements

```
"java-method" on page 98 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml); "query-method" on page 129, "method" on page 117 (sun-ejb-jar.xml)
```

Subelements

The following table describes subelements for the method-params element.

TABLE A-76 method-params Subelements

Element	Required	Description
"method-param" on page 118	zero or more	Specifies the fully qualified Java type name of a method parameter.

N

name

Specifies the name of the entity.

Superelements

"call-property" on page 66, "default-resource-principal" on page 82, "stub-property" on page 150 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml); "enterprise-beans" on page 89, "principal" on page 125, "property (with subelements)" on page 127 (sun-ejb-jar.xml)

Subelements

none - contains data

named-group

Specifies the name of one independent fetch group. All the fields and relationships that are part of a named group are fetched at the same time. A field belongs to only one fetch group, regardless of what type of fetch group is used.

Superelements

"fetched-with" on page 92 (sun-cmp-mappings.xml)

Subelements

none - contains data

namespaceURI

Specifies the namespace URI.

Superelements

"service-qname" on page 143, "wsdl-port" on page 165 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

none

Specifies that this field or relationship is fetched by itself, with no other fields or relationships.

Superelements

"consistency" on page 77, "fetched-with" on page 92 (sun-cmp-mappings.xml)

Subelements

none - element is present or absent

0

one-one-finders

Describes the finders for CMP 1.1 beans.

Superelements

"cmp" on page 72 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the one-one-finders element.

TABLE A-77 one-one-finders Subelements

Element	Required	Description
"finder" on page 93	one or more	Describes the finders for CMP 1.1 with a method name and query.

operation-name

Specifies the WSDL name of an operation of a web service.

Superelements

"message" on page 112 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

P

parameter-encoding

Specifies the default request character encoding and how the web container decodes parameters from forms according to a hidden field value.

If both the "sun-web-app" on page 154 and "locale-charset-info" on page 105 elements have parameter-encoding subelements, the subelement of sun-web-app takes precedence. For encodings, see http://java.sun.com/j2se/1.5.0/docs/guide/intl/encoding.doc.html.

Superelements

"locale-charset-info" on page 105, "sun-web-app" on page 154 (sun-web.xml)

Subelements

none

Attributes

The following table describes attributes for the parameter-encoding element.

TABLE A-78 parameter-encoding Attributes

Attribute	Default	Description
form-hint-field	none	(optional) The name of the hidden field in the form. This field specifies the character encoding the web container uses for request.getParameter and request.getReader calls when the charset is not set in the request's content-type header.
default-charset	ISO-8859-1	(optional) The default request character encoding.

pass-by-reference

Specifies the passing method used by a servlet or enterprise bean calling a remote interface method in another bean that is colocated within the same process.

- If false (the default if this element is not present), this application uses pass-by-value semantics.
- If true, this application uses pass-by-reference semantics.

Note – The pass-by-reference element only applies to remote calls. As defined in the EJB 2.1 specification, section 5.4, calls to local interfaces use pass-by-reference semantics.

If the pass-by-reference element is set to its default value of false, the passing semantics for calls to remote interfaces comply with the EJB 2.1 specification, section 5.4. If set to true, remote calls involve pass-by-reference semantics instead of pass-by-value semantics, contrary to this specification.

Portable programs cannot assume that a copy of the object is made during such a call, and thus that it's safe to modify the original. Nor can they assume that a copy is not made, and thus that changes to the object are visible to both caller and callee. When this element is set to true, parameters and return values should be considered read-only. The behavior of a program that modifies such parameters or return values is undefined.

When a servlet or enterprise bean calls a remote interface method in another bean that is colocated within the same process, by default the Application Server makes copies of all the call parameters in order to preserve the pass-by-value semantics. This increases the call overhead and decreases performance.

However, if the calling method does not change the object being passed as a parameter, it is safe to pass the object itself without making a copy of it. To do this, set the pass-by-reference value to true.

The setting of this element in the sun-application.xml file applies to all EJB modules in the application. For an individually deployed EJB module, you can set the same element in the sun-ejb-jar.xml file. If pass-by-reference is used at both the bean and application level, the bean level takes precedence.

Superelements

"sun-application" on page 151 (sun-application.xml), "ejb" on page 84 (sun-ejb-jar.xml)

Subelements

none - contains data

password

Specifies the password for the principal.

Superelements

```
"default-resource-principal" on page 82 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)
```

Subelements

pm-descriptors

This element and its subelements are deprecated. Do not use.

Superelements

"enterprise-beans" on page 89 (sun-ejb-jar.xml)

pool-idle-timeout-in-seconds

Specifies the maximum time, in seconds, that a bean instance is allowed to remain idle in the pool. When this timeout expires, the bean instance in a pool becomes a candidate for passivation or deletion. This is a hint to the server. A value of 0 specifies that idle beans remain in the pool indefinitely. Default value is 600.

Applies to stateless session beans, entity beans, and message-driven beans.

Note – For a stateless session bean or a message-driven bean, the bean is removed (garbage collected) when the timeout expires.

Superelements

"bean-pool" on page 62 (sun-ejb-jar.xml)

Subelements

none - contains data

port-component-name

Specifies a unique name for a port component within a web or EJB module.

Superelements

"webservice-endpoint" on page 163 (sun-web.xml, sun-ejb-jar.xml)

Subelements

none - contains data

port-info

Specifies information for a port within a web service reference.

Either a service-endpoint-interface or a wsdl-port or both must be specified. If both are specified, wsdl-port specifies the port that the container chooses for container-managed port selection.

The same wsdl-port value must not appear in more than one port-info element within the same service-ref.

If a service-endpoint-interface is using container-managed port selection, its value must not appear in more than one port-info element within the same service-ref.

Superelements

"service-ref" on page 144 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

The following table describes subelements for the port-info element.

TABLE A-79 port - info subelements

Element	Required	Description
"service-endpoint-interface" on page 143	zero or one	Specifies the web service reference name relative to java: comp/env.
"wsdl-port" on page 165	zero or one	Specifies the WSDL port.
"stub-property" on page 150	zero or more	Specifies JAX-RPC property values that are set on a <code>javax.xml.rpc.Stub</code> object before it is returned to the web service client.
"call-property" on page 66	zero or more	Specifies JAX-RPC property values that are set on a <code>javax.xml.rpc.Call</code> object before it is returned to the web service client.
"message-security-binding" on page 115	zero or one	Specifies a custom authentication provider binding.

prefetch-disabled

Disables prefetching of entity bean states for the specified query methods. Container-managed relationship fields are prefetched if their "fetched-with" on page 92 element is set to "default" on page 81.

Superelements

"cmp" on page 72 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the prefetch-disabled element.

TABLE A-80 prefetch-disabled Subelements

Element	Required	Description
"query-method" on page 129	one or more	Specifies a query method.

principal

Defines a node that specifies a user name on the platform.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the principal element.

TABLE A-81 principal Subelements

Element	Required	Description
"name" on page 119	only one	Specifies the name of the user.

principal-name

Contains the principal (user) name.

In an enterprise bean, specifies the principal (user) name that has the run-as role specified.

Superelements

```
"security-role-mapping" on page 142 (sun-application.xml, sun-web.xml, sun-ejb-jar.xml), "servlet" on page 145 (sun-web.xml)
```

Subelements

none - contains data

Attributes

The following table describes attributes for the principal-name element.

TABLE A-82 principal - name Attributes

Attribute	Default	Description
class-name	com.sun.enterprise.deployment. PrincipalImpl	(optional) Specifies the custom principal implementation class corresponding to the named principal.

property (with attributes)

Specifies the name and value of a property. A property adds configuration information to its parent element that is one or both of the following:

- Optional with respect to Application Server
- Needed by a system or object that Application Server doesn't have knowledge of, such as an LDAP server or a Java class

Superelements

"cache" on page 62, "cache-helper" on page 64, "class-loader" on page 69, "cookie-properties" on page 79, "default-helper" on page 82, "manager-properties" on page 109, "session-properties" on page 147, "store-properties" on page 149, "sun-web-app" on page 154, "webservice-endpoint" on page 163 (sun-web.xml); "auth-realm" on page 60, "client-container" on page 70, "client-credential" on page 71, "log-service" on page 108, "provider-config" on page 127 (sun-acc.xml)

Subelements

The following table describes subelements for the property element.

TABLE A-83 property Subelements

Element	Required	Description
"description" on page 83	zero or one	Specifies an optional text description of a property.

Note - The property element in the sun-acc.xml file has no subelements.

Attributes

The following table describes attributes for the property element.

TABLE A-84 property Attributes

Attribute	Default	Description	
name	none	Specifies the name of the property.	
value	none	Specifies the value of the property.	

Example

roperty name="reapIntervalSeconds" value="20" />

property (with subelements)

Specifies the name and value of a property. A property adds configuration information to its parent element that is one or both of the following:

- Optional with respect to Application Server
- Needed by a system or object that Application Server doesn't have knowledge of, such as an LDAP server or a Java class

Superelements

"cmp-resource" on page 73, "schema-generator-properties" on page 140, "webservice-endpoint" on page 163 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the property element.

TABLE A-85 property subelements

Element	Required	Description
"name" on page 119	only one	Specifies the name of the property.
"value" on page 160	only one	Specifies the value of the property.

Example

provider-config

Specifies a configuration for one message security provider.

Although the request-policy and response-policy subelements are optional, the provider-config element does nothing if they are not specified.

Use property subelements to configure provider-specific properties. Property values are passed to the provider when its initialize method is called.

Superelements

"message-security-config" on page 116 (sun-acc.xml)

Subelements

The following table describes subelements for the provider-config element.

TABLE A-86 provider-config Subelements

Element	Required	Description
"request-policy" on page 133	zero or one	Defines the authentication policy requirements of the authentication provider's request processing.
"response-policy" on page 137	zero or one	Defines the authentication policy requirements of the authentication provider's response processing.
"property (with attributes)" on page 126	zero or more	Specifies a property, which has a name and a value.

Attributes

The following table describes attributes for the provider-config element.

TABLE A-87 provider-config Attributes

Attribute	Default	Description
provider-id	none	Specifies the provider ID.
provider-type	none	Specifies whether the provider is a client, server, or client-server authentication provider.
class-name	none	Specifies the Java implementation class of the provider. Client authentication providers must implement the com.sun.enterprise.security.jauth.ClientAuthModule interface. Server authentication providers must implement the com.sun.enterprise.security.jauth. ServerAuthModule interface. Client-server providers must implement both interfaces.

Q

query-filter

Specifies the query filter for the CMP 1.1 finder.

Superelements

"finder" on page 93 (sun-ejb-jar.xml)

Subelements

none - contains data

query-method

Specifies a query method.

Superelements

"prefetch-disabled" on page 124 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the query-method element.

TABLE A-88 query-method Subelements

Element	Required	Description
"method-name" on page 117	only one	Specifies a method name.
"method-params" on page 118	only one	Specifies the fully qualified Java type names of method parameters.

query-ordering

Specifies the query ordering for the CMP 1.1 finder.

Superelements

"finder" on page 93 (sun-ejb-jar.xml)

Subelements

none - contains data

Appendix A • Deployment Descriptor Files

query-params

Specifies the query parameters for the CMP 1.1 finder.

Superelements

"finder" on page 93 (sun-ejb-jar.xml)

Subelements

none - contains data

query-variables

Specifies variables in the query expression for the CMP 1.1 finder.

Superelements

"finder" on page 93 (sun-ejb-jar.xml)

Subelements

none - contains data

R

read-only

Specifies that a field is read-only if true. If this element is absent, the default value is false.

Superelements

"cmp-field-mapping" on page 73 (sun-cmp-mappings.xml)

Subelements

none - contains data

realm

Specifies the name of the realm used to process all authentication requests associated with this application. If this element is not specified or does not match the name of a configured realm, the default realm is used. For more information about realms, see "Realm Configuration" in *Sun Java System Application Server Platform Edition 9 Developer's Guide*.

Superelements

```
"sun-application" on page 151 (sun-application.xml), "as-context" on page 59 (sun-ejb-jar.xml)
```

Subelements

none - contains data

refresh-field

Specifies a field that gives the application component a programmatic way to refresh a cached entry.

Superelements

"cache-mapping" on page 66 (sun-web.xml)

Subelements

none

Attributes

The following table describes attributes for the refresh-field element.

TABLE A-89 refresh-field Attributes

Attribute	Default	Description
name	none	Specifies the input parameter name.
scope	request.parameter	(optional) Specifies the scope from which the input parameter is retrieved. Allowed values are context.attribute, request.header, request.parameter, request.cookie, session.id, and session.attribute.

refresh-period-in-seconds

Specifies the rate at which a read-only-bean must be refreshed from the data source. If the value is less than or equal to zero, the bean is never refreshed; if the value is greater than zero, the bean instances are refreshed at the specified interval. This rate is just a hint to the container. Default is 0 (no refresh).

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Subelements

removal-timeout-in-seconds

Specifies the amount of time a bean instance can remain idle in the container before it is removed (timeout). A value of 0 specifies that the container does not remove inactive beans automatically. The default value is 5400.

If removal-timeout-in-seconds is less than or equal to cache-idle-timeout-in-seconds, beans are removed immediately without being passivated.

Applies to stateful session beans.

For related information, see "cache-idle-timeout-in-seconds" on page 65.

Superelements

"bean-cache" on page 61 (sun-ejb-jar.xml)

Subelements

none - contains data

remote-home-impl

Specifies the fully-qualified class name of the generated EJBHome impl class.

Note – This value is automatically generated by the server at deployment or redeployment time. Do not specify it or change it after deployment.

Superelements

"gen-classes" on page 94 (sun-ejb-jar.xml)

Subelements

none - contains data

remote-impl

Specifies the fully-qualified class name of the generated EJBObject impl class.

Note – This value is automatically generated by the server at deployment or redeployment time. Do not specify it or change it after deployment.

Superelements

"gen-classes" on page 94 (sun-ejb-jar.xml)

Subelements

none - contains data

request-policy

Defines the authentication policy requirements of the authentication provider's request processing.

Superelements

"provider-config" on page 127 (sun-acc.xml)

Subelements

none

Attributes

The following table describes attributes for the request-policy element.

TABLE A-90 request-policy Attributes

Attribute	Default	Description
auth-source	none	Specifies the type of required authentication, either sender (user name and password) or content (digital signature).
auth-recipient	none	Specifies whether recipient authentication occurs before or after content authentication. Allowed values are before-content and after-content.

request-protection

Defines the authentication policy requirements of the application's request processing.

Superelements

"message-security" on page 114 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

none

Attributes

The following table describes attributes for the request-protection element.

TABLE A-91 request-protection Attributes

Attribute	Default	Description
auth-source	none	Specifies the type of required authentication, either sender (user name and password) or content (digital signature).
auth-recipient	none	Specifies whether recipient authentication occurs before or after content authentication. Allowed values are before-content and after-content.

required

Specifies whether the authentication method specified must be used for client authentication. The value is true or false.

Superelements

"as-context" on page 59 (sun-ejb-jar.xml)

Subelements

none - contains data

res-ref-name

Specifies the res-ref-name in the corresponding Java EE deployment descriptor file resource-ref entry. The res-ref-name element specifies the name of a resource manager connection factory reference. The name must be unique within an enterprise bean.

Superelements

"resource-ref" on page 136 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

resize-quantity

Specifies the number of bean instances to be:

- Created, if a request arrives when the pool has less than "steady-pool-size" on page 149 quantity
 of beans (applies to pools only for creation). If the pool has more than steady-pool-size minus
 "resize-quantity" on page 135 of beans, then resize-quantity is still created.
- Removed, when the "pool-idle-timeout-in-seconds" on page 123 timer expires and a cleaner thread removes any unused instances.
 - For caches, when "max-cache-size" on page 110 is reached, resize-quantity beans are selected for passivation using the "victim-selection-policy" on page 161. In addition, the "cache-idle-timeout-in-seconds" on page 65 or "removal-timeout-in-seconds" on page 132 timers passivate beans from the cache.
 - For pools, when the "max-pool-size" on page 111 is reached, resize-quantity beans are selected for removal. In addition, the "pool-idle-timeout-in-seconds" on page 123 timer removes beans until steady-pool-size is reached.

Values are from 0 to MAX_INTEGER. The pool is not resized below the steady-pool-size. Default is 16.

Applies to stateless session beans, entity beans, and message-driven beans.

For EJB pools, the value can be defined in the EJB container. Default is 16.

For EJB caches, the value can be defined in the EJB container. Default is 32.

For message-driven beans, the value can be defined in the EJB container. Default is 2.

Superelements

"bean-cache" on page 61, "bean-pool" on page 62 (sun-ejb-jar.xml)

Subelements

none - contains data

resource-adapter-mid

Specifies the module ID of the resource adapter that is responsible for delivering messages to the message-driven bean.

Superelements

"mdb-resource-adapter" on page 112 (sun-ejb-jar.xml)

Subelements

resource-env-ref

Maps the res-ref-name in the corresponding Java EE deployment descriptor file resource-env-ref entry to the absolute indi-name of a resource.

Superelements

```
"sun-web-app" on page 154 (sun-web.xml), "ejb" on page 84 (sun-ejb-jar.xml), "sun-application-client" on page 151 (sun-application-client.xml)
```

Subelements

The following table describes subelements for the resource-env-ref element.

TABLE A-92 resource-env-ref Subelements

Element	Required	Description
"resource-env-ref-name" on page 136	only one	Specifies the res-ref-name in the corresponding Java EE deployment descriptor file resource-env-ref entry.
"jndi-name" on page 100	only one	Specifies the absolute jndi-name of a resource.

Example

```
<resource-env-ref>
  <resource-env-ref-name>jms/StockQueueName</resource-env-ref-name>
  <jndi-name>jms/StockQueue</jndi-name>
</resource-env-ref>
```

resource-env-ref-name

Specifies the res-ref-name in the corresponding Java EE deployment descriptor file resource-env-ref entry.

Superelements

"resource-env-ref" on page 136 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

none - contains data

resource-ref

Maps the res-ref-name in the corresponding Java EE deployment descriptor file resource-ref entry to the absolute jndi-name of a resource.

Note – Connections acquired from JMS connection factories are not shareable in the current release of the Application Server. The res-sharing-scope element in the ejb-jar.xml file resource-ref element is ignored for JMS connection factories.

When resource-ref specifies a JMS connection factory for the Sun Java System Message Queue, the default-resource-principal (name/password) must exist in the Message Queue user repository. Refer to the Security Management chapter in the Sun Java System Message Queue 3 2006Q2 Administration Guide for information on how to manage the Message Queue user repository.

Superelements

```
"sun-web-app" on page 154 (sun-web.xml), "ejb" on page 84 (sun-ejb-jar.xml), "sun-application-client" on page 151 (sun-application-client.xml)
```

Subelements

The following table describes subelements for the resource-ref element.

TABLE A-93 resource-ref Subelements

Element	Required	Description
"res-ref-name" on page 134	only one	Specifies the res-ref-name in the corresponding Java EE deployment descriptor file resource-ref entry.
"jndi-name" on page 100	only one	Specifies the absolute jndi-name of a resource.
"default-resource-principal" on page 82	zero or one	Specifies the default principal (user) for the resource.

Example

```
<resource-ref>
  <res-ref-name>jdbc/EmployeeDBName</res-ref-name>
  <jndi-name>jdbc/EmployeeDB</jndi-name>
</resource-ref>
```

response-policy

Defines the authentication policy requirements of the authentication provider's response processing.

Superelements

```
"provider-config" on page 127 (sun-acc.xml)
```

Subelements

none

Attributes

The following table describes attributes for the response-policy element.

TABLE A-94 response-policy Attributes

Attribute	Default	Description
auth-source	none	Specifies the type of required authentication, either sender (user name and password) or content (digital signature).
auth-recipient	none	Specifies whether recipient authentication occurs before or after content authentication. Allowed values are before-content and after-content.

response-protection

Defines the authentication policy requirements of the application's response processing.

Superelements

"message-security" on page 114 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

none

Attributes

The following table describes attributes for the response-protection element.

TABLE A-95 response-protection Attributes

Attribute	Default	Description
auth-source	none	Specifies the type of required authentication, either sender (user name and password) or content (digital signature).
auth-recipient	none	Specifies whether recipient authentication occurs before or after content authentication. Allowed values are before-content and after-content.

role-name

Contains the role-name in the security-role element of the corresponding Java EE deployment descriptor file.

Superelements

"security-role-mapping" on page 142 (sun-application.xml, sun-web.xml, sun-ejb-jar.xml)

Subelements

none - contains data

S

sas-context

Describes the sas-context fields.

Superelements

"ior-security-config" on page 96 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the sas-context element.

TABLE A-96 sas - context Subelements

Element	Required	Description
"caller-propagation" on page 67	only one	Specifies whether the target accepts propagated caller identities. The values are NONE, SUPPORTED, or REQUIRED.

schema

Specifies the file that contains a description of the database schema to which the beans in this sun-cmp-mappings.xml file are mapped. If this element is empty, the database schema file is automatically generated at deployment time. Otherwise, the schema element names a .dbschema file with a pathname relative to the directory containing the sun-cmp-mappings.xml file, but without the .dbschema extension. See "Automatic Database Schema Capture" in Sun Java System Application Server Platform Edition 9 Developer's Guide.

Superelements

"sun-cmp-mapping" on page 152 (sun-cmp-mappings.xml)

Subelements

Examples

```
<schema/> <!-- use automatic schema generation -->
<schema>CompanySchema</schema> <!-- use "CompanySchema.dbschema" -->
```

schema-generator-properties

Specifies field-specific column attributes in property subelements.

Superelements

"cmp-resource" on page 73 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the schema-generator-properties element.

TABLE A-97 schema-generator-properties Subelements

Element	Required	Description
"property (with subelements)" on page 127	zero or more	Specifies a property name and value.

Properties

The following table describes properties for the schema-generator-properties element.

TABLE A-98 schema-generator-properties Properties

Property	Default	Description
use-unique-table-names	false	Specifies that generated table names are unique within each application server domain. This property can be overridden during deployment. See "Generation Options for CMP" in Sun Java System Application Server Platform Edition 9 Developer's Guide.
bean-name . field-name . attribute	none	Defines a column attribute. For attribute descriptions, see Table A-99.

The following table lists the column attributes for properties defined in the schema-generator-properties element.

TABLE A-99 schema-generator-properties Column Attributes

Attribute	Description
jdbc-type	Specifies the JDBC type of the column created for the CMP field. The actual SQL type generated is based on this JDBC type but is database vendor specific.
jdbc-maximum- length	Specifies the maximum number of characters stored in the column corresponding to the CMP field. Applies only when the actual SQL that is generated for the column requires a length.
	For example, a jdbc-maximum-length of 32 on a CMP String field such as firstName normally results in a column definition such as VARCHAR(32). But if the jdbc-type is CLOB and you are deploying on Oracle, the resulting column definition is CLOB. No length is given, because in an Oracle database, a CLOB has no length.
jdbc-precision	Specifies the maximum number of digits stored in a column which represents a numeric type.
jdbc-scale	Specifies the number of digits stored to the right of the decimal point in a column that represents a floating point number.
jdbc-nullable	Specifies whether the column generated for the CMP field allows null values.

Example

secondary-table

Specifies a bean's secondary table(s).

Superelements

```
"entity-mapping" on page 90 (sun-cmp-mappings.xml)
```

Subelements

The following table describes subelements for the secondary-table element.

TABLE A-100 secondary table Subelements

Element	Required	Description
"table-name" on page 156	only one	Specifies the name of a database table.
"column-pair" on page 76	one or more	Specifies the pair of columns that determine the relationship between two database tables.

security

Defines the SSL security configuration for IIOP/SSL communication with the target server.

Superelements

"target-server" on page 157 (sun-acc.xml)

Subelements

The following table describes subelements for the security element.

TABLE A-101 security Subelements

Element	Required	Description
"ssl" on page 148	only one	Specifies the SSL processing parameters.
"cert-db" on page 67	only one	Not implemented. Included for backward compatibility only.

security-role-mapping

Maps roles to users or groups in the currently active realm. See "Realm Configuration" in Sun Java System Application Server Platform Edition 9 Developer's Guide.

The role mapping element maps a role, as specified in the EJB JAR role-name entries, to a environment-specific user or group. If it maps to a user, it must be a concrete user which exists in the current realm, who can log into the server using the current authentication method. If it maps to a group, the realm must support groups and the group must be a concrete group which exists in the current realm. To be useful, there must be at least one user in that realm who belongs to that group.

Superelements

"sun-application" on page 151 (sun-application.xml), "sun-web-app" on page 154 (sun-web.xml), "sun-ejb-jar" on page 153 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the security-role-mapping element.

TABLE A-102 security-role-mapping Subelements

Element	Required	Description
"role-name" on page 138	only one	Contains the role-name in the security-role element of the corresponding Java EE deployment descriptor file.
"principal-name" on page 125	one or more if no group-name, otherwise zero or more	Contains a principal (user) name in the current realm. In an enterprise bean, the principal must have the run-as role specified.
"group-name" on page 95	one or more if no principal-name, otherwise zero or more	Contains a group name in the current realm.

service-endpoint-interface

Specifies the web service reference name relative to java: comp/env.

Superelements

"port-info" on page 123 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

none - contains data

service-impl-class

Specifies the name of the generated service implementation class.

Superelements

"service-ref" on page 144 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

none - contains data

service-qname

Specifies the WSDL service element that is being referred to.

Superelements

"service-ref" on page 144 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml); "webservice-endpoint" on page 163 (sun-web.xml, sun-ejb-jar.xml)

Subelements

The following table describes subelements for the service-qname element.

TABLE A-103 service-gname subelements

Element	Required	Description
"namespaceURI" on page 119	only one	Specifies the namespace URI.
"localpart" on page 107	only one	Specifies the local part of a QNAME.

service-ref

Specifies runtime settings for a web service reference. Runtime information is only needed in the following cases:

- To define the port used to resolve a container-managed port
- To define the default Stub/Call property settings for Stub objects
- To define the URL of a final WSDL document to be used instead of the one associated with the service-ref in the standard Java EE deployment descriptor

Superelements

```
"sun-web-app" on page 154 (sun-web.xml), "ejb" on page 84 (sun-ejb-jar.xml), "sun-application-client" on page 151 (sun-application-client.xml)
```

Subelements

The following table describes subelements for the service-ref element.

TABLE A-104 service - ref subelements

Element	Required	Description
"service-ref-name" on page 145	only one	Specifies the web service reference name relative to java: comp/env.
"port-info" on page 123	zero or more	Specifies information for a port within a web service reference.
"call-property" on page 66	zero or more	Specifies JAX-RPC property values that can be set on a javax.xml.rpc.Call object before it is returned to the web service client.
"wsdl-override" on page 164	zero or one	Specifies a valid URL pointing to a final WSDL document.
"service-impl-class" on page 143	zero or one	Specifies the name of the generated service implementation class.
"service-qname" on page 143	zero or one	Specifies the WSDL service element that is being referenced.

service-ref-name

Specifies the web service reference name relative to java: comp/env.

Superelements

"service-ref" on page 144 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

none - contains data

servlet

Specifies a principal name for a servlet. Used for the run-as role defined in web-xml.

Superelements

"sun-web-app" on page 154 (sun-web.xml)

Subelements

The following table describes subelements for the servlet element.

TABLE A-105 servlet Subelements

Element	Required	Description
"servlet-name" on page 146	only one	Contains the name of a servlet, which is matched to a servlet-name in web.xml.
"principal-name" on page 125	zero or one	Contains a principal (user) name in the current realm.
"webservice-endpoint" on page 163	zero or more	Specifies information about a web service endpoint.

servlet-impl-class

Specifies the automatically generated name of the servlet implementation class.

Superelements

"webservice-endpoint" on page 163 (sun-web.xml, sun-ejb-jar.xml)

Subelements

none - contains data

servlet-name

Specifies the name of a servlet, which is matched to a servlet-name in web.xml. This name must be present in web.xml.

Superelements

"cache-mapping" on page 66, "servlet" on page 145 (sun-web.xml)

Subelements

none - contains data

session-config

Specifies session configuration information. Overrides the web container settings for an individual web application.

Superelements

"sun-web-app" on page 154 (sun-web.xml)

Subelements

The following table describes subelements for the session-config element.

TABLE A-106 session-config Subelements

Element	Required	Description
"session-manager" on page 146	zero or one	Specifies session manager configuration information.
"session-properties" on page 147	zero or one	Specifies session properties.
"cookie-properties" on page 79	zero or one	Specifies session cookie properties.

session-manager

Specifies session manager information.

Superelements

"session-config" on page 146 (sun-web.xml)

Subelements

The following table describes subelements for the session-manager element.

TABLE A-107 session-manager Subelements

Element	Required	Description
"manager-properties" on page 109	zero or one	Specifies session manager properties.
"store-properties" on page 149	zero or one	Specifies session persistence (storage) properties.

Attributes

The following table describes attributes for the session-manager element.

TABLE A-108 session-manager Attributes

Attribute	Default	Description
persistence-type	memory	(optional) Specifies the session persistence mechanism. Allowed values are memory and file

session-properties

Specifies session properties.

Superelements

"session-config" on page 146 (sun-web.xml)

Subelements

The following table describes subelements for the session-properties element.

TABLE A-109 session-properties Subelements

Element	Required	Description
"property (with attributes)" on page 126	zero or more	Specifies a property, which has a name and a value.

Properties

The following table describes properties for the session-properties element.

TABLE A-110 session-properties Properties

Property	Default	Description
timeoutSeconds	1800	Specifies the default maximum inactive interval (in seconds) for all sessions created in this web module. If set to 0 or less, sessions in this web module never expire.
		If a session-timeout element is specified in the web.xml file, the session-timeout value overrides any timeoutSeconds value. If neither session-timeout nor timeoutSeconds is specified, the timeoutSeconds default is used.
		Note that the session-timeout element in web.xml is specified in minutes, not seconds.
enableCookies	true	Uses cookies for session tracking if set to true.
enableURLRewriting	true	Enables URL rewriting. This provides session tracking via URL rewriting when the browser does not accept cookies. You must also use an encodeURL or encodeRedirectURL call in the servlet or JSP.

ssl

Defines SSL processing parameters.

Superelements

"security" on page 142 (sun-acc.xml)

Subelements

none

Attributes

The following table describes attributes for the SSL element.

TABLE A-111 ssl attributes

Attribute	Default	Description
cert-nickname	none	(optional) The nickname of the server certificate in the certificate database or the PKCS#11 token. In the certificate, the name format is <i>tokenname</i> : <i>nickname</i> . Including the <i>tokenname</i> : part of the name in this attribute is optional.
ssl2-enabled	false	(optional) Determines whether SSL2 is enabled.
ssl2-ciphers	none	(optional) A space-separated list of the SSL2 ciphers used with the prefix + to enable or - to disable. For example, +rc4. Allowed values are rc4, rc4export, rc2, rc2export, idea, des, desede3.

TABLE A-111 ssl attribu	tes (Co	ontinued)
Attribute	Default	Description
ssl3-enabled	true	(optional) Determines whether SSL3 is enabled.
ssl3-tls-ciphers	none	(optional) A space-separated list of the SSL3 ciphers used, with the prefix + to enable or - to disable, for example +SSL_RSA_WITH_RC4_128_MD5. Allowed values are SSL_RSA_WITH_RC4_128_MD5, SSL_RSA_WITH_3DES_EDE_CBC_SHA, SSL_RSA_WITH_DES_CBC_SHA, SSL_RSA_WITH_RC4_40_MD5, SSL_RSA_WITH_NULL_MD5, SSL_RSA_WITH_RC4_128_SHA, and SSL_RSA_WITH_NULL_SHA. Values available in previous releases are supported for backward compatibility.
tls-enabled	true	(optional) Determines whether TLS is enabled.

steady-pool-size

Specifies the initial and minimum number of bean instances that are maintained in the pool. Default is 32. Applies to stateless session beans and message-driven beans.

Superelements

"bean-pool" on page 62 (sun-ejb-jar.xml)

Subelements

none - contains data

store-properties

Specifies session persistence (storage) properties.

Superelements

"session-manager" on page 146 (sun-web.xml)

Subelements

The following table describes subelements for the store-properties element.

TABLE A-112 store-properties Subelements

Element	Required	Description
"property (with attributes)" on page 126	zero or more	Specifies a property, which has a name and a value.

Properties

The following table describes properties for the store-properties element.

TABLE A-113 store-properties Properties

Property	Default	Description
directory	domain-dir/generated/ jsp/j2ee-apps/app-name/ app-name_war	Specifies the absolute or relative pathname of the directory into which individual session files are written. A relative path is relative to the temporary work directory for this web application.
		Applicable only if the persistence-type attribute of the parent "session-manager" on page 146 element is file.

stub-property

Specifies JAX-RPC property values that are set on a <code>javax.xml.rpc.Stub</code> object before it is returned to the web service client. The property names can be any properties supported by the JAX-RPC <code>Stub</code> implementation.

Superelements

"port-info" on page 123 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

The following table describes subelements for the stub-property element.

TABLE A-114 stub-property subelements

Element	Required	Description
"name" on page 119	only one	Specifies the name of the entity.
"value" on page 160	only one	Specifies the value of the entity.

Properties

The following table describes properties for the stub-property element.

TABLE A-115 stub-property properties

Property	Default	Description
jbi-enabled	true	Determines whether the visibility of this endpoint as a Java Business Integration service is enabled or disabled.

Example

<service-ref>
<service-ref-name>service/FooProxy</service-ref-name>
 <port-info>

sun-application

Defines the Application Server specific configuration for an application. This is the root element; there can only be one sun-application element in a sun-application.xml file. See "The sun-application.xml File" on page 43.

Superelements

none

Subelements

The following table describes subelements for the sun-application element.

TABLE A-116 sun-application Subelements

Element	Required	Description
"web" on page 162	zero or more	Specifies the application's web tier configuration.
"pass-by-reference" on page	zero or one	Determines whether EJB modules use pass-by-value or pass-by-reference semantics.
"unique-id" on page 159	zero or one	Contains the unique ID for the application.
"security-role-mapping" on page 142	zero or more	Maps a role in the corresponding Java EE XML file to a user or group.
"realm" on page 130	zero or one	Specifies an authentication realm.

sun-application-client

Defines the Application Server specific configuration for an application client. This is the root element; there can only be one sun-application-client element in a sun-application-client.xml file. See "The sun-application-client.xml file" on page 55.

Superelements

none

Subelements

The following table describes subelements for the sun-application-client element.

TABLE A-117 sun-application-client subelements

Element	Required	Description
"ejb-ref" on page 87	zero or more	Maps the absolute JNDI name to the ejb-ref in the corresponding Java EE XML file.
"resource-ref" on page 136	zero or more	Maps the absolute JNDI name to the resource-ref in the corresponding Java EE XML file.
"resource-env-ref" on page 136	zero or more	Maps the absolute JNDI name to the resource-env-ref in the corresponding Java EE XML file.
"service-ref" on page 144	zero or more	Specifies runtime settings for a web service reference.
"message-destination" on page 113	zero or more	Specifies the name of a logical message destination.
"message-destination-ref" on page 114	zero or more	Specifies the name of a physical message destination.
"java-web-start-access" on page 98	zero or one	Specifies changes to default Java Web Start parameters.

sun-cmp-mapping

Specifies beans mapped to a particular database schema.

Note – A bean cannot be related to a bean that maps to a different database schema, even if the beans are deployed in the same EJB JAR file.

Superelements

"sun-cmp-mappings" on page 153 (sun-cmp-mappings.xml)

Subelements

The following table describes subelements for the sun-cmp-mapping element.

TABLE A-118 sun-cmp-mapping Subelements

Element	Required	Description
"schema" on page 139	only one	Specifies the file that contains a description of the database schema.
"entity-mapping" on page 90	one or more	Specifies the mapping of a bean to database columns.

sun-cmp-mappings

Defines the Application Server specific CMP mapping configuration for an EJB JAR file. This is the root element; there can only be one sun-cmp-mappings element in a sun-cmp-mappings.xml file. See "The sun-cmp-mappings.xml File" on page 51.

Superelements

none

Subelements

The following table describes subelements for the sun-cmp-mappings element.

TABLE A-119 sun - cmp - mappings Subelements

Element	Required	Description
"sun-cmp-mapping" on page 152	one or more	Specifies beans mapped to a particular database schema.

sun-ejb-jar

Defines the Application Server specific configuration for an EJB JAR file. This is the root element; there can only be one sun-ejb-jar element in a sun-ejb-jar.xml file. See "The sun-ejb-jar.xml File" on page 46.

Superelements

none

Subelements

The following table describes subelements for the sun-ejb-jar element.

TABLE A-120 sun-ejb-jar Subelements

Element	Required	Description
"security-role-mapping" on page 142	zero or more	Maps a role in the corresponding Java EE XML file to a user or group.
"enterprise-beans" on page 89	l '	Describes all the runtime properties for an EJB JAR file in the application.

sun-web-app

Defines Application Server specific configuration for a web module. This is the root element; there can only be one sun-web-app element in a sun-web.xml file. See "The sun-web.xml File" on page 43.

Superelements

none

Subelements

The following table describes subelements for the sun-web-app element.

TABLE A-121 sun-web-app Subelements

Element	Required	Description
"context-root" on page 79	zero or one	Contains the web context root for the web application.
"security-role-mapping" on page 142	zero or more	Maps roles to users or groups in the currently active realm.
"servlet" on page 145	zero or more	Specifies a principal name for a servlet, which is used for the run-as role defined in web.xml.
"idempotent-url-pattern" on page 96	zero or more	Enterprise Edition only. Do not use.
"session-config" on page 146	zero or one	Specifies session manager, session cookie, and other session-related information.
"ejb-ref" on page 87	zero or more	Maps the absolute JNDI name to the ejb-ref in the corresponding Java EE XML file.
"resource-ref" on page 136	zero or more	Maps the absolute JNDI name to the resource-ref in the corresponding Java EE XML file.
"resource-env-ref" on page 136	zero or more	Maps the absolute JNDI name to the resource-env-ref in the corresponding Java EE XML file.
"service-ref" on page 144	zero or more	Specifies runtime settings for a web service reference.

 TABLE A-121 sun-web-app Subelements
 (Continued)

Element	Required	Description
"message-destination-ref" on page 114	zero or more	Specifies the name of a physical message destination.
"cache" on page 62	zero or one	Configures caching for web application components.
"class-loader" on page 69	zero or one	Specifies class loader configuration information.
"jsp-config" on page 100	zero or one	Specifies JSP configuration information.
"locale-charset-info" on page 105	zero or one	Deprecated. Use the parameter-encoding subelement of sun-web-app instead.
"property (with attributes)" on page 126	zero or more	Specifies a property, which has a name and a value.
"parameter-encoding" on page 121	zero or one	Determines the default request character encoding and how the web container decodes parameters from forms according to a hidden field value.
"message-destination" on page 113	zero or more	Specifies the name of a logical message destination.
"webservice-description" on page 162	zero or more	Specifies a name and optional publish location for a web service.

Attributes

The following table describes attributes for the sun-web-app element.

TABLE A-122 sun-web-app Attributes

Attribute	Default	Description
error-url	(blank)	(optional) Not implemented. Do not use.
httpservlet-security-provider	none	(optional) Specifies the HttpServlet message layer provider that the web container's servlet auth-constraint processing calls.

Properties

The following table describes properties for the sun-web-app element.

TABLE A-123 sun-web-app Properties

Property	Default	Description
allowLinking	true	If true, resources in this web application that are symbolic links are served.

Property	Default	Description
crossContextAllowed	true	If true, allows this web application to access the contexts of other web applications using the ServletContext. getContext() method.
relativeRedirect Allowed	false	If true, allows this web application to send a relative URL to the client using HttpServletResponse.sendRedirect(), and instructs the web container not to translate any relative URLs to fully qualified ones.
reuseSessionID	false	If true, sessions generated for this web application use the session ID specified in the request.
singleThreaded ServletPoolSize	5	Specifies the maximum number of servlet instances allocated for each SingleThreadModel servlet in the web application.
tempdir	domain-dir/generated/ j2ee-apps/app-name or domain-dir/generated/ j2ee-modules/module-name	Specifies a temporary directory for use by this web module. This value is used to construct the value of the javax.servlet.context.tempdir context attribute. Compiled JSP files are also placed in this directory.
useResponse CTForHeaders	false	If true, response headers are encoded using the response's charset instead of the default (UTF-8).

table-name

Specifies the name of a database table. The table must be present in the database schema file. See "Automatic Database Schema Capture" in Sun Java System Application Server Platform Edition 9 Developer's Guide.

Superelements

"entity-mapping" on page 90, "secondary-table" on page 141 (sun-cmp-mappings.xml)

Subelements

none - contains data

target-server

Specifies the IIOP listener for the target server. A listener is in the form *host:port*, where the *host* is an IP address or host name, and the *port* specifies the port number.

Superelements

"client-container" on page 70 (sun-acc.xml)

Subelements

The following table describes subelements for the target-server element.

TABLE A-124 target - server subelements

Element	Required	Description
"description" on page 83	zero or one	Specifies the description of the target server.
"security" on page 142	zero or one	Specifies the security configuration for the IIOP/SSL communication with the target server.

Attributes

The following table describes attributes for the target-server element.

TABLE A-125 target - server attributes

Attribute	Default	Description
name	none	Specifies the name of the application server instance accessed by the client container.
address	none	Specifies the host name or IP address (resolvable by DNS) of the server to which this client attaches.
port	none	Specifies the naming service port number of the server to which this client attaches. For a new server instance, assign a port number other than 3700. You can change the port number in the Admin Console. Click the Help button in the Admin Console for more information.

tie-class

Specifies the automatically generated name of a tie implementation class for a port component.

Superelements

"webservice-endpoint" on page 163 (sun-web.xml, sun-ejb-jar.xml)

Subelements

none - contains data

timeout

Specifies the "cache-mapping" on page 66 specific maximum amount of time in seconds that an entry can remain in the cache after it is created or refreshed. If not specified, the default is the value of the timeout attribute of the "cache" on page 62 element.

Superelements

"cache-mapping" on page 66 (sun-web.xml)

Subelements

none - contains data

Attributes

The following table describes attributes for the timeout element.

TABLE A-126 timeout Attributes

Attribute	Default	Description
name	none	Specifies the timeout input parameter, whose value is interpreted in seconds. The field's type must be java.lang.Long or java.lang.Integer.
scope	request.attribute	(optional) Specifies the scope from which the input parameter is retrieved. Allowed values are context.attribute, request.header, request.parameter, request.cookie, request.attribute, and session.attribute.

transport-config

Specifies the security transport information.

Superelements

"ior-security-config" on page 96 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the transport-config element.

TABLE A-127 transport-config Subelements

Element	Required	Description
"integrity" on page 96	only one	Specifies if the target supports integrity-protected messages. The values are NONE, SUPPORTED, or REQUIRED.
"confidentiality" on page 76	only one	Specifies if the target supports privacy-protected messages. The values are NONE, SUPPORTED, or REQUIRED.
"establish-trust-in-target" on page 91	only one	Specifies if the target is capable of authenticating <i>to</i> a client. The values are NONE, SUPPORTED, or REQUIRED.
"establish-trust-in-client" on page 91	only one	Specifies if the target is capable of authenticating a client. The values are NONE, SUPPORTED, or REQUIRED.

transport-guarantee

Specifies that the communication between client and server is NONE, INTEGRAL, or CONFIDENTIAL.

- NONE means the application does not require any transport guarantees.
- INTEGRAL means the application requires that the data sent between client and server be sent in such a way that it can't be changed in transit.
- CONFIDENTIAL means the application requires that the data be transmitted in a fashion that prevents other entities from observing the contents of the transmission.

In most cases, a value of INTEGRAL or CONFIDENTIAL indicates that the use of SSL is required.

Superelements

"webservice-endpoint" on page 163 (sun-web.xml, sun-ejb-jar.xml)

Subelements

none - contains data

U

unique-id

Contains the unique ID for the application. This value is automatically updated each time the application is deployed or redeployed. Do not edit this value.

Superelements

"sun-application" on page 151 (sun-application.xml), "enterprise-beans" on page 89 (sun-ejb-jar.xml)

Subelements

none - contains data

url-pattern

Specifies a servlet URL pattern for which caching is enabled. See the Servlet 2.4 specification section SRV. 11.2 for applicable patterns.

Superelements

"cache-mapping" on page 66 (sun-web.xml)

Subelements

none - contains data

use-thread-pool-id

Specifies the thread pool from which threads are selected for remote invocations of this bean.

Superelements

"ejb" on page 84 (sun-ejb-jar.xml)

Subelements

none - contains data

۷

value

Specifies the value of the entity.

Superelements

"call-property" on page 66, "stub-property" on page 150 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml); "property (with subelements)" on page 127 (sun-ejb-jar.xml)

Subelements

none - contains data

vendor

Specifies the name of the vendor as it appears in Java Web Start download and launch screens. The default value is Application Client.

Superelements

"java-web-start-access" on page 98 (sun-application-client.xml)

Subelements

none - contains data

victim-selection-policy

Specifies how stateful session beans are selected for passivation. Possible values are First In, First Out (FIFO), Least Recently Used (LRU), Not Recently Used (NRU). The default value is NRU, which is actually pseudo-LRU.

Note – You cannot plug in your own victim selection algorithm.

The victims are generally passivated into a backup store (typically a file system or database). This store is cleaned during startup, and also by a periodic background process that removes idle entries as specified by removal-timeout-in-seconds. The backup store is monitored by a background thread (or sweeper thread) to remove unwanted entries.

Applies to stateful session beans.

Superelements

"bean-cache" on page 61 (sun-ejb-jar.xml)

Subelements

none - contains data

Example

<victim-selection-policy>LRU</victim-selection-policy>

If both SSL2 and SSL3 are enabled, the server tries SSL3 encryption first. If that fails, the server tries SSL2 encryption. If both SSL2 and SSL3 are enabled for a virtual server, the server tries SSL3 encryption first. If that fails, the server tries SSL2 encryption.



web

Specifies the application's web tier configuration.

Superelements

"sun-application" on page 151 (sun-application.xml)

Subelements

The following table describes subelements for the web element.

TABLE A-128 web Subelements

Element Required [Description	
"web-uri" on page 162	only one	Contains the web URI for the application.	
"context-root" on page 79	only one	Contains the web context root for the application.	

web-uri

Contains the web URI for the application. Must match the corresponding element in the application.xml file.

Superelements

"web" on page 162 (sun-application.xml)

Subelements

none - contains data

webservice-description

Specifies a name and optional publish location for a web service.

Superelements

"sun-web-app" on page 154 (sun-web.xml), "enterprise-beans" on page 89 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the webservice-description element.

TABLE A-129 webservice-description subelements

Element	Required	Description
"webservice-description-name" on page 163	only one	Specifies a unique name for the web service within a web or EJB module.
"wsdl-publish-location" on page 165	zero or one	Specifies the URL of a directory to which a web service's WSDL is published during deployment.

webservice-description-name

Specifies a unique name for the web service within a web or EJB module.

Superelements

"webservice-description" on page 162 (sun-web.xml, sun-ejb-jar.xml)

Subelements

none - contains data

webservice-endpoint

Specifies information about a web service endpoint.

Superelements

"servlet" on page 145 (sun-web.xml), "ejb" on page 84 (sun-ejb-jar.xml)

Subelements

The following table describes subelements for the webservice-endpoint element.

Appendix A • Deployment Descriptor Files

TABLE A-130 webservice-endpoint subelements

Element	Required	Description	
"port-component-name" on page 123	only one	Specifies a unique name for a port component within a web or EJB module.	
"endpoint-address-uri" on page 88	zero or one	Specifies the automatically generated endpoint address.	
"login-config" on page 108	zero or one	Specifies the authentication configuration for an EJB web service endpoint.	
"message-security-binding" on page 115	zero or one	Specifies a custom authentication provider binding.	
"transport-guarantee" on page 159	zero or one	Specifies that the communication between client and server is NONE, INTEGRAL, or CONFIDENTIAL.	
"service-qname" on page 143	zero or one	Specifies the WSDL service element that is being referenced.	
"tie-class" on page 157	zero or one	Specifies the automatically generated name of a tie implementation class for a port component.	
"servlet-impl-class" on page 145	zero or one	Specifies the automatically generated name of the generated servlet implementation class.	
"debugging-enabled" on page 81	zero or one	Specifies whether the debugging servlet is enabled for this web service endpoint. Allowed values are true and false (the default).	
"property (with attributes)" on page 126 (sun-web.xml)	zero or more	Specifies a property, which has a name and a value.	
"property (with subelements)" on page 127 (sun-ejb-jar.xml)			

wsdl-override

Specifies a valid URL pointing to a final WSDL document. If not specified, the WSDL document associated with the service-ref in the standard Java EE deployment descriptor is used.

Superelements

"service-ref" on page 144 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

none - contains data

Example

// available via HTTP
<wsdl-override>http://localhost:8000/myservice/myport?WSDL</wsdl-override>

```
// in a file
<wsdl-override>file:/home/user1/myfinalwsdl.wsdl</wsdl-override>
```

wsdl-port

Specifies the WSDL port.

Superelements

"port-info" on page 123 (sun-web.xml, sun-ejb-jar.xml, sun-application-client.xml)

Subelements

The following table describes subelements for the wsdl-port element.

TABLE A-131 wsdl-port subelements

Element	Required	Description
"namespaceURI" on page 119 only one		Specifies the namespace URI.
"localpart" on page 107	only one	Specifies the local part of a QNAME.

wsdl-publish-location

Specifies the URL of a directory to which a web service's WSDL is published during deployment. Any required files are published to this directory, preserving their location relative to the module-specific WSDL directory (META-INF/wsdl or WEB-INF/wsdl).

Superelements

"webservice-description" on page 162 (sun-web.xml, sun-ejb-jar.xml)

Subelements

none - contains data

Example

Suppose you have an ejb. jar file whose webservices.xml file's wsdl-file element contains the following reference:

META-INF/wsdl/a/Foo.wsdl

Suppose your sun-ejb-jar file contains the following element:

Appendix A · Deployment Descriptor Files

<wsdl-publish-location>file:/home/user1/publish</wsdl-publish-location>

The final WSDL is stored in /home/user1/publish/a/Foo.wsdl.

Index

A	asadmin deploy command (Continued)			
ACC clients	force option, 30			
deploying, 37-40	precompilejsp option, 36			
module definition, 18	asadmin deploydir command, 32-33, 34			
preparing the client machine, 39	asadmin get-client-stubs command, 37, 38			
activation-config element, 57-58	asenv.conf file, 39			
activation-config-property element, 58	assembly			
activation-config-property-name element, 58	of EJB components, 24			
activation-config-property-value element, 58-59	overview, 17-23			
address attribute, 157	auth-layer attribute,116			
Admin Console	auth-method element, 59			
using for deployment, 35	auth-realm element, 60			
using for dynamic reloading, 31	auth-recipient attribute, 133, 134, 138			
using for lifecycle module deployment, 37	auth-source attribute, 133, 134, 138			
using to disable modules and applications, 30	authentication, realm, 60			
agent attribute, 106	autodeployment, 31-32			
allowLinking property, 155	availability-enabled attribute, 86			
annotation, 21				
Apache Ant				
and deployment descriptor verification, 25, 27				
appclient script, 38	В			
application-client.xml file, 22	BaseCache cacheClassName value, 64			
application.xml file, 21	bean-cache element, 61			
applications	bean-pool element, 62			
See also modules	BoundedMultiLruCache cacheClassName value, 64			
definition, 19-21				
deployment plan, 33				
directory structure, 23				
disabling, 30	C			
naming, 22-23	cache element, 62-64			
redeploying, 29	cache-helper element, 64-65			
as-context element, 59	cache-helper-ref element, 65			
asadmin create-lifecycle-module command, 37	cache-idle-timeout-in-seconds element, 65			
asadmin deploy command, 34	cache-mapping element, 66			

cache-on-match attribute, 78, 79	cookieComment property, 80
cache-on-match-failure attribute, 78, 79	cookieDomain property, 80
cacheClassName property, 63, 64	cookieMaxAgeSeconds property, 80
CacheHelper interface, 64	cookiePath property, 80
cacheKeyGeneratorAttrName property, 82	create-tables-at-deploy element, 80
call-property element, 66-67	crossContextAllowed property, 156
caller-propagation element, 67	
cert-db element, 67-68	
cert-nickname attribute, 148	
charset attribute, 106	D
check-all-at-commit element, 68	database-vendor-name element, 81
check-modified-at-commit element, 68	.dbschema file, 24
check-version-of-accessed-instances element, 68	debugging-enabled element, 81
checkInterval property, 101	default-charset attribute, 121
checkpoint-at-end-of-method element, 69	default-client-provider attribute, 116
checkpointed-methods element, 69	default element, 81-82
class loader delegation model, 70	default-helper element, 82
class-loader element, 69-70	default-locale attribute, 106
class-name attribute, 65, 126, 128	default-provider attribute, 116
classdebuginfo property, 101	default-resource-principal element, 82-83
classname attribute, 60	delegate attribute, 70
classpath property, 101	delegation model for classloaders, 70
client-container element, 70	deployment
client-credential element, 71-72	directory deployment, 32-33, 34
client JAR file, 38	disabling deployed applications and modules, 30
cmp element, 72	dynamic, 29, 30
cmp-field-mapping element, 73	errors during, 29
cmp-resource element, 73-74	forcing, 30
cmr-field-mapping element, 74	JSR 88, 23, 34
cmr-field-name element, 75	life cycle, 29
cmt-timeout-in-seconds element, 75	module or application based, 35
column-name element, 75	of ACC clients, 37-40
column-pair element, 76	of connectors, 40
commit-option element, 76	of EJB components, 37
compiler property, 101	of lifecycle modules, 37
compilerSourceVM property, 101	of web applications, 36
compilerTargetVM property, 102	overview, 17-23
confidentiality element, 76	redeployment, 30
connectors	standard Java EE descriptors, 21-22
deploying, 40	Sun Java System Application Server descriptors, 22,
module definition, 18	41-42
consistency element, 77	tools for, 34-35
constraint-field element, 77-78	undeploying an application or module, 35
constraint-field-value element, 78-79	using the Admin Console, 35
context-root element, 79	verifying descriptor correctness, 24-28
cookie-properties element, 79-80	deployment plan, 33
* * * * * * * * * * * * * * * * * * *	1 / 1 '

description element, 83 development property, 102 directory deployment, 32-33, 34 directory property, 150 dispatcher element, 83		extra-class-path attribute, 70
domain.xml file, keeping stubs, 37 drop-tables-at-undeploy element, 84 DTD files, 41 location of, 41 dumpSmap property, 102 dynamic deployment, 30 reloading, 31 dynamic deployment, 29 dynamic-reload-interval attribute, 70	fetched-with element, 92 field-name element, 93 finder element, 93 flush-at-end-of-method element, 94 forcing deployment, 30 fork property, 102 form-hint-field attribute, 121	
E EJB components assembling, 24 deploying, 37 elements, 89-90 generated source code, 37 module definition, 18		genStrAsCharArray property, 102 getDeploymentManager method, URI for, 34 getParameter method, 121 getReader method, 121 group-name element, 95 groups in realms, 142
ejb element, 84-87 ejb-jar.xml file, 22 ejb-name element, 87 ejb-ref element, 87-88 ejb-ref-name element, 88 elements in XML files, 89-90 eligible element, 88		H http-method element, 95 httpservlet-security-provider attribute, 155
enableCookies property, 148 enabled attribute, 63 enablePooling property, 102 enableTldValidation property, 102 enableURLRewriting property, 148 encoding, of JSP files, 102 endpoint-address-uri element, 88-89 enterprise-beans element, 89 entity-mapping element, 90 error-url attribute, 155 errorOnUseBeanInvalidClassAttribute property, errors during deployment, 29 establish-trust-in-client element, 91 establish-trust-in-target element, 91	102	idempotent-url-pattern element, 96 ieClassId property, 102 ignoreHiddenJarFiles property, 70 IIOP/SSL configuration, 142 initialCapacity property, 102 integrity element, 96 ior-security-config element, 96 is-cache-overflow-allowed element, 97 is-failure-fatal attribute, 37 is-one-one-cmp element, 97 is-read-only-bean element, 97

J	lock-when-modified element, 107			
JAR Extension Mechanism Architecture, 24	log-file attribute, 108			
JAR file, client for a deployed application, 38	log-service element, 108			
java-config element, 37	login-config element, 108-109			
Java EE, standard deployment descriptors, 21-22	LruCache cacheClassName value, 64			
Java Message Service, See JMS	Era-daene caene chassivame variae, 101			
java-method element, 98				
Java Web Start, 37-40				
java-web-start-access element, 98-99	M			
javaEncoding property, 102				
jbi-enabled property, 150	manager-properties element, 109-110			
JMS, 82	mappedfile property, 102			
jms-durable-subscription-name element, 99	mapping-properties element, 110			
jms-max-messages-load, 99	match-expr attribute, 79			
JNDI, lookup names for EJB components, 23	max-cache-size element, 110			
jndi-name element, 100	max-entries attribute, 63			
jsp-config element, 36, 100-103	max-pool-size element, 111			
JSP files	max-wait-time-in-millis element, 111			
configuring, 100-103	maxSessions property, 110			
encoding of, 102	MaxSize property, 64			
generated source code, 36	mdb-connection-factory element, 111			
•	mdb-resource-adapter element, 112			
precompiling, 36	message-destination element, 113			
JSR 88 deployment, 23, 34	message-destination-name element, 113			
	message-destination-ref element, 114			
	message-destination-ref-name element, 114			
K	-			
	message element, 112-113			
-keepgenerated flag, 36,37	message-security-binding element, 115-116			
keepgenerated property, 102	message-security-config element, 116-117			
key-field element, 103-104	message-security element, 114-115			
	method element, 117			
	method-intf element, 117			
I	method-name element, 117-118			
-	method-param element, 118			
level attribute, 108	method-params element, 118			
level element, 104	modificationTestInterval property, 103			
lib directory	modules			
and ACC clients, 39	See also applications			
DTD file location, 41	definition, 18-19			
libraries, 40	directory structure, 23			
lifecycle modules, deploying, 37	disabling, 30			
locale attribute, 106	individual deployment of, 35			
locale-charset-info element, 105-106	naming, 22			
locale-charset-map element, 106-107	•			
localpart element, 107	MultiLruCache cacheClassName value, 64			
lock-when-loaded element, 107	MultiLRUSegmentSize property, 64			

name element, 119 named-group element, 119 namespaceURI element, 119 NetBeans, using for assembly, 24 none element, 120

0

one-one-finders element, 120 operation-name element, 120

P

package-appclient script, 39 packaging, See assembly parameter-encoding element, 121 pass-by-reference element, 121-122 pass-by-value semantics, 121 password element, 122 path attribute, 68 persistence-type attribute, 147 plugin tag, 102 pm-descriptors element, 123 pool-idle-timeout-in-seconds element, 123 port attribute, target-server element, 157 port-component-name element, 123 port-info element, 123-124 --precompilejsp option, 36 prefetch-disabled element, 124 principal element, 125 principal-name element, 125-126 properties about, 126-127, 127 property element, 126-127, 127 provider-config element, 127-128 provider-id attribute, 116, 128 provider-type attribute, 128

0

query-filter element, 129 query-method element, 129

query-ordering element, 129 query-params element, 130 query-variables element, 130

R

ra.xml file, 22 read-only element, 130 realm attribute, 72 realm element, 130-131 realms, 60 mapping groups and users to, 142 reapIntervalSeconds property, 110 redeploying applications, 29 redeployment, 30 refresh-field element, 131 refresh-period-in-seconds element, 131 relativeRedirectAllowed property, 156 .reload file, 31 reloading, dynamic, 31 removal-timeout-in-seconds element, 132 request-policy element, 133 request-protection element, 133-134 required element, 134 res-ref-name element, 134 resize-quantity element, 135 resource-adapter-mid element, 135 resource-env-ref element, 136 resource-env-ref-name element, 136 resource-ref element, 136-137 response-policy element, 137-138 response-protection element, 138 reuseSessionID property, 156 rmic-options attribute, 37 role-name element, 138-139

S

sas-context element, 139 schema element, 139 schema example, 52 schema-generator-properties element, 140-141 scope attribute, 78, 104, 131, 158 scratchdir property, 103

secondary table, 73
secondary-table element, 141
security element, 142
security-role-mapping element, 142-143
send-password attribute, 71
server
lib directory of, 39, 41
Sun Java System Application Server deployment
descriptors, 22,41-42
service-endpoint-interface element, 143
service-impl-class element, 143
service-qname element, 143-144
service-ref element, 144-145
service-ref-name element, 145
servlet element, 145
servlet-impl-class element, 145
servlet-name element, 146
session-config element, 146
session-manager element, 146-147
session-properties element, 147-148
session-timeout element, 148
sessionFilename property, 110
sessions
and dynamic redeployment, 30
and dynamic reloading, 31
singleThreadedServletPoolSize property, 156
ssl element, 148-149
ssl2-ciphers attribute, 148
ssl2-enabled attribute, 148
ssl3-enabled attribute, 149
ssl3-tls-ciphers attribute, 149
steady-pool-size element, 149
store-properties element, 149-150
stub-property element, 150-151
stubs
keeping, 37
retrieving after deployment, 37
sun-acc.xml file, 39, 42
elements in, 57
sun-application_5_0-0.dtd file, 42
sun-application-client_5_0-0.dtd file, 42
sun-application-client-container_1_2.dtd file, 42
sun-application-client element, 151-152
sun-application-client.xml file, 42
elements in, 55-56

sun-application element, 151 sun-application.xml file, 42 elements in, 43 example of, 43 sun-cmp-mapping_1_2.dtd file, 42 sun-cmp-mapping element, 152 sun-cmp-mappings element, 153 sun-cmp-mappings.xml file, 42 elements in, 51-55 example of, 53 sun-ejb-jar_3_0-0.dtd file, 42 sun-ejb-jar element, 153-154 sun-ejb-jar.xml file, 42 elements in, 46-51 example of, 50 Sun Java System Message Queue, 82 sun-web-app_2_5-0.dtd file, 42 sun-web-app element, 154-156 sun-web.xml file, 36, 42 elements in, 43-46 example of, 46 suppressSmap property, 103

т

table-name element, 156
tempdir property, 156
tie-class element, 157
timeout element, 158
timeout-in-seconds attribute, 63
timeoutSeconds property, 148
tls-enabled attribute, 149
tools, for deployment, 34-35
transport-config element, 158
transport-guarantee element, 159
trimSpaces property, 103

U

unique-id element, 159-160 URI, configuring for an application, 162 url-pattern element, 160 use-thread-pool-id element, 160 use-unique-table-names property, 140

example of, 56

usePrecompiled property, 103 user-name attribute, 72 useResponseCTForHeaders property, 156 users in realms, 142 utility classes, 24, 40

٧

value attribute, 127 value element, 160-161 vendor element, 161 verifier tool, 24-28 victim-selection-policy element, 161

W

web applications
deploying, 36
module definition, 18
web element, 162
web services
debugging, 81
deployment, 36
web-uri element, 162
web.xml file, 22
webservice-description element, 162-163
webservice-description-name element, 163
webservice-endpoint element, 163-164
wsdl-override element, 164-165
wsdl-publish-location element, 165-166

X

XML specification, 42 XML syntax verifier, 25 xpoweredBy property, 103