TIP132
TIP135 TIP137

COMPLEMENTARY SILICON POWER DARLINGTON TRANSISTORS

- STMicroelectronics PREFERRED SALESTYPES



TO-220

APPLICATION

- LINEAR AND SWITCHING INDUSTRIAL EQUIPMENT

DESCRIPTION

The TIP132 is a silicon Epitaxial-Base NPN power transistor in monolithic Darlington configuration, mounted in Jedec TO-220 plastic package. It is intented for use in power linear and switching applications.

The complementary PNP type is TIP137 .

Also TIP135 is a PNP type.

INTERNAL SCHEMATIC DIAGRAM



R_1 Typ. = 5 KΩ R_2 Typ. = 150 Ω

ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter		Value		Unit
		NPN		TIP132	
		PNP	TIP135	TIP137	
V_{CBO}	Collector-Base Voltage (I_E = 0)		60	100	V
V_{CEO}	Collector-Emitter Voltage (I_B = 0)		60	100	V
V_{EBO}	Emitter-Base Voltage (I_C = 0)		5		V
I_C	Collector Current		8		A
I_{CM}	Collector Peak Current		12		A
I_B	Base Current		0.3		A
P_{tot}	Total Dissipation at $T_{case} \leq 25\ ^oC$ $T_{amb} \leq 25\ ^oC$		70 2		W W
T_{stg}	Storage Temperature		-65 to 150		^oC
T_j	Max. Operating Junction Temperature		150		^oC

* For PNP types voltage and current values are negative.

THERMAL DATA

$R_{thj\text{-}case}$	Thermal Resistance Junction-case	Max	1.78	°C/W
$R_{thj\text{-}amb}$	Thermal Resistance Junction-ambient	Max	63.5	°C/W

ELECTRICAL CHARACTERISTICS (T_{case} = 25 °C unless otherwise specified)

Symbol	Parameter	Test Conditions		Min.	Typ.	Max.	Unit
I_{CEO}	Collector Cut-off Current (I_B = 0)	V_{CE} = Half Rated V_{CEO}				0.5	mA
I_{CBO}	Collector Cut-off Current (I_E = 0)	V_{CB} = Rated V_{CBO}				0.2	mA
I_{EBO}	Emitter Cut-off Current (I_C = 0)	V_{EB} = 5 V				5	mA
$V_{CEO(sus)}$*	Collector-Emitter Sustaining Voltage (I_B = 0)	I_C = 30 mA for **TIP135** for **TIP132/TIP137**		 60 100			 V V
$V_{CE(sat)}$*	Collector-Emitter Saturation Voltage	I_C = 4 A I_C = 6 A	I_B = 16 mA I_B = 30 mA			2 4	V V
V_{BE}*	Base-Emitter Voltage	I_C = 4 A	V_{CE} = 4 V			2.5	V
h_{FE}*	DC Current Gain	I_C = 1 A I_C = 4 A	V_{CE} = 4 V V_{CE} = 4 V	500 1000		 15000	

∗ Pulsed: Pulse duration = 300 µs, duty cycle 1.5 %
For PNP types voltage and current values are negative.

Safe Operating Areas



Power Derating Curve



TO-220 MECHANICAL DATA

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	4.40		4.60	0.173		0.181
C	1.23		1.32	0.048		0.051
D	2.40		2.72	0.094		0.107
D1		1.27			0.050	
E	0.49		0.70	0.019		0.027
F	0.61		0.88	0.024		0.034
F1	1.14		1.70	0.044		0.067
F2	1.14		1.70	0.044		0.067
G	4.95		5.15	0.194		0.203
G1	2.4		2.7	0.094		0.106
H2	10.0		10.40	0.393		0.409
L2		16.4			0.645	
L4	13.0		14.0	0.511		0.551
L5	2.65		2.95	0.104		0.116
L6	15.25		15.75	0.600		0.620
L7	6.2		6.6	0.244		0.260
L9	3.5		3.93	0.137		0.154
DIA.	3.75		3.85	0.147		0.151



P011C