

Change Log

Date	Changed by	Version	Change Description
25 APR 2022	Nontawat.K	1.0	Initial version
23 MAY 2022	Nontawat.K	1.1.0	Update Follow Contact API
25 MAY 2022	Nontawat.K	1.1.1	Update Notification API
03 JAN 2023	Nontawat.K	1.1.2	Update Notification V3 API (Broadcast, Dynamic, Bulk)
01 SEP 2023	Nontawat.K	1.2.0	Update All API Route to V 3, Spam-Unspam and logout as spam
07 FEB 2024	Nontawat.K	1.2.1	Update API Verification, Notification message of Line, Facebook Get tags list
	Nontawat.K	1.2.2	Notification by Bulk, Dynamic with Social Id

API Specification

Verification , Update Contact and Tags,
Spam

Command: System tags

Description: Callback after verification success.

Methods: POST

URL: https://open-api.chatcone.com/v3/verify/system_tags

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String	Mandatory key for using API	-
channel_key	String	Verification channel for their follower	* Available for Line and Facebook Channel only

Body

Parameter	Type	Description	Remark
line_id or fb_id	String	Social id from Line or Facebook	-
(A1)system_tags	Object	Verification channel for their follower	-

(A1) system_tags objects

Parameter	Type	Description	Remark
customer_id	String	Api name of customer id in chatcone api setting page	Ex. cx00001
customer_type	string	Api name of customer type in chatcone api setting page	Ex. verified

Request Example

```
curl --location -g --request POST 'https://open-api.chatcone.com/v3/verify/system_tags' \
--header 'channel_key: xxx' \
--header 'api_key: yyy' \
--header 'Content-Type: application/json' \
--data-raw '{
  "line_id": "AAA",
  "system_tags": {
    "customer_id": "cx00001",
    "customer_type": "verified"
  }
}'
```

Response Example

```
{"response_status":{"code":"00000","operation":"","message":"","message_type":"","status":"SUCCESS"},"result":"system_tags"}
```

Command: Logout

Description: Set a user to logout.

Methods: POST

URL: <https://open-api.chatcone.com/v3/verify/logout>

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String	Mandatory key for using API	-
channel_key	String	Verification channel for their follower	* Available for Line and Facebook Channel only
line_id or fb_id	String	Social id from Line or Facebook	

Body

Parameter	Type	Description	Remark
is_spam	Boolean	Flag for marking as spam when logged out	Default = false , Not required Ex. true

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/verify/logout' \  
--header 'channel_key: xxx' \  
--header 'api_key: yyy' \  
--header 'line_id: xxxxxxxxxxxx' \  
--data '{ "is_spam":true }'
```

Response Example

```
{"response_status":{"code":"200","operation":"verify_logout","message":"","message_type":"Information","status":"SUCCESS"},"result":{"success":1}}
```

Command: Contact Description & Tags

Description: Update user's contact description & tags.

Methods: POST

URL: <https://open-api.chatcone.com/v3/verify/contact>

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String	Mandatory key for using API	-
channel_key	String	Verification channel for their follower	* Available for Line and Facebook Channel only

Body

Parameter	Type	Description	Remark
customer_id	String	Api name of customer id in chatcone api setting page	-
contact_description	Object	Object that contain key of contact description	Not required but if attaching the field, it should contain a key value for updating. Ex. { first_name: "AAA",last_name: "BBB" }
tag_name	Array	Array data of key tags	Not required but if attaching the field with the empty body array, it will replace all the old tags. Ex. ["VIP", "Sales", "Promotion"]

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/verify/contact' \  
--header 'channel_key: xxx' \  
--header 'api_key: yyy' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
  "customer_id":"cx001",  
  "contact_description":{  
    "first_name":"AAA",  
    "last_name":"BBB"  
  },  
  "tag_name":[  
    "VIP",  
    "Sales",  
    "Promotion",  
  ]  
'
```

Response Example

```
{"response_status":{"code":"200","operation":"service_verify_contact","message":"","message_type":"Information","status":"SUCCESS"},"result":{"tags":[{"customer_id":"cx001","success":24,"failed":0,"failed_result":[]}]}}
```

Command: Contact Description & Tags (Bulk)

Description: Multiple update user's contact description & tags.

Methods: POST

URL: <https://open-api.chatcone.com/v3/verify/contact/bulk>

Remark: The headers, body are the same as command Contact Description & Tags but the body send its as Array

Limit only 10 data per request

Ex.

```
{
  data: [{
    "customer_id": "cx001",
    "contact_description": {
      "first_name": "AAA",
      "last_name": "BBB"
    },
    "tag_name": [
      "VIP",
      "Sales",
      "Promotion",
    ]
  }, {
    "customer_id": "cx002",
    "contact_description": {
      "first_name": "CCC",
      "last_name": "DDD"
    },
    "tag_name": [
      "Normal",
      "Closed",
    ]
  }
]
```

Command: (Follower) Contact Description & Tags

Description: Update follower's contact description & tags.

Methods: POST

URL: <https://open-api.chatcone.com/v3/follower/contact>

Remark: No required verified user

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String	Mandatory key for using API	-
channel_key	String	Verification channel for their follower	* Available for Line and Facebook Channel only

Body

Parameter	Type	Description	Remark
social_id	String	Social id from social channel (Line, Facebook)	-
contact_description	Object	Object that contain key of contact description	Not required but if attaching the field, it should contain a key value for updating. Ex. { first_name: "AAA",last_name: "BBB" }
tag_name	Array	Array data of key tags	Not required but if attaching the field with the empty body array, it will replace all the old tags. Ex. ["VIP", "Sales", "Promotion"]

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/follower/contact' \
--header 'channel_key: xxx' \
--header 'api_key: yyy' \
--header 'Content-Type: application/json' \
--data-raw '{
  "social_id":"UXXXXXXXXXXXXX",
  "contact_description":{
    "first_name":"AAA",
    "last_name":"BBB"
  },
  "tag_name":[
    "VIP",
    "Sales",
    "Promotion",
  ]
}'
```

Response Example

```
{"response_status":{"code":"200","operation":"service_follower_contact","message":"","message_type":"Information","status":"SUCCESS"},"result":{"tags":[{"social_id":"UXXXXXXXXXXXXX","success":3,"failed":0,"failed_result":[]}]}}
```

Command: (Follower) Contact Description & Tags (Bulk)

Description: Multiple update follower's contact description & tags.

Methods: POST

URL: <https://open-api.chatcone.com/v3/follower/contact/bulk>

Remark: No required verified user and the headers, body are the same as command (Follower) Contact Description & Tags but the body send its as Array

Limit only 10 data per request

Ex.

```
{
  data: [{
    "social_id": "UXXXXXXXXXXXXXXXX",
    "contact_description": {
      "first_name": "AAA",
      "last_name": "BBB"
    },
    "tag_name": [
      "VIP",
      "Sales",
      "Promotion",
    ]
  }, {
    "social_id": "UYYYYYYYYYYYYYYYY",
    "contact_description": {
      "first_name": "CCC",
      "last_name": "DDD"
    },
    "tag_name": [
      "Normal",
      "Closed",
    ]
  }
]
```

Command: Upgrade Customer Type

Description: Upgrade user's customer type.

Methods: POST

URL: <https://open-api.chatcone.com/v3/verify/contact/upgrade>

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String	Mandatory key for using API	-
channel_key	String	Verification channel for their follower	* Available for Line and Facebook Channel only

Body

Parameter	Type	Description	Remark
system_tags	Object	Object that contain Customer Id and Customer Type key's name from API Setting	-
contact_description	Object	Object that contain key of contact description	Not required but if attaching the field, it should contain a key value for updating. Ex. { first_name: "AAA",last_name: "BBB" }
tag_name	Array	Array data of key tags	Not required but if attaching the field with the empty body array, it will replace all the old tags. Ex. ["VIP", "Sales", "Promotion"]

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/verify/contact/upgrade' \  
--header 'channel_key: xxx' \  
--header 'api_key: yyy' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
  "system_tags": {  
    "customer_id ": "cx001",  
    "customer_type ": "verified"  
  },  
  "contact_description":{  
    "first_name":"AAA",  
    "last_name":"BBB"  
  },  
  "tag_name":[  
    "VIP",  
    "Sales",  
    "Promotion",  
  ]  
'
```

Response Example

```
{"response_status":{"code":"00000","operation":"","message":"","message_type":"","status":"SUCCESS"},"result":"upgrade_system_tags"}
```

Command: Spam (Verified customer)

Description: Mark as spam for verified customer

Methods: POST

URL: <https://open-api.chatcone.com/v3/verify/contact/spam>

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String	Mandatory key for using API	-
channel_key	String	Verification channel for their follower	* Available for Line and Facebook Channel only

Body

Parameter	Type	Description	Remark
customer_id	Array	Api name of customer id in chatcone api setting page	Ex. ['cx001','cx002']

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/verify/contact/spam \
--header 'channel_key: xxx'\
--header 'api_key: yyy'\
--header 'Content-Type: application/json' \
--data-raw '{
  "customer_id": [
    "cx001",
    "cx002"
  ]
}'
```

Response Example

```
{"response_status":{"code":"200","operation":"service_verify_contact_spam","message":"","message_type":"Information","status":"SUCCESS"},"result":{"complete":2}}
```

Command: Unspam (Verified customer)

Description: Mark as unspam for verified customer

Methods: POST

URL: <https://open-api.chatcone.com/v3/verify/contact/unspam>

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String	Mandatory key for using API	-
channel_key	String	Verification channel for their follower	* Available for Line and Facebook Channel only

Body

Parameter	Type	Description	Remark
customer_id	Array	Api name of customer id in chatcone api setting page	Ex. ['cx001','cx002']

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/verify/contact/unspam \
--header 'channel_key: xxx'\
--header 'api_key: yyy'\
--header 'Content-Type: application/json' \
--data-raw '{
  "customer_id": [{
    "cx001",
    "cx002"
  ]
}'
```

Response Example

```
{"response_status":{"code":"200","operation":"service_verify_contact_unspam","message":"","message_type":"Information","status":"SUCCESS"},"result":{"complete":2}}
```

Command: Spam (Follower)

Description: Mark as spam for follower

Methods: POST

URL: <https://open-api.chatcone.com/v3/follower/contact/spam>

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String	Mandatory key for using API	-
channel_key	String	Verification channel for their follower	* Available for Line and Facebook Channel only

Body

Parameter	Type	Description	Remark
social_id	Array	Social id from social channel (Line, Facebook)	Ex. ['UXXXXXXXXXXXXXXXXX','UYYXXXXXXXXXXXXXXXXX']

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/follower/contact/spam \
--header 'channel_key: xxx'\
--header 'api_key: yyy'\
--header 'Content-Type: application/json' \
--data-raw '{
  "customer_id": [{
    "XXXXXXXXXXXXXXXXXX",
    "YYYYXXXXXXXXXXXXX"
  ]
}'
```

Response Example

```
{"response_status":{"code":"200","operation":"service_follower_spam","message":"","message_type":"Information","status":"SUCCESS"},"result":{"complete":2}}
```

Command: Unspam (Follower)

Description: Mark as unspam for follower

Methods: POST

URL: <https://open-api.chatcone.com/v3/follower/contact/unspam>

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String	Mandatory key for using API	-
channel_key	String	Verification channel for their follower	* Available for Line and Facebook Channel only

Body

Parameter	Type	Description	Remark
social_id	Array	Social id from social channel (Line, Facebook)	Ex. ['UXXXXXXXXXXXXXX','UYYXXXXXXXXXXXXX']

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/follower/contact/unspam \
--header 'channel_key: xxx'\
--header 'api_key: yyy'\
--header 'Content-Type: application/json' \
--data-raw '{
  "customer_id": [{
    "XXXXXXXXXXXXXXXXXX",
    "UYYXXXXXXXXXXXXXXXX"
  ]
}'
```

Response Example

```
{"response_status":{"code":"200","operation":"service_follower_unspam","message":"","message_type":"Information","status":"SUCCESS"},"result":{"complete":2}}
```

Command: Get Tags List

Description: Get all tags list , group tag and type

Methods: Get

URL: <https://open-api.chatcone.com/v3/tags/list>

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String	Mandatory key for using API	-
channel_key	String	Verification channel for their follower	* Any Channel Key

Request Example

```
curl --location --request GET 'https://open-api.chatcone.com/v3/tags/list \
--header 'channel_key: xxx'\
--header 'api_key: yyy'
```

Response Example

```
{"response_status":{"code":"200","operation":"get_tags_list","message":"","message_type":"Information","status":"SUCCESS"},"result":{"data":[{"group_name":"All","tag_list":[{"type":"User","tags":[{"tag_name":"good day","tag_type":"User"}]}]}], "total_count_tag": 2, "total_count_group_tags": 1}
```

Notification

Command: Broadcast (ALL)

Description: Broadcast message template to all followers.

Methods: POST

URL: <https://open-api.chatcone.com/v3/notification/broadcast>

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String (Required)	Mandatory key for using API	-
channel_key	String (Required)	Verification channel for their follower	* Available for Line Channel only

Body

Parameter	Type	Description	Remark
type	String (Required)	Type of sending	type = 'NOW'
message_id	String (Required)	Message id of template in Chatcone	-
(A1) data	Object	Object to pass through the template	Use [[-]] symbols to replace the data in message template Ex. [[text]]

(A1) data

Parameter	Type	Description	Remark
{key}	{key}:String {value}:String	Key and value to pass through the template	-

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/notification/broadcast' \  
--header 'channel_key: xxx' \  
--header 'api_key: yyy' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
  "type": "NOW",  
  "message_id": "60dd32de3d3d963abe4e77a5",  
  "data": {  
    "text": "ทดสอบ Broadcast"  
  }  
'
```

Response Example

```
{"response_status":{"code":"200","operation":"notification_broadcast","message":"","message_type":"Information","status":"SUCCESS"},"result":""}
```

Command: Notification by customer id (Dynamic message)

Description: Send notification to a verified user by Customer Id (Dynamic)

Methods: POST

URL: <https://open-api.chatcone.com/v3/notification/dynamic>

Limit only 10 data per request

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String (Required)	Mandatory key for using API	-
channel_key	String (Required)	Verification channel for their follower	* Available for Line Channel only

Body

Parameter	Type	Description	Remark
type	String (Required)	Type of sending	type = 'CUSTOMER_ID'
message_id	String (Required)	Message id of template in Chatcone	-
(A1) data	Array Object (Required)	Object to pass through the template	Use [[-]] symbols to replace the data in message template Ex. [[text]]

(A1) data

Parameter	Type	Description	Remark
customer_id	String (Required)	Customer Id from verified	-
{key}	{key}:String {value}:String	Key and value to pass through the template	-

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/notification/dynamic' \  
--header 'channel_key: xxx' \  
--header 'api_key: yyy' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
  "type": "CUSTOMER_ID",  
  "message_id": "628df5275a894c0335c3ff15",  
  "data": [  
    {  
      "customer_id": "22222222222222",  
      "text": "Test1"  
    }  
  ]  
'
```

Response Example

```
{"response_status":{"code":"200","operation":"notification_dynamic","message":"","message_type":"Information","status":"SUCCESS"},"result":{"success":1,"failed":0,"failed_result":[],"failed_send":[]}}
```

Command: Notification by social id (Dynamic message)

Description: Send notification to a verified user by Social Id (Dynamic)

Methods: POST

URL: <https://open-api.chatcone.com/v3/notification/dynamic>

Limit only 10 data per request

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String (Required)	Mandatory key for using API	-
channel_key	String (Required)	Verification channel for their follower	* Available for Line Channel only

Body

Parameter	Type	Description	Remark
type	String (Required)	Type of sending	type = 'SOCIAL_ID'
message_id	String (Required)	Message id of template in Chatcone	-
(A1) data	Array Object (Required)	Object to pass through the template	Use [[-]] symbols to replace the data in message template Ex. [[text]]

(A1) data

Parameter	Type	Description	Remark
social_id	String (Required)	Social Id	-
{key}	{key}:String {value}:String	Key and value to pass through the template	-

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/notification/dynamic' \  
--header 'channel_key: xxx' \  
--header 'api_key: yyy' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
  "type": "SOCIAL_ID",  
  "message_id": "628df5275a894c0335c3ff15",  
  "data": [  
    {  
      "social_id": "22222222222222",  
      "text": "Test1"  
    }  
  ]  
'
```

Response Example

```
{"response_status":{"code":"200","operation":"notification_dynamic","message":"","message_type":"Information","status":"SUCCESS"},"result":{"success":1,"failed":0,"failed_result":[],"failed_send":[]}}
```

Command: Notification by customer id (Bulk message)

Description: Send notification to a verified user by Customer Id (Bulk)

Methods: POST

URL: <https://open-api.chatcone.com/v3/notification/bulk>

Limit only 300 customer id per request

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String (Required)	Mandatory key for using API	-
channel_key	String (Required)	Verification channel for their follower	* Available for Line Channel only

Body

Parameter	Type	Description	Remark
type	String (Required)	Type of sending	type = 'CUSTOMER_ID'
message_id	String (Required)	Message id of template in Chatcone	-
customer_id	Array (Required)	Array of Customer Id from verified	-
(A1) data	Array Object	Object to pass through the template	Use [[-]] symbols to replace the data in message template Ex. [[text]]

(A1) data

Parameter	Type	Description	Remark
{key}	{key}:String {value}:String	Key and value to pass through the template	-

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/notification/bulk \
--header 'channel_key: xxx'\
--header 'api_key: yyy'\
--header 'Content-Type: application/json' \
--data-raw '{
  "type": "CUSTOMER_ID",
  "message_id": "628df5275a894c0335c3ff15",
  "customer_id": ["22222222222222"],
  "data": {
    "text": "Test1"
  }
}'
```

Response Example

```
{"response_status":{"code":"200","operation":"notification_bulk","message":"","message_type":"Information","status":"SUCCESS"},"result":{"success":1,"failed":0,"failed_result":[],"failed_send":[]}}
```

Command: Notification by customer type (Bulk message)

Description: Send notification to a verified user by Customer Type

Methods: POST

URL: <https://open-api.chatcone.com/v3/notification/bulk>

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String (Required)	Mandatory key for using API	-
channel_key	String (Required)	Verification channel for their follower	* Available for Line Channel only

Body

Parameter	Type	Description	Remark
type	String (Required)	Type of sending	type = 'CUSTOMER_ID'
message_id	String (Required)	Message id of template in Chatcone	-
customer_type	Array (Required)	Array of Customer Type from verified	-
(A1) data	Array Object	Object to pass through the template	Use [[-]] symbols to replace the data in message template Ex. [[text]]

(A1) data

Parameter	Type	Description	Remark
{key}	{key}:String {value}:String	Key and value to pass through the template	-

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/notification/bulk \
--header 'channel_key: xxx'\
--header 'api_key: yyy'\
--header 'Content-Type: application/json' \
--data-raw '{
  "type": "CUSTOMER_TYPE",
  "message_id": "628df5275a894c0335c3ff15",
  "customer_type": ["verified"],
  "data": {
    "text": "Test1"
  }
}'
```

Response Example

```
{"response_status":{"code":"200","operation":"notification_bulk","message":"","message_type":"Information","status":"SUCCESS"},"result":{"success":1,"failed":0,"failed_result":[],"failed_send":[]}}
```

Command: Notification by social id (Bulk message)

Description: Send notification to a verified user by Social Id (Bulk)

Methods: POST

URL: <https://open-api.chatcone.com/v3/notification/bulk>

Limit only 300 social id per request

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String (Required)	Mandatory key for using API	-
channel_key	String (Required)	Verification channel for their follower	* Available for Line Channel only

Body

Parameter	Type	Description	Remark
type	String (Required)	Type of sending	type = 'SOCIAL_ID'
message_id	String (Required)	Message id of template in Chatcone	-
social_id	Array (Required)	Array of Social Id from verified	-
(A1) data	Array Object	Object to pass through the template	Use [[-]] symbols to replace the data in message template Ex. [[text]]

(A1) data

Parameter	Type	Description	Remark
{key}	{key}:String {value}:String	Key and value to pass through the template	-

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/notification/bulk \
--header 'channel_key: xxx'\
--header 'api_key: yyy'\
--header 'Content-Type: application/json' \
--data-raw '{
  "type": "SOCIAL_ID",
  "message_id": "628df5275a894c0335c3ff15",
  "social_id": ["222222222222"],
  "data": {
    "text": "Test1"
  }
}'
```

Response Example

```
{"response_status":{"code":"200","operation":"notification_bulk","message":"","message_type":"Information","status":"SUCCESS"},"result":{"success":1,"failed":0,"failed_result":[],"failed_send":[]}}
```


Command: Notification message (By Customer Id)

Description: Send notification to user

Methods: POST

URL: <https://open-api.chatcone.com/v3/notification/message>

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String (Required)	Mandatory key for using API	-
channel_key	String (Required)	Verification channel for their follower	* Available for Line and Facebook Channel only

Body

Parameter	Type	Description	Remark
type	String (Required)	Type of sending	type = 'CUSTOMER_ID'
message_id	String (Required)	Message id of template in Chatcone	-
customer_id	String (Required)	Customer Id from verified	-
(A1) data	Array Object	Object to pass through the template	Use [[-]] symbols to replace the data in message template Ex. [[text]]

(A1) data

Parameter	Type	Description	Remark
{key}	{key}:String {value}:String	Key and value to pass through the template	-

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/notification/message \
--header 'channel_key: xxx'\
--header 'api_key: yyy'\
--header 'Content-Type: application/json' \
--data-raw '{
  "type": "CUSTOMER_ID",
  "message_id": "628df5275a894c0335c3ff15",
  "customer_id": "AAA",
  "data": {
    "text": "Test1"
  }
}'
```

Response Example

```
{"response_status":{"code":"200","operation":"notification-message","message":"","message_type":"Information","status":"SUCCESS"},"result":{"success":1,"failed":0,"failed_result":[],"failed_send":[]}}
```

Command: Notification message (By Social Id)

Description: Send notification to user

Methods: POST

URL: <https://open-api.chatcone.com/v3/notification/message>

Request Information

Headers

Parameter	Type	Description	Remark
api_key	String (Required)	Mandatory key for using API	-
channel_key	String (Required)	Verification channel for their follower	* Available for Line and Facebook Channel only

Body

Parameter	Type	Description	Remark
type	String (Required)	Type of sending	type = 'SOCIAL_ID'
message_id	String (Required)	Message id of template in Chatcone	-
social_id	String (Required)	Social Id from verified	-
(A1) data	Array Object	Object to pass through the template	Use [[-]] symbols to replace the data in message template Ex. [[text]]

(A1) data

Parameter	Type	Description	Remark
{key}	{key}:String {value}:String	Key and value to pass through the template	-

Request Example

```
curl --location --request POST 'https://open-api.chatcone.com/v3/notification/message \
--header 'channel_key: xxx'\
--header 'api_key: yyy'\
--header 'Content-Type: application/json' \
--data-raw '{
  "type": "SOCIAL_ID",
  "message_id": "628df5275a894c0335c3ff15",
  "social_id": "AAA",
  "data": {
    "text": "Test1"
  }
}'
```

Response Example

```
{"response_status":{"code":"200","operation":"notification-message","message":"","message_type":"Information","status":"SUCCESS"},"result":{"success":1,"failed":0,"failed_result":[],"failed_send":[]}}
```

Response Details

Field	Description	Remarks
response_status.code	รหัสสถานะการตอบกลับจากระบบ	200 = ใช้งานได้ปกติ 400 = ข้อมูลผิดพลาด 500 = ระบบมีปัญหา
response_status.operation	ชื่อของ Service ที่ทำงาน	เช่น notification-dynamic
response_status.message	ข้อความแสดงข้อผิดพลาดในระบบ (เฉพาะเมื่อ code ≠ 200) หากไม่มีข้อผิดพลาด จะกลายเป็นค่าว่าง	เช่น invalid syntax json schema (ข้อมูลผิดรูปแบบ)
response_status.message_type	มีค่าเป็น Information เสมอ	-
response_status.status	สถานะของการดำเนินการ	SUCCESS (เมื่อ code = 200) ERROR (เมื่อ code ≠ 200)
result	จะมีค่าเมื่อมีการ ส่งออกข้อความไปยัง LINE และจะเป็นค่าว่างเมื่อมีข้อผิดพลาดในระบบ	-
result.success	จำนวนรายการที่ส่งสำเร็จ	Bulk - แสดงจำนวนของการส่งชุดข้อมูลที่สำเร็จ Dynamic - แสดงจำนวนของการส่งตามจำนวน UID ที่สำเร็จ Message - แสดงจำนวนของการส่งตามจำนวน UID ที่สำเร็จ
result.failed	จำนวนรายการที่ส่งไม่สำเร็จ	Bulk - แสดงจำนวนของการส่งชุดข้อมูลที่ไม่สำเร็จ Dynamic - แสดงจำนวนของการส่งตามจำนวน UID ที่ไม่สำเร็จ Message - แสดงจำนวนของการส่งตามจำนวน UID ที่ไม่สำเร็จ
result.failed_result	รายการที่เกิดข้อผิดพลาดจากฝั่งระบบ Chatcone	เช่น ไม่พบ UID ในฐานข้อมูล
result.failed_send	รายการที่เกิดข้อผิดพลาดจากฝั่งการส่งข้อความออกไปยัง LINE	เช่น เครดิตในการส่งข้อความไม่เพียงพอ
result.failed_send (Array Object)	1.social_id หรือ customer_id (กรณีที่ส่งเป็น Type CUSTOMER_ID) 2. msg แสดงข้อความ Error จาก Line	-