BigDL 2.0

Seamlessly scale E2E distributed AI from laptop to cluster

Guoqiong Song Intel Jennie Wang Intel



Content


- What is BigDL?
- What does BigDL have?
- How does BigDL leverage Ray?
- Real world use cases





BigDL 2.0

Seamlessly scale end-to-end, distributed AI applications



BigDL 2.0 (https://github.com/intel-analytics/BigDL/) combines the original BigDL and Analytics Zoo projects

^{* &}quot;BigDL: A Distributed Deep Learning Framework for Big Data", in Proceedings of ACM Symposium on Cloud Computing 2019 (SOCC'19)



^{* &}quot;BigDL 2.0: Seamless Scaling of AI Pipelines from Laptops to Distributed Cluster", 2022 Conference on Computer Vision and Pattern Recognition (CVPR 2022)


BigDL: End-to-End Distributed AI Pipelines

- DLlib: Distributed Deep Learning Library for Spark
- Orca: Seamlessly Scale E2E AI Pipeline from Laptop to Distributed Cluster
- Nano: Automatic Integration of Modern CPU Accelerations for Al




BigDL-Orca: Building End-to-End Distributed Al Pipeline


E2E, distributed, in-memory pipeline





BigDL-Orca: Seamless Scaling from Laptop to Distributed Cluster






https://bigdl.readthedocs.io/en/latest/doc/UseCase/xshards-pandas.html



Seamless Pipeline between Spark and Ray using Orca

RayOnSpark

Connecting Spark Dataframe & Ray Dataset



```
#spark dataframe processing
df = spark.read.csv(...)
train df = data process(df)
#connecting spark dataframe to ray dataset
from bigdl.orca.data \
  import spark df to ray dataset
train data = spark df to ray dataset (train df)
#xgboost on ray
from xgboost ray import RayDMatrix, train
dtrain = RayDMatrix(train data, ...)
bst = train(config, dtrain, ...)
```

End-to-End Distributed AI Pipeline Example

```
#1. Initialize OrcaContext
                                                                               Distributed Data processing
sc = init orca context("local", init ray on spark=True)
                                                                                         Distributed Python APIs in Orca
                                                                                  Spark
                                                                                Dataframe
                                                                                         TensorFlow
                                                                                                 PvData
#2. Distributed data processing using Spark Dataframe
                                                                                                        Pylmage
                                                                                                 (pandas,
                                                                                         Dataset.
                                                                                  Rav
                                                                                                        (pillow,
raw df = spark.read.format("csv").load(data source path) \
                                                                                          PvTorch
                                                                                                 sklearn.
                                                                                 Dataset
                                                                                                        opency, ...
  .select("Cardholder Last Name", "Cardholder First Initial", \
                                                                                         DataLoader
                                                                                                numpy, ...
           "Amount", "Vendor", "Year-Month") \
                                                                               ML/DL Model
#3. Building model using TensorFlow
import tensorflow as tf
                                                                                  Standard TensorFlow/PyTorch APIs for
model = tf.keras.models.Model(inputs=input, outputs=output)
                                                                                         building models
model.compile(optimizer='rmsprop',
                loss='sparse categorical crossentropy',
                metrics=['accuracy'])
#4. Distributed training on Orca
                                                                               Distributed Training (& Inference)
from zoo.orca.learn.tf.estimator import Estimator
est = Estimator.from keras(model, model dir=args.log dir)
                                                                               sklearn-style APIs for transparently distributed
est.fit(data=trainingDF, batch size=batch size, epochs=max epoch, \
                                                                                        training & inference
   feature cols=['features'], label cols=['labels'], ...)
```


https://github.com/Mastercard/udap-analytic-zoo-examples



Orca AutoML: Distributed HyperParameter Tuning Pipeline using Ray-tune

```
from bigdl.orca import init orca context
sc = init orca context(...,init ray on spark=True)
from bigdl.orca.automl.xgboost import
AutoXGBRegressor
auto est = AutoXGBRegressor(...)
from bigdl.orca.automl import hp
search space = {
  "n estimators": hp.grid search([50, 100]),
  "max depth": hp.choice([2, 4, 6])}
auto est.fit (data=data,
      search space=search space,...)
best model = auto est.get best model()
```

AutoXGBoost



1.7x Speedup for AutoXGBoost



BigDL-Nano: Automatic Integration of Modern CPU Accelerations for TensorFlow & PyTorch

Accelerations	Tuning / Configuration / Tool	Action Needed
Better Memory Allocator	tcmalloc, jemelloc	Download, set environment variables correctly
Proper environment variables	Intel OpenMP (OMP/KMP)	Install, set environment variables correctly
AVX512, BF16	IPEX, Intel Optimized TensorFlow, oneDNN	Install, change some code to use the extensions
Multi-processing	Torch distributed, TF Distributed Strategy, Horovod, etc.	Change some code to use the functionality
Inference Engine	OpenVINO, ONNX Runtime, etc.	Install, Export your model to onnx file, use ort/IE API
Quantization	INC, NNCF/POT	Install, quantize through tool APIs and save/load the quantized model



Nano: Automatic & Transparent Integration of Many IA-Specific Accelerations


```
# define model
import fastface as ff
model = ff.FaceDetector.build(arch="lffd", config="slim",
                              preprocess=preprocess,
                                     hparams=hparams)
model.add metric("average precision",
             ff.metric.AveragePrecision(iou threshold=0.5))
# define train loader
train loader = ff.dataset.FDDBDataset(
    phase="train", transforms=train transforms
).get dataloader(batch size=8, shuffle=True, num workers=8)
# define Trainer
                                                                 # define Trainer
import pytorch lightning as pl
                                                                 from bigdl.nano.pytorch.trainer import Trainer
                                                                 trainer = pl.Trainer(num processes=4, use ipex=True, ...)
trainer = pl.Trainer(...)
# start training
trainer.fit(model, train dataloader=train loader)
```



BigDL-Nano: Automatic Integration of Modern CPU Accelerations for TensorFlow & PyTorch


- Substantial speedup
 - Up to ~5.8x training speedup, and ~9.6x inference speedup

Speedup of BigDL-Nano for training and inference on Laptop



laptop - a single 8-core Intel(R) Core (TM) i7-11800H CPU @ 2.30GHz, 12G Memory, Ubuntu 20.04 OS

Speedup of BigDL-Nano for training and inference on Container



container - a docker container with 28 cores in a single socket Intel(R)
Xeon(R) Platinum 8380H CPU @ 2.90GHz, 192G memory, Ubuntu 16.04 OS




BigDL 2.0: Seamless Scaling of Al Pipelines from Laptops to Distributed Cluster", CVPR 2022


BigDL-Nano: acceleration on Ray-tune

Speedup of BigDL-Nano	Ray Tune default	Ray Tune multi-core
Ray Tune + BigDL-Nano	4.34x	1.20x
Ray Tune + BigDL-Nano + core binding	5.74x	1.59x

- Cat vs dog using ResNet 50, 40 cores requested, 5 actors is used
- Known issue: reuse_actor may not be valid on some cases (~5%)



Accelerated by LightningTrainable based on bigdl-nano





https://github.com/ray-project/ray/pull/25654

For more complete information about performance and benchmark results, visit www.intel.com/benchmarks


BigDL: Domain-Specific Toolkits

- BigDL PPML (Privacy Preserving ML & Data Analytics)
- Project Chronos: Scalable Time Series Toolkit
- Project Friesian: E2E Recommender Toolkit



BigDL PPML (Privacy Preserving ML)

Secure & Trusted Big Data and AI,














BigDL PPML: Trusted Big Data Al

Secure Big Data Al




- Standard, distributed AI applications on encrypted data
- Hardware (Intel SGX/TDX) protected computation (and memory)
- End-to-end security enabled for the entire workflow
 - Provision and attestation of "trusted cluster environment" on K8s (of SGX nodes)
 - Secrete key management through KMS for distributed data decryption/encryption
 - Secure distributed compute and communication (via SGX, encryption, TLS, etc.)



BigDL-Chronos

Application framework for scalable time series analysis w/ AutoML




^{* &}quot;Scalable AutoML for Time Series Forecasting using Ray", USENIX OpML'20



BigDL-Friesian

Application framework for large-scale E2E recommender solution





BigDL-real world End to end Deep Learning examples













CONSUMER

HEALTH

FINANCE

RETAIL

MANUFACTURING

NFRASTRUCTURE

https://github.com/intel-analytics/BigDL



"Al at Scale" in Mastercard with BigDL




- Building distributed AI applications directly on Enterprise Data Warehouse platform
- Supporting up to 2.2 billion users, 100s of billions of records, and distributed training on several hundred Intel Xeon servers

https://www.intel.com/content/www/us/en/developer/articles/technical/ai-at-scale-in-mastercard-with-bigdl0.html




Network Quality Prediction in SK Telecom with BigDL





Fast Food Recommendation in Burger King with BigDL and Ray



- * https://medium.com/riselab/context-aware-fast-food-recommendation-at-burger-king-with-rayonspark-2e7a6009dd2d
- * "Context-aware Fast Food Recommendation with Ray on Apache Spark at Burger King", Data + Al Summit Europe 2020



Summary

• BigDL 2.0

- E2E distributed AI pipelines (seamless scaling from laptop to cluster)
- Domain-specific AI toolkits (PPML, Time Series, Recommender)
- Real word use cases

References

- https://github.com/intel-analytics/bigdl
- https://jason-dai.github.io/cvpr2022/
- https://bigdl.readthedocs.io/en/latest/



LEGAL NOTICES & DISCLAIMERS

This document contains information on products, services and/or processes in development. All information provided here is subject to change without notice. Contact your Intel representative to obtain the latest forecast, schedule, specifications and roadmaps.

Intel technologies' features and benefits depend on system configuration and may require enabled hardware, software or service activation. Learn more at intel.com, or from the OEM or retailer. No computer system can be absolutely secure.

Tests document performance of components on a particular test, in specific systems. Differences in hardware, software, or configuration will affect actual performance. Consult other sources of information to evaluate performance as you consider your purchase. For more complete information about performance and benchmark results, visit http://www.intel.com/performance.

Cost reduction scenarios described are intended as examples of how a given Intel-based product, in the specified circumstances and configurations, may affect future costs and provide cost savings. Circumstances will vary. Intel does not guarantee any costs or cost reduction.

Statements in this document that refer to Intel's plans and expectations for the quarter, the year, and the future, are forward-looking statements that involve a number of risks and uncertainties. A detailed discussion of the factors that could affect Intel's results and plans is included in Intel's SEC filings, including the annual report on Form 10-K.

The products described may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

No license (express or implied, by estoppel or otherwise) to any intellectual property rights is granted by this document.

Intel does not control or audit third-party benchmark data or the web sites referenced in this document. You should visit the referenced web site and confirm whether referenced data are accurate.

Intel, the Intel logo, Pentium, Celeron, Atom, Core, Xeon and others are trademarks of Intel Corporation in the U.S. and/or other countries.

*Other names and brands may be claimed as the property of others.

© 2016 Intel Corporation.

