

Cluster Analysis – Density based Algorithms


Density-based Clustering

- **Basic idea**

- Clusters are dense regions in the data space, separated by regions of lower object density
- A cluster is defined as a maximal set of density-connected points
- Discovers clusters of arbitrary shape

- **Method**

- DBSCAN




Density Definition

- ε -Neighborhood – Objects within a radius of ε from an object.

$$N_{\varepsilon}(p) : \{q \mid d(p, q) \leq \varepsilon\}$$

- “High density” - ε -Neighborhood of an object contains at least *MinPts* of objects.




ε -Neighborhood of p

ε -Neighborhood of q

Density of p is “high” (MinPts = 4)

Density of q is “low” (MinPts = 3)

Core, Border & Outlier



$\epsilon = 1\text{unit}$, $\text{MinPts} = 5$

Given ϵ and MinPts , categorize the objects into three exclusive groups.


A point is a **core point** if it has more than a specified number of points (MinPts) within ϵ —These are points that are at the interior of a cluster.

A **border point** has fewer than MinPts within ϵ , but is in the neighborhood of a core point.

A **noise point** is any point that is not a core point nor a border point.

Density-reachability


- Directly density-reachable
 - An object q is directly density-reachable from object p if p is a core object and q is in p 's ϵ -neighborhood.



- q is directly density-reachable from p
- p is not directly density-reachable from q
- Density-reachability is asymmetric

Density-reachability

- Density-Reachable (directly and indirectly):
 - A point p is directly density-reachable from p_2
 - p_2 is directly density-reachable from p_1
 - p_1 is directly density-reachable from q
 - $p \leftarrow p_2 \leftarrow p_1 \leftarrow q$ form a chain



- p is (indirectly) density-reachable from q
- q is not density-reachable from p

DBSCAN Algorithm: Example


- **Parameter**
 - $\varepsilon = 2$ cm
 - $MinPts = 3$



```
for each  $o \in D$  do
  if  $o$  is not yet classified then
    if  $o$  is a core-object then
      collect all objects density-reachable from  $o$ 
      and assign them to a new cluster.
    else
      assign  $o$  to NOISE
```

DBSCAN Algorithm: Example


- **Parameter**
 - $\varepsilon = 2$ cm
 - $MinPts = 3$



```
for each  $o \in D$  do
  if  $o$  is not yet classified then
    if  $o$  is a core-object then
      collect all objects density-reachable from  $o$ 
      and assign them to a new cluster.
    else
      assign  $o$  to NOISE
```


DBSCAN Algorithm: Example

- **Parameter**
 - $\varepsilon = 2$ cm
 - $MinPts = 3$



```
for each  $o \in D$  do
  if  $o$  is not yet classified then
    if  $o$  is a core-object then
      collect all objects density-reachable from  $o$ 
      and assign them to a new cluster.
    else
      assign  $o$  to NOISE
```

DBSCAN: Sensitive to Parameters

Figure 8. DBScan results for DS1 with MinPts at 4 and Eps at (a) 0.5 and (b) 0.4.






Figure 9. DBScan results for DS2 with MinPts at 4 and Eps at (a) 5.0, (b) 3.5, and (c) 3.0.



DBSCAN: determining EPS and MinPts


- Idea is that for points in a cluster, their k^{th} nearest neighbors are at roughly the same distance
- Noise points have the k^{th} nearest neighbor at farther distance
- So, plot sorted distance of every point to its k^{th} nearest neighbor



When DBSCAN works well




original points



clusters


- resistant to noise
- can handle clusters of different shapes and sizes

When DBSCAN does NOT work well




original points

- varying densities
- high-dimensional data



(MinPts=4, Eps=9.75).



(MinPts=4, Eps=9.92)