

Course: _____

Name: _____

Date: _____

Part I: DOM Basics (7)

0. What is the `document` object?

- ☐ The elements tab in chrome developer tools
- ☐ An HTML file
- ☐ A javascript object representing the content of a page
- ☐ A javascript data type for very long strings

1. The `document` object, like all other global variables, is a property of which object?

- ☐ body
- ☐ window
- ☐ location
- ☐ process

2. What object does the `getElementById` method exist on?

- ☐ Any javascript object
- ☐ window
- ☐ document
- ☐ addEventListener

Example A:

```
const shoppingList1 = document.querySelector('#shopping-list');  
const shoppingList2 = document.getElementById('shopping-list');
```

3. In the example above: shoppingList1 and shoppingList2 are the same thing

- ☐ true
- ☐ false

4. What does Element.querySelector() return?

- ☐ HTMLElement Object
- ☐ NodeList Object
- ☐ HTML String
- ☐ Boolean

5. What is a difference between the querySelector and querySelectorAll methods?

- ☐ There is no difference between them
- ☐ querySelector returns all matches in the document querySelectorAll returns the first match
- ☐ querySelector returns the first match in the document querySelectorAll returns all matches
- ☐ querySelector returns a CSS Selector in the document querySelectorAll returns a list of CSS selectors

Example B:

```
<body>
  <ul id="shopping-list">
    <li class="shopping-item">Milk</li>
    <li class="shopping-item">Eggs</li>
    <li class="shopping-item">Butter</li>
    <li class="shopping-item">Flour</li>
  </ul>
</body>
```

6. How would you select all list items in the list from the example above?

- ☐ document.body.querySelectorAll('#shopping-list li')
- ☐ document.body.querySelector('#shopping-list li')
- ☐ document.body.querySelectorAll('#shopping-list .shopping-item')
- ☐ Both (0) and (2)

Part II: DOM Manipulation (8)

0. Creating an element with the `createElement` method makes that element appear on the page

☐ true ☐ false

1. What `Element` object property can you use to change the entire value of an element's class attribute?

☐ `class`

☐ `className`

☐ `classList`

☐ None of the above

2. The `Node.insertBefore()` method takes only **one** argument:

☐ true ☐ false

3. Which method can be used to remove an element from the DOM?

☐ `Node.removeChild()`

☐ `Node.removeElement()`

☐ `Node.deleteElement()`

☐ `Node.removeNode()`

4. To retrieve user input from a form control (`input`, `textarea`, `select`) you can use:

☐ The ``.value`` property

☐ An element's dataset

☐ The ``.textContent`` property

☐ There is no way to retrieve the user input without sending the form to a server

Example C:

```
const fibonnaci = [0, 1, 1, 2, 3, 5, 8, 13, 21];

const div = document.createElement('div');

div.style['background-color'] = 'black';
div.style['color'] = 'white';
div.style['font-family'] = 'monospace';

fibonnaci.forEach(number => {
  let span = document.createElement('span');
  let text = document.createTextNode(number + ' ');

  span.style['font-size'] = `${number}px`;

  span.appendChild(text);
  div.appendChild(span);
});

document.body.appendChild(div);
```

5. What HTML will be added to the page as the result of example C?

- ☐

```
<div>
  <span>0 </span>
  <span>1 </span>
  <span>1 </span>
  <span>2 </span>
  <span>3 </span>
  <span>5 </span>
  <span>8 </span>
  <span>13 </span>
  <span>21 </span>
</div>
```
- ☐

```
<div style="background-color: black; color: white; font-family: monospace;
font-size: 21px;">
  <span>0 </span>
  <span>1 </span>
  <span>1 </span>
  <span>2 </span>
  <span>3 </span>
  <span>5 </span>
  <span>8 </span>
  <span>13 </span>
  <span>21 </span>
</div>
```
- ☐

```
<div style="background-color: black; color: white; font-family: monospace;">
  <span style="font-size: 0px;">0 </span>
  <span style="font-size: 1px;">1 </span>
  <span style="font-size: 1px;">1 </span>
  <span style="font-size: 2px;">2 </span>
  <span style="font-size: 3px;">3 </span>
  <span style="font-size: 5px;">5 </span>
  <span style="font-size: 8px;">8 </span>
  <span style="font-size: 13px;">13 </span>
  <span style="font-size: 21px;">21 </span>
</div>
```
- ☐ None of the above, there is no text added to the ```` elements

Example D:

```
const students = [
  {
    name: 'Inkar Haber',
    age: '27',
    location: 'Tehran'
  },
  {
    name: 'Joakim MacDermott',
    age: '31',
    location: 'Birmingham'
  },
  {
    name: 'Eilert Schwartz',
    age: '52',
    location: 'Saint Petersburg'
  }
]

const listElem = document.createElement('ul');

students
  .sort((studentA, studentB) => studentA.name.localeCompare(studentB.name))
  .map(student => {
    let listItem = document.createElement('li');

    listItem.innerText = `${student.name} is ${student.age} years old from
    ${student.location}`;
    listItem.classList.add('student-item');

    return listItem;
  })
  .forEach(listItem => listElem.appendChild(listItem));

document.body.appendChild(listElem);
```

6. What HTML will be added to the page as the result of example D?

- [] ``
 `<li class="student-item">`
 Inkar Haber is 27 years old from Tehran
 ``
 `<li class="student-item">`
 Joakim MacDermott is 31 years old from Birmingham
 ``
 `<li class="student-item">`
 Eilert Schwartz is 52 years old from Saint Petersburg
 ``
 ``
- [] ``
 `<li class="student-item">`
 Eilert Schwartz is 52 years old from Saint Petersburg
 ``
 `<li class="student-item">`
 Inkar Haber is 27 years old from Tehran
 ``
 `<li class="student-item">`
 Joakim MacDermott is 31 years old from Birmingham
 ``
 ``
- [] `<ul class="student-item">`
 ``
 Eilert Schwartz is 52 years old from Saint Petersburg
 ``
 ``
 Inkar Haber is 27 years old from Tehran
 ``
 ``
 Joakim MacDermott is 31 years old from Birmingham
 ``
 ``
- [] Nothing, this is not valid javascript

Example E:

```
let animals = ['chicken', 'cow', 'pigeon', 'duck', 'pig', 'dog', 'sheep', 'goat', 'horse'];

animals.filter(animal => animal.includes('o'))
  .map(animal => {
    let image = document.createElement('img');
    image.src = `images/${animal}.jpg`;
    image.data.animal = animal;

    return image;
  })
  .forEach(image => {
    let container = document.createElement('div');
    container.className = 'animal-container';
    container.appendChild(image);

    document.body.appendChild(container);
  });
```

7. What HTML will be added to the page as the result of example E?

- []

```
<div class="animal-container">
  
</div>
<div class="animal-container">
  
</div>
<div class="animal-container">
  
</div>
<div class="animal-container">
  
</div>
<div class="animal-container">
  
</div>
```
- []

```








```
- []

```
<div class="animal-container" data-animal="cow">
  
</div>
<div class="animal-container" data-animal="pigeon">
  
</div>
<div class="animal-container" data-animal="dog">
  
</div>
<div class="animal-container" data-animal="goat">
  
</div>
<div class="animal-container" data-animal="horse">
  
</div>
```
- [] None of the above, some of the animals are missing

Part III: DOM Traversal (8)

0. What is DOM Traversal?

- ☐ Adding and Removing elements from the DOM
- ☐ Changing elements in the DOM
- ☐ Selecting Elements based on their relationship with a specific element
- ☐ Both (0) and (2)

1. A Node and an Element are the exact same thing

- ☐ true ☐ false

Example F:

```
<body>
<main class="recipe-container">
  <header id="recipe-header">
    <h1 class="recipe-title">Shakshuka</h1>
    <p class="additional-info">Great algorithm for an easy meal. Feeds 2 adult
humans.</p>
  </header>

  <section id="recipe-ingredients">
    <h2>Prepare Before:</h2>
    <p>Some kind of sentence...</p>
    <ul class="ingredients-list">
      <li class="ingredient-item">Item 1</li>
      <li class="ingredient-item">Item 2</li>
      <li class="ingredient-item">Item 3</li>
      <li class="ingredient-item">Item 4</li>
      <li class="ingredient-item">Item 5</li>
    </ul>
  </section>

  <section id="recipe-instructions">
    <h2>Cooking Time...</h2>
    <ol class="instructions-list">
      <li class="instruction-item">Instruction 1</li>
      <li class="instruction-item">Instruction 2</li>
      <li class="instruction-item">Instruction 3</li>
      <li class="instruction-item">Instruction 4</li>
    </ol>
  </section>
</main>
</body>
```

2 - 6. In example F: Assuming that `current` is the list item with the text "Instruction 3", match the following descriptions with the Element properties that will select them in JS

a. <code>ul.ingredients-list</code>	<input type="checkbox"/> <code>current.parentElement</code>
b. <code>li.instruction-item</code> with the text "Instruction 4"	<input type="checkbox"/> <code>current.parentElement.previousElementSibling</code>
c. <code>h2</code> with the text "Cooking Time..."	<input type="checkbox"/> <code>current.closest('section').previousElementSibling.children[2]</code>
d. <code>p.additional-info</code>	<input type="checkbox"/> <code>current.closest('.recipe-container').firstElementChild.children[1]</code>
e. <code>ol.instructions-list</code>	<input type="checkbox"/> <code>current.nextElementSibling</code>

7. Why is `previousElementSibling` preferred to `previousSibling` when traversing the DOM?

- ☐ `previousSibling` has a larger performance impact than `previousElementSibling`
- ☐ `previousSibling` and `previousElementSibling` are exactly the same
- ☐ `previousSibling` is not part of the DOM API
- ☐ `previousElementSibling` will always contain a DOM Element, while `previousSibling` might contain other things

Part IV: Events (7)

0. Which arguments does the `EventTarget.addEventListener()` method take?

- ☐ Event Name String, Element to listen to, Function expression to call when the event occurs
- ☐ Element to listen to, Function expression to call when the event occurs
- ☐ Event Name String, Function expression to call when the event occurs
- ☐ Function expression to call when the event occurs

1. The function that you pass as an argument to the `EventTarget.addEventListener()` method is often called:

- ☐ A callback
- ☐ An event listener
- ☐ An event handler
- ☐ Both (0) and (2)

2. `Event.preventDefault()` is a method that:

- ☐ Stops the event from bubbling up the DOM
- ☐ Has to be called in order to attach an event handler to an element
- ☐ Prevents any default browser behaviour from executing when the event handler is called on the element it is attached to
- ☐ Both (0) and (2)

3. What is the difference between `event.target` and `event.currentTarget`?

- ☐ `event.target` is the event name that was triggered, `event.currentTarget` is the element that triggered the event
- ☐ `event.target` is the element that triggered the event, `event.currentTarget` is the event name that was triggered
- ☐ `event.target` is the element the event listener is attached to, `event.currentTarget` is the element that triggered the event
- ☐ `event.target` is the element that triggered the event, `event.currentTarget` is the element the event listener is attached to

4. A parent will respond to the same event a child does because of event bubbling.

- ☐ true
- ☐ false

```
const triggers = document.querySelectorAll('#trigger-container .trigger');

triggers.forEach(trigger => trigger.addEventListener('click', event => {
  event.preventDefault();

  let currentTrigger = event.target;
  let triggerParent = currentTrigger.parentElement;

  for(let i = 0; i < 100; i++){
    let paragraph = document.createElement('p');
    paragraph.innerText = 'Haha, you clicked the trigger!';
    triggerParent.appendChild(paragraph);
  }
}));
```

5. In example G: What will happen when a user clicks on an element with the class trigger?

- ☐ Nothing will happen
- ☐ 100 paragraphs will be added inside the '.trigger' element
- ☐ 100 paragraphs will be added to all parents of all trigger elements
- ☐ 100 paragraphs will be added to the parent of the trigger element that was clicked

6. In example G: What code will we write to ****delegate**** the click event?

```
[ ] const triggers = document.querySelectorAll('#trigger-container .trigger');

triggers.forEach(trigger => {
  trigger.delegate('click', trigger.parentElement, event => {
    // ... Same code as in example
  })
});
```

```
[ ] const triggerContainer = document.querySelector('#trigger-container');

triggerContainer.delegate('click', '.trigger', event => {
  event.preventDefault();

  let currentTrigger = event.target;
  let triggerParent = event.currentTarget;

  // ... Same code as in example
});
```

```
[ ] const triggerContainer = document.querySelector('#trigger-container');

triggerContainer.addEventListener('click', event => {
  if(!event.target.classList.contains('trigger')) return;

  event.preventDefault();

  let currentTrigger = event.target;
  let triggerParent = event.currentTarget;

  // ... Same code as in example
});
```

```
[ ] const triggers = document.querySelectorAll('#trigger-container .trigger');

triggers.forEach(trigger => {
  trigger.addEventListener('click', event => {
    event.preventDefault();

    let currentTrigger = event.target;
    let triggerParent = event.currentTarget;

    // ... Same code as in example
  })
});
```