REFERENCE AGREEMENT IS NOT ACOUSTIC CORRECTNESS: EVALUATING LARGE AUDIO LANGUAGE MODEL CAPTIONS ON CLOTHO

Anandaswarup Vadapalli

International Institute of Information Technology, Hyderabad, India

ABSTRACT

Audio captions are usually evaluated by their agreement with human references, yet a caption can disagree with the references because it describes audible content they omit, or agree with them while misdescribing the recording. We examine this gap for large audio language models (LALMs). Captions from GPT-Audio-1.5, Gemini 3.8 Flash, Qwen2.5-Omni-7B and Audio Flamingo 3 for the 1,045 recordings of the Clotho v2.1 evaluation split are scored with twelve reference-based and two audio-aware metrics and compared with a matched human leave-one-out baseline. Every model scores below the human baseline on every reference-based metric, and the two open-weight models score highest. A single-reviewer assessment of 200 sampled captions, first against the references and then against the audio, ranks the models differently: GPT-Audio-1.5, third or fourth on the text metrics, was rated accurate for 47 of 50 recordings, the most of any model, and 56 of the 64 captions with weak reference agreement had no major acoustic error. Within recordings, none of the ten metrics tested showed significantly above-chance concordance with the audio ratings, although the intervals are wide. Reference agreement is therefore insufficient on its own to establish acoustic correctness.

***Index Terms*—** Audio captioning, large audio language models, evaluation metrics, Clotho, human references

1. INTRODUCTION

Automated audio captioning (AAC) describes the sound sources, events and acoustic characteristics of a recording in natural language [1]. Large audio language models (LALMs) now perform this task without task-specific training, and produce longer and more detailed descriptions than captioning systems trained on AAC datasets [2–5].

AAC systems are evaluated by comparing their captions with human references, using metrics such as BLEU [6], METEOR [7], CIDEr [8] and SPIDEr [9]. A recording often contains several sounds, and each listener describes a selection of them. Two cases then arise that the scores conflate: a caption can disagree with the references because it describes audible content that they omit, and a caption can agree with the references while misdescribing the recording. A reference-based score alone cannot tell whether low agreement marks an acoustic error or a legitimate description that the references do not cover. The problem is sharper for LALMs, whose captions differ from the references in length and style.

We study this problem for four LALMs on Clotho v2.1 [10] with three complementary research questions:

1. **RQ1: How closely do model captions agree with the five human reference captions?** This establishes the degree of reference agreement under twelve reference-based metrics, with two audio-aware metrics for comparison.
2. **RQ2: How do model captions compare with held-out human captions in metric scores and caption length?** This calibrates that agreement against human captions scored against the same references.
3. **RQ3: What patterns of agreement, additional detail, omission and mismatch appear in model captions?** This relates reference agreement to acoustic correctness as judged by a single reviewer, who assessed sampled captions first against the references and then by listening.

2. RELATED WORK

2.1. Automated audio captioning

AAC benchmarks such as AudioCaps [11] and Clotho [10] provide several crowdsourced captions per evaluation recording, and the DCASE challenge has made them standard [1]. In Clotho, annotators write captions, other annotators correct or rephrase them, and the five captions rated highest for accuracy and fluency are kept [12]. Each Clotho reference is a single sentence of 8–20 words, so it describes a selection of the sounds, typically the most salient, rather than the whole recording. Larger, weakly labelled collections such as WavCaps [13] support pre-training. When a captioner describes more of a recording than its references do, the references no longer bound what a correct caption may contain.

2.2. Large audio language models

LALMs couple a pre-trained audio encoder with a large language model and follow free-form instructions about audio [2, 3, 14, 15]. Recent models are either general multimodal assistants, such as Qwen2.5-Omni [4], or audio specialists, such as Audio Flamingo 3 [5]. Unlike AAC systems trained on reference captions, they are not necessarily constrained to a benchmark's caption length or vocabulary, so their captions can contain correct detail that no reference mentions. They can also describe sounds that are absent from the recording [16]. Deciding whether an added detail is correct or hallucinated therefore requires the audio, not the references.

2.3. Audio caption evaluation metrics

Reference-based metrics compare a caption with the human references. BLEU [6] and CIDEr [8] count n-gram overlap, METEOR [7] also matches stems and synonyms, SPICE [17] compares scene graphs, and SPIDEr [9] averages CIDEr and SPICE. Zhou et al. [18] found that these metrics agree poorly with human judgements of audio captions and proposed FENSE, which adds a fluency penalty to Sentence-BERT similarity. Later metrics use contextual embeddings [19], sound descriptors [20], a language-model judge [21] or several candidates [22], but all measure similarity to

the references, not to the recording. Audio-aware metrics use the recording itself: CLAP [23, 24] embeds audio and text in a joint space, analogous to CLIPScore [25] for images, and MACE [26] combines CLAP audio–text and text–text similarity with a fluency penalty. Both measure global similarity; neither verifies individual sound events.

2.4. Reference agreement and acoustic grounding

Our approach transfers two analyses from image captioning evaluation to audio. First, image captioning calibrates reference-based scores with human agreement: for the COCO captions, each human caption is scored against the remaining references, which shows how well a human scores on the same metrics [27]. A model score can then be read relative to human performance. Second, image captioning separates agreement with the references from correctness about the image: CHAIR checks the objects a caption mentions against the objects annotated in the image, and showed that captions can score well on reference-based metrics while describing objects that are not present [28]. In AAC, metric studies have compared scores with human preferences between caption pairs, judged on description accuracy and fluency [18, 26], but the combination of human calibration and audio-grounded assessment remains underexplored for LALM captions. We adapt both: a matched human leave-one-out baseline calibrates the model scores (RQ2), and, since audio has no object annotations, a manual review checks sampled captions and their reference-unsupported phrases against the recording (RQ3).

3. METHODOLOGY

3.1. Data and models

We use the complete evaluation split of Clotho v2.1 [10]: 1,045 recordings of 15–30 s (6.5 h in total), each with five human captions (5,225 captions). We evaluate two API models, GPT-Audio-1.5 and Gemini 3.8 Flash, and two open-weight models, Qwen2.5-Omni-7B [4] and Audio Flamingo 3 [5], at pinned checkpoint revisions. Every model received a single user turn with the full recording followed by the same instruction (prompt template below). No references were shown, no length was imposed, and no model-specific prompt tuning was done; only the provider-specific encoding of the audio differed.

Prompt template (one user turn, identical for all models)
`[audio]` *full recording, 15–30 s, no cropping*
`[text]` Describe the sounds heard in this audio recording in one clear sentence that mentions the main sound sources, audible events, and distinguishing acoustic characteristics. Do not speculate about sources or events that are not supported by the audio. Respond with the sentence only, as plain text, without JSON, lists, labels or other formatting.

Decoding used temperature 0, top-p 1 and a seed of 42 where supported; Gemini 3.8 Flash ran at its lowest thinking level (`low`). This gave one caption per model and recording (4,180 in total).

3.2. Metrics and human leave-one-out calibration

3.2.1. Metrics

The twelve reference-based metrics are BLEU-1 to BLEU-4, METEOR, CIDEr-D, SPICE, SPIDEr, SPIDEr-FL, FENSE, and the raw and baseline-rescaled F1 of BERTScore, computed on PTB-tokenized text with the aac-metrics package [29]. The two audio-aware metrics are CLAP similarity, the cosine between the audio and caption embeddings of MS-CLAP 2023 [24] (each clip embedded whole as the duration-weighted mean of 7 s chunks), and MACE [26].

3.2.2. Matched human calibration

A model's score against the references is hard to interpret without knowing how well a human caption agrees with the other references. We therefore hold out each human caption h_j of a recording in turn and score it against the remaining four, $R_{-j} = H \setminus \{h_j\}$, where $H = \{h_1, \ldots, h_5\}$. Each model caption is scored against the same five four-reference subsets $R_{-1}, \ldots, R_{-5}$, so model and human captions face identical references. Scores are averaged over j per recording; corpus-level metrics are computed per j and averaged. This baseline measures inter-reference agreement, not caption quality or acoustic correctness. Because CIDEr-D, and hence SPIDEr and SPIDEr-FL, depend on the reference set, five-reference (RQ1) and four-reference (RQ2) scores are never compared with each other. Clotho's protocol keeps original and rephrased captions without deduplication, and 33% of held-out captions have a word-set Jaccard overlap of at least 0.6 with a reference. This threshold is operational, not a test of paraphrase; as a sensitivity analysis, we repeat RQ2 without these captions.

3.3. Caption length and qualitative review

Caption length is the number of whitespace-separated words; we relate it to each score with Spearman correlations over captions. For RQ3, we drew 50 recordings at random (seed 42), independently of the scores, and reviewed the four model captions of each, 200 in total. The review had two stages:

1. *Stage 1, reference-only.* Without audio, the reviewer compared each caption with the five references and assigned one of six reference-agreement categories: aligned (1 strong agreement, 2 mostly aligned, 3 mostly aligned with additional details), partially aligned (4 with missing details, 5 with additional details), or 6 weak agreement or source/event mismatch. Phrases that no reference mentions (*reference-unsupported phrases*) were listed.
2. *Stage 2, audio-grounded.* After the stage-1 labels were final, the reviewer listened to each recording and assigned each caption one of three ratings: (1) accurate, where omitting a secondary sound alone does not lower the rating; (2) minor errors: principal source and event correct, but a wrong attribute or order or an unsupported secondary detail; or (3) major error: principal source or event wrong or invented, or the dominant sound omitted. Each reference-unsupported phrase was judged audible, inaudible or unverifiable in the recording.

A single reviewer performed both stages by hand; no AI system assigned or suggested labels. Captions were blinded to model identity.

3.4. Statistical analysis

The recording is the unit of analysis, and every comparison is paired. We test mean differences with two-sided sign-flip permutation tests (10,000 permutations) and report 95% percentile bootstrap intervals over recordings (10,000 resamples). Holm correction is applied within predefined families over all 14 metrics: 84 model-pair tests for RQ1 and 56 model-versus-human tests for RQ2. We report

the paired effect size d_z, because with 1,045 recordings very small differences are significant. Ranking stability is the share of bootstrap resamples that reproduce the observed model order. To relate a metric to the audio ratings within recordings, we take every pair of captions of the same recording with different ratings and compute the share in which the metric scores the better-rated caption higher, counting ties as one half (*concordance*; 0.5 is chance). Its intervals and tests resample or sign-flip whole recordings, with Holm correction over the ten metrics of Table 1 (not BLEU-2, BLEU-3, SPIDEr-FL or raw BERTScore). Review proportions carry Wilson 95% intervals.

4. RESULTS

4.1. RQ1: Agreement with five references

Audio Flamingo 3 scores highest and Qwen2.5-Omni-7B second on every reference-based metric, and the two API models take the third and fourth places (Table 1, left). The order is stable: at least 99% of bootstrap resamples reproduce it for nine of the twelve metrics, and only the order of the two API models varies for BLEU-3 (87%), SPIDEr and SPIDEr-FL (55%). Across all 14 metrics, 76 of the 84 model-pair differences are Holm-significant.

The audio-aware metrics order the models differently: CLAP similarity and MACE score GPT-Audio-1.5 close to Qwen2.5-Omni-7B (0.466 and 0.462; 0.573 and 0.575), and Gemini 3.8 Flash last. Per caption, the text metrics correlate with each other (Spearman ρ = 0.41–0.88), and CLAP and MACE correlate 0.89 with each other but only 0.28–0.67 with the text metrics. These correlations show how the metrics covary, not agreement with the audio.

4.2. RQ2: Comparison with held-out human captions

Under the same four references, every model scores below the held-out human captions on every reference-based metric, and all of these differences are Holm-significant (Table 1, right). Because the baseline measures how closely one human caption agrees with the other four, this shows that the models agree less with the held-out human references, not that their captions are less correct. The effect sizes (d_z from -0.48 to -2.55) are standardized differences in metric scores, not in caption quality.

The audio-aware metrics are the exception: on CLAP similarity, Audio Flamingo 3 is not significantly different from the human captions ($+0.006$, $d_z = 0.06$), the only one of the 56 comparisons that is not significant. Without near-paraphrase captions, the human baseline falls (CIDEr-D 0.91 to 0.46), but every model remains significantly below it on all reference-based metrics; Audio Flamingo 3 rises above it on CLAP similarity, at the uncorrected level only.

Model captions are 1.45 (Gemini 3.8 Flash) to 1.85 (GPT-Audio-1.5) times as long as human captions, and 92% of GPT-Audio-1.5's captions are longer than every reference of their recording. For the models, length is negatively associated with the overlap metrics, from -0.09 (Gemini 3.8 Flash) to -0.63 (Audio Flamingo 3) for CIDEr-D and from -0.19 to -0.52 for rescaled BERTScore. CLAP similarity and MACE are almost independent of length except for Audio Flamingo 3 (-0.11 and -0.17), and human captions show near-zero correlations throughout. These associations do not isolate a causal effect of length.




Fig. 1. Stage-1 reference-agreement category (rows; references only) by stage-2 audio-grounded rating (columns; by listening) for the 200 sampled captions of all four models, single reviewer.

4.3. RQ3: Agreement patterns and acoustic correctness

The sample was similar to the full set on the measured summary statistics (standardized differences ≤ 0.37). The reference-only and audio-grounded assessments produced substantially different model rankings (Table 2). Against the references, Audio Flamingo 3 and Qwen2.5-Omni-7B are most often aligned and Gemini 3.8 Flash least often, and GPT-Audio-1.5 has the most captions with missing detail. Against the audio, GPT-Audio-1.5 ranks first despite placing third or fourth on the reference-based metrics: it was rated accurate for 47 of 50 recordings (94%, 95% CI 84–98%) with no major error, while the other models were rated accurate for 23 to 27 (46–54%, intervals within 33–67%) and had 5 to 9 major errors (single-reviewer ratings; the other three keep their unstable order). Two further analyses examine these differences:

1. *Details absent from the references.* The 200 captions contain 262 reference-unsupported phrases. Of these, 64% were audible in the recording, 28% inaudible and 8% unverifiable; these proportions are descriptive, because phrases of a caption are not independent. Inaudible phrases occur in 26 of Gemini 3.8 Flash's captions, 19 of Qwen2.5-Omni-7B's and 15 of Audio Flamingo 3's, but in only one of GPT-Audio-1.5's. At the caption level (Fig. 1), 56 of the 64 captions in category 6 had no major error (42 accurate, 14 minor errors), and 23 of the 26 category-4 captions were rated accurate. In this sample, weak reference agreement therefore did not imply an incorrect description; incomplete reference coverage is a plausible explanation, alongside reference errors, ambiguous sounds and reviewer judgement. Conversely, agreement did not guarantee correctness: 7 of the 70 captions in categories 1–3 had a major error, 2 of them in category 1.
2. *Metrics and the two reviews.* Across models, the metrics follow the reference-only review: Kendall's τ between each metric's model order and the reference-review order is 0.67–1.00, but with the audio-review order it is 0–0.33 for every metric except CLAP similarity (0.67). Mean scores fall from category 1 to 6 on every metric but are flat or reversed across audio ratings (rescaled

Table 1. Mean per-recording scores. RQ1 (left): model captions against all five references; bold marks the highest model. RQ2 (right): held-out human captions against the other four references, and the paired effect size d_z of each model minus that baseline under the same references; all Holm-significant except †. Five- and four-reference scores are not comparable. Last row: mean words, and d_z of model minus mean reference length. GPT: GPT-Audio-1.5; Gemini: Gemini 3.8 Flash; Qwen: Qwen2.5-Omni-7B; AF3: Audio Flamingo 3.

	RQ1: models, five references				RQ2: human	RQ2: model − human, d_z (four ref.)			
Metric	GPT	Gemini	Qwen	AF3	(four ref.)	GPT	Gemini	Qwen	AF3
BLEU-1	0.277	0.251	0.368	**0.407**	0.640	−2.49	−2.55	−1.67	−1.40
BLEU-4	0.004	0.002	0.015	**0.030**	0.234	−1.27	−1.28	−1.18	−1.05
METEOR	0.124	0.102	0.151	**0.174**	0.319	−1.84	−2.05	−1.57	−1.32
CIDEr-D	0.048	0.064	0.164	**0.191**	0.906	−1.83	−1.75	−1.54	−1.41
SPICE	0.067	0.051	0.091	**0.117**	0.232	−1.47	−1.58	−1.19	−0.91
SPIDEr	0.057	0.058	0.127	**0.154**	0.569	−1.90	−1.84	−1.59	−1.41
FENSE	0.401	0.387	0.474	**0.510**	0.575	−1.10	−1.05	−0.73	−0.48
BERTScore-F1 (rescaled)	0.254	0.238	0.331	**0.352**	0.598	−2.40	−2.47	−1.80	−1.51
CLAP similarity	0.466	0.381	0.462	**0.509**	0.503	−0.34	−0.94	−0.42	+0.06†
MACE	0.573	0.489	0.575	**0.608**	0.635	−0.61	−1.18	−0.69	−0.34
Caption length (words)	21.0	16.4	17.0	19.0	11.3	+2.40	+1.30	+1.13	+1.16

Table 2. Two-stage review of 50 sampled captions per model. Last row: inaudible phrases among the model's reference-unsupported phrases.

	GPT	Gemini	Qwen	AF3
Stage 1: reference-agreement category				
1–3 Aligned	15	8	21	**26**
4 Partial, missing detail	10	6	5	5
5 Partial, added detail	10	12	9	9
6 Weak or mismatch	15	24	15	10
Stage 2: audio-grounded rating				
1 Accurate	**47**	23	25	27
2 Minor errors	3	18	20	16
3 Major error	0	9	5	7
Category 6 with major error	0	6	1	1
Inaudible / reference-unsupported	1/59	34/80	20/58	19/65

BERTScore 0.29, 0.31, 0.34 for ratings 1–3). Within recordings, across 156 caption pairs from 42 recordings, concordance with the audio ratings ranges from 0.39 (rescaled BERTScore) to 0.58 (MACE, 95% CI [0.46, 0.69]; CLAP similarity 0.56 [0.45, 0.66]), and none of the ten metrics differs significantly from chance after Holm correction. The intervals are wide, so this analysis can neither confirm nor exclude useful discrimination.

5. DISCUSSION

Reference agreement and acoustic correctness are different evaluation targets, and in the reviewed sample they diverged. GPT-Audio-1.5 illustrates the divergence, not a general superiority. Most of its departures from the references are not errors under the rubric: 10 of its captions omit reference content, and 55 of its 59 reference-unsupported phrases were audible. Omissions and additional audible details can reduce reference agreement without reducing acoustic correctness, while errors about principal sound sources affect acoustic correctness regardless of their agreement with the references; reference-based scores cannot tell these cases apart.

The human baseline should be read in the same light: that every model falls below it means lower agreement with Clotho's references, not less correct captions. Longer captions and audible content missing from the references are associated with the gap, but neither was isolated as a cause.

Audio-aware metrics are at best a partial remedy. CLAP similarity is the only metric on which a model was not significantly below the human baseline, and its model order came closest to the audio review, but neither it nor MACE showed significant within-recording concordance. For LALM captions we therefore recommend reporting audio-aware metrics alongside reference-based ones, and checking a sample of captions against the audio before reading score differences as differences in correctness.

6. LIMITATIONS

Measurement reliability. The audio ratings are an operational assessment by a single reviewer, not an independently established ground truth, and the reviewer had read the references before listening. *Statistical precision.* The audio review covers 50 recordings: the order of Audio Flamingo 3, Qwen2.5-Omni-7B and Gemini 3.8 Flash in it is not stable (33% of resamples), and the concordance analysis (156 pairs from 42 recordings) has little power, so its null result does not show that metrics cannot track acoustic correctness. *Generalizability.* Each model was run with one prompt and decoding setting, the undisclosed training data of the API models may overlap with Clotho, and the findings are limited to Clotho's everyday sounds.

7. CONCLUSION

Agreement with human references and correctness about the recording are distinct properties of LALM captions. On Clotho v2.1, the reference-based ranking of four LALMs differed from a single-reviewer audio-grounded assessment, and 56 of the 64 sampled captions with weak reference agreement had no major acoustic error. Reference agreement should therefore not be taken as sufficient evidence that a caption is correct about the recording.

Availability. Code and data: `https://github.com/anandaswarup/lalm-acoustic-caption-eval`.

8. ACKNOWLEDGMENTS

No funding was received for conducting this study. The authors have no relevant financial or nonfinancial interests to disclose. We acknowledge Tampere University for the Clotho dataset.

9. COMPLIANCE WITH ETHICAL STANDARDS

This study uses the publicly available Clotho dataset and captions generated by AI models. No human participants were recruited, and no ethical approval was required.

10. REFERENCES

[1] Xinhao Mei, Xubo Liu, Mark D. Plumbley, and Wenwu Wang, "Automated audio captioning: An overview of recent progress and new challenges," *EURASIP J. Audio, Speech, Music Process.*, vol. 2022, no. 26, 2022.

[2] Yuan Gong, Hongyin Luo, Alexander H. Liu, Leonid Karlinsky, and James R. Glass, "Listen, think, and understand," in *Proc. ICLR*, 2024.

[3] Changli Tang et al., "SALMONN: Towards generic hearing abilities for large language models," in *Proc. ICLR*, 2024.

[4] Jin Xu et al., "Qwen2.5-Omni technical report," *arXiv preprint arXiv:2503.20215*, 2025.

[5] Sreyan Ghosh et al., "Audio Flamingo 3: Advancing audio intelligence with fully open large audio language models," in *Proc. NeurIPS*, 2025, vol. 38, pp. 41819–41886.

[6] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu, "BLEU: A method for automatic evaluation of machine translation," in *Proc. ACL*, 2002, pp. 311–318.

[7] Satanjeev Banerjee and Alon Lavie, "METEOR: An automatic metric for MT evaluation with improved correlation with human judgments," in *Proc. ACL Workshop Intrinsic Extrinsic Eval. Measures Mach. Transl. Summarization*, 2005, pp. 65–72.

[8] Ramakrishna Vedantam, C. Lawrence Zitnick, and Devi Parikh, "CIDEr: Consensus-based image description evaluation," in *Proc. CVPR*, 2015, pp. 4566–4575.

[9] Siqi Liu, Zhenhai Zhu, Ning Ye, Sergio Guadarrama, and Kevin Murphy, "Improved image captioning via policy gradient optimization of SPIDEr," in *Proc. ICCV*, 2017, pp. 873–881.

[10] Konstantinos Drossos, Samuel Lipping, and Tuomas Virtanen, "Clotho: An audio captioning dataset," in *Proc. ICASSP*, 2020, pp. 736–740.

[11] Chris Dongjoo Kim, Byeongchang Kim, Hyunmin Lee, and Gunhee Kim, "AudioCaps: Generating captions for audios in the wild," in *Proc. NAACL-HLT*, 2019, pp. 119–132.

[12] Samuel Lipping, Konstantinos Drossos, and Tuomas Virtanen, "Crowdsourcing a dataset of audio captions," in *Proc. DCASE Workshop*, 2019, pp. 139–143.

[13] Xinhao Mei et al., "WavCaps: A ChatGPT-assisted weakly-labelled audio captioning dataset for audio-language multimodal research," *IEEE/ACM Trans. Audio, Speech, Lang. Process.*, vol. 32, pp. 3339–3354, 2024.

[14] Soham Deshmukh, Benjamin Elizalde, Rita Singh, and Huaming Wang, "Pengi: An audio language model for audio tasks," in *Proc. NeurIPS*, 2023, pp. 18090–18108.

[15] Yunfei Chu et al., "Qwen-Audio: Advancing universal audio understanding via unified large-scale audio-language models," *arXiv preprint arXiv:2311.07919*, 2023.

[16] Chun-Yi Kuan, Wei-Ping Huang, and Hung-yi Lee, "Understanding sounds, missing the questions: The challenge of object hallucination in large audio-language models," in *Proc. Interspeech*, 2024, pp. 4144–4148.

[17] Peter Anderson, Basura Fernando, Mark Johnson, and Stephen Gould, "SPICE: Semantic propositional image caption evaluation," in *Proc. ECCV*, 2016, pp. 382–398.

[18] Zelin Zhou, Zhiling Zhang, Xuenan Xu, Zeyu Xie, Mengyue Wu, and Kenny Q. Zhu, "Can audio captions be evaluated with image caption metrics?," in *Proc. ICASSP*, 2022, pp. 981–985.

[19] Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q. Weinberger, and Yoav Artzi, "BERTScore: Evaluating text generation with BERT," in *Proc. ICLR*, 2020.

[20] Gijs Wijngaard, Elia Formisano, Bruno L. Giordano, and Michel Dumontier, "ACES: Evaluating automated audio captioning models on the semantics of sounds," in *Proc. EUSIPCO*, 2023, pp. 770–774.

[21] Tsung-Han Wu, Joseph E. Gonzalez, Trevor Darrell, and David M. Chan, "CLAIR-A: Leveraging large language models to judge audio captions," in *Proc. IEEE ASRU*, 2025.

[22] Étienne Labbé, Thomas Pellegrini, and Julien Pinquier, "Is my automatic audio captioning system so bad? SPIDEr-max: A metric to consider several caption candidates," in *Proc. DCASE Workshop*, 2022.

[23] Benjamin Elizalde, Soham Deshmukh, Mahmoud Al Ismail, and Huaming Wang, "CLAP: Learning audio concepts from natural language supervision," in *Proc. ICASSP*, 2023.

[24] Benjamin Elizalde, Soham Deshmukh, and Huaming Wang, "Natural language supervision for general-purpose audio representations," in *Proc. ICASSP*, 2024, pp. 336–340.

[25] Jack Hessel, Ari Holtzman, Maxwell Forbes, Ronan Le Bras, and Yejin Choi, "CLIPScore: A reference-free evaluation metric for image captioning," in *Proc. EMNLP*, 2021, pp. 7514–7528.

[26] Satvik Dixit, Soham Deshmukh, and Bhiksha Raj, "MACE: Leveraging audio for evaluating audio captioning systems," in *Proc. ICASSP Workshops*, 2025.

[27] Xinlei Chen et al., "Microsoft COCO captions: Data collection and evaluation server," *arXiv preprint arXiv:1504.00325*, 2015.

[28] Anna Rohrbach, Lisa Anne Hendricks, Kaylee Burns, Trevor Darrell, and Kate Saenko, "Object hallucination in image captioning," in *Proc. EMNLP*, 2018, pp. 4035–4045.

[29] Étienne Labbé, "aac-metrics: Metrics for evaluating automated audio captioning systems for PyTorch," `https://github.com/Labbeti/aac-metrics`, 2025, Version 0.5.5.