REFERENCE AGREEMENT IS NOT ACOUSTIC CORRECTNESS: EVALUATING LARGE AUDIO LANGUAGE MODEL CAPTIONS AGAINST HUMAN REFERENCES ON CLOTHO

Anandaswarup Vadapalli

International Institute of Information Technology, Hyderabad, India

ABSTRACT

Large audio language models (LALMs) describe everyday sound recordings in fluent natural language, but their captions are usually judged by how closely they agree with human references. We evaluate captions from four LALMs, GPT-Audio-1.5, Gemini 3.8 Flash, Qwen2.5-Omni-7B and Audio Flamingo 3, on the complete Clotho v2.1 evaluation split (1,045 recordings, 5,225 human captions) with twelve reference-based and two audio-aware metrics. A matched leave-one-out procedure scores held-out human captions against the same four references as the models. The two open-weight models score highest on every reference-based metric, yet all four models remain below the human baseline on each of them; only Audio Flamingo 3 reaches the human level, and only on CLAP audio–text similarity. Model captions are 1.4–1.9 times longer than human captions, and longer captions score lower on overlap metrics. A review of 200 sampled captions against the audio reverses the model order: GPT-Audio-1.5, ranked third or fourth by the text metrics, describes 47 of 50 recordings accurately, and 56 of the 64 captions that disagree most with the references are acoustically correct. No metric tracks acoustic correctness within a recording. Reference-based metrics therefore measure agreement with the captioning style of the references, not acoustic accuracy.

***Index Terms*—** Audio captioning, large audio language models, evaluation metrics, Clotho, human references

1. INTRODUCTION

Automated audio captioning (AAC) describes the sound sources, events and acoustic characteristics of a recording in natural language [1]. Applications include accessibility, multimedia retrieval and soundscape analysis. Large audio language models (LALMs) now perform this task without task-specific training, and produce longer and more detailed descriptions than captioning systems trained on AAC datasets [2, 3, 4, 5].

AAC systems are evaluated by comparing their captions with human references. Metrics such as BLEU [6], METEOR [7], CIDEr [8] and SPIDEr [9] measure the lexical or semantic overlap between a caption and the references. A recording, however, often contains several sounds, and different listeners describe different aspects of it. A caption may therefore describe an audible event that no reference mentions and receive a low score, or overlap well with the references while misrepresenting the audio. The difference matters more for LALMs, whose captions differ from the references in length and style.

In this paper we compare captions from four LALMs with the human references of Clotho v2.1 [10]. We address three research questions:

1. **RQ1: How closely do model captions agree with the five human reference captions?** We score each model's caption against all five references of its recording with twelve reference-based metrics and two audio-aware metrics, and compare the models.
2. **RQ2: How do model captions compare with held-out human captions in metric scores and caption length?** We score each human caption against the other four references and each model caption against the same four, so that model and human scores are directly comparable. We also compare caption lengths.
3. **RQ3: What patterns of agreement, additional detail, omission and mismatch appear in model captions?** We review a random sample of 200 model captions first against the references and then against the audio, and test whether the metrics follow either review.

We find that the reference-based metrics agree with each other and with the reference-only review, but not with correctness against the audio. The model with the most accurate captions in the audio review ranks third or fourth on every text metric. Section 2 reviews related work, Section 3 describes the method, Section 4 presents the results for RQ1–RQ3, and Section 5 discusses their implications and limitations.

2. RELATED WORK

AAC research relies on two crowdsourced datasets, AudioCaps [11] and Clotho [10], and on the DCASE challenge [1]. Clotho provides five captions per recording, collected with a three-step protocol in which annotators write captions, other annotators correct or rephrase them, and the top-rated five are kept [12]. LALMs couple an audio encoder with a large language model and follow free-form instructions; examples include LTU [2], SALMONN [3], Qwen2.5-Omni [4] and Audio Flamingo 3 [5].

AAC metrics were largely borrowed from image captioning [6, 7, 8, 13, 9]. Zhou et al. [14] showed that these metrics correlate poorly with human judgements of audio captions and proposed FENSE, which combines Sentence-BERT similarity with a fluency-error penalty. BERTScore [15] compares contextual token embeddings. CLAP [16] embeds audio and text in a joint space, so a caption can be scored against the recording itself, and MACE [17] combines CLAP audio–text and text–text similarity with a fluency penalty. In image captioning, human leave-one-out scores serve as a reference point for model scores [18]. We apply this calibration to LALM audio captions and, unlike metric-correlation studies, verify the disputed content of each sampled caption against the audio.

3. METHOD

3.1. Data and models

We use the complete evaluation split of Clotho v2.1 [10]: 1,045 recordings of 15–30 s (6.5 h in total), each with five human captions of 8–20 words (5,225 captions). We evaluate two API models, GPT-Audio-1.5 (`gpt-audio-1.5`) and Gemini 3.8 Flash (`gemini-3.8-flash`), and two open-weight models, Qwen2.5-Omni-7B [4] and Audio Flamingo 3 [5], at pinned checkpoint revisions. Every model received the full recording followed by the same instruction: *"Describe the sounds heard in this audio recording in one clear sentence that mentions the main sound sources, audible events, and distinguishing acoustic characteristics. Do not speculate about sources or events that are not supported by the audio. Respond with the sentence only, as plain text, without JSON, lists, labels or other formatting."* No references were shown, no length was imposed, and no model-specific prompt tuning was done.

Decoding used temperature 0, top-p 1 and a seed of 42 where supported; Gemini 3.8 Flash ran at its lowest thinking level, as thinking cannot be disabled. This gave one caption per model and recording (4,180 in total). GPT-Audio-1.5 sometimes answered in JSON despite the instruction: 85 captions were plain sentences wrapped in braces and were unwrapped, and 21 malformed captions were scored as returned. Excluding the 21 affected recordings changes no model order and no significance decision. The API models are not deterministic at temperature 0, so all results are conditional on the released captions.

3.2. Metrics and human leave-one-out calibration

The reference-based metrics are BLEU-1 to BLEU-4, METEOR, CIDEr-D, SPICE [13], SPIDEr, SPIDEr-FL, FENSE, and the raw and baseline-rescaled F1 of BERTScore, computed on PTB-tokenized text with the aac-metrics package [19]. The audio-aware metrics are CLAP similarity, the cosine between the audio and caption embeddings of MS-CLAP 2023 [20], and MACE [17]. CLAP embeds each clip whole, as the duration-weighted mean of 7 s chunks. BERTScore uses the last layer of RoBERTa-large without IDF weighting. We compute it with our own batching code, because the torchmetrics version used by aac-metrics restores length-sorted embeddings in the wrong order in batched calls and thus scores captions against other items' references.

For RQ2, let $H = \{h_1, \ldots, h_5\}$ be the human captions of a recording and m_k the caption of model k. For each position j, the held-out caption h_j and m_k are both scored against $R_{-j} = H \setminus \{h_j\}$. The five scores are averaged per recording; corpus-level metrics are computed once per position and averaged. Because CIDEr-D, and hence SPIDEr and SPIDEr-FL, depend on the reference set, five-reference (RQ1) and four-reference (RQ2) scores are never compared with each other. Clotho's protocol keeps original and rephrased captions without deduplication, which is consistent with the near-paraphrase pairs we observe: 33% of held-out captions share a word-set Jaccard overlap of at least 0.6 with one of their references. We therefore repeat the comparison without these captions.

3.3. Caption length and qualitative review

Caption length is the number of whitespace-separated words. We relate it to each score with Spearman correlations over captions. For RQ3, we drew 50 recordings at random (seed 42), independently of the scores, giving 200 model captions. A single reviewer labelled them blind to model identity, with captions shown under per-recording random labels. The reviewer first compared each caption with the five references only and assigned one of six agreement categories: (1) strong agreement, (2) mostly aligned, (3) mostly aligned with additional details, (4) partially aligned with missing details, (5) partially aligned with additional details, and (6) weak agreement or source/event mismatch. Phrases supported by no reference were recorded. After these labels were final, the reviewer listened to each recording and rated each caption as (1) accurate, (2) minor errors, or (3) major error or wrong sound source, and judged each recorded phrase as supported, unsupported or unverifiable by the audio.

3.4. Statistical analysis

The recording is the unit of analysis, and every comparison is paired. We test mean differences with two-sided sign-flip permutation tests (10,000 permutations) and report 95% percentile bootstrap intervals over recordings (10,000 resamples). Holm correction is applied within predefined families: 84 model-pair tests for RQ1 and 56 model-versus-human tests for RQ2. We report the paired effect size d_z, because with 1,045 recordings very small differences are significant. Ranking stability is the share of bootstrap resamples that reproduce the observed model order. To relate the metrics to the audio review, we count, over pairs of captions of the same recording with different audio ratings, how often a metric scores the better-rated caption higher (concordance; 0.5 is chance).

4. RESULTS

4.1. RQ1: Agreement with five references

Table 1 (left) shows that Audio Flamingo 3 scores highest and Qwen2.5-Omni-7B second on every reference-based metric. The two API models share the third and fourth places: for example, CIDEr-D is 0.191 and 0.164 for the open-weight models and 0.064 and 0.048 for Gemini 3.8 Flash and GPT-Audio-1.5. The order is stable: at least 99% of bootstrap resamples reproduce it for BLEU-1, BLEU-2, BLEU-4, METEOR, CIDEr-D, SPICE, FENSE and both BERTScores. The exceptions are BLEU-3 (87%) and SPIDEr (55%), where GPT-Audio-1.5 and Gemini 3.8 Flash are tied. After Holm correction, 76 of the 84 model-pair differences are significant. Absolute agreement is low: CIDEr-D ranges from 0.05 to 0.19.

The audio-aware metrics order the models differently. CLAP similarity places GPT-Audio-1.5 level with Qwen2.5-Omni-7B (0.466 and 0.462), and MACE finds no difference between them (0.573 and 0.575); Gemini 3.8 Flash is last on both. Per caption, the text metrics correlate with each other (Spearman ρ = 0.41–0.88), whereas CLAP and MACE correlate 0.89 with each other but only 0.28–0.67 with the text metrics.

4.2. RQ2: Comparison with held-out human captions

Under the same four references, every model is below the human baseline on every reference-based metric, with large effects (d_z from -0.48 to -2.55; Table 1, right). 55 of the 56 comparisons are significant after Holm correction. The exception is CLAP similarity, where Audio Flamingo 3 is level with the human captions ($+0.006$, $d_z = 0.06$); when held-out captions with a near-paraphrase reference are removed, Audio Flamingo 3 is significantly above the human baseline on CLAP similarity (uncorrected). The near-paraphrase pairs inflate the human baseline: without them,

Table 1. Mean per-recording scores. Left: model captions against all five references (RQ1); bold marks the highest model. Right: held-out human captions against four references, and the paired effect size d_z of each model minus the human baseline under the same four references (RQ2). Every difference is Holm-significant except the one marked †. The last row gives mean caption length and d_z of model length minus the mean reference length.

	Five references				Human	Model − human, d_z (four references)			
Metric	GPT	Gemini	Qwen	AF3	(four ref.)	GPT	Gemini	Qwen	AF3
BLEU-1	0.277	0.251	0.368	**0.407**	0.640	−2.49	−2.55	−1.67	−1.40
BLEU-4	0.004	0.002	0.015	**0.030**	0.234	−1.27	−1.28	−1.18	−1.05
METEOR	0.124	0.102	0.151	**0.174**	0.319	−1.84	−2.05	−1.57	−1.32
CIDEr-D	0.048	0.064	0.164	**0.191**	0.906	−1.83	−1.75	−1.54	−1.41
SPICE	0.067	0.051	0.091	**0.117**	0.232	−1.47	−1.58	−1.19	−0.91
SPIDEr	0.057	0.058	0.127	**0.154**	0.569	−1.90	−1.84	−1.59	−1.41
FENSE	0.401	0.387	0.474	**0.510**	0.575	−1.10	−1.05	−0.73	−0.48
BERTScore-F1 (rescaled)	0.254	0.238	0.331	**0.352**	0.598	−2.40	−2.47	−1.80	−1.51
CLAP similarity	0.466	0.381	0.462	**0.509**	0.503	−0.34	−0.94	−0.42	+0.06†
MACE	0.573	0.489	0.575	**0.608**	0.635	−0.61	−1.18	−0.69	−0.34
Caption length (words)	21.0	16.4	17.0	19.0	11.3	+2.40	+1.30	+1.13	+1.16

Table 2. Review of 50 sampled captions per model, first against the references and then against the audio. Counts of captions out of 50, except the last row (phrases).

	GPT	Gemini	Qwen	AF3
Against the references				
Categories 1–3 (main content agrees)	15	8	21	**26**
Category 4 (missing details)	10	6	5	5
Category 6 (weak or mismatch)	15	24	15	10
Against the audio				
Rated accurate	**47**	23	25	27
Major error or wrong source	0	9	5	7
Category 6 and major error	0	6	1	1
Unreferenced phrases unsupported	1/59	34/80	20/58	19/65

human CIDEr-D falls from 0.91 to 0.46 and rescaled BERTScore from 0.60 to 0.47. Even so, every model remains significantly below human on all reference-based metrics.

Model captions are 1.45 (Gemini 3.8 Flash) to 1.85 (GPT-Audio-1.5) times as long as human captions, and 92% of GPT-Audio-1.5's captions are longer than every reference of their recording. For the models, length correlates negatively with the overlap metrics: from -0.09 (Gemini 3.8 Flash) to -0.63 (Audio Flamingo 3) for CIDEr-D, and from -0.19 to -0.52 for rescaled BERTScore. CLAP similarity and MACE are almost independent of length, except for Audio Flamingo 3 (-0.11 and -0.17), and human captions show near-zero correlations throughout.

4.3. RQ3: Agreement patterns and acoustic correctness

The sample is representative of the full set: no recording, length or score statistic differs from the population mean by more than 0.37 standard deviations. Against the references, Audio Flamingo 3 and Qwen2.5-Omni-7B agree most often with the main content and Gemini 3.8 Flash least often (Table 2). GPT-Audio-1.5's most frequent deviation is omission: it has the most captions in category 4.

Against the audio, the order changes. GPT-Audio-1.5 describes 47 of 50 recordings accurately and makes no major error, while the other three models are accurate for 23 to 27 recordings and make 5 to 9 major errors. Most disagreement with the references is not an acoustic error: of the 64 captions in category 6, only 8 have a major error, and the other 56 describe the recording correctly or with minor errors, which means that the references are incomplete. Of the 262 phrases that no reference supports, 64% are audible in the recording, 28% are not and 8% cannot be verified. Unsupported phrases occur in 26 of Gemini 3.8 Flash's captions, 19 of Qwen2.5-Omni-7B's and 15 of Audio Flamingo 3's, but in only one of GPT-Audio-1.5's. In addition, 23 of the 26 category-4 captions are rated accurate.

The metrics follow the reference review, not the audio review. Kendall's τ between each metric's model order and the reference-review order is 0.67–1.00, but with the audio-review order it is 0–0.33 for every metric except CLAP similarity (0.67). Mean scores fall from category 1 to category 6 on every metric (e.g. FENSE 0.68 to 0.28), but are flat or reversed across audio ratings (rescaled BERTScore 0.29, 0.31 and 0.34 for ratings 1, 2 and 3). Within a recording, across 156 caption pairs with different audio ratings, concordance ranges from 0.39 (rescaled BERTScore) to 0.58 (MACE), and no metric differs from chance after Holm correction.

5. DISCUSSION AND LIMITATIONS

The results separate two properties that reference-based evaluation treats as one: agreement with the references and correctness about the audio. The text metrics agree with each other, with the reference-only review and with the model order of RQ1, but none of them follows the audio review across models or within recordings. GPT-Audio-1.5 is the clearest case: it ranks third or fourth on every text metric, yet its captions are the most accurate, because its deviations from the references are omissions and correct additional details rather than errors. The models' longer captions and the negative length–score correlations suggest that part of the gap to the human baseline reflects the short, generic style of Clotho's references rather than wrong content. We did not control for length, so this explanation remains untested. The human baseline is also not an upper bound on quality: near-paraphrase pairs among the references inflate it, although removing them does not close the gap.

Among the metrics, only CLAP similarity, which compares the caption with the audio, places a model at the human level and comes

close to the audio-review order. Its within-recording concordance (0.56; 0.62 for accurate versus major-error pairs) is the highest along with MACE, but not significantly above chance. For LALM captions we therefore recommend reporting audio-aware metrics alongside reference-based ones, and checking a sample of captions against the audio before interpreting differences in reference agreement as differences in quality.

This study has several limitations. The audio review rests on one reviewer and 50 recordings; the reviewer had read the references before listening, and the order of Audio Flamingo 3, Qwen2.5-Omni-7B and Gemini 3.8 Flash in the audio review is not stable (33% of resamples). The concordance analysis has little power (156 pairs from 42 recordings), so the absence of evidence that metrics track correctness is not evidence that they cannot. Each model was run with one prompt and one decoding setting, and the training data of the API models are undisclosed, so overlap with Clotho cannot be ruled out. Finally, the findings are limited to Clotho's everyday and environmental sounds.

6. CONCLUSION

We compared captions from four LALMs with the human references of Clotho v2.1. The open-weight models agree most with the references (RQ1), but every model remains below a matched human baseline on every reference-based metric and writes captions 1.4–1.9 times longer than humans (RQ2). Most disagreement with the references reflects incomplete references rather than acoustic errors, and the model that agrees least with the references describes the audio most accurately (RQ3). Reference-based scores should therefore be read as agreement with a captioning style, and claims about the acoustic quality of LALM captions require evidence from the audio itself. Code, captions, scores and review annotations are available at `https://github.com/anandaswarup/lalm-acoustic-caption-eval`.

7. ACKNOWLEDGMENTS

No funding was received for conducting this study. The authors have no relevant financial or nonfinancial interests to disclose. We acknowledge Tampere University for the Clotho dataset.

8. COMPLIANCE WITH ETHICAL STANDARDS

This is a numerical simulation study for which no ethical approval was required.

9. REFERENCES

[1] Xinhao Mei, Xubo Liu, Mark D. Plumbley, and Wenwu Wang, "Automated audio captioning: An overview of recent progress and new challenges," *EURASIP Journal on Audio, Speech, and Music Processing*, vol. 2022, no. 26, 2022.

[2] Yuan Gong, Hongyin Luo, Alexander H. Liu, Leonid Karlinsky, and James R. Glass, "Listen, think, and understand," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2024.

[3] Changli Tang, Wenyi Yu, Guangzhi Sun, Xianzhao Chen, Tian Tan, Wei Li, Lu Lu, Zejun Ma, and Chao Zhang, "SALMONN: Towards generic hearing abilities for large language models," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2024.

[4] Jin Xu, Zhifang Guo, Jinzheng He, Hangrui Hu, Ting He, Shuai Bai, Keqin Chen, Jialin Wang, Yang Fan, Kai Dang, Bin Zhang, Xiong Wang, Yunfei Chu, and Junyang Lin, "Qwen2.5-Omni technical report," *arXiv preprint arXiv:2503.20215*, 2025.

[5] Sreyan Ghosh, Arushi Goel, Jaehyeon Kim, Sonal Kumar, Zhifeng Kong, Sang-gil Lee, Chao-Han Huck Yang, Ramani Duraiswami, Dinesh Manocha, Rafael Valle, and Bryan Catanzaro, "Audio Flamingo 3: Advancing audio intelligence with fully open large audio language models," in *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, 2025, vol. 38, pp. 41819–41886.

[6] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu, "BLEU: A method for automatic evaluation of machine translation," in *Proc. Annual Meeting of the Association for Computational Linguistics (ACL)*, 2002, pp. 311–318.

[7] Satanjeev Banerjee and Alon Lavie, "METEOR: An automatic metric for MT evaluation with improved correlation with human judgments," in *Proc. ACL Workshop on Intrinsic and Extrinsic Evaluation Measures for Machine Translation and/or Summarization*, 2005, pp. 65–72.

[8] Ramakrishna Vedantam, C. Lawrence Zitnick, and Devi Parikh, "CIDEr: Consensus-based image description evaluation," in *Proc. IEEE Conf. Computer Vision and Pattern Recognition (CVPR)*, 2015, pp. 4566–4575.

[9] Siqi Liu, Zhenhai Zhu, Ning Ye, Sergio Guadarrama, and Kevin Murphy, "Improved image captioning via policy gradient optimization of SPIDEr," in *Proc. IEEE Int. Conf. Computer Vision (ICCV)*, 2017, pp. 873–881.

[10] Konstantinos Drossos, Samuel Lipping, and Tuomas Virtanen, "Clotho: An audio captioning dataset," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process. (ICASSP)*, 2020, pp. 736–740.

[11] Chris Dongjoo Kim, Byeongchang Kim, Hyunmin Lee, and Gunhee Kim, "AudioCaps: Generating captions for audios in the wild," in *Proc. Conf. North American Chapter of the Association for Computational Linguistics (NAACL-HLT)*, 2019, pp. 119–132.

[12] Samuel Lipping, Konstantinos Drossos, and Tuomas Virtanen, "Crowdsourcing a dataset of audio captions," in *Proc. Detection and Classification of Acoustic Scenes and Events Workshop (DCASE)*, 2019, pp. 139–143.

[13] Peter Anderson, Basura Fernando, Mark Johnson, and Stephen Gould, "SPICE: Semantic propositional image caption evaluation," in *Proc. European Conf. Computer Vision (ECCV)*, 2016, pp. 382–398.

[14] Zelin Zhou, Zhiling Zhang, Xuenan Xu, Zeyu Xie, Mengyue Wu, and Kenny Q. Zhu, "Can audio captions be evaluated with image caption metrics?," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process. (ICASSP)*, 2022, pp. 981–985.

[15] Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q. Weinberger, and Yoav Artzi, "BERTScore: Evaluating text generation with BERT," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2020.

[16] Benjamin Elizalde, Soham Deshmukh, Mahmoud Al Ismail, and Huaming Wang, "CLAP: Learning audio concepts from natural language supervision," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process. (ICASSP)*, 2023.

[17] Satvik Dixit, Soham Deshmukh, and Bhiksha Raj, "MACE: Leveraging audio for evaluating audio captioning systems," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process. Workshops (ICASSPW)*, 2025.

[18] Xinlei Chen, Hao Fang, Tsung-Yi Lin, Ramakrishna Vedantam, Saurabh Gupta, Piotr Dollár, and C. Lawrence Zitnick, "Microsoft COCO captions: Data collection and evaluation server," *arXiv preprint arXiv:1504.00325*, 2015.

[19] Étienne Labbé, "aac-metrics: Metrics for evaluating automated audio captioning systems for PyTorch," `https://github.com/Labbeti/aac-metrics`, 2025, Version 0.5.5.

[20] Benjamin Elizalde, Soham Deshmukh, and Huaming Wang, "Natural language supervision for general-purpose audio representations," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process. (ICASSP)*, 2024, pp. 336–340.