

Module 1: Introduction to Java Fundamentals

Premanand S

Assistant Professor
School of Electronics Engineering
Vellore Institute of Technology
Chennai Campus

premanand.s@vit.ac.in

February 9, 2026

Contents

OOP Paradigm

Features of Java Language

JVM - Bytecode and Java program structure

Basic programming constructs

Data types variables Java naming conventions

Operators

Control and looping constructs

Arrays one dimensional and multi-dimensional

Enhanced for loop

Strings - S

StringBuffer, StringBuilder and Math - Wrapper classes.

Why Not Always Use String?

Strings in Java are **immutable**.

Why Not Always Use String?

Strings in Java are **immutable**.

- Cannot change existing content
- Every change creates a new object

Why Not Always Use String?

Strings in Java are **immutable**.

- Cannot change existing content
- Every change creates a new object

Problem:

- Waste of memory
- Slower for repeated changes

Solution — Mutable Strings

Java provides:

Solution — Mutable Strings

Java provides:

- **StringBuffer**
- **StringBuilder**

Solution — Mutable Strings

Java provides:

- **StringBuffer**
- **StringBuilder**

They are:

- Mutable
- Faster for modifications

Creating StringBuffer and StringBuilder

```
StringBuffer sb1 = new StringBuffer("Hello");  
StringBuilder sb2 = new StringBuilder("Hello");
```

append() Method

```
StringBuilder sb = new StringBuilder("Java");  
sb.append(" Programming");  
  
System.out.println(sb);
```

StringBuffer vs StringBuilder

- StringBuffer → safer

StringBuffer vs StringBuilder

- StringBuffer → safer
- StringBuilder → faster

StringBuffer vs StringBuilder

- StringBuffer → safer
- StringBuilder → faster

Rule:

- Single-user program → StringBuilder

Tricky Understanding

- String → creates new object

Tricky Understanding

- String → creates new object
- Buffer/Builder → modifies same object

Tricky Understanding

- String → creates new object
- Buffer/Builder → modifies same object

Think: Paper vs Whiteboard

Understanding

- Create a `StringBuilder` with "Hello", append " World", and print it.
- Create a `StringBuffer` with "Java", append " Programming", and print its length.
- Reverse the string "MADAM" using `StringBuilder`.
- Insert the word "Programming " into "I Love Java" using `StringBuilder`.
- Remove numeric characters from "Java123" using `StringBuffer`.

- 1 Predict the output:

```
String s = "Hello";  
s.concat(" World");  
System.out.println(s);
```

- 2 Predict the output and explain why the result occurs.

- 1 Predict the output:

```
StringBuilder sb1 = new StringBuilder("Hi");  
StringBuilder sb2 = sb1;  
sb2.append(" All");  
System.out.println(sb1);
```

- 2 Which is faster for repeated string modification: String, StringBuffer, or StringBuilder? Why?

Math Class — What is it?

The **Math class** provides ready-made mathematical functions.

Math Class — What is it?

The **Math class** provides ready-made mathematical functions.

- Square root
- Power
- Rounding
- Maximum / Minimum
- Random numbers

Math Class — Important Rule

You do **NOT** create an object of Math class.

Math Class — Important Rule

You do **NOT** create an object of Math class.

Correct:

- `Math.sqrt(25)`

Math Class — Important Rule

You do **NOT** create an object of Math class.

Correct:

- `Math.sqrt(25)`

Reason:

- All Math methods are **static**

- `Math.abs(x)`

Math Class — Common Methods

- `Math.abs(x)`
- `Math.max(a, b)`

Math Class — Common Methods

- `Math.abs(x)`
- `Math.max(a, b)`
- `Math.min(a, b)`

Math Class — Common Methods

- `Math.abs(x)`
- `Math.max(a, b)`
- `Math.min(a, b)`
- `Math.sqrt(x)`

Math Class — Common Methods

- `Math.abs(x)`
- `Math.max(a, b)`
- `Math.min(a, b)`
- `Math.sqrt(x)`
- `Math.pow(a, b)`

Math Class — Rounding Methods

- `Math.round(4.6)` \rightarrow 5

Math Class — Rounding Methods

- `Math.round(4.6)` \rightarrow 5
- `Math.ceil(4.1)` \rightarrow 5.0

Math Class — Rounding Methods

- `Math.round(4.6)` \rightarrow 5
- `Math.ceil(4.1)` \rightarrow 5.0
- `Math.floor(4.9)` \rightarrow 4.0

Math Class — Rounding Methods

- `Math.round(4.6)` \rightarrow 5
- `Math.ceil(4.1)` \rightarrow 5.0
- `Math.floor(4.9)` \rightarrow 4.0

Tip: Ceil = ceiling, Floor = floor

Method:

- `Math.random()`

Method:

- `Math.random()`

Range:

- $0.0 \leq \text{value} < 1.0$

Method:

- `Math.random()`

Range:

- $0.0 \leq \text{value} < 1.0$

Example:

- `(int)(Math.random() * 10) → 0 to 9`

Math Class — Example Program

```
public class MathExample {  
    public static void main(String[] args) {  
  
        System.out.println(Math.abs(-20));  
        System.out.println(Math.sqrt(36));  
        System.out.println(Math.pow(3, 2));  
        System.out.println(Math.round(5.6));  
  
        int r = (int)(Math.random() * 50);  
        System.out.println(r);  
    }  
}
```

Wrapper Classes — Introduction

A **Wrapper class** converts a **primitive data type** into an **object**.

Wrapper Classes — Introduction

A **Wrapper class** converts a **primitive data type** into an **object**.
In simple words:

- Wraps primitive values into objects

Wrapper Classes — Introduction

A **Wrapper class** converts a **primitive data type** into an **object**.
In simple words:

- Wraps primitive values into objects

Example:

- `int` → `Integer`
- `double` → `Double`

Wrapper Classes — Why Needed?

Java is an **object-oriented language**.

Wrapper Classes — Why Needed?

Java is an **object-oriented language**.

But:

- Primitive types are NOT objects

Wrapper Classes — Why Needed?

Java is an **object-oriented language**.

But:

- Primitive types are NOT objects

Wrapper classes help when:

- Working with Collections
- Using Generics
- Converting data types

Primitive Types vs Wrapper Classes

Primitive	Wrapper Class
int	Integer
double	Double
char	Character
boolean	Boolean
float	Float
long	Long
byte	Byte
short	Short

Creating Wrapper Objects

```
Integer a = new Integer(10);    // old style  
Integer b = Integer.valueOf(20);
```

Creating Wrapper Objects

```
Integer a = new Integer(10);    // old style  
Integer b = Integer.valueOf(20);
```

Modern Java

```
Integer c = 30;    // autoboxing
```

Autoboxing:

- Automatic conversion of primitive \rightarrow object

Autoboxing:

- Automatic conversion of primitive \rightarrow object

Example:

- Integer `x = 10;`

Autoboxing:

- Automatic conversion of primitive \rightarrow object

Example:

- Integer `x = 10;`

Done by JVM automatically

Unboxing:

- Automatic conversion of object \rightarrow primitive

Unboxing:

- Automatic conversion of object \rightarrow primitive

Example:

- `int y = x;`

Wrapper Classes — Useful Methods

- `parseInt()`

Wrapper Classes — Useful Methods

- `parseInt()`
- `parseDouble()`

Wrapper Classes — Useful Methods

- `parseInt()`
- `parseDouble()`
- `valueOf()`

Wrapper Classes — Useful Methods

- `parseInt()`
- `parseDouble()`
- `valueOf()`
- `toString()`

String to Primitive Conversion

```
String s = "123";  
  
int num = Integer.parseInt(s);  
double d = Double.parseDouble("45.6");  
  
System.out.println(num);  
System.out.println(d);
```


Wrapper Classes — Tricky Understandings

- Wrapper classes are immutable

Wrapper Classes — Tricky Understandings

- Wrapper classes are immutable
- Autoboxing can cause `NullPointerException`

Wrapper Classes — Tricky Understandings

- Wrapper classes are immutable
- Autoboxing can cause `NullPointerException`
- `parseInt()` throws exception for invalid input

Wrapper Classes

```
public class WrapperDemo {  
    public static void main(String[] args) {  
  
        int a = 10;  
        Integer obj = a;           // autoboxing  
  
        int b = obj;               // unboxing  
  
        String s = "100";  
        int num = Integer.parseInt(s);  
  
        System.out.println(obj);  
        System.out.println(b);  
        System.out.println(num);  
    }  
}
```

Wrapper Classes — Real-Life Usage

- Collections like ArrayList

Wrapper Classes — Real-Life Usage

- Collections like ArrayList
- Parsing user input

Wrapper Classes — Real-Life Usage

- Collections like ArrayList
- Parsing user input
- Generics and frameworks

Output

```
Integer a = 20;
```

```
Integer b = a;
```

```
b = 30;
```

```
System.out.println(a);
```


Output

```
String s = "50";  
int x = Integer.parseInt(s);  
System.out.println(x * 2);
```

Thank You!

Stay Connected

Premanand S

Email: premanand.s@vit.ac.in

Phone: +91-7358679961

LinkedIn: linkedin.com/in/premsanand

Instagram: instagram.com/premsanand

WhatsApp Channel: [anandsDataX](#)

Google Scholar: [Google Scholar Profile](#)

GitHub: github.com/anandprems