Quick Deploy: Next.js on Ubuntu + Nginx

Copy-paste summary | http://192.168.6.128/ocr

Changes from RHEL: owner is `www-data` (not `nginx`); no `restorecon` (Ubuntu has no SELinux), a `chmod` is used instead; config goes in `sites-available` with a link in `sites-enabled` and the default site is disabled; firewall is `ufw`.

1. Build on Windows (PowerShell)

```
cd C:\path\to\your\project
$env:BASE_PATH="/ocr"
npm run build
```

Check: `out\index.html` should contain `/ocr/_next/`.

2. Upload with FileZilla

Connect with `sftp://192.168.6.128`, your Ubuntu user, port 22. Upload the **contents** of `out` to `/home/youruser/ocr/` on the server.

3. Copy into the web folder (SSH)

```
sudo mkdir -p /var/www/html/ocr
sudo rm -rf /var/www/html/ocr/*
sudo cp -r ~/ocr/* /var/www/html/ocr/
sudo chown -R www-data:www-data /var/www/html/ocr
sudo chmod -R u=rwX,go=rX /var/www/html/ocr
```

4. Create the Nginx config (one-time)

```
sudo tee /etc/nginx/sites-available/ocr > /dev/null <<'EOF'
server {
    listen 80;
    server_name 192.168.6.128;
    root /var/www/html;
    index index.html;

    location = /ocr {
        return 301 /ocr/;
    }

    location /ocr/ {
        try_files $uri $uri/ $uri.html =404;
        error_page 404 /ocr/404.html;
    }

    location /ocr/_next/static/ {
        expires 1y;
        add_header Cache-Control "public, immutable";
    }
}
EOF
```

Enable it, disable Ubuntu's default site, test and reload:

```
sudo ln -sf /etc/nginx/sites-available/ocr /etc/nginx/sites-enabled/ocr
sudo rm -f /etc/nginx/sites-enabled/default
sudo nginx -t && sudo systemctl enable --now nginx && sudo systemctl reload nginx
```

5. Open the firewall (one-time)

Check first with `sudo ufw status`. If it says **inactive**, skip this step. If **active**:

```
sudo ufw allow 'Nginx HTTP'
sudo ufw reload
```

> If you turn ufw on (`sudo ufw enable`), run `sudo ufw allow OpenSSH` first, or you lose SSH and FileZilla access.

6. Test

Open `http://192.168.6.128/ocr`

Future updates

Windows:

```
$env:BASE_PATH="/ocr"; npm run build
```

FileZilla: upload the contents of `out` to `~/ocr` and choose **Overwrite**.

Linux:

```
sudo rm -rf /var/www/html/ocr/* && \
sudo cp -r ~/ocr/* /var/www/html/ocr/ && \
sudo chown -R www-data:www-data /var/www/html/ocr && \
sudo chmod -R u=rwX,go=rX /var/www/html/ocr
```

If something breaks

```
sudo tail -20 /var/log/nginx/error.log
```

- **403:** run the `chown` and `chmod` commands again.
- **Unstyled page:** rebuild with `BASE_PATH=/ocr`.
- **"Welcome to nginx!" page:** `sudo rm -f /etc/nginx/sites-enabled/default`, then `sudo systemctl reload nginx`.
- **Page does not load:** `sudo ufw status` and `sudo systemctl status nginx`.

RHEL → Ubuntu

RHEL	Ubuntu
`chown -R nginx:nginx`	`chown -R www-data:www-data`
`restorecon -Rv /var/www/html/ocr`	`chmod -R u=rwX,go=rX /var/www/html/ocr`
`/etc/nginx/conf.d/ocr.conf`	`/etc/nginx/sites-available/ocr + link in sites-enabled`
`(default server in nginx.conf)`	`rm -f /etc/nginx/sites-enabled/default`
`firewall-cmd --permanent --add-service=http`	`ufw allow 'Nginx HTTP'`
`firewall-cmd --reload`	`ufw reload`