5 | Apps, evaluation and release

Streaming

FastAPI SSE carries progress, text and a final done/error event. Partial text is not successful completion. Handle disconnects, deadlines and admission cleanup. Streamlit keeps session state per browser session.

Authentication

Authenticate first, derive the principal on the server, then authorize the thread or review. Never accept customer identity from tool arguments. Give reviewers separate credentials.

Evaluation

Run the actual application path on held-out cases. Score tool trajectory, ownership, quote support, factual correctness and tone separately. Fakes test contracts; live and human review measure real quality.

Budgets and traces

Reserve a conservative call allowance before execution, including nested calls. Unknown token usage is not zero cost. Redact logs and avoid raw sensitive spans; tracing can upload prompts.

Deployment

Build from the repository root, inject secrets at runtime, run as non-root and keep source read-only. SQLite plus local admission uses one worker. A Postgres saver probe does not prove full horizontal scalability.

Release decision

The corrected scripted Support Copilot passes 6/6 complete contracts; all 19 capstone cases pass. Missing facts still block the strict gate. Offline success does not establish live-model quality or customer deployment readiness.

Try it

```
uv sync --extra apps
uv run --no-sync python scripts/evaluate.py --offline
uv run --no-sync python scripts/evaluate.py --offline --release
```