LangGraph | API at a glance

LARKSPUR CLAIMS | OFFLINE-FIRST PRACTICE COURSE

StateGraph(State)
Define named state channels and optional input/output/context schemas.

add_node / add_edge
Register work and fixed connections. START enters; END completes.

add_conditional_edges
Map a router's result to the next destination; cover every possible result.

Command / Send
Update and route, resume an interrupt, or schedule parameterized parallel work.

compile(checkpointer=...)
Create a runnable with an explicit persistence lifecycle.

invoke / ainvoke
Pass version='v2'; inspect result.value and result.interrupts.

stream / astream
Pass version='v2'; handle each part's type, ns, and data.

interrupt / Command(resume=...)
Save a request, then continue the same thread with validated answers.

get_state / get_state_history
Inspect current and earlier snapshots, including next scheduled work.

update_state
Create a state update at a selected boundary; use checkpoint configuration deliberately.

Runtime / Store
Read trusted context and scoped cross-thread memory inside a node.

entrypoint / task
Use ordinary Python orchestration with durable task results.

create_agent
Build a bounded model/tool loop from langchain.agents and the shared model factory.

Beta: stream_events / DeltaChannel
Optional B4 only; v3 events use method/params, unlike core v2 parts.

Verified 2026-11-06. Core Python output: v2. Optional Beta APIs: B4.
Sources and pinned versions: docs/VERIFICATION_NOTES.md