Tier 3 | Compose and recover

LARKSPUR CLAIMS | OFFLINE-FIRST PRACTICE COURSE

Subgraphs
Share only intended state fields. Use adapters for private schemas. Choose inherited or independent checkpoint ownership explicitly.

Multiple agents
Use specialists for distinct contexts or capabilities. A supervisor adds latency and coordination work; compare a single-agent baseline.

Handoffs
Command.PARENT transfers control to the parent. Preserve matched tool responses and keep state contracts compatible.

Functional API
entrypoint orchestrates; task saves repeatable work results. Entry code may re-enter while a completed task result is reused.

External calls
Use timeouts, bounded retries, cancellation cleanup, and a stable idempotency key tied to a canonical payload.

MCP
Own the client session lifetime. Local stdio needs no network. Keep protocol stdout free of logs and expose read-only tools first.

Fault recovery
Test a crash after effect commit but before task completion. A checkpoint and an external transaction are separate boundaries.

Long waits
Persist before waiting; reopen the same thread after restart. Never keep a Python process asleep for days to represent a business wait.

Practice
Modules 13-17; inject failures at boundaries. Checkpoint project: Fraud Investigation Team.

Verified 2026-11-06. Core Python output: v2. Optional Beta APIs: B4.
Sources and pinned versions: docs/VERIFICATION_NOTES.md