Tier 5 / Shipping

Install, deploy, operate and recover.

Packages

Build wheel/sdist, npm package and MCPB bundle from reviewed source. Inspect archive contents.

Launch installed packages outside the checkout; test uvx/npx and environment configuration.

Publication is separate from local packaging and requires the learner account.

Registry

Validate server.json against the pinned official schema and match package identity/version.

Verify namespace ownership before publishing. Registry metadata is discovery, not endorsement.

Review candidate endpoints and dependencies before installation or credential disclosure.

Remote operations

Use HTTPS externally, exact public resource URLs and configured trusted key endpoints.

Separate health/readiness from protected data; limit rates, bytes, runtime and costs.

Single-worker teaching state must become shared durable state before scaling out.

Production host

Bound connection attempts and calls. Retry only locally allowlisted reads; reconcile uncertain writes.

Refetch changed catalogs and revoke stale approvals.

Keep provider credentials server-side; isolate App frames and enforce their tool allowlist.

Run and teardown

uv run python scripts/package_lab.py --prepare

npm run build:chat; npm run test:browser

Use the documented Docker Compose stack; stop it afterward. Remove persistent volumes only intentionally.

Checkpoint

Prove installed launches, OAuth rejection, host approval/decline, Tasks and App isolation.

Finish Ops and Chat Pro capstones; review docs/DEFINITION_OF_DONE.md.