



EQUIPMENT NO/FEEDER NO
CONN. LOAD IN HP
CONN. LOAD IN KW
CONT. CURRENT IN AMPS
RATED VOLTAGE IN VOLTS
SWITCH RATING IN AMPS
BACK UP FUSE IN AMPS
SPEED IN RPM
AYFY CABLE SIZE SQ.MM
RUNS/NO. OF CORES
LENGTH OF CABLE IN MTRS
EARTH CU - STRIP/WIRE
TYPE OF STARTER
RELAY RANGE IN AMPS
CAPACITOR RATING IN KVAR

-	-	-	-	-
-	-	-	-	-
14.744	5.030	7.240	23	14
-	-	-	-	-
415	415	415	415	415
125A	100A	100A	125A	125A
100A	63A	63A	100A	100A
-	-	-	-	-
50	35	35	70	70
1 x 3.5	1 x 3.5	1 x 3.5	1 x 3.5	1 x 3.5
30	35	25	10	15
8	10	10	25 x 3	8
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-

-	-	-	-	-	-
-	-	-	-	-	-
2.404	2.758	3.212	6.37	-	-
-	-	-	-	-	-
415	415	415	415	415	415
32A	32A	32A	32A	32A	32A
-	-	-	-	-	-
-	-	-	-	-	-
10	10	10	16	-	-
1 x 4	1 x 4	1 x 4	1 x 4	-	-
5	40	35	5	-	-
10	10	10	10	-	-
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-