

Lumiere: A Space-Time Diffusion Model for Video Generation

Omer Bar-Tal, Hila Chefer, Omer Tov, Charles Herrmann, Roni Paiss, Shiran Zada, Ariel Ephrat, Junhwa Hur, Guanghui Liu, Amit Raj, Yuanzhen Li, Michael Rubinstein, Tomer Michaeli, Oliver Wang, Deqing Sun, Tali Dekel, Inbar Mosseri

SIGGRAPH 2024, 259 citations

Presented by:
Anantapadmanaabha Prasannakumar

Outline

- Motivation
- Method
- Evaluations
- Applications
- Societal Impact
- Limitations
- Conclusion

Motivation

- ▶ Restricted capability of existing models
 - ▶ Sensitive to error
 - ▶ Suffers from memory and computing constraints
 - ▶ Obtaining large-scale data is cumbersome
 - ▶ Training large-scale T2V is challenging

Motivation


- ▶ Employing temporal cascades is hindersome
 - ▶ Generates aggressively sub-sampled set of keyframes
 - ▶ TSR modules are constrained to fixed, small temporal context
 - ▶ Cascaded training suffers from domain gap

Method - Lumiere

- ▶ Utilizes Diffusion Probabilistic Models
 - ▶ Through denoising steps, trained to approximate data distribution
 - ▶ Starting from noise, a clean sample is drawn from the targeted distribution
- ▶ Incorporates additional guiding signals

Method - Pipeline

(a) Common Approach with TSR model(s)




Common T2V Framework:


- Base Model
- Temporal Super-resolution Model (TSR)
- Spatial Super-resolution Model (SSR)

Method - Pipeline

(a) Common Approach with TSR model(s)



(b) Our Approach




Lumiere Framework:

- Base Model
- Spatial Super-resolution Model (SSR)
- Multidiffusion


Method - STUnet

(a) Space-Time UNet (STUnet)




Employs traditional U-Net Model

Method - STUnet



- Interleave temporal blocks to T2I Architecture
- Trains only new parameters
- Performs identity Initialization
- Low computational Overhead

Method - Multidiffusion



Multidiffusion Framework:

- New generation process from a pre-trained model
- Fuses inconsistent directions into one global denoising step

SSR with Multidiffusion

- ▶ An inflated SSR network can only operate on short videos
- ▶ Employ multidiffusion for smooth temporal transition
- ▶ Multidiffusion prevents temporal artifacts
 - ▶ Resolved by linearly combining video segments

SSR with Multidiffusion

- ▶ At each generation step:
 - ▶ split noisy input video $J \in \mathbb{R}^{H \times W \times T \times 3}$ into $1 \dots N$ overlapping segments
 - ▶ Where $J_i \in \mathbb{R}^{H \times W \times T' \times 3}$ is the i^{th} segment
 - ▶ Temporal duration: $T' < T$
- ▶ To reconcile per-segment SSR predictions:

$$\arg \min_{J'} \sum_{i=1}^n \|J' - \Phi(J_i)\|^2.$$

Evaluation Setup

- ▶ Train T2V model on 30M videos with text prompts
 - ▶ Videos are 80 frames long at 16 fps
 - ▶ 109 text prompts
 - ▶ Base model dimension: 128 x 128 frames
 - ▶ SSR dimension: 1024 x 1024 frames

Zero-shot on UCF-101


Method	FVD ↓	IS ↑
MagicVideo (Zhou et al., 2022)	655.00	-
Emu Video (Girdhar et al., 2023)	606.20	42.70
Video LDM (Blattmann et al., 2023b)	550.61	33.45
Show-1 (Zhang et al., 2023a)	394.46	35.42
Make-A-Video (Singer et al., 2022)	367.23	33.00
PYoCo (Ge et al., 2023)	355.19	47.76
SVD (Blattmann et al., 2023a)	242.02	-
Lumiere (Ours)	332.49	37.54

User Study

- ▶ Two-alternative Forced Choice protocol Adopted
 - ▶ Randomly ordered pairs of videos are provided
 - ▶ 400 user judgments obtained
 - ▶ 109 prompts were utilized
 - ▶ Fixed random seed
 - ▶ Spatial and Temporal alignment


User Study

Video Quality




(a) Text-to-Video

Text Alignment



Video Quality



(b) Image-to-Video

User Study


Left video




Right video




Qualitative Evaluation



Temporal Consistency



Ablation - Initialization



Visualize Initialization Schemes



Standard



Identity



Ablation - Multidiffusion



Applications – Video Editing



Original Video



Generated Video

Application – Stylized Generation


- ▶ Pre-trained T2I weights remain fixed
- ▶ Newly added temporal layers are trained
- ▶ Linear interpolation between fixed and fine-tuned T2I weights
 - ▶ $W_{interpolate} = \alpha \cdot W_{style} + (1 - \alpha) \cdot W_{orig}$
 - ▶ Where $\alpha \in [0.5, 1]$

Application – Stylized Generation

Vector art styles



Reference Image




Output

Application – Stylized Generation

Realistic styles



Reference Image



Output

Application – Conditional Generation

- ▶ Model conditioned on additional input signals
 - ▶ Noisy video $J \in \mathbb{R}^{H \times W \times T \times 3}$
 - ▶ Text prompt
 - ▶ Masked conditioning video $C \in \mathbb{R}^{H \times W \times T \times 3}$
 - ▶ Binary Mask $M \in \mathbb{R}^{H \times W \times T \times 1}$
- ▶ Concatenated Tensor $\langle J, C, M \rangle = \mathbb{R}^{T \times H \times W \times 7}$

Application – Image to Video




Application - Inpainting



Video + Mask



Output



Application - Cinemagraphs



Source Image + Mask



Output



Societal Impact

- ▶ Risk of misuse
 - ▶ Tools for detecting biases and malicious use cases
 - ▶ To ensure safe and fair use

Limitations

- ▶ The model cannot generate videos
 - ▶ Multiple shots
 - ▶ Transition between scenes
- ▶ The model operates in pixel space

Conclusion

- ▶ Presents a novel T2V framework
 - ▶ Built on a pre-trained T2I model
 - ▶ Introduces space-time U-Net Architecture
 - ▶ Utilizes Multidiffusion framework
- ▶ Demonstrates state-of-the-art generation results
- ▶ Showcases applicability to various downstream tasks



Thank you