



PHY654

Machine learning (ML) in particle physics



Swagata Mukherjee • IIT Kanpur
22nd August 2024

Initialisation of w and b parameters



Random initialisation of weights (w) is necessary for NN.

Initializing w parameters to 0 does not work for NN.
(all hidden units become same)

Use **small** random values. Large values may lead to vanishing gradient issue.

You can use `np.random.randn(i,j) * 0.01`

However, b can be initialized to 0.

Vectorisation: why is it important?

Process of training a neural net is often **iterative** and **empirical** process.

Idea → Implement → Run and check performance → Repeat



This part should be fast

If your code is computationally non-optimal, then it may take a long time to run. That can become a huge bottleneck. That's why we will always try to use vectorization whenever possible.

Code to see how the speed-up works

<https://github.com/swagata87/IITKanpurPhy654/blob/main/vectorisation.ipynb>

Parameters and hyperparameters

Parameters: w and b

Learned from the data during
the training process

Hyperparameters: learning rate, number of iterations, number of hidden layers, number of hidden units in each layer, choice of activation function.

Hyperparameters control / influence parameters.

Train / dev / test set



A horizontal bar divided into three colored segments: a large orange segment on the left, a medium blue segment in the middle, and a smaller green segment on the right. The orange segment is labeled 'training', the blue segment is labeled 'dev', and the green segment is labeled 'test'.

training

dev

test

Recall that applied ML is an iterative process.

Idea → Code it up → Check performance → Repeat

Use training set to keep on training your NN.

Use dev set to check which network is performing best.

Once you are happy with a NN, check final performance in test set.


In modern era of big data, where we have **millions** of data,

Train: 98%, Dev: 1%, Test: 1%

If you have small amount of data (few **thousand**), then **60%, 20%, 20%** will be more appropriate.

In some cases, people do not have a test set, i.e, you can have only train and dev.

Bias variance trade-off




1D or 2D example → so we can visualise this.

In high dimensional problems, no way to visualise this. Instead we have some metric that we can look at.



Bias variance trade-off

Two key numbers to look at to understand bias and variance are: Train Set error and Dev set error


Let's say you are writing a photon-vs-jet classifier



Bias variance trade-off




Bias variance trade-off




Signature of high bias



Signature of high variance



How to solve high-bias / high-variance?



Next items

- Regularization
- Exponentially weighted average
- RMSprop
- Adam optimizer
- Mini-batch