Ex.no:13 Date:

Implement your own ping program.

Aim:

To implement a ping program using python to check the connectivity between two computers and measure the response time

Program:

```
import os
import platform
import subprocess

def ping(host="google.com", count=4):
    param = "-n" if platform.system().lower() ==
                "windows" else "-c"
    command = ["ping", param, str(count), host]
    try:
        output = subprocess.check_output(command,
                universal_newlines:True)
        print(output)
    except Exception as e:
        print(f"Ping failed: {e}")
if __name__ == "__main__":
    ping("8.8.8.8")
```

Output:

Pinging 8.8.8.8 with 32 bytes of data

Reply from 8.8.8.8 bytes = 32 time = 6ms TTL=119

Reply from 8.8.8.8 bytes = 32 time = 9ms TTL=119

Reply from 8.8.8.8 bytes = 32 time = 5ms TTL=119

Reply from 8.8.8.8 bytes = 32 time = 9ms TTL=119

Ping statistics for 8.8.8.8:

Packets: sent = 4, Received = 4, lost = 0 (0% loss)

approximate round trip in milli-seconds:

Minimum = 5ms, Max = 9ms, Average = 7ms

(6) Result:

Thus, the ping program was implemented successfully, and the connectivity between the computers are checked.