



LITE SERIES DIRECT CURRENT PANEL METER

Our ET1300 Series Direct Current Shunt Programmable Multi-Function Meters (MFM) are the simple, robust solution for advanced power & energy monitoring. These meters are engineered with easy integration to sustain any kind of projects environment and a wide range of measuring parameters to meet the required energy monitoring needs.

CLASS 1.0, 0.5

MULTI-FUNCTION METER

DC PARAMETERS

LOGGING ENABLED

FEATURES

- Available in 4 Current channels/ 1 Current channel, & 1 Voltage channel
- Crisp, super bright LCD display.
- Data retention for indefinite period during absence of auxiliary supply.
- Both AC & DC supply are available.
- Automatic scaling for Kilo or Mega units. Automatic placement of decimal point.
- User programmable for shunt values.
- Communication through RS485 Modbus RTU.
- Unique service support over-the-counter free replacement within warranty.

PARAMETERS DISPLAYED

Model	V	A	kW	kWh	RS485
ET 1300	●	●	●	●	●

TECHNICAL PARTICULARS

- Input V Nominal
- Measuring Voltage
- Current Range
 - Range
- Shunt mV rating
- Accuracy
- Display
- Isolation
- IP

OFFERED SPECIFICATION

85 - 270 V AC or 20 - 60 V DC
Upto 100 V, 500 V, 1000 V, 1500 V DC range on request
Through Shunt, 1 or 4 independent current channels
10% to 129% of Nominal
50 mV, 60 mV or 75 mV
Supports 2000 Amps Shunt
Class 1.0, 0.5 IEC 62053-21
± (0.5% of FS + 0.5% of Rdg + 1 digit)
Displays of 3 digit, 12.5 mm, 7 segment, super-bright LCD Display.
2000 V AC for one minute
20

● Safety	Measurement Category III, Pollution Degree 2 as per EN61010-1 First Edition
● Volts/Amp	Auto scaling depending on input
● Power	Auto scaling depending on input
● Energy	1 kWh upto 866 kW 10 kWh above 866 kW
● Aux Supply	80 - 275 V AC or 20-60 V DC
● Ambient Temperature	Temp. 0-50 deg C, RH < 95% non-condensing
● Weight	~ 600 gm
● Dimensions	96 x 96 mm (Bezel), x 52 mm,
Cutout Size	92 x 92 mm
● Mounting	Panel Mount with Slide & Lock Clamps
● Warranty	12 months from date of sale

Note: * Ordering option,
Type test carried at "Electrical Research and Development Association" Vadodara India.
Reports are available on request.



128,000+
Telecom Towers



700+
Solar Sites



15+ Global
MNO/Tower CO



54+
Countries



500,000+
Connected Assets



20,000+
Enterprise Users

Invendis
Invent, Discover.

DIN EN ISO 9001:2015

Get in touch :



sales@invendis.com



www.invendis.com



No. 230, 1st Cross, 38th Main, BOOHBCS Layout,
BTM 2nd Stage, Bangalore – 560 068

**SCAN FOR
MORE DETAILS**

