



LITE SERIES DIGITAL PANEL METER

Our ET4001S Series Multi-Function Meters (MFM) are the simple, robust solution for advanced power & energy monitoring. These meters are engineered with easy integration to sustain any kind of projects environment and a wide range of measuring parameters to meet the required energy monitoring needs.

CLASS 1.0

MULTI-FUNCTION METER

TRUE RMS

LOGGING ENABLED

FEATURES

- Crisp, bright 3 LED displays, displaying each parameter simultaneously.
- Data retention for indefinite period during absence of auxiliary supply.
- A single 3 Element Meter caters to 2 Wire(Single Phase).
- Automatic scaling for Kilo or Mega units. Automatic placement of decimal point.
- Unrestricted range of user programmable CT and PT ratios from the front panel of the meter.
- RS 485 Serial Port with Modbus RTU Protocol (refer product selection chart).
- Unique service support over-the-counter free replacement within warranty.

PARAMETERS DISPLAYED

Model	V	A	F	kW	kVA	kVAR	PF	kWh	kVAh	kVArh	RS485
ET 4001S	●	●	●	●	●	●	●	●	●	●	●

TECHNICAL PARTICULARS

- Configuration
- Input V Nominal
 - Range
- Input I Nominal
 - Range
- Input PF Range
- Computation
- Accuracy

- Display
- Isolation

OFFERED SPECIFICATION

1 Phase, 2 Wire
230 V LT or 110 V through PT (line to line)
50% to 120% of Nominal
5 A or 1 A through CT
1% to 120% of Nominal
0.5 Lag to Unity to 0.5 Lead
True RMS for all Power & Energy Parameters
Class 1.0 IEC 62053-21
± (0.5% of FS + 0.5% of Rdg + 1 digit)
± 0.2% for Frequency
± 1.0% of FS for Current
Displays of 3 digit, 12.5 mm, 7 segment, super-bright LEDs
2000 V AC for one minute

• Safety	Measurement Category III, Pollution Degree 2 as per EN61010-1 First Edition
• Volts/Amp	Auto scaling depending on input
• Frequency	0.1 Hz
• Power	Auto scaling depending on input
• Power Factor	0.01
• Energy	1 kWh upto 866 kW 10 kWh above 866 kW
• Aux Supply	85 - 270 V AC or DC
• Burden	0.1 VA typical per Voltage / Current input, 0.2 VA typical on Aux. Supply
• Ambient	Temp. 0-50 deg C, RH < 95% non-condensing
• Weight	~ 400 gm
• Dimensions	96 x 96 mm (Bezel), x 52 mm
• Panel Cutout	(90+1-0) mm x (90+1-0) mm
• Mounting	Slide and Lock clamp
• Warranty	12 months from date of sale

Note: * Ordering option,
Type test carried at "Electrical Research and Development Association" Vadodara India.
Reports are available on request.



128,000+
Telecom Towers



700+
Solar Sites



15+ Global
MNO/Tower CO



54+
Countries



500,000+
Connected Assets



20,000+
Enterprise Users

DIN EN ISO 9001:2015

Get in touch :



sales@invendis.com



www.invendis.com



No. 230, 1st Cross, 38th Main, BOOHBCS Layout,
BTM 2nd Stage, Bangalore – 560 068

Invendis
Invent, Discover.



**SCAN FOR
MORE DETAILS**