



LITE SERIES DIGITAL DEMAND MONITOR

Our ET5001 Series Demand Monitor is simple, robust solution for advanced demand monitoring. These meters are engineered with easy integration to sustain any kind of projects environment and a wide range of measuring parameters to meet the required energy monitoring needs.

CLASS 1.0

DEMAND MONITORING

TRUE RMS

LOGGING ENABLED

FEATURES

- Super bright LCD displays each displaying 3 parameters simultaneously.
- Data retention for indefinite period during absence of auxiliary supply.
- A single 3 Element Meter caters to 3 Wire or 4 Wire.
- Automatic scaling for Kilo or Mega units. Automatic placement of decimal point.
- Unrestricted range of user programmable CT and PT ratios from the front panel of the meter.
- RS 485 Serial Port with Modbus RTU Protocol (refer product selection chart).
- Unique service support over-the-counter free replacement within warranty.

PARAMETERS DISPLAYED

Model	V	A	F	kW	kVA	kVAR	PF	kWh	kVAh	kVArh	V-THD	I-THD	MD	RS485
ET 5001	●	●	●	●	●	●	●	●	●	●	●	●	●	●

TECHNICAL PARTICULARS

- Configuration
- Input V Nominal
 - Range
- Input I Nominal
 - Range
- Input PF Range
- Computation
- Accuracy
- Display
- Isolation

OFFERED SPECIFICATION

1/3 Phase, 3 Element; 3 / 4 Wire (Note Order code)
415 V LT or 110 V through PT (line to line)
50% to 120% of Nominal
5 A or 1 A through CT
1% to 120% of Nominal
0.5 Lag to Unity to 0.5 Lead
True RMS for all Power & Energy Parameters
Class 1.0 IEC 62053-21
Displays of 3 digit, 12.5 mm, 7 segment, Super-bright LCD Display.
2000 V AC for one minute

• Safety	Measurement Category III, Pollution Degree 2 as per EN61010-1 First Edition
• Volts/Amp	Auto scaling depending on input
• Frequency	0.1 Hz
• Power	Auto scaling depending on input
• Power Factor	0.01
• Energy	1 kWH upto 866 kW 10 kWH above 866 kW
• Aux Supply	85 - 270 V AC or DC
• Burden	0.1 VA typical per Voltage / Current input, 0.2 VA typical on Aux. Supply
• Ambient	Temp. 0-50 deg C, RH < 95% non-condensing
• Weight	~ 400 gm
• Dimensions	96 x 96 mm (Bezel), x 52 mm
• Panel Cutout	(90+1-0) mm x (90+1-0) mm
• Mounting	Panel Mount with Slide & Lock clamp
• Warranty	12 months from date of sale

Note: * Ordering option,
Type test carried at "Electrical Research and Development Association" Vadodara India.
Reports are available on request.



118,000+
Telecom Towers



700+
Solar Sites



15+ Global
MNO/Tower CO



26+
Countries



500,000+
Connected Assets



20,000+
Enterprise Users

DIN EN ISO 9001:2015

Get in touch :



sales@invendis.com



www.invendis.com



No. 230, 1st Cross, 38th Main, BOOHBCS Layout,
BTM 2nd Stage, Bangalore – 560 068

Inven*dis*
Invent, Discover.

**SCAN FOR
MORE DETAILS**

