



SINGLE PHASE SMART METER

INVSM-101 is single phase static meter used for revenue billing and submetering applications. This is a whole current meter offers continues comprehensive measurement. The device is equipped with optical port for seamless communication to headend system.

SMART METER

REVENUE METER

PRE-POST PAID

SUB-METERING

FEATURES

- Device has wider measurement range up to 60A with DLMS COSEM standard protocol.
- Meter offers higher accuracy as per IEC 62053-21
- DG sensing: Support for dual source energy measurement
- Two-way “energy” measurements for Active energy & power, reactive energy & power, apparent energy & power, four quadrant energy & power, the instantaneous value of voltage, current, power factor, frequency, and power.
- Up to 12 months billing data registers with pre and post switchable option.
- Anti tamper: Detection of meter cover, terminal and communication module cover opening, bypass, etc. External magnetic field detection and magnetic immunity

TECHNICAL PARTICULARS

- Model No
- Meter type
- Standard applicable
- Rated voltage
- Rated current
- Frequency
- Power Factor
- Minimum starting current in % of base current
- Maximum continuous current
- Power loss
 - a. Voltage circuit
 - b. Current circuit

OFFERED SPECIFICATION

INVSM-101
*Whole current meter (1Phase, Pre or Post paid)
IEC 62053-21
Nominal:240V(L-N) Operating: -40% to+20%
10-60 A
50Hz +/- 5%
0.5 lag- unity-0.866 lead
4% of Ib
60A
AS per IEC 62053-21, IS 13779
AS per IEC 62053-21

● Accuracy class	Class 1.0
● Insulation level	Double Insulation 4KV AC
● Measured values	Active Energy Apparent Energy Reactive Energy Max demand in kW,kVAr,kVA RMS voltage RMS current PF (lead/lag/UPF) Frequency
● Display type	LCD: back light 7 segments for display parameters and icons for tamper indication, communication status and data communication
● Communication interface	DLMS COSEM on Optical port Modbus RTU on RS485 (Isolated 4kv)
● Billing registers	Up to 12 months (Bill point)
● Maximum demand register	15 or 30 or 60 Sliding window and Fixed window method (programable)
● Tariffs	4 with group
● TOU (Time of use)	4 default/Programmable
● Event and Tamper logging	Neutral Missing (Single Wire) Current Reversal Earth load Current bypass Magnetic influence Top Cover Open/module cover open/terminal cover open Detection/Removal *Overload Neutral Disturbance
● DG sensing terminals	*For DG parameters measurement
● Temperature range	-10 to 60 C

● Humidity	95%
● Enclosure IP rating	IP51
● Dimensions	185x130x85mm (+/- 5mm)
● Weight	>500grams
● Enclosure Material	Lexan 543 PC
● Country of Origin	India

Note: * Ordering option,
Type test report available on request.



118,000+
Telecom Towers



700+
Solar Sites



15+ Global
MNO/Tower CO



26+
Countries



500,000+
Connected Assets



20,000+
Enterprise Users

Authorised dealer



Get in touch :



sales@invendis.com



www.invendis.com



No. 230, 1st Cross, 38th Main, BOOHBCS Layout,
BTM 2nd Stage, Bangalore – 560 068

Invendis
Invent, Discover.

**SCAN FOR
MORE DETAILS**

