

Brief Specification of Intel X7425E based 6 port Edge Compute SDWAN Box



Brief Specification of Intel X7425E based 6 port Edge Compute SDWAN Box

<u>HARDWARE SPECIFICATION</u>	
CPU	Intel X7425E, 4 cores with 3.4GHz Turbo Frequency.
RAM	64GB DDR5 SODIMM (Max) (Memory to be Separately Ordered)
Ethernet Ports	6 X 10/100/1000 (Realtek RTL8111H)
Cellular	One M.2(B Key, supports both types 3042 and 3052) with USB2.0 and USB3.0 Supporting both 4G and 5G Modems. (Cellular module to be Separately Ordered), One M.2 slot with dual SIM optional
SIM	2x Nano SIM (additional 2 X nano SIM optional)
Wi-Fi	One M.2 (E Key, 2032 for Wifi/BLE Module 802.11b/g/n/ac/ax (1 x CNVio, 1 X USB2.0) (WiFi module to be Separately Ordered)
Storage	One M.2 (B Key,2280), Upto 512GB SSD, Upto 64GB eMMC ((Memory to be Separately Ordered)
TPM	Firmware/Hardware TPM (Optional)
RTC Battery Backup	3V, CR2032
Input Power	12V DC , DC Jack
Button	Power and Reset
LEDs	Power, SATA, WiFi (depending on WiFi module), Cellular Activity (depending on modem),Link and Activity for Ethernets
Antenna	Cellular: 4 x SMA Connector, Wi-Fi: 2x SMA connector
USB	2 x USB2.0, Optional 2 X USB 2.0
RS232	2 X RS232 (Optional)
HDMI	1 (Optional)
Console	1 x RJ45
Enclosure	Sheet Metal Enclosure
Mounting	Desktop Mount, Rack Mount
Design	Fan
Dimensions	150mm X 250mm X 55mm (L X W X H)
<u>Operational & Environmental</u>	
Storage Temperature	-20 ~ 75°C
Operating Temperature	0 ~ 50°C
Humidity	10 ~ 90% (non-condensing)
<u>Operating System</u>	
Operating System	Ubuntu/Oracle Linux/OpenWRT/Windows/VyOS
Boot Loader	Intel Slim Boot Loader

Brief Specification of Intel X7425E based 6 port Edge Compute SDWAN Box

Block Diagram:

INTEL ADL / AML 6-port ETH carrier board (INV-CI)

