

TECHNICAL PARTICULARS

OFFERED SPECIFICATION

● Meter Type	1 phase AC Ammeter
● Standard applicable	IS1377
● Rated voltage	85 - 270 AC
● Rated current	32 A
● Minimum starting current in % of base	1% of the CT value
● Current	30 A
● Maximum continuous current	According to Load
● Power loss	Less than 2W
● Voltage circuit	@230 V 0.267
● Current circuit	@5 A 0.18 VA
● Accuracy class	1.0
● Insulation level	CAT.2
● Measured values	0.4
● Display type	LED display 4 Digits 1 Row
● Temperature range	- 10° to + 55° C
● Humidity	95%
● Dimensions	70mm L X 32 mm W X 28mm H
● Weight	65 gms
● Country of Origin	India

DIN EN ISO 9001:2015

Get in touch : +91 99000 91518



sales@invendis.com



www.invendis.com



No. 230, 1st Cross, 38th Main, BOOHBCS Layout,
BTM 2nd Stage, Bangalore – 560 068

Invendis
Invent, Discover.



**SCAN FOR
MORE DETAILS**

TECHNICAL PARTICULARS

OFFERED SPECIFICATION

● Meter Type	3 phase AC Ammeter
● Standard applicable	IS1377
● Rated voltage	500 volts AC
● Rated current	32 A
● Minimum starting current in % of base	1% of the CT value
● Current	30 A
● Maximum continuous current	According to Load
● Power loss	Less than 2W
● Voltage circuit	@230 V 0.715
● Current circuit	@5 A 0.18 VA Per phase
● Accuracy class	1.0
● Insulation level	CAT.2
● Measured values	0.4
● Display type	LED display 4 Digits 3 Row
● Temperature range	- 10° to + 55° C
● Humidity	95%
● Dimensions	105mm L X 35mm W X 28mm H
● Weight	183 gms
● Country of Origin	India

DIN EN ISO 9001:2015

Get in touch : +91 99000 91518



sales@invendis.com



www.invendis.com



No. 230, 1st Cross, 38th Main, BOOHBCS Layout,
BTM 2nd Stage, Bangalore – 560 068

Invendis
Invent, Discover.



**SCAN FOR
MORE DETAILS**

TECHNICAL PARTICULARS

OFFERED SPECIFICATION

● Meter Type	3 phase AC Ammeter
● Standard applicable	IS1377
● Rated voltage	500 volts AC
● Rated current	63 A
● Minimum starting current in % of base	1% of the CT value
● Current	60 A
● Maximum continuous Current	According to Load
● Power loss	Less than 2W
● Voltage circuit	@230 V 0.715
● Current circuit	@5 A 0.18 VA Per phase
● Accuracy class	1.0
● Insulation level	CAT.2
● Measured values	0.55
● Display type	LED display 4 Digits 3 Row
● Temperature range	- 10° to + 55° C
● Humidity	95%
● Dimensions	105mm L X 35 mm W X 28mm H
● Weight	183 gms
● Country of Origin	India

DIN EN ISO 9001:2015

Get in touch : +91 99000 91518



sales@invendis.com



www.invendis.com



No. 230, 1st Cross, 38th Main, BOOHBCS Layout,
BTM 2nd Stage, Bangalore – 560 068

Invendis
Invent, Discover.



**SCAN FOR
MORE DETAILS**

TECHNICAL PARTICULARS

OFFERED SPECIFICATION

● Meter Type	1 phase V and A
● Standard applicable	IS1377
● Rated voltage	85 - 270 AC
● Rated current	300 V AC 32A
● Minimum starting current in % of base	1% of the CT value
● Current	30 A
● Maximum continuous current	According to Load
● Power loss	Less than 2W
● Voltage circuit	@230 V 0.267
● Current circuit	@5 A 0.18 VA
● Accuracy class	1.0
● Insulation level	CAT.2
● Measured values	0.4
● Display type	LED display 4 Digits 1 Row
● Temperature range	- 10° to + 55° C
● Humidity	95%
● Dimensions	70mm L X 32 mm W X 28mm H
● Weight	65 gms
● Country of Origin	India

DIN EN ISO 9001:2015

Get in touch : +91 99000 91518



sales@invendis.com



www.invendis.com



No. 230, 1st Cross, 38th Main, BOOHBCS Layout,
BTM 2nd Stage, Bangalore – 560 068

Invendis
Invent, Discover.



**SCAN FOR
MORE DETAILS**

TECHNICAL PARTICULARS

OFFERED SPECIFICATION

● Meter Type	1 phase V and A
● Standard applicable	IS1377
● Rated voltage	85 - 270 AC
● Rated current	300 V AC 32A
● Minimum starting current in % of base	1% of the CT value
● Current	30 A
● Maximum continuous current	According to Load
● Power loss	Less than 2W
● Voltage circuit	@230 V 0.267
● Current circuit	@5 A 0.18 VA
● Accuracy class	1.0
● Insulation level	CAT.2
● Measured values	0.4
● Display type	LED display 4 Digits 1 Row
● Temperature range	- 10° to + 55° C
● Humidity	95%
● Dimensions	70mm L X 32 mm W X 28mm H
● Weight	65 gms
● Country of Origin	India

DIN EN ISO 9001:2015

Get in touch : +91 99000 91518



sales@invendis.com



www.invendis.com



No. 230, 1st Cross, 38th Main, BOOHBCS Layout,
BTM 2nd Stage, Bangalore – 560 068

Invendis
Invent, Discover.



**SCAN FOR
MORE DETAILS**