



ADVANCED DIGITAL BRANCH CIRCUIT POWER MONITOR (BCPM)

Our ET 7021/7023 Series Branch circuit power monitor (BCPM) are advanced space saving to monitor various electrical parameters. These meters are engineered with easy integration to suit any kind of projects environment and a wide range of Measuring parameters to meet your energy efficiency monitoring needs.

9/18 CHANNEL

SINGLE/THREE PHASE

LCD DISPLAY

MIN/MAX VALUE CHANNEL

RS485 MODBUS COMMUNICATION

FEATURES

- Monitors V, A, kW, kWh & PF.
- High Accuracy class 1.0 - IEC 62053-21.
- RS485 Modbus communication.
- LCD Display with auto scrolling facility.
- Din rail mounting.
- Password protection.
- Application in Data Centers, Solar Panels.
- CT card 20A, 40A, 60A & 80A available.

TECHNICAL PARTICULARS

- Meter Type
- Electrical Parameters

- Voltage
- Current
- Line Frequency
- Current rating
- Active power
- Energy
- Power Factor

- Control parameters

- Aux. Supply
- Voltage Range
- Current

OFFERED SPECIFICATION

Single & Three phase

Phase wise – LL , LN, Max and min values

I1, I2, I3

Hz

CT Primary programmable, CTS 1A / 5A

Total kW & Phase wise

Total kWh, Phase wise

Lag/Lead

85 – 270V AC/DC

60V to 415V (Line to Line)

CT primary programmable. Secondary 5A

● Indicators	LCD & LED for power on & communication indication
● Operating Temperature	0 to 50°C
● Storage Temperature	0 to 75°C
● Relative Humidity	Up to 95% non-Condensing
● Weight	750 g approx (BCPM)
● Dimensions	
● Mounting	Din Rail mounting (Both BCPM & CT Card)
● Communication port	Isolated RS485: 3 wire communication port with
●	MODBUS protocol
● Baud rate	Default with 9600
● Parity	None Selectable



118,000+
Telecom Towers



700+
Solar Sites



15+ Global
MNO/Tower CO



26+
Countries



500,000+
Connected Assets



20,000+
Enterprise Users

DIN EN ISO 9001:2015

Get in touch :



sales@invendis.com



www.invendis.com



No. 230, 1st Cross, 38th Main, BOOHBCS Layout,
BTM 2nd Stage, Bangalore – 560 068

Invendis
Invent, Discover.

**SCAN FOR
MORE DETAILS**

