



ADVANCED DIGITAL POWER & ENERGY MULTI-FUNCTION METERS

Our IN4600 Series Multi-Function Meters (MFM) are the simple, robust solution for advanced power & energy monitoring. This meter provides Co2 live monitoring feature to know the Carbon Emission from any kind of sources. These meters are engineered with easy integration to suit any kind of projects environment and a wide range of Measuring parameters to meet your energy efficiency monitoring needs.

CO2 MONITORING

TOD/TOU

DUAL SOURCE

REAL TIME CLOCK

INDIVIDUAL HARMONICS & THD

FEATURES

- Carbon Emission Monitoring.
- High Accuracy class 0.2s,0.5s - IEC 62053-22.
- RS485 Modbus communication.
- Voltage & Current THD, Individual Harmonics up to 31st.
- Load ON & Power ON hours.
- Favourite page configuration.
- Calculated Neutral current measurement.
- True RMS measurement.
- Diagnostic LED for self-health check.
- Addon modules for Analog, Pulse, Relay Output.
- On site firmware upgrade through communication port.
- Maximum Demand recording.
- Password protection

TECHNICAL PARTICULARS

- Meter Type
- Electrical Parameters

- Voltage
- Current
- Line Frequency
- Current rating
- Active power
- Apparent Power
- Reactive power
- Energy
- Apparent Energy
- Reactive Energy

OFFERED SPECIFICATION

Three phase Multifunction panel mountable meter

Phase wise – LL , LN, Max and min values

L1, L2, L3 – Maximum and minimum values and
Neutral current

Hz

CT Primary programmable, CTS 1A / 5A

Total kW & Phase wise

Total kVA & Phase wise

Total kVAR

Total kWh, Phase wise

Total kVAH. Phase wise

Total kVARH Quadrant wise

● Apparent Import / Export energy	KVAH
● Load Hour	Hr : min
● Phase angle	
● Control parameters	
● Aux. Supply	85 – 270V AC/DC
● Voltage Range	60V to 415V (Line to Line)
● Current	CT primary programmable. Secondary 5A
● PF Range	0.5 lag to unity to 0.5 lead
● Resolution	0.1 kW /kVA
● RTC	Available
● Memory	Data storage
● Power Quality Parameters	THD (V & I)
● Burden	0.1VA per Voltage/ Current input, 2VA for Aux input
● Power Consumption	< 2 Watt
● Reverse Protection	Aux supply reverse polarity protection
● Operating Temperature	0 to 50°C
● Storage Temperature	0 to 75°C
● Relative Humidity	Up to 95% non-Condensing
● Weight	300 g
● Dimensions	96mmX96mm (Bezel) X52mm
● Mounting	Panel mountable (Slide and Lock Clamp)
● Communication port	Isolated RS485: 3 wire communication port with MODBUS protocol and Inbuilt TVS protection
● Baud rate	Default with 9600
● Parity	None /Even Selectable

	IN4641	IN4642	IN4643	IN4644
● Active Import/ Export energy		●	●	●
● Apparent Import / Export energy		●	●	●
● Active and Reactive Quadrant wise energy			●	●
● Cumulative Max Demand – selectable kW or kVA	●	●	●	●
● Current demand			●	●
● Voltage Demand			●	●
● Dual Source	●	●	●	
● Max Min values		●	●	●
● THD – Volt, Amp and Power		●	●	●
● Individual Harmonics V, I			●	●
● Neutral Current			●	●
● TOU – 8 slots			●	●
● TOD – 6 slots		●	●	●
● *Ethernet -Modbus TCP/IP (Module)		●	●	●
● *Relay output – 1 relay (Module)		●	●	●
● *Pulse output – 2 outputs (Module)	●	●	●	●
● *Digital I/O -2 (Module)		●	●	●
● RTC		●	●	●
● *Accuracy Class	0.5	0.5	0.5/0.2	0.2
● Display	LED	LED	LCD	LCD
● Diagnostic LED	●	●	●	●
● Firmware Update through communication	●	●	●	●
● Co2 Monitoring	●	●	●	●

New Editions:

Note: * Ordering option,

Type test carried at “Electrical Research and Development Association” Vadodara India.

Reports are available on request.

MECHANICAL DETAILS

- Product dimension = 96 x 96 x 52 mm
- Panel cut out = 91 x 91 mm
- Display window = 80 x 51mm
- ABS box with side clamp mounting
- Transparent PC front panel



118,000+
Telecom Towers



700+
Solar Sites



15+ Global
MNO/Tower CO



26+
Countries



500,000+
Connected Assets



20,000+
Enterprise Users

DIN EN ISO 9001:2015

Get in touch



sales@invendis.com



www.invendis.com



No. 230, 1st Cross, 38th Main, BOOHBCS Layout,
BTM 2nd Stage, Bangalore – 560 068

Inven^{dis}
Invent, Discover.

**SCAN FOR
MORE DETAILS**

