



LITE SERIES DUAL SOURCE PANEL METER

Our ET4602 Series Dual source Multi-Function Meters (MFM) are the simple, robust solution for advanced power & energy monitoring. These meters are engineered with easy integration to sustain any kind of projects environment and a wide range of measuring parameters to meet the required energy monitoring needs.

CLASS 1.0

MULTI-FUNCTION METER

TRUE RMS

LOGGING ENABLED

FEATURES

- Crisp, bright 3 LCD displays each displaying 3 parameters simultaneously.
- Data retention for indefinite period during absence of auxiliary supply.
- A single 3 Element Meter caters to 3 Wire or 4 Wire.
- Automatic scaling for Kilo or Mega units. Automatic placement of decimal point.
- Unrestricted range of user programmable CT and PT ratios from the front panel of the meter.
- Communication with PC, PLC, DCS through RS485 Serial Interface.
- Optically Isolated RS485 or Pulse Output for energy management.
- Unique service support over-the-counter free replacement within warranty.

PARAMETERS DISPLAYED

Model	V	A	F	kW	kVA	PF	kWh	RS485
ET 4602 Dual Source	●	●	●	●	●	●	●	●

TECHNICAL PARTICULARS

- Configuration
- Input V Nominal
- Input I Nominal
 - Range
- Input PF Range
- Computation
- Accuracy

- Display

- Isolation

OFFERED SPECIFICATION

1/3 Phase, 3 Element; 3 / 4 Wire (Note Order code)

20 - 40 V DC

5 A or 1 A through CT

1% to 120% of Nominal

0.5 Lag to Unity to 0.5 Lead

True RMS for all Power & Energy Parameters

Class 1.0 IEC 62053-21

± (0.5% of FS + 0.5% of Rdg + 1 digit)

± 0.2% for Frequency

± 1.0% of FS for Current

Displays of 3 digit, 12.5 mm, 7 segment, super-bright LCD Display.

2000 V AC for one minute

● Safety	Measurement Category III, Pollution Degree 2 as per EN61010-1 First Edition
● Volts/Amp	Auto scaling depending on input
● Frequency	0.1 Hz
● Power	Auto scaling depending on input
● Power Factor	0.01
● Energy	1 kWH upto 866 kW 10 kWH above 866 kW
● Aux Supply	85 - 270 V AC or DC
● Burden	0.1 VA typical per Voltage / Current input, 0.2 VA typical on Aux. Supply
● Ambient	Temp. 0-50 deg C, RH < 95% non-condensing
● Weight	~ 500 gm
● Dimensions	100 x 130 mm (Bezel), x 55 mm
● Mounting	Din rail Mounting
● Warranty	12 months from date of sale

Note: * Ordering option,
Type test carried at "Electrical Research and Development Association" Vadodara India.
Reports are available on request.



118,000+
Telecom Towers



700+
Solar Sites



15+ Global
MNO/Tower CO



26+
Countries



500,000+
Connected Assets



20,000+
Enterprise Users

DIN EN ISO 9001:2015

Get in touch :



sales@invendis.com



www.invendis.com



No. 230, 1st Cross, 38th Main, BOOHBCS Layout,
BTM 2nd Stage, Bangalore – 560 068

Invendis
Invent, Discover.

**SCAN FOR
MORE DETAILS**

