



THREE PHASE SMART METER

INVSM-301 is three phase static meter used for revenue billing and submetering applications. This is a whole current meter offers continues comprehensive measurement. The device is equipped with optical port for seamless communication to headend system.

SMART METER

REVENUE METER

PRE-POST PAID

SUB-METERING

FEATURES

- Device has wider measurement range up to 60A with DLMS COSEM standard protocol.
- Meter offers higher accuracy as per IEC 62053-22
- DG sensing: Support for dual source energy measurement
- Two-way “energy” measurements for Active energy & power, reactive energy & power, apparent energy & power, four quadrant energy & power, the instantaneous value of voltage, current, power factor, frequency, and power.
- Up to 12 months billing data registers with pre and post switchable option.
- Anti tamper: Detection of meter cover, terminal and communication module cover opening, bypass, etc. External magnetic field detection and magnetic immunity

TECHNICAL PARTICULARS

● Model No	INVSM-301
● Meter type	*Whole current meter (3Phase, Pre or Post paid)
● Standard applicable	IEC 62053-22
● Rated voltage	3 x 230 V AC Phase to Neutral, 3PH 3W System
● Rated current	Basic 1 A
● Frequency	50Hz +/- 5%
● Power Factor	Zero lag - unity - zero lead (0.5 lag - unity - 0.866 lead)
● Minimum starting current in % of base current	0.1% of Ib
● Maximum current	200% of IB
● Power loss	
● a. Voltage circuit	AS per IEC 62053-22
● b. Current circuit	AS per IEC 62053-22

OFFERED SPECIFICATION

● Accuracy class	Class 0.5
● Insulation level	4KV AC for 1 minute
● Measured values	R, Y, B Phase Voltage R, Y, B Phase Current Active/Reactive/Apparent Power PF Phase wise/with sign for Lag & Lead Max demand in KW/KVARh/KVA % THD V R, Y, B % THD R, Y, B Frequency
● Display type	LCD: back light 7 segments for display parameters and icons for tamper indication, communication status and data communication
● Communication interface	ICS Compactibility (DLMS protocol) IS15959:2011
● Billing registers	Up to 12 months (Bill point)
● Maximum demand register	15 or 30 or 60 Sliding window and Fixed window method (programable)
● Tariffs	4 with group
● TOU (Time of use)	4 default/Programmable
● Event and Tamper logging	Neutral Missing (Single Wire) Current Reversal Earth load Current bypass Magnetic influence Top Cover Open/module cover open/terminal cover open Detection/Removal *Overload Neutral Disturbance
● DG sensing terminals	*For DG parameters measurement
● Temperature range	-10 to 60 C

● Humidity	95%
● Enclosure IP rating	IP51
● Dimensions	250 x 190 x 85(+/- 10mm)
● Weight	>850grams(+/- 50gm)
● Enclosure Material	Lexan 543 PC
● Country of Origin	India

Note: * Ordering option,
Type test report available on request.



118,000+
Telecom Towers



700+
Solar Sites



15+ Global
MNO/Tower CO



26+
Countries



500,000+
Connected Assets



20,000+
Enterprise Users

Authorised dealer



Get in touch :



sales@invendis.com



www.invendis.com



No. 230, 1st Cross, 38th Main, BOOHBCS Layout,
BTM 2nd Stage, Bangalore – 560 068

Invendis
Invent, Discover.

**SCAN FOR
MORE DETAILS**

