

24 Port Switch-XI 244-2M

DATA SHEET

PRODUCT INFO

INTERFACE

24 x 10/100/1000Mbps+4G Combo(RJ45 Or Fiber) Auto-Negotiation ports,The Fiber is SFP

POWER

Internal power 100-240VAC,50/60Hz

PoE & POWER BUDGET

400 W (Max)

Hardware Specification

Model Name		XI 244-2M
Chipset		EN8853D+EN8808Q*2+EN8804+3*AN8503
Standards and Protocols		IEEE802.3、IEEE 802.3u、IEEE802.3ab、IEEE802.3x、IEEE802.1q
Interface		24 x 10/100/1000Mbps+4G Combo(RJ45 Or Fiber) Auto-Negotiation ports,The Fiber is SFP
Network Media		10Base-T: UTP category 3, 4, 5 cable (maximum 100m) 100Base-Tx: UTP category 5, 5e cable (maximum 100m) 1000Base-T: UTP category 5, 5e cable (maximum 100m)
Transfer Method		Store-and-Forward
MAC Address Table		32K
Switching Capacity		56Gbps
Packet Forwarding Rate		35.7Mpps
Packet buffer		4M bits
Jumbo frame		15 Bytes
Operation Module	Standard	All ports can communicate normally, which is suitable for monitoring and office environment.
	Network cloning	The flow control function is turned off, and all ports can communicate with each other, which is suitable for virtualized desktop and diskless system.
	VLAN	The uplink port (Port25、Port26,Port27,Port28) of the switch can communicate with each other, and the 1-24 port are isolated from each other and cannot communicate.
Indicators	Per Device	Power (Red)
	Per Port	Link/Activity (Green),Poe(Green)
Power Supply		Internal power 100-240VAC,50/60Hz
Power Consumption		Full Load: 400W
Enclosure		19" Rack mountable 1U enclosure
Dimensions (W x D x H)		440x220x44.5 MM

Features

Layer	Layer 2
Management Type	Managed
Smart Managed Switch	Yes
Switching Capacity	56 Gbps
MAC Address table entries	32K
Packet Forwarding Rate	14.88 Mpps
Packet Buffer Size	4 Mbit
Jumbo Frame	15K Byte
VLAN	Upto 4096
Basic Function	Compatible with IEEE 802.3AF/AT compliant Powered Devices (PD) Wire-speed forwarding MAC self-learning and aging IEEE802.3X Full-duplex and backpressure for half-duplex mode
Spanning Tree Protocol	Support 802.1d STP Support 802.1S (MSTP)
Security	MAC Manage, Storm Control, Traffic Monitoring, DHCP Snooping
QoS	QoS Basic, QoS Advance (802.1p)
Switch Monitoring and Management	Web, CLI (Console Port, Telnet, SSH), SNMP V1/V2/V3, Support trap: cold start, warm start, link down and link up
EEE	Support Energy-Efficient Ethernet (EEE) function (IEEE802.3az)
PoE	POE configuration, POE scheduling management, etc.
VLAN Function	Port-based VLAN, Tag based VLAN (802.1Q)
DHCP Function	DHCP Snooping, DHCP Relay
Managed Features	IGMP Snooping, LAG, Port Mirror, LLDP Config, LLDP Neighbour, Loop Prevention, ERPS.
Diagnostics	Ping Tool, Cable diagnostics
Configuration Utility	Import and Export Configuration backup

Operational & Environmental

Storage Temperature	-40°C~+70°C
Operating Temperature	-10°C~+60°C
Humidity	10%~90% non-condensing

Standard Packaging

Switch, Power Cord and Rack Mount Brackets
--

Images

*All rights reserved, subject to change without prior notice.

Get in touch:



sales@invendis.com



www.silbonetworks.com <https://invendis.com/>



Invendis Technologies India Private Limited

No. 230, 1st Cross, 38th Main, BOOHBCS Layout, BTM
2nd Stage, Bangalore – 560 068

