

# RVG-44-C

## DATASHEET

### PRODUCT INFO

#### PROCESSOR

MediaTek MT7621 Dual-core 880 MHz, 512MB DDR3 RAM, 64MB Flash

#### CELLULAR

4G/3G with Dual SIM, External 5dBi antenna

#### Wi-Fi

Dual-Band Wi-Fi, AP/Station, External 5dBi antennas

#### INTERFACE

6x LAN 10/100/1000 , 3x RS485, 1 x RS 232, 1 x USB 2.0, BLE (Optional)

#### POWER

9-30V DC IN

#### OPERATING SYSTEM

Open-WRT Linux



### Hardware Specification

|                     |                                                                                                                                            |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| CPU                 | MediaTek MT7621 Dual-core 880 MHz                                                                                                          |
| RAM                 | 512MB DDR3                                                                                                                                 |
| FLASH               | 32MB                                                                                                                                       |
| WAN                 | 1x 10/100/1000 (Configurable WAN/LAN)                                                                                                      |
| LAN                 | 5x 10/100/1000                                                                                                                             |
| Serial Interface    | 3x RS485, 1 X RS 232                                                                                                                       |
| BLE Chipset         | nRF54L05 BLE 6.0 SOC with LR Radio and 128 MHz Arm® Cortex®-M33 processor, 500KB NVM and 96KB RAM                                          |
| SIM                 | 2x Nano SIM (1x Active & 1x Passive)                                                                                                       |
| RTC                 | Built-in RTC                                                                                                                               |
| Reset               | Pinhole Reset Button                                                                                                                       |
| Antenna             | Cellular: 4x SMA Connector, Wi-Fi 2 x SMA Connector, BLE 1 x SMA Connector                                                                 |
| Status LED's        | 3x Signal strength, 2x SIM Indication , 3x RS485 Rx/Tx , 1 x RS232 Rx/Tx, 1 x Power , 1 x ACT , 1x SYS & 1x Mode LED's, 2 x Wi-Fi, 1 x BLE |
| Power Connector     | DC Jack                                                                                                                                    |
| Input Voltage Range | 9-30 Vdc                                                                                                                                   |
| Power Adapter       | N/A                                                                                                                                        |
| Enclosure           | Industrial Aluminium Enclosure                                                                                                             |
| Mounting            | DIN rail mounting Kit (Optional)                                                                                                           |
| Design              | Fanless                                                                                                                                    |
| Dimensions          | 110 x 44 x 94 mm (W x H x D)                                                                                                               |
| Weight              | 400 gm                                                                                                                                     |

### Operational & Environmental

|                       |                           |
|-----------------------|---------------------------|
| Storage Temperature   | -30 ~ 70 °C               |
| Operating Temperature | -0 ~ 60 °C                |
| Humidity              | 10 ~ 90% (non-condensing) |

# SOFTWARE SPECIFICATIONS

## Cellular

|                          |                                                                            |
|--------------------------|----------------------------------------------------------------------------|
| Cellular Module          | 4G (LTE) - Cat 4 up to 150 Mbps, 3G - up to 42 Mbps, 2G - up to 236.8 Kbps |
| Status                   | Single strength (RSSI), SINR, RSRP, RSRQ                                   |
| Band Management          | Auto/User configurable                                                     |
| Operator Lock            | Automatic/Manual                                                           |
| APN                      | Configurable, Auto APN                                                     |
| Modem configuration mode | Single SIM, Dual SIM                                                       |
| SIM switching            | Signal strength, ICMP echo, Data limit based                               |
| PDP Type                 | IPv4, IPv6, IPv4v6                                                         |
| SIM Authentication       | PAP, CHAP, No Authentication                                               |
| SMS                      | Send SMS, Read SMS, SMS Commands                                           |

## Wi-Fi

|                  |                                                                                  |
|------------------|----------------------------------------------------------------------------------|
| Technology       | 802.11 b/g/n/ac                                                                  |
| Channel Selector | Auto/Configurable                                                                |
| Channel Width    | 20 MHz, 20/40 MHz                                                                |
| Wi-Fi Mode       | Access Point (AP), Station, AP & Client, Guest Wi-Fi                             |
| TX Power         | Configurable                                                                     |
| Authentication   | WPA (PSK), WPA2 (PSK), WPA3 (PSK), WPA & WPA2 Mixed Mode, WPA2 & WPA3 Mixed Mode |
| Encryption       | TKIP, AES, TKIP & AES                                                            |
| Wi-Fi Scheduler  | Scheduled ON/OFF                                                                 |
| MAC ID Filtering | Whitelisting, Blacklisting                                                       |
| Other            | WMM (Enabled/Disabled)                                                           |

## Firewall & Networking

|                         |                                                                                                                                |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Routing                 | Static routing, Advanced Static Routing, Dynamic Routing                                                                       |
| Network Protocols       | TCP, UDP, IPv4, IPv6, ICMP, NTP, HTTP, HTTPS, SCP, PPP, SSH, DHCP                                                              |
| Connection Monitoring   | Ping Reboot, Scheduled Periodic Reboot                                                                                         |
| Firewall features       | Port forward, traffic rules, SNAT, Zone forwarding, Parental Control, Masquerading, MSS Clamping, Loopback IP, Loopback Rules. |
| Attack Prevention       | SYN Flood Protection, Drop Invalid Packets                                                                                     |
| DHCP                    | Static and Dynamic                                                                                                             |
| Multi-WAN Configuration | Configurable Failover, load balancing between Cellular WAN, and Wired.                                                         |
| VLAN                    | Tagged VLAN, Untagged VLAN                                                                                                     |
| VPN                     | Open VPN, IPsec, GRE, L2TP, PPTP, Wireguard, Zero Tier, IPsec Tunnel                                                           |
| Open VPN                | TUN/TAP with TLS Certificates                                                                                                  |
| IPsec                   | IKEv1, IKEv2, Aggressive/Main Mode                                                                                             |
| IPsec Encryption        | 3DES, AES128, AES192, AES256                                                                                                   |
| IPsec Authentication    | SHA1, MD5, SHA256, SHA384, SHA512                                                                                              |
| IPsec DH Group          | MODP768, MODP1024, MODP1536, MODP2048, MODP3072, MODP4096                                                                      |
| PPTP/L2TP               | Server & Client with/without MPPE Encryption                                                                                   |
| Monitoring Application  | Modem Monitoring with ICMP Echo, Router Monitoring with ICMP Echo                                                              |
| Time Synchronization    | NTP Client, RTC, Manual                                                                                                        |
| Diagnostic              | Ping, Traceroute, Modem Debug Info, Iperf, Download Logs                                                                       |
| Other Features          | MAC binding, Connection Diagnostics, URL Filtering, Router Health Monitoring, Package Manager                                  |

## Remote Management

|              |                                                                       |
|--------------|-----------------------------------------------------------------------|
| NMS          | Remote Monitoring & Management Platform for SILBO Networking products |
| NMS VPN      | Remote Access of SILBO and non-SILBO Networking Devices               |
| TR069        | TR069 Client for CPE Management                                       |
| SMS Commands | Reboot Command, Uptime Command                                        |

## Gateway

|                   |                                       |
|-------------------|---------------------------------------|
| Gateway Protocols | Modbus TCP Master, Modbus RTU Master  |
| Serial Mode       | Transparent (Over IP), Modbus Gateway |
| Data sender       | HTTP, MQTT, Azure MQTT                |

## Operating System

|                     |                                                        |
|---------------------|--------------------------------------------------------|
| Operating System    | Open-WRT based Linux OS                                |
| Supported Languages | Shell scripting, C, C++                                |
| Development tools   | SDK package with built environment provided (Optional) |

## Standard Packaging

RVG44-C Cellular Gateway with Industrial Aluminium Housing , 4x Cellular Rubber Duck Antennas, Power TB,  
01-Meter Ethernet cable, Rs485 TB.

\*All rights reserved, subject to change without prior notice.

Get in touch:

 [sales@invendis.com](mailto:sales@invendis.com)

 [www.silbonetworks.com](http://www.silbonetworks.com)

 Invendis Technologies India Private Limited

No. 230, 1st Cross, 38th Main, BOOHBCS Layout, BTM  
2nd Stage, Bangalore – 560 068

