



ISMC-1

Product Highlights

Compact Form Factor

- MC-1 Media Converter series offers signal conversion in a compact device

Utilize Your Fiber

- Send a fiber signal over a variety of distances, with a selection of models suitable for 550 m, 10 km or 20 km

Reliable Technology

- The Standalone Media Converters adhere to industry standards and are compliant with 802.3u, 802.3ab & 802.3x.
- ISMC1-SD851G-S5, ISMC1-SD311G-10, ISMC1-SD311G-20 Series Standalone Media Converters

OVERVIEW

The Unmanaged Media Converter provides conversion between 10/100/1000Base-T and 100/1000Base-X. It is an ideal solution to extend the distance of an existing network, the distance of non-fiber based equipment, or the distance between two devices. The Unmanaged 1G Ethernet Media Converter is equipped with one 10/100/1000M BASE-T auto-negotiation port and one 100/1000M BASE-X SFP+ slot. It is designed for use in network environments where the high bandwidth provided by 1Gigabit Ethernet is required, for example, data center cloud computing, enterprise backbones, campus networks, and carrier infrastructure.

Accessories:



Power Cable



Metal Din Rail

FEATURES

Small Size	• Tiny footprint allows you to keep space free for other networking devices • Deploy it wherever you need without occupying an entire rack slot
High Performance	• Store & forward traffic forwarding • Low latency
Variety	• ISMC1-SD851G-S5, ISMC1-SD311G-10, ISMC1-SD311G-20 provides data rates at Gigabit speeds • Fiber distance options vary from 550 m to 20 km Control costs by buying only the equipment your organization needs Auto MDI/MDIX Auto-Negotiation Status LED's for information

TECHNICAL SPECIFICATIONS

Model	ISMC1-SD851G-S5	ISMC1-SD311G-10	SMC1-SD311G-20
Description	10/100/1000 Base-T to 1000 Base-SX	10/100/1000 Base-T to 1000 Base-LX	10/100/1000 Base-T to 1000 Base-LX
Fiber Wavelength	850nm	1310nm	1310nm
Max Distance	550m	10Km	20Km
Ports	One RJ - 45 and One Fiber port (Duplex SC type connector)	One RJ - 45 and One Fiber port (Duplex SC type connector)	One RJ - 45 and One Fiber port (Duplex SC type connector)
Mode	Multi - mode	Single - mode	Single - mode
Auto MDI support	Yes		
Operating Temperature	0° C to 70° C		
Storage Temperature	-20° C to 85° C		
Operating Humidity	5% to 90%		
Operating Voltage	5-12V DC IN		
External Power Adapter	Yes		
Dimensions	92 x 66 x 26 mm (HxWxD)		

ORDER INFORMATION

ISMC1-SD851G-S5	850nm, 550m, 10/100/1000 Base-T to 1000 Base-SX
ISMC1-SD311G-10	1310nm, 10Km, 10/100/1000 Base-T to 1000 Base-LX
ISMC1-SD311G-20	1310nm, 20Km, 10/100/1000 Base-T to 1000 Base-LX

STANDARD PACKAGING

MC-1 Media Converter with Sheet Metal Housing , 01-meter Ethernet cable, Power Adaptor.

*All rights reserved, subject to change without prior notice.

Get in touch :

-  sales@invendis.com
-  www.silbonetworks.com
-  No. 230, 1st Cross, 38th Main, BOOHBCS Layout,
BTM 2nd Stage, Bangalore – 560 068

