RTS00

DATA SHEET

PRODUCT INFO

PROCESSOR
MediaTek MT7981, Dual core ARM A53, 1.3 GHz,1GB DDR4 RAM, 128MB NAND

CELLULAR
NA

Wi-Fi
NA

INTERFACE
6x LAN 10/100/1000, 1x USB 3.0

POWER
9-30 DC IN (Dual power Source 2PIN Screw Terminal and DC JACK)

OPERATING SYSTEM
Open-WRT Linux

Hardware Specification

CPU	MediaTek MT7981, Dual core ARM A53, 1.3 GHz
RAM	1GB
FLASH	256MB NAND
Ethernet	6x 10/100/1000
USB	USB 3.0 host
Reset	Pinhole Reset Button
Status LED	1x Power, 1x PRG, 6x Ethernet
Power Connector	Dual power Source 2PIN Screw Terminal and DC JACK
Input Voltage Range	9-30 Vdc
Power Adapter	YES
Enclosure	Sheet Metal Enclosure
Mounting	DIN rail mounting Kit (Optional)
Design	Fanless
Dimensions	190 x 30 x 120 mm (W x H x D)
Weight	640 gm
Other	Grounding Screw

Operational & Environmental

Storage Temperature	-20 ~ 65 ˚C
Operating Temperature	0~ 50 ˚C
Humidity	10 ~ 90% (non-condensing)

SOFTWARE SPECIFICATION

Firewall & Networking

Routing	Static routing, Advanced Static Routing
Network Protocols	TCP, UDP, IPv4, IPv6, ICMP, NTP, HTTP, HTTPS, SCP, PPP, SSH, DHCP
Connection Monitoring	Ping Reboot, Scheduled Periodic Reboot, Hardware Watchdog (Enable / Disable)
Firewall features	Port forward, traffic rules, SNAT, Zone forwarding, Parental Control, Masquerading, MSS Clamping, Loopback IP, Loopback Rules.
Attack Prevention	SYN Flood Protection, Drop Invalid Packets
DHCP	Static and Dynamic
Multi-WAN Configuration	Configurable Failover, load balancing between Wired WAN's.
VLAN	Tagged VLAN, Untagged VLAN
VPN	Open VPN, IPsec, GRE, L2TP, PPTP, Wireguard, Zero Tier, IPIP Tunnel
Open VPN	TUN/TAP with TLS Certificates
IPsec	IKEv1, IKEv2, Aggressive/Main Mode
IPsec Encryption	3DES, AES128, AES192, AES256
IPsec Authentication	SHA1, MD5, SHA256, SHA384, SHA512
IPsec DH Group	MODP768, MODP1024, MODP1536, MODP2048, MODP3072, MODP4096
PPTP/L2TP	Server & Client with/without MPPE Encryption
Monitoring Application	Modem Monitoring with ICMP Echo, Router Monitoring with ICMP Echo
Time Synchronization	NTP Client, RTC, Manual
Diagnostic	Ping, Traceroute, Modem Debug Info, Iperf, Download Logs
Other Features	MAC binding, Connection Diagnostics, URL Filtering, Router Health Monitoring, Package Manager

Remote Management

NMS	Remote Monitoring & Management Platform for SILBO Networking products
NMS VPN	Remote Access of SILBO and non-SILBO Networking Device
TR069	TR069 Client for CPE Management

Operating System

Operating System	Open-WRT based Linux OS
Supported Languages	Shell scripting, C, C++
Development tools	SDK package with built environment provided (Optional)

Standard Packaging

RTS00 Router with Sheet Metal housing, Power Adapter, 01-meter Ethernet cable.

*All rights reserved, subject to change without prior notice.

Get in touch:

sales@invendis.com

www.silbonetworks.com

Invendis Technologies India Private Limited
No. 230, 1st Cross, 38th Main, BOOHBCS Layout, BTM
2nd Stage, Bangalore – 560 068