RTS65-2

DATA SHEET

PRODUCT INFO

PROCESSOR
MediaTek MT7981,1GB DDR RAM, 128MB NAND

CELLULAR
Dual Modem 5G/4G/3G/2G with Dual SIM, External 5dBi antenna 2x 4G Modem)

Wi-Fi
Dual-Band Wi-Fi, AP/Station, External 5dBi antennas

INTERFACE
5x LAN 10/100/1000, 2x SFP, 1x USB 3.0

POWER
9-30 DC IN (Dual power Source 2PIN Screw Terminal or DC JACK)

OPERATING SYSTEM
Open-WRT Linux

Hardware Specification

CPU	MediaTek MT7981
RAM	1GB
FLASH	128MB NAND
Ethernet	5x 10/100/1000, 2x SFP, 1x USB 3.0
USB	1x USB 3.0 / USB 2.0 Host
SIM	2x Nano SIM (Active, Active)
Wi-Fi	802.11 b/g/n/ac/ax
Reset	Pinhole Reset Button
Antenna	Cellular: 4x SMA Connector, Wi-Fi: 3x SMA connector
Status LED	8x Single strength, 1x Power, 1x Wi-Fi 5G, 1x Wi-Fi 2G, 1x PRG, 2x Mode, 2x ACT, 5x Ethernet
Power Connector	(Dual power Source 2PIN Screw Terminal or DC JACK)
Input Voltage Range	9-30 Vdc
Power Adapter	YES
Enclosure	Sheet Metal Enclosure
Mounting	DIN rail mounting Kit (Optional)
Design	Fanless
Dimensions	190 x 45 x 120 mm (W x H x D)
Weight	700 gm
Other	Grounding Screw

Operational & Environmental

Storage Temperature	-20 ~ 65 ˚C
Operating Temperature	0~ 50 ˚C
Humidity	10 ~ 90% (non-condensing)

SOFTWARE SPECIFICATIONS

Cellular

Cellular Module	4G (LTE) - Cat 4 up to 150 Mbps, 3G - up to 42 Mbps, 2G - up to 236.8 Kbps
Status	Single strength (RSSI), SINR, RSRP, RSRQ
Band Management	Auto/User configurable
Operator Lock	Automatic/Manual
APN	Configurable, Auto APN
Modem configuration mode	Single SIM, Dual SIM
SIM switching	Signal strength, ICMP echo, Data limit based
PDP Type	IPv4, IPv6, IPv4v6
SIM Authentication	PAP,CHAP, No Authentication
SMS	Send SMS, Read SMS, SMS Commands

Wi-Fi

Technology	802.11 b/g/n/ac/ax
Channel Selector	Auto/Configurable
Channel Width	20 MHz, 20/40/80/160 MHz
Wi-Fi Mode	Access Point (AP), Station, AP & Client, Guest Wi-Fi, Mesh Wi-Fi
TX Power	Configurable
Authentication	WPA (PSK), WPA2 (PSK), WPA3 (PSK), WPA & WPA2 Mixed Mode, WPA2 & WPA3 Mixed Mode
Encryption	TKIP, AES, TKIP & AES
Wi-Fi Scheduler	Scheduled ON/OFF
MAC ID Filtering	Whitelisting, Blacklisting
Other	WMM (Enabled/Disabled)

Firewall & Networking

Routing	Static routing, Advanced Static Routing
Network Protocols	TCP, UDP, IPv4, IPv6, ICMP, NTP, HTTP, HTTPS, SCP, PPP, SSH, DHCP
Connection Monitoring	Ping Reboot, Scheduled Periodic Reboot, Hardware Watchdog (Enable / Disable)
Firewall features	Port forward, traffic rules, SNAT, Zone forwarding, Parental Control, Masquerading, MSS Clamping, Loopback IP, Loopback Rules.
Attack Prevention	SYN Flood Protection, Drop Invalid Packets
DHCP	Static and Dynamic
Multi-WAN Configuration	Configurable Failover, load balancing between Cellular WAN, Wi-Fi WAN and Wired.
VLAN	Tagged VLAN, Untagged VLAN
VPN	Open VPN, IPsec, GRE, L2TP, PPTP, Wireguard, Zero Tier, IPIP Tunnel
Open VPN	TUN/TAP with TLS Certificates
IPsec	IKEv1, IKEv2, Aggressive/Main Mode
IPsec Encryption	3DES, AES128, AES192, AES256
IPsec Authentication	SHA1, MD5, SHA256, SHA384, SHA512
IPsec DH Group	MODP768, MODP1024, MODP1536, MODP2048, MODP3072, MODP4096
PPTP/L2TP	Server & Client with/without MPPE Encryption
Monitoring Application	Modem Monitoring with ICMP Echo, Router Monitoring with ICMP Echo
Time Synchronization	NTP Client, RTC, Manual
Diagnostic	Ping, Traceroute, Modem Debug Info, Iperf, Download Logs
Other Features	MAC binding, Connection Diagnostics, URL Filtering, Router Health Monitoring, Package Manager

Remote Management

NMS	Remote Monitoring & Management Platform for SILBO Networking products
NMS VPN	Remote Access of SILBO and non-SILBO Networking Device
TR069	TR069 Client for CPE Management
SMS Commands	Reboot Command, Uptime Command

Operating System

Operating System	Open-WRT based Linux OS
Supported Languages	Shell scripting, C, C++
Development tools	SDK package with built environment provided (Optional)

Standard Packaging

RTS65-2 Cellular Router with Sheet Metal housing, 4x Cellular Rubber Duck Antennas, 3x Wi-Fi Rubber Duck Antennas, Power Adapter, 01-meter Ethernet cable.

*All rights reserved, subject to change without prior notice.

Get in touch:

sales@invendis.com

www.silbonetworks.com

Invendis Technologies India Private Limited
No. 230, 1st Cross, 38th Main, BOOHBCS Layout, BTM
2nd Stage, Bangalore – 560 068