PC312-P

DATA SHEET

PRODUCT INFO

PROCESSOR
MediaTek MT7628 128MB

CELLULAR
NA

Wi-Fi
2.4GHz, 300Mbps AP/Station,

INTERFACE
1x LAN 10/100

POWER
12-24V DC IN

OPERATING SYSTEM
Open-WRT Linux

Hardware Specification

CPU	MediaTek MT7628
RAM	128MB
FLASH	32MB
WAN	NA
LAN	1x 10/100 Mbps
Serial Interface	1x RS485
SIM	NA
Wi-Fi	802.11b/g/n(Optional)
RTC	NA
Reset	Pinhole Reset Button
Antenna	NA
Status LED	1x Power, 1x RS485, 2x Prog, 1x Ethernet
Power Connector	DC Jack
Input Voltage Range	12V-24V
Power Adapter	Yes
Enclosure	Sheet Metal Enclosure
Mounting	DIN rail mounting Kit (Optional)
Design	Fanless
Dimensions	80 x 26 x 78 mm (W x H x D)
Weight	400 gm
Other	Grounding Screw

Operational & Environmental

Storage Temperature	-30 ~ 70 ˚C
Operating Temperature	0~ 50 ˚C
Humidity	10 ~ 90% (non-condensing)

SOFTWARE SPECIFICATIONS

Remote Management

NMS	Remote Monitoring & Management Platform for SILBO Networking products
NMS VPN	Remote Access of SILBO and non-SILBO Networking Devices
TR069	TR069 Client for CPE Management
SMS Commands	Reboot Command, Uptime Command

Gateway

Gateway Protocols	Transparent Serial to Remote TCP Client Transparent Serial to Remote TCP Server Modbus TCP Master to Modbus RTU Slave Modbus RTU Master to Modbus TCP Slave Modbus RTU Master to Modbus MQTT/HTTP Gateway
Serial Mode	Transparent (Over IP), Modbus Gateway

Operating System

Operating System	Open-WRT based Linux OS
Supported Languages	Shell scripting, C, C++
Development tools	SDK package with built environment provided (Optional)

Standard Packaging

PC312 Protocol convertor with Plastic Housing, 1x RS485 TB and 1X Power Adabpter.

*All rights reserved, subject to change without prior notice.

Get in touch:

sales@invendis.com

www.silbonetworks.com

Invendis Technologies India Private Limited
No. 230, 1st Cross, 38th Main, BOOHBCS Layout, BTM
2nd Stage, Bangalore – 560 068